

Gaussian Process Regression – Lab 3

Mines Saint-Étienne, Data Science, 2016 - 2017

The aim of this lab session is to implement various methods for generating designs of experiments and to be able to assess the quality of a DoE. During the whole lab, we will assume that the DoE is over $[0, 1]^d$, and we will denote by n the number of design points.

A reminder of *R* basic commands can be found on my webpage.

Latin Hypercube Samples

- Q 1. Write a function with parameters n and d that returns a Latin hypercube design.
- Q 2. Plot a few DoE for $d = 2$ or 3 . Do they fill the space?
- Q 3. What can you say about the distributions of the points on the marginals?

Centroidal Voronoi Tessellations

- Q 4. Write a function with parameters n and d that returns a CVT design. Feel free to use either the McQueen or the k-means algorithm.
- Q 5. Plot a few DoE for $d = 2$ or 3 . Do they fill the space?
- Q 6. What can you say about the distributions of the points on the marginals?

Low Discrepancy Sequence

The functions `sobol` and `halton` are already implemented in the package `randtoolbox`.

- Q 7. Plot a few DoE for $d = 2$ or 3 . Do they fill the space?
- Q 8. What can you say about the distributions of the points on the marginals?

Assessing a design

- Q 9. Write a function that takes a DoE as input and that returns the value of the maximin criterion.
- Q 10. Write a function that takes a DoE as input and that returns the value of the minimax criterion.
- Q 11. Write a function that takes a DoE as input and that returns the value of the minimax criterion.
- Q 12. Write a function that takes a DoE as input and that returns the value of the discrepancy.

- Q 13. Write a function that takes a DoE as input and that returns the IMSE criterion.
- Q 14. According to these, which design is the best? You can also compare your DoE with n points sampled uniformly over $[0, 1]^d$.

Optimization of DoE

- Q 15. Write an exchange algorithm that can optimize a LHS design.