Kalman Filtering for Real-Time Probability Estimation in Prediction Markets

Nicolas Leyva

March 12, 2026

Abstract

Prediction market prices are noisy estimates of the true probability of future events, distorted by thin order books, behavioral biases, and microstructure effects. We develop a suite of Kalman filter variants—scalar, adaptive, logit-space, and multivariate—to extract cleaner probability estimates from raw market prices in real time. Each variant addresses a specific limitation: the adaptive filter handles regime changes via innovation monitoring, the logit-space filter guarantees bounded estimates in $[0, 1]$, and the multivariate filter exploits cross-market correlations to improve estimation even when individual markets are unobserved. We evaluate all filters on synthetic data with known ground truth using Brier scores, log loss, calibration analysis, and innovation diagnostics. The adaptive Kalman filter reduces post-regime-change tracking error by 65% compared to the basic filter, the logit filter eliminates boundary violations, and maximum likelihood estimation recovers true noise parameters within a factor of two from 500 observations.

1 Introduction

Prediction markets are exchange-traded instruments whose prices converge to the consensus probability of a future event [Polymarket, 2024]. A contract trading at \$0.65 on a question like "Will the Federal Reserve cut rates in June?" implies a 65% market-consensus probability. However, the observed price z_t is a noisy realization of the true underlying probability x_t, corrupted by several sources of error:

- **Bid-ask spread**: The platform's order book has a spread between best bid and best ask, so the midpoint is only an approximation.
- **Thin liquidity**: With few shares outstanding, individual trades cause disproportionate price impact.
- **Behavioral biases**: Favorite-longshot bias, YES bias, and herding behavior systematically distort prices.
- **Stale quotes**: In low-activity periods, the last trade may not reflect current information.

The Kalman filter [Kalman, 1960] is a recursive Bayesian state estimator that is well-suited to this problem. At each time step it maintains a probability estimate and an associated uncertainty, updating both as new price observations arrive. When the market is liquid, the filter trusts observations more; when spreads are wide and books are thin, it trusts its own prior estimate more.

This paper presents four filter variants of increasing sophistication, each implemented from scratch without external filtering libraries. We validate all filters on synthetic data with known ground truth and evaluate them using proper scoring rules.

Contributions:

1. A scalar Kalman filter with maximum likelihood parameter estimation for single markets.
2. An adaptive filter that detects regime changes via innovation monitoring and dynamically adjusts process noise.
3. A logit-space filter that guarantees bounded probability estimates and produces asymmetric confidence intervals.
4. A multivariate filter that tracks correlated market clusters using Ledoit-Wolf covariance shrinkage.
5. A regime detection module combining CUSUM, chi-square, and autocorrelation tests.

2 Mathematical Framework

2.1 State-Space Model

We model the true probability of an event as a random walk observed with additive Gaussian noise:

State transition:

$$x_t = x_{t-1} + w_t, \quad w_t \sim \mathcal{N}(0, Q) \tag{1}$$

Observation model:

$$z_t = x_t + v_t, \quad v_t \sim \mathcal{N}(0, R) \tag{2}$$

where x_t is the true (latent) probability, z_t is the observed market price, Q is the process noise variance (how much the true probability drifts per step), and R is the measurement noise variance (how noisy the market price is).

2.2 Scalar Kalman Filter

The standard Kalman filter alternates between predict and update steps [Kalman, 1960]:

Predict:

$$\hat{x}_{t|t-1} = \hat{x}_{t-1|t-1} \tag{3}$$

$$P_{t|t-1} = P_{t-1|t-1} + Q \tag{4}$$

Update:

$$y_t = z_t - \hat{x}_{t|t-1} \qquad \text{(innovation)} \tag{5}$$

$$S_t = P_{t|t-1} + R \qquad \text{(innovation covariance)} \tag{6}$$

$$K_t = \frac{P_{t|t-1}}{S_t} \qquad \text{(Kalman gain)} \tag{7}$$

$$\hat{x}_{t|t} = \hat{x}_{t|t-1} + K_t y_t \qquad \text{(state update)} \tag{8}$$

$$P_{t|t} = (1 - K_t) P_{t|t-1} \qquad \text{(covariance update)} \tag{9}$$

The Kalman gain $K_t \in [0, 1]$ controls the trade-off between trusting the prediction and trusting the observation. As $t \to \infty$, the gain converges to a steady-state value determined by the algebraic Riccati equation:

$$P_\infty = \frac{Q + \sqrt{Q^2 + 4QR}}{2}, \quad K_\infty = \frac{P_\infty}{P_\infty + R} \tag{10}$$

2.3 Maximum Likelihood Parameter Estimation

The innovation sequence of a correctly specified Kalman filter is Gaussian white noise: $y_t \sim \mathcal{N}(0, S_t)$. This yields the log-likelihood [Schweppe, 1965]:

$$\log L(Q, R) = -\frac{1}{2} \sum_{t=1}^{T} \left[\log(2\pi S_t) + \frac{y_t^2}{S_t} \right] \tag{11}$$

We maximize $\log L$ over (Q, R) using L-BFGS-B optimization in log-space to enforce positivity, with initial guesses $Q_0 = 10^{-4}$, $R_0 = 10^{-3}$. The first 10 observations are excluded as a warm-up period.

2.4 Adaptive Process Noise

The basic filter assumes constant Q, which causes it to lag behind sudden regime changes. We extend it with innovation-based adaptation [Mehra, 1972, Mohamed and Schwarz, 1999]:

$$\tilde{y}_t = \frac{y_t}{\sqrt{S_t}} \quad \text{(normalized innovation)} \tag{12}$$

When $|\tilde{y}_t| > \tau$ (threshold, default $\tau = 2.5$), we inflate the process noise:

$$Q_t = Q_{\text{base}} \cdot \alpha_t \tag{13}$$

where α_t is an inflation multiplier initialized to $\alpha_{\max}$ (default 10) and decayed exponentially:

$$\alpha_{t+1} = \max\left(1,\ 1 + (\alpha_t - 1) \cdot \lambda\right), \quad \lambda = 0.8 \tag{14}$$

This allows the filter to "open up" its uncertainty after a surprise, track the new regime quickly, then settle back to steady-state filtering.

2.5 Dynamic Observation Noise

The observation noise R_t is estimated from market microstructure data [Hasbrouck, 2007]:

$$R_t = w_1 R_{\text{spread}} + w_2 R_{\text{depth}} + w_3 R_{\text{imbalance}} + w_4 R_{\text{stale}} \tag{15}$$

where each component captures a different source of measurement noise: bid-ask spread width, order book depth, order flow imbalance, and quote staleness.

2.6 Logit-Space Filter

The standard Kalman filter can produce estimates outside $[0, 1]$, which is invalid for probabilities. The logit-space filter operates in log-odds space where the domain is unbounded:

$$\ell = \text{logit}(p) = \log \frac{p}{1-p}, \quad p = \sigma(\ell) = \frac{1}{1 + e^{-\ell}} \tag{16}$$

Observation noise transforms via the delta method:

$$R_{\text{logit}} = \frac{R_{\text{prob}}}{(p(1-p))^2} \tag{17}$$

Note that R_{logit} varies with price level: near $p = 0.5$, $R_{\text{logit}} \approx 16 R_{\text{prob}}$; near $p = 0.95$, $R_{\text{logit}} \approx 400 R_{\text{prob}}$. This correctly captures that small price changes near the boundaries correspond to large changes in log-odds.

Confidence intervals are constructed in logit space (where they are symmetric) and transformed back:

$$\text{CI}_{95\%} = \left[\sigma(\hat{\ell}_t - 2\sqrt{P_t}),\ \sigma(\hat{\ell}_t + 2\sqrt{P_t}) \right] \tag{18}$$

producing asymmetric bands in probability space that never violate $[0, 1]$.

2.7 Multivariate Filter

For n correlated markets, the state vector is $\mathbf{x}_t \in \mathbb{R}^n$ with:

$$\mathbf{x}_t = \mathbf{x}_{t-1} + \mathbf{w}_t, \qquad \mathbf{w}_t \sim \mathcal{N}(\mathbf{0}, \mathbf{Q}) \tag{19}$$

$$\mathbf{z}_t = \mathbf{H}_t \mathbf{x}_t + \mathbf{v}_t, \qquad \mathbf{v}_t \sim \mathcal{N}(\mathbf{0}, \mathbf{R}_t) \tag{20}$$

where $\mathbf{H}_t$ is a selection matrix that handles missing observations (rows are removed for unobserved markets).

The Kalman gain becomes:

$$\mathbf{K}_t = \mathbf{P}_{t|t-1}\mathbf{H}_t^\top \left(\mathbf{H}_t \mathbf{P}_{t|t-1}\mathbf{H}_t^\top + \mathbf{R}_t\right)^{-1} \tag{21}$$

We use the Joseph form for the covariance update for numerical stability:

$$\mathbf{P}_{t|t} = (\mathbf{I} - \mathbf{K}_t\mathbf{H}_t)\mathbf{P}_{t|t-1}(\mathbf{I} - \mathbf{K}_t\mathbf{H}_t)^\top + \mathbf{K}_t\mathbf{R}_t\mathbf{K}_t^\top \tag{22}$$

Covariance estimation. The cross-market process noise covariance $\mathbf{Q}$ is estimated from historical price returns using Ledoit-Wolf shrinkage [Ledoit and Wolf, 2004]:

$$\hat{\mathbf{\Sigma}} = \alpha \cdot \frac{\mathrm{tr}(\mathbf{S})}{n}\mathbf{I} + (1-\alpha) \cdot \mathbf{S} \tag{23}$$

where $\mathbf{S}$ is the sample covariance and $\alpha \in [0, 1]$ is the data-driven shrinkage intensity. This stabilizes estimation when the number of markets is comparable to the number of observations.

2.8 Regime Detection

We combine three complementary detection methods applied to the normalized innovation sequence $\tilde{y}_t = y_t/\sqrt{S_t}$:

CUSUM [Page, 1954]: Accumulates squared normalized innovations:

$$C_t = C_{t-1} + (\tilde{y}_t^2 - 1), \quad \text{detect when } C_t - \min_{s \le t} C_s > h \tag{24}$$

with threshold $h = 4.0$.

Chi-square test: Over a sliding window of size $W = 20$:

$$\chi^2 = \sum_{i=t-W+1}^{t} \tilde{y}_i^2, \quad \text{reject } H_0 \text{ when } \chi^2 > \chi^2_{1-\alpha}(W) \tag{25}$$

Autocorrelation: Detects serial correlation at lag 1, which should be approximately zero under correct model specification.

3 Experimental Setup

3.1 Synthetic Data

All experiments use synthetic data with known ground truth, generated as random walks with Gaussian noise (Equations 1–2) clipped to $[0, 1]$. We test three data types:

- **Random walk**: Stationary process with fixed Q and R.
- **Step change**: Sudden jump from one probability level to another (e.g., $0.3 \to 0.75$ at $t = 250$), with small $Q = 10^{-6}$ away from the jump.
- **Correlated markets**: Three markets driven by a shared process noise covariance with off-diagonal terms.

3.2 Evaluation Metrics

Brier score [Brier, 1950]: Mean squared error between predicted probabilities and binary outcomes:

$$\mathrm{BS} = \frac{1}{T}\sum_{t=1}^{T}(\hat{p}_t - y_t)^2 \tag{26}$$

where $y_t \in \{0, 1\}$ is the resolved outcome. Lower is better; 0.25 corresponds to always predicting 0.5.

Log loss: $\mathrm{LL} = -\frac{1}{T}\sum_t [y_t \log \hat{p}_t + (1 - y_t)\log(1 - \hat{p}_t)]$.

Innovation diagnostics: For a correctly specified filter, normalized innovations should be approximately $\mathcal{N}(0, 1)$, with $\sim$95% falling within $\pm 2\sigma$.

Calibration: Predicted probabilities are binned and compared against the observed frequency of the event.

4 Results

All results presented in this section are from actual simulation runs. Figures are extracted directly from executed Jupyter notebooks.

4.1 Scalar Kalman Filter

We apply the scalar filter to a synthetic random walk ($Q = 10^{-4}$, $R = 2 \times 10^{-3}$, $T = 500$, price range $[0.303, 0.678]$). The filter converges to a final state estimate $\hat{x} = 0.5370$ with covariance $P = 2.70 \times 10^{-4}$ and steady-state gain $K_\infty = 0.2702$.

Figure 1 shows the filtered output tracking the true state while suppressing observation noise.



Figure 1: Scalar Kalman filter on synthetic data. Gray: raw noisy prices. Cyan: filtered estimate with $\pm 2\sigma$ confidence band. Green: true underlying state.

Figure 2 shows the Kalman gain converging to its steady-state value $K_\infty = 0.2702$ within approximately 20 steps.



Figure 2: Kalman gain convergence to steady state.

Figure 3 shows the innovation diagnostics. A well-tuned filter should have approximately 95% of innovations within the $\pm 2\sigma$ bounds.



Figure 3: Innovation sequence with $\pm 2\sigma$ bounds from the innovation covariance S_t.

Figure 4 demonstrates the sensitivity of the filter to the Q/R ratio.



Figure 4: Parameter sensitivity. Left: varying Q with fixed $R = 10^{-3}$. Right: varying R with fixed $Q = 10^{-4}$. Larger Q makes the filter more responsive but noisier; larger R produces smoother but more lagging estimates.

Figure 5 quantifies the noise reduction as a signal-to-noise ratio improvement.



Figure 5: Signal-to-noise ratio improvement: variance of raw price changes vs filtered estimate changes.

4.1.1 MLE Parameter Estimation

Maximum likelihood estimation recovers the true parameters from 500 observations: $\hat{Q} = 6.54 \times 10^{-5}$ (true: 10^{-4}, error 34.6%) and $\hat{R} = 2.03 \times 10^{-3}$ (true: 2×10^{-3}, error 1.5%). The R estimate is highly accurate; the Q estimate is within the expected range given the sample size. Figure 6 shows the log-likelihood surface with a clear global maximum.



Figure 6: Log-likelihood surface over Q and R parameter space. The red star marks the MLE estimate $(\hat{Q}, \hat{R})$.

Figure 7 compares the hand-tuned filter against the MLE-optimized filter.



Figure 7: Hand-tuned parameters (top, $Q = 10^{-4}$, $R = 10^{-3}$) vs MLE-estimated parameters (bottom, $\hat{Q} = 6.54 \times 10^{-5}$, $\hat{R} = 2.03 \times 10^{-3}$).

4.2 Adaptive Kalman Filter

We test on synthetic data with a step change from $p = 0.3$ to $p = 0.75$ at $t = 250$ ($T = 500$, $Q = 10^{-6}$, $R = 10^{-3}$). Figure 8 compares the basic and adaptive filters. The basic filter lags behind the regime change for over 50 steps, while the adaptive filter (threshold $\tau = 2.5$, inflation factor 15, decay $\lambda = 0.8$) tracks the new regime within approximately 15 steps.



Figure 8: Basic scalar filter (top) vs adaptive filter (bottom) on step change data. The adaptive filter tracks the regime change significantly faster.

Figure 9 shows the effective Q_t over time. The process noise spikes at the regime change and decays exponentially back to $Q_{\text{base}} = 10^{-5}$.



Figure 9: Effective process noise Q_t on log scale. The spike at $t \approx 250$ corresponds to the detected regime change, decaying back to baseline via exponential decay.

The post-regime-change mean absolute error ($t = 250$ to $t = 300$) is **0.0897** for the basic filter and **0.0316** for the adaptive filter—a **65% reduction** in tracking error (Figure 10).



Figure 10: Absolute tracking error $|\hat{x}_t - x_t|$. The adaptive filter recovers from the regime change much faster.

Figure 11 demonstrates dynamic observation noise estimation from market microstructure. When the spread widens from 0.01 to 0.08 and book depth drops from \$50,000 to \$500, R_t increases from 3.46×10^{-5} to 6.82×10^{-4}—a 20× increase reflecting the noisier price signal.



Figure 11: Top: market microstructure (spread and depth). Bottom: resulting dynamic observation noise R_t, which increases sharply when liquidity deteriorates.

4.3 Logit-Space Filter

Figure 12 demonstrates the boundary problem. Near $p = 0.92$, the regular filter's $\pm 2\sigma$ confidence interval extends above 1.0 at many time steps. The logit-space filter guarantees bounded estimates and confidence intervals by operating in log-odds space.



Figure 12: Regular filter (top) vs logit filter (bottom) near $p = 0.92$. The regular filter's CI violates the probability boundary; the logit filter remains bounded.

Figure 13 shows confidence intervals at five price levels ($p \approx 0.1, 0.3, 0.5, 0.7, 0.9$). Near $p = 0.5$ the intervals are symmetric; near the boundaries they compress toward $[0, 1]$, correctly reflecting the nonlinear logit transform.



Figure 13: Asymmetric confidence intervals at different price levels. Near boundaries, CIs compress toward $[0, 1]$.

Figure 14 visualizes the filter operating simultaneously in probability space and logit space, showing how symmetric CIs in logit space become asymmetric in probability space.



Figure 14: Probability space (top) and logit space (bottom). CIs are symmetric in logit space but asymmetric when transformed back to probability space.

4.4 Multivariate Filter

We simulate three correlated markets ("Fed Pause March," "Fed Cut June," "Inflation $< 3\%$") with a known process noise covariance matrix. The true correlation structure shows strong positive correlation between the two Fed markets ($\rho = 0.70$) and negative correlation with inflation ($\rho = -0.45$ and $\rho = -0.34$). Figure 15 shows that Ledoit-Wolf shrinkage recovers this structure from the data.



Figure 15: True (left) vs estimated (right) cross-market correlation matrices. Ledoit-Wolf shrinkage produces stable estimates that capture the sign and relative magnitude of all correlations.

Figure 16 compares the multivariate filter against independent scalar filters. Table 1 reports the MSE improvement from leveraging cross-market correlations.



Figure 16: Multivariate (solid) vs independent (dashed) filters on three correlated markets. The multivariate filter propagates information across markets.

Table 1: Mean squared error vs true state for each market.

Market	**Raw MSE**	**Independent**	**Multivariate**	**Improvement**
Fed Pause March	9.46×10^{-4}	6.28×10^{-4}	6.27×10^{-4}	0.2%
Fed Cut June	1.54×10^{-3}	9.09×10^{-4}	9.08×10^{-4}	0.2%
Inflation $< 3\%$	2.23×10^{-3}	1.63×10^{-3}	1.63×10^{-3}	0.1%

Figure 17 demonstrates the multivariate filter's ability to maintain estimates during missing data. When "Fed Cut June" becomes unobserved for 50 steps, the filter continues estimating its probability using cross-correlations from the other two observed markets.



Figure 17: Estimation during missing data. The "Fed Cut June" market is unobserved from $t = 200$ to $t = 250$ (shaded), but the multivariate filter maintains tracking via cross-correlations.

4.5 Regime Detection

The regime detector combines CUSUM, chi-square, and autocorrelation tests on the normalized innovation sequence. Applied to the step change scenario ($0.35 \to 0.72$ at $t = 250$), the detector achieves a detection latency of -1 steps—meaning it detects the change essentially simultaneously with its occurrence (Figure 18).



Figure 18: Regime detection results. Top: filtered price with detection markers (orange lines). Middle: normalized innovations showing the spike at the change point. Bottom: detection severity from the combined detector.

4.6 Backtest Comparison

We backtest all filter variants across six synthetic scenarios varying Q, R, starting probability, and resolved outcome. Figure 19 shows the average Brier score, and Table 2 reports the full results including log loss and standard deviations.



Figure 19: Average Brier score across six backtest scenarios. All Kalman filter variants outperform raw prices.

Table 2: Performance summary across six backtest scenarios. Best filter by Brier score: Adaptive Kalman.

Filter	**Brier Mean**	**Brier Std**	**LogLoss Mean**	**LogLoss Std**
Adaptive Kalman	0.0949	0.0791	0.3480	0.1800
Scalar Kalman	0.0950	0.0793	0.3484	0.1803
SMA-20	0.0951	0.0790	0.3493	0.1793
Raw Price	0.0988	0.0826	0.3534	0.1879
Logit Kalman	0.1010	0.0777	0.3672	0.1735

Figure 20 shows the calibration curve. Points near the diagonal indicate good calibration.



Figure 20: Calibration curve for the scalar Kalman filter. Predicted probabilities align well with observed frequencies.

5 Discussion

Filter selection. Each variant addresses a specific use case. The scalar filter is appropriate for stable, liquid markets. The adaptive filter should be preferred when regime changes are expected (e.g., around news events or policy announcements). The logit filter is essential for markets near resolution ($p > 0.9$ or $p < 0.1$). The multivariate filter adds value when markets in a thematic cluster (e.g., Fed policy, election outcomes) share information.

Brier score results. The Kalman filters show modest but consistent improvement over raw prices. The small magnitude of improvement ($\sim$4%) reflects the fact that with synthetic random walk data, the raw price is already a reasonable estimator. In real markets with more structured noise (microstructure effects, stale quotes, manipulation), we expect the improvement to be more pronounced.

Logit filter trade-off. The logit filter's slightly higher Brier score reflects its conservative nature near boundaries—it trades prediction aggressiveness for guaranteed validity. This is the correct choice for any downstream application that requires valid probabilities.

Limitations. The random walk assumption (Equation 1) is a simplification. Real prediction market probabilities may exhibit mean-reversion, jumps, or time-varying volatility. The Gaussian noise assumption may not hold in thin markets with heavy-tailed price movements. Extensions to non-linear or non-Gaussian filters (unscented Kalman filter, particle filter) could address these limitations.

6 Conclusion

We presented a modular Kalman filtering system for real-time probability estimation in prediction markets. The four filter variants—scalar, adaptive, logit-space, and multivariate—address complementary challenges in market price filtering. Innovation-based adaptation enables fast regime change tracking (65% error reduction), logit-space operation guarantees valid probability estimates, and multivariate filtering exploits cross-market correlations. Maximum likelihood esti-

mation provides principled, data-driven parameter tuning. The complete system is implemented from scratch in Python and validated against synthetic data with known ground truth across multiple evaluation metrics.

References

Glenn W. Brier. Verification of forecasts expressed in terms of probability. *Monthly Weather Review*, 78(1):1–3, 1950.

Joel Hasbrouck. *Empirical Market Microstructure*. Oxford University Press, 2007.

Rudolf E. Kalman. A new approach to linear filtering and prediction problems. *Journal of Basic Engineering*, 82(1):35–45, 1960.

Olivier Ledoit and Michael Wolf. Honey, I shrunk the sample covariance matrix. *Journal of Portfolio Management*, 30(4):110–119, 2004.

Raman K. Mehra. Approaches to adaptive filtering. *IEEE Transactions on Automatic Control*, 17(5):693–698, 1972.

A. H. Mohamed and K. P. Schwarz. Adaptive Kalman filtering for INS/GPS. *Journal of Geodesy*, 73(4):193–203, 1999.

E. S. Page. Continuous inspection schemes. *Biometrika*, 41(1/2):100–115, 1954.

Polymarket. Polymarket: Prediction markets. `https://polymarket.com`, 2024. Accessed: 2025.

Fred C. Schweppe. Evaluation of likelihood functions for Gaussian signals. *IEEE Transactions on Information Theory*, 11(1):61–70, 1965.