

not event(BDone(x\_12,y\_6,nx,ny)) in process 1.

**GOAL**  
event(BDone(I[],B[],nx,Nb[]))

If the message  
encrypt(msg1(I[],Na\_12),pk(skB[])) is  
received at {119}, the message  
encrypt(msg3(Nb[],pk(skB[])) is received at  
{122}, then event BDone(I[],B[],Na\_12,Nb[])  
may be executed at {124}.

then the message  
encrypt(msg3(Nb\_7),pk(skB[])) may be sent at  
output {24}

the message  
encrypt(msg2(Na\_1[],Nb\_7),pk(skA[])) is  
received at {21}  
encrypt(msg2(Na\_1[],Nb[],pk(skA[]))

then the message  
encrypt(msg2(Na\_12,Nb[],pk(skA[])) may be  
sent at output {41}

the message  
encrypt(msg1(A[],Na\_12),pk(skB[])) is  
received at {39}  
encrypt(msg1(A[],Na\_1[],pk(skB[]))

The message  
encrypt(msg1(A[],Na\_1[],pk(skB[])) may be  
sent at output {20}.

*The attacker applies function encrypt.*

apply msg1 msg1(I[],nx)

apply 2-proj-3-tuple pk(skB[])

initial knowledge I[]

hypothesis nx

The message (pk(skA[]),pk(skB[]),skI[]) may  
be sent at output {4}.