

not event(BDone(x_12,y_6,nx,ny)) in process 1.

GOAL
event(BDone(l[],B[],nx,Nb[]))

If the message
encrypt(msg1(l[],Na_12),pk(skB[])) is
received at {99}, the message
encrypt(msg3(Nb[]),pk(skB[])) is received at
{102}, then event BDone(l[],B[],Na_12,Nb[])
may be executed at {104}.

then the message
encrypt(msg3(Nb_7),pk(skB[])) may be sent at
output {14}

The attacker applies function encrypt.

the message
encrypt(msg2(Na[],Nb_7),pk(skA[])) is
received at {11}
encrypt(msg2(Na[],Nb[]),pk(skA[]))

apply msg1 msg1(l[],nx)

apply 2-proj-3-tuple pk(skB[])

then the message
encrypt(msg2(Na_12,Nb[]),pk(skA[])) may be
sent at output {51}

initial knowledge l[]

hypothesis nx

The message (pk(skA[]),pk(skB[]),skl[]) may
be sent at output {4}.

the message
encrypt(msg1(A[],Na_12),pk(skB[])) is
received at {49}
encrypt(msg1(A[],Na[]),pk(skB[]))

The message encrypt(msg1(A[],Na[]),pk(skB[]))
may be sent at output {10}.