

not event(BDone(x_4,y_2,nx,ny)) in process 1.

GOAL
event(BDone(l[],B[],nx,Nb[]))

If the message
encrypt(msg1(l[],Na_4),pk(skB[])) is received
at {43}, the message
encrypt(msg3(Nb[]),pk(skB[])) is received at
{46}, then event BDone(l[],B[],Na_4,Nb[]) may
be executed at {48}.

The applies function encrypt.

The applies function encrypt.

apply msg3 attacker(msg3(Nb[]))

duplicate

apply msg1 attacker(msg1(l[],nx))

apply 2-proj-3-tuple attacker(pk(skB[]))

apply 2-proj-msg2 attacker(Nb[])

initial knowledge attacker(l[])

hypothesis attacker(nx)

The message (pk(skA[]),pk(skB[]),skl[]) may
be sent at output {4}.

The applies function decrypt.

then the message
encrypt(msg2(Na_4,Nb[]),pk(skl[])) may be
sent at output {45}

apply 3-proj-3-tuple attacker(skl[])

If the message
encrypt(msg1(l[],Na_4),pk(skB[])) is received
at {43}

The message (pk(skA[]),pk(skB[]),skl[]) may
be sent at output {4}.

The applies function encrypt.

apply msg1 attacker(msg1(l[],Na_4))

duplicate

duplicate

any attacker(Na_4)