

not event(BDone(x_4,y_2,nx,ny)) in process 1.

GOAL
event(BDone(l[],B[],nx,Nb[]))

If the message
encrypt(msg1(l[],Na_4),pk(skB[])) is received
at {43}, the message
encrypt(msg3(Nb[]),pk(skB[])) is received at
{46}, then event BDone(l[],B[],Na_4,Nb[]) may
be executed at {48}.

then the message
encrypt(msg3(Nb_3),pk(skB[])) may be sent at
output {15}

The attacker applies function encrypt.

If the message
encrypt(msg2(Na_4,Nb_3),pk(skA[])) is
received at {12}
encrypt(msg2(Na_4,Nb[]),pk(skA[]))

then the message
encrypt(msg2(Na_4,Nb[]),pk(skA[])) may be
sent at output {23}

If the message
encrypt(msg1(A[],Na_4),pk(skB[])) is received
at {21}
encrypt(msg1(A[],Na_4),pk(skB[]))

The message encrypt(msg1(A[],Na_4),pk(skB[]))
may be sent at output {11}.

apply msg1 msg1(l[],nx)

apply 2-proj-3-tuple pk(skB[])

initial knowledge l[]

hypothesis nx

The message (pk(skA[]),pk(skB[]),skl[]) may
be sent at output {4}.