

- Exchange Rates
- Configuration
- Currency Converter
- Function Buttons
- Configuration
 - UDF forms
 - Multi Button Configuration
 - Data launcher
 - Data launcher: Main window
 - Data launcher: Function configuration
 - Data launcher: Add/edit lines
- Item Placement Tool
 - Basic configuration
 - On the Fly configurations
 - Configuration
 - Introduction to windows and pivots
 - Understanding panelevels
 - SAP Business One sizing rules
 - The limitations in screen layout
- Kanban Boards
 - Kanban Administration
 - Add/Edit Kanban Boards
 - Import/ Export Kanban Board
- Letter Merge
 - Create a Microsoft Word Template
 - The Merge table Configuration
 - Daily Use
- Make Items Read Only
 - Configuration
- Mandatory Fields
 - Configuration
 - Daily use
- Master Data Manager
 - Master Data Managers
 - Step 1 - Apply conditions and find data
 - Step 2 - Select Business Partners that need to be modified
 - Step 3 - Select values that need to change
 - Step 4 - Apply transactions if needed and execute
 - Form-Settings Manager
 - Authorization Manager
 - Metadata Manager
 - Import
 - Replace Sales Employee
 - Export
 - Security
 - Mass update Lines
 - Draft Data Manager
 - Prefill Extension
 - PLD Extensions
 - Quick Create
 - Recurring Invoices
 - Right-click menu creator
 - Tab Control
 - Tab Wizard
 - Template System
 - Toolbox
 - Universal Functions
 - Technical Reference
 - Appendix 1 - Dynamic Syntax

Schedule

Schedules are a powerful type of configurations that together with our server component allows you to modify common data on existing objects on a minutely, hourly, daily, weekly or monthly schedule.
NOTE: YOU CANNOT SETUP SCHEDULES BEFORE THE SERVER COMPONENT HAS BEEN INSTALLED AND ACTIVATED.

Master Data Manager Schedule (2019-09-30 10:33:10) MSSQL (2020102015)

NameBusiness PartnerNumber8

TypeBusiness PartnerUse transaction

SQLSELECT DISTINCT OCDO.CatCode FROM OCDO

Condition

Header Field (S)	User-Defined Fields (S)	Properties (S)	Charge	Value	Schedule
Property	Type	Charge	Value	Schedule	
AcceptedIndorredChecks	DBL click to choose				
AccountCriteria	DBL click to choose				
AddressCatID	String				
Address	String				
Affiliate	DBL click to choose				
AgentCode	String				
AltName	String				
AttachmentEntry	Integer				
AutomaticPosting	DBL click to choose				
AvanRate	Integer				
BackOrder	DBL click to choose				
BankChargeAllocationCode	String				
BankCountry	String				
BillExchangeCollection	String				
BillExchangePurRoom	String				
BillDefault	String				
Block	String				
BlockCurring	DBL click to choose				
BlockEndingPostingContext	DBL click to choose				
BlockkeepingCertified	DBL click to choose				
BlockID	String				

Tell You can use PROPERTY<propertyname> to copy the value of that property

Tell You can use SQL<SQL> ref. to ref. value. In the SQL you can use DocKeyID for key

Warning: Updating many objects can potentially take a very long time. If you do not wish this to affect daily operations it is recommended to do it outside normal work hours

☒ Active

Success email

Error email

AddCancelPreview

Part	Description																		
Header data	<table><tr><th>Field</th><th>Description</th></tr><tr><td>Change</td><td>This is your name for the configuration for reference, this is also the name that will be shown in success and error emails from the scheduler.</td></tr><tr><td>Type</td><td>The type of object there will be updated</td></tr><tr><td>Use transaction</td><td>Here you may be the updates should happen in a transaction</td></tr><tr><td>SQL</td><td>Shows the standard SQL there will be used to find the objects there should be updated</td></tr><tr><td>Condition</td><td>Here you can write the condition for the SQL, there is used determine which objects should be updated.</td></tr><tr><td>Success email</td><td>If set you will receive an email confirming that the schedule where run correctly.</td></tr><tr><td>Error email</td><td>The email that will receive an error report if the schedule encounters and error.</td></tr><tr><td>Preview button</td><td>The preview button will show you a list containing all the primary keys there will be found by running the SQL with the given condition</td></tr></table>	Field	Description	Change	This is your name for the configuration for reference, this is also the name that will be shown in success and error emails from the scheduler.	Type	The type of object there will be updated	Use transaction	Here you may be the updates should happen in a transaction	SQL	Shows the standard SQL there will be used to find the objects there should be updated	Condition	Here you can write the condition for the SQL, there is used determine which objects should be updated.	Success email	If set you will receive an email confirming that the schedule where run correctly.	Error email	The email that will receive an error report if the schedule encounters and error.	Preview button	The preview button will show you a list containing all the primary keys there will be found by running the SQL with the given condition
Field	Description																		
Change	This is your name for the configuration for reference, this is also the name that will be shown in success and error emails from the scheduler.																		
Type	The type of object there will be updated																		
Use transaction	Here you may be the updates should happen in a transaction																		
SQL	Shows the standard SQL there will be used to find the objects there should be updated																		
Condition	Here you can write the condition for the SQL, there is used determine which objects should be updated.																		
Success email	If set you will receive an email confirming that the schedule where run correctly.																		
Error email	The email that will receive an error report if the schedule encounters and error.																		
Preview button	The preview button will show you a list containing all the primary keys there will be found by running the SQL with the given condition																		
Header Field Tab	<table><tr><th>Field</th><th>Description</th></tr><tr><td>Type Column</td><td>Here you can see what kind of value there is valid for the properties</td></tr><tr><td>Change Column</td><td>this column tell decides if a given property should be updated</td></tr><tr><td>Value</td><td>Here you write the value the properties should be updated with. TIP: IT IS POSSIBLE IN THE VALUE TO WRITE PROPERTY<NAME OF SQL RE PROPERTY> TO GET THE VALUE FROM AN EXISTING FIELD. EXAMPLE: PROPERTY.CARDNAME TIP: IT IS POSSIBLE IN THE VALUE TO WRITE SQL<<SQL SENTENCE>> TO GET THE VALUE FROM AN EXISTING FIELD. YOU CAN USE DOCKEYID TO REFER TO THE CURRENTLY UPDATING PRIMARY KEY. EXAMPLE: SQL.SELECT COUNT(*) FROM INVW WHERE CARCODE = 'DOCKEYID'.</td></tr></table>	Field	Description	Type Column	Here you can see what kind of value there is valid for the properties	Change Column	this column tell decides if a given property should be updated	Value	Here you write the value the properties should be updated with. TIP: IT IS POSSIBLE IN THE VALUE TO WRITE PROPERTY<NAME OF SQL RE PROPERTY> TO GET THE VALUE FROM AN EXISTING FIELD. EXAMPLE: PROPERTY.CARDNAME TIP: IT IS POSSIBLE IN THE VALUE TO WRITE SQL<<SQL SENTENCE>> TO GET THE VALUE FROM AN EXISTING FIELD. YOU CAN USE DOCKEYID TO REFER TO THE CURRENTLY UPDATING PRIMARY KEY. EXAMPLE: SQL.SELECT COUNT(*) FROM INVW WHERE CARCODE = 'DOCKEYID'.										
Field	Description																		
Type Column	Here you can see what kind of value there is valid for the properties																		
Change Column	this column tell decides if a given property should be updated																		
Value	Here you write the value the properties should be updated with. TIP: IT IS POSSIBLE IN THE VALUE TO WRITE PROPERTY<NAME OF SQL RE PROPERTY> TO GET THE VALUE FROM AN EXISTING FIELD. EXAMPLE: PROPERTY.CARDNAME TIP: IT IS POSSIBLE IN THE VALUE TO WRITE SQL<<SQL SENTENCE>> TO GET THE VALUE FROM AN EXISTING FIELD. YOU CAN USE DOCKEYID TO REFER TO THE CURRENTLY UPDATING PRIMARY KEY. EXAMPLE: SQL.SELECT COUNT(*) FROM INVW WHERE CARCODE = 'DOCKEYID'.																		
UDF Tab	<table><tr><th>Field</th><th>Description</th></tr><tr><td>Change Column</td><td>this column tell decides if a given Udf should be updated</td></tr><tr><td>Value</td><td>Here you write the value the Udf should be updated with. TIP: IT IS POSSIBLE IN THE VALUE TO WRITE PROPERTY<NAME OF SQL RE PROPERTY> TO GET THE VALUE FROM AN EXISTING FIELD. EXAMPLE: PROPERTY.CARDNAME TIP: IT IS POSSIBLE IN THE VALUE TO WRITE SQL<<SQL SENTENCE>> TO GET THE VALUE FROM AN EXISTING FIELD. YOU CAN USE DOCKEYID TO REFER TO THE CURRENTLY UPDATING PRIMARY KEY. EXAMPLE: SQL.SELECT COUNT(*) FROM INVW WHERE CARCODE = 'DOCKEYID'.</td></tr></table>	Field	Description	Change Column	this column tell decides if a given Udf should be updated	Value	Here you write the value the Udf should be updated with. TIP: IT IS POSSIBLE IN THE VALUE TO WRITE PROPERTY<NAME OF SQL RE PROPERTY> TO GET THE VALUE FROM AN EXISTING FIELD. EXAMPLE: PROPERTY.CARDNAME TIP: IT IS POSSIBLE IN THE VALUE TO WRITE SQL<<SQL SENTENCE>> TO GET THE VALUE FROM AN EXISTING FIELD. YOU CAN USE DOCKEYID TO REFER TO THE CURRENTLY UPDATING PRIMARY KEY. EXAMPLE: SQL.SELECT COUNT(*) FROM INVW WHERE CARCODE = 'DOCKEYID'.												
Field	Description																		
Change Column	this column tell decides if a given Udf should be updated																		
Value	Here you write the value the Udf should be updated with. TIP: IT IS POSSIBLE IN THE VALUE TO WRITE PROPERTY<NAME OF SQL RE PROPERTY> TO GET THE VALUE FROM AN EXISTING FIELD. EXAMPLE: PROPERTY.CARDNAME TIP: IT IS POSSIBLE IN THE VALUE TO WRITE SQL<<SQL SENTENCE>> TO GET THE VALUE FROM AN EXISTING FIELD. YOU CAN USE DOCKEYID TO REFER TO THE CURRENTLY UPDATING PRIMARY KEY. EXAMPLE: SQL.SELECT COUNT(*) FROM INVW WHERE CARCODE = 'DOCKEYID'.																		
Properties Tab (BP and Items Only)	<table><tr><th>Field</th><th>Description</th></tr><tr><td>Property</td><td>Name of the property</td></tr><tr><td>Value</td><td>The value to be set for the property</td></tr></table>	Field	Description	Property	Name of the property	Value	The value to be set for the property												
Field	Description																		
Property	Name of the property																		
Value	The value to be set for the property																		
Schedule	<table><tr><th>Field</th><th>Description</th></tr><tr><td>Server start time (24 H/M)</td><td>When the schedule should be executed the first time.</td></tr><tr><td>Recurrence pattern</td><td>There are currently five supported types: Minutely: Run the schedule every X minutes. Hourly: Run the schedule every X hours. Daily: Run the schedule once each day on the server start time. Weekly: Run the schedule on specific days of the week on the server time. Monthly: Run the schedule every X day of the month on the server time. Only ones: Run the schedule only on the start date and the server start time. Last day of month: Run the schedule on the last day of the month on the server start time (hour and minute)</td></tr><tr><td>Range of recurrence</td><td>Start: Start date of the recurrence. No end date: The schedule should never end. End by: The schedule should end by the specific date.</td></tr></table>	Field	Description	Server start time (24 H/M)	When the schedule should be executed the first time.	Recurrence pattern	There are currently five supported types: Minutely: Run the schedule every X minutes. Hourly: Run the schedule every X hours. Daily: Run the schedule once each day on the server start time. Weekly: Run the schedule on specific days of the week on the server time. Monthly: Run the schedule every X day of the month on the server time. Only ones: Run the schedule only on the start date and the server start time. Last day of month: Run the schedule on the last day of the month on the server start time (hour and minute)	Range of recurrence	Start: Start date of the recurrence. No end date: The schedule should never end. End by: The schedule should end by the specific date.										
Field	Description																		
Server start time (24 H/M)	When the schedule should be executed the first time.																		
Recurrence pattern	There are currently five supported types: Minutely: Run the schedule every X minutes. Hourly: Run the schedule every X hours. Daily: Run the schedule once each day on the server start time. Weekly: Run the schedule on specific days of the week on the server time. Monthly: Run the schedule every X day of the month on the server time. Only ones: Run the schedule only on the start date and the server start time. Last day of month: Run the schedule on the last day of the month on the server start time (hour and minute)																		
Range of recurrence	Start: Start date of the recurrence. No end date: The schedule should never end. End by: The schedule should end by the specific date.																		