

Beyond Consumer-Driven Contract Testing



NICOLE RAUCH
software development &
development coaching

Soooo...

- ▶ We want to build this nice webapp / distributed system / these microservices
- ▶ We want to make sure “Frontend” and “Backend” play nicely together

Soooo...

- ▶ We want to build this nice webapp / distributed system / these microservices
- ▶ We want to make sure “Frontend” and “Backend” play nicely together
- ▶ HOW???

“Super-Naïve” Approach

Frontend

Backend




Frontend

Backend




Frontend

Backend




Frontend

Backend



Frontend


Backend



But . . .


Frontend

Backend




Frontend

Backend




Frontend

Backend



Frontend

Backend



“Still Quite Naïve” Approach

Frontend

Backend



Frontend

Backend



Frontend



Backend




Frontend




Backend



Frontend



Backend




But . . .

Frontend




Backend




Frontend


Backend



Frontend





Backend



Frontend

Backend



“Industry-Strength” Approach: Consumer-Driven Contract Testing







Generate



SINON.JS



Use in Dev





SINON.JS




Generate











Welcome to our Pet Store

Add a New Pet

Pet name:

Pet price:

Species:



Add Pet

Pets in our Store



Dodo

Sell Dodo



Fifi

Sell Fifi



Minka

Sell Minka



Welcome to our Pet Store

Add a New Pet

Pet name:

Pet price:

Species:



Add Pet

Pets in our Store

GET



Dodo

Sell Dodo



Fifi

Sell Fifi



Minka

Sell Minka


Welcome to our Pet Store

Add a New Pet

Pet name:

Pet price:

Species:



Add Pet

Pets in our Store



Dodo

Sell Dodo



Fifi

Sell Fifi



Minka

Sell Minka

POST



Welcome to our Pet Store

Add a New Pet

Pet name:

Pet price:

Species:



Add Pet

Pets in our Store



Dodo

Sell Dodo



Fifi

Sell Fifi



Minka

Sell Minka

DELETE

Example: Pet Store Contracts I

```
{
  "description": "a request for all pets",
  "providerState": "i have no pets",
  "request": {
    "method": "GET",
    "path": "/pets",
    "headers": { "Accept": "application/json" }
  },
  "response": {
    "status": 200,
    "headers": { "Content-Type": "application/json" },
    "body": {
      "tag": "Pets",
      "pets": []
    }
  }
}
```

Situation

- ▶ GET-Request

Situation

- ▶ GET-Request
- ▶ Does not depend on state

Situation

- ▶ GET-Request
- ▶ Does not depend on state
- ▶ Easy to handle with CDCT

Questions

- ▶ Completeness

Questions

- ▶ Completeness
 - ▶ Did we really capture all requests (+ responses) in our contract?

Example: Pet Store Contracts II

```
{
  "description": "a request for all pets",
  "providerState": "i have a list of pets",
  "request": {
    "method": "GET",
    "path": "/pets",
    "headers": { "Accept": "application/json" }
  },
  "response": {
    "status": 200,
    "headers": { "Content-Type": "application/json" },
    "body": {
      "tag": "Pets",
      "pets": [
        { "petName": "Fifi", "petType": "Dog" },
        { "petName": "Minki", "petType": "Cat" }
      ]
    }
  }
}
```

Situation

- ▶ GET-Request that depends on state

Situation

- ▶ GET-Request that depends on state
- ▶ POST-/PUT-/DELETE-Requests

Situation

- ▶ GET-Request that depends on state
- ▶ POST-/PUT-/DELETE-Requests
- ▶ Difficult to handle with CDCT

Situation

- ▶ GET-Request that depends on state
- ▶ POST-/PUT-/DELETE-Requests
- ▶ Difficult to handle with CDCT
- ▶ Backend state needs to be established somehow

Situation

- ▶ GET-Request that depends on state
- ▶ POST-/PUT-/DELETE-Requests
- ▶ Difficult to handle with CDCT
- ▶ Backend state needs to be established somehow
- ▶ State checks need to be established somehow

Questions

- ▶ Completeness

Questions

- ▶ Completeness
 - ▶ Did we really capture all requests (+ responses) in our contract?

Questions

- ▶ Completeness
 - ▶ Did we really capture all requests (+ responses) in our contract?
 - ▶ All possible combinations with different backend states?

Questions

- ▶ Completeness
 - ▶ Did we really capture all requests (+ responses) in our contract?
 - ▶ All possible combinations with different backend states?
- ▶ State Validity

Questions

- ▶ Completeness
 - ▶ Did we really capture all requests (+ responses) in our contract?
 - ▶ All possible combinations with different backend states?
- ▶ State Validity
 - ▶ What are valid states in our stub?

Questions

- ▶ Completeness

- ▶ Did we really capture all requests (+ responses) in our contract?
- ▶ All possible combinations with different backend states?

- ▶ State Validity

- ▶ What are valid states in our stub?
- ▶ Did we always establish a valid state in our stub?

Questions

- ▶ Completeness
 - ▶ Did we really capture all requests (+ responses) in our contract?
 - ▶ All possible combinations with different backend states?
- ▶ State Validity
 - ▶ What are valid states in our stub?
 - ▶ Did we always establish a valid state in our stub?
 - ▶ How do we establish them (technically) before the request?

Questions

- ▶ Completeness

- ▶ Did we really capture all requests (+ responses) in our contract?
- ▶ All possible combinations with different backend states?

- ▶ State Validity

- ▶ What are valid states in our stub?
- ▶ Did we always establish a valid state in our stub?
- ▶ How do we establish them (technically) before the request?
- ▶ How do we validate them after the (modifying) request?

Questions

- ▶ Completeness
 - ▶ Did we really capture all requests (+ responses) in our contract?
 - ▶ All possible combinations with different backend states?
- ▶ State Validity
 - ▶ What are valid states in our stub?
 - ▶ Did we always establish a valid state in our stub?
 - ▶ How do we establish them (technically) before the request?
 - ▶ How do we validate them after the (modifying) request?
- ▶ Maintenance

Questions

▶ Completeness

- ▶ Did we really capture all requests (+ responses) in our contract?
- ▶ All possible combinations with different backend states?

▶ State Validity

- ▶ What are valid states in our stub?
- ▶ Did we always establish a valid state in our stub?
- ▶ How do we establish them (technically) before the request?
- ▶ How do we validate them after the (modifying) request?

▶ Maintenance

- ▶ How can we keep track of our contracts and avoid redundancies?

Questions

▶ Completeness

- ▶ Did we really capture all requests (+ responses) in our contract?
- ▶ All possible combinations with different backend states?

▶ State Validity

- ▶ What are valid states in our stub?
- ▶ Did we always establish a valid state in our stub?
- ▶ How do we establish them (technically) before the request?
- ▶ How do we validate them after the (modifying) request?

▶ Maintenance

- ▶ How can we keep track of our contracts and avoid redundancies?
- ▶ How can we effectively maintain the contracts in case of changes?

We need the Functional Essence!



Sounds cool, but...

Sounds cool, but...

...what does that mean?

Functional Essence

- ▶ Fake Server

Functional Essence

- ▶ Fake Server
- ▶ Lightweight Implementation

Functional Essence

- ▶ Fake Server
- ▶ Lightweight Implementation
- ▶ Model

Functional Essence

- ▶ Fake Server
- ▶ Lightweight Implementation
- ▶ Model
- ▶ Rapid Prototype

Functional Essence

- ▶ Fake Server
- ▶ Lightweight Implementation
- ▶ Model
- ▶ Rapid Prototype
- ▶ Minimal Viable Product

Functional Essence Serves Many Purposes

- ▶ To learn about the domain

Functional Essence Serves Many Purposes


- ▶ To learn about the domain
- ▶ To discuss with domain experts


Functional Essence Serves Many Purposes


- ▶ To learn about the domain
- ▶ To discuss with domain experts
- ▶ To validate assumptions at an early stage

Functional Essence Serves Many Purposes

- ▶ To learn about the domain
- ▶ To discuss with domain experts
- ▶ To validate assumptions at an early stage
- ▶ To check the real implementation:










Use in Dev



Compare



Sounds cool, but...

Sounds cool, but...

...how can I build this?

How to Build a Functional Essence

- ▶ Implement the domain logic

How to Build a Functional Essence

- ▶ Implement the domain logic
- ▶ In the simplest possible way

How to Build a Functional Essence

- ▶ Implement the domain logic
- ▶ In the simplest possible way
- ▶ In an arbitrary language

How to Build a Functional Essence

- ▶ Implement the domain logic
- ▶ In the simplest possible way
- ▶ In an arbitrary language



The Pets Essence

```
class Pets {
  constructor(){
    this._pets = [];
  }

  getPets() {
    return petSorter.sortPets(this._pets);
  }

  addPet(pet) {
    this._pets.push(pet);
    return 'Pet successfully added.';
  }

  removePet(pet) {
    this._pets = this._pets.filter(
      p => p.petName !== pet.petName || p.petType !== pet.petType);
    return 'Pet successfully removed.';
  }
}
```

The Overall Essence

```
class Essence {  
    constructor() {  
        this._pets = new Pets();  
        this._somethingElse = new SomethingElse();  
    }  
  
    pets() {  
        return this._pets;  
    }  
  
    somethingElse() {  
        return this._somethingElse;  
    }  
}
```

The Essence App

```
let essence = new Essence();

router.get('/pets', (req, res) => {
  const pets = essence.pets().getPets();
  res.json({tag: 'Pets', pets});
});

router.post('/pets', (req, res) => {
  const message = essence.pets().addPet({ petName: req.body.petName,
    petPrice: req.body.petPrice, petType: req.body.petType });
  res.json({message});
});

router.delete('/pets', (req, res) => {
  const message = essence.pets().removePet({ petName: req.body.petName,
    petPrice: req.body.petPrice, petType: req.body.petType });
  res.json({message});
});
```

Important Addition

```
router.delete('/reset', (req, res) => {  
  essence = new Essence();  
  res.json({message: 'All pets successfully removed.'});  
});
```

Isn't That The Same Code As The Backend?

Isn't That The Same Code As The Backend?

- ▶ Maybe... but usually not:

Isn't That The Same Code As The Backend?

- ▶ Maybe... but usually not:
- ▶ Can be in another language

Isn't That The Same Code As The Backend?

- ▶ Maybe... but usually not:
- ▶ Can be in another language
- ▶ Can use simpler datatypes (e.g. List vs. HashMap)

Isn't That The Same Code As The Backend?

- ▶ Maybe... but usually not:
- ▶ Can be in another language
- ▶ Can use simpler datatypes (e.g. List vs. HashMap)
- ▶ No performance-tuning (e.g. slower but simpler algorithms)

Isn't That The Same Code As The Backend?

- ▶ Maybe... but usually not:
- ▶ Can be in another language
- ▶ Can use simpler datatypes (e.g. List vs. HashMap)
- ▶ No performance-tuning (e.g. slower but simpler algorithms)
- ▶ No technical overhead (e.g. database)

Isn't That The Same Code As The Backend?

- ▶ Maybe... but usually not:
- ▶ Can be in another language
- ▶ Can use simpler datatypes (e.g. List vs. HashMap)
- ▶ No performance-tuning (e.g. slower but simpler algorithms)
- ▶ No technical overhead (e.g. database)
- ▶ Some parts can be left out

Isn't That The Same Code As The Backend?

- ▶ Maybe... but usually not:
- ▶ Can be in another language
- ▶ Can use simpler datatypes (e.g. List vs. HashMap)
- ▶ No performance-tuning (e.g. slower but simpler algorithms)
- ▶ No technical overhead (e.g. database)
- ▶ Some parts can be left out
- ▶ ...

How does the Comparison work?

Detour: Quick Check / Property-Based Testing

Detour: Quick Check / Property-Based Testing

- ▶ User specifies properties
- ▶ Tool generates examples
- ▶ Checks properties against examples

Detour: Quick Check / Property-Based Testing

- ▶ User specifies properties
- ▶ Tool generates examples
- ▶ Checks properties against examples

```
prop_RevRev xs = reverse (reverse xs) == xs  
  where types = xs::[Int]
```

Detour: Quick Check / Property-Based Testing

- ▶ User specifies properties
- ▶ Tool generates examples
- ▶ Checks properties against examples

```
prop_RevRev xs = reverse (reverse xs) == xs  
  where types = xs::[Int]
```

```
Main> quickCheck prop_RevRev  
OK, passed 100 tests.
```

Detour: Quick Check / Property-Based Testing

- ▶ User specifies properties
- ▶ Tool generates examples
- ▶ Checks properties against examples

```
prop_RevRev xs = reverse (reverse xs) == xs  
  where types = xs::[Int]
```

```
Main> quickCheck prop_RevRev  
OK, passed 100 tests.
```

```
prop_RevId xs = reverse xs == xs  
  where types = xs::[Int]
```

Detour: Quick Check / Property-Based Testing

- ▶ User specifies properties
- ▶ Tool generates examples
- ▶ Checks properties against examples

```
prop_RevRev xs = reverse (reverse xs) == xs  
  where types = xs::[Int]
```

```
Main> quickCheck prop_RevRev  
OK, passed 100 tests.
```

```
prop_RevId xs = reverse xs == xs  
  where types = xs::[Int]
```

```
Main> quickCheck prop_RevId  
Falsifiable, after 1 tests:  
[-3,15]
```


How to Mimic QuickCheck?

Reset

Reset



Random
Queries




Reset





Modify




Check









Comparator Implementation

Pet Generator

```
const chooseFrom = arr => arr[Math.floor(arr.length * Math.random())];

const possibleNames = ['A', 'B', 'C'];
const possibleSpecies = ['Cat', 'Dog', 'Canary', 'Rabbit', 'Fish'];

const name = () => chooseFrom(possibleNames);
const price = () => Math.floor(150 * Math.random());
const species = () => chooseFrom(possibleSpecies);

const randomPet = () =>
  ({petName: name(), petPrice: price(), petType: species()});
```

Request Generator

```
const resets = [  
  // delete all pets  
  () => ({url: '/reset', method: 'DELETE'}),  
];  
  
const modifyingRequestGenerator = [  
  // addPet  
  () => ({url: '/pets', method: 'POST', json: true, body: randomPet()}),  
  // removePet  
  () => ({url: '/pets', method: 'DELETE', json: true, body: randomPet()})  
];  
  
const comparisons = [  
  // getPets  
  () => ({url: '/pets', method: 'GET'}),  
];
```

Query Submission

```
const backend = {baseUrl: 'http://localhost:9090'};
const essence = {baseUrl: 'http://localhost:8080'};

const merge = (req, server) =>
  Object.assign({}, req, {url: server.baseUrl + req.url});

const requestFunctionFor = (req, server) =>
  callback => request(merge(req, server),
    (err, response) => callback(err, response.body));

const runRequest = (req, callback) => {
  console.log('Now checking:', req);
  async.parallel({
    backend: requestFunctionFor(req, backend),
    essence: requestFunctionFor(req, essence)
  }, callback);
};
```

Request-Compare-Loop

```
const requestAndCompare = (request, mainCallback) => {  
  
  console.log('Running the modification request:');  
  
  runRequest(request, (err, result) => {  
    const backendString = JSON.stringify(result.backend);  
    const essenceString = JSON.stringify(result.essence);  
  
    if (backendString !== essenceString) {  
      mainCallback('Backend and Essence responses differ! Backend: '  
        + backendString + ' - Essence: ' + essenceString);  
    } else {  
  
      console.log('Comparing all data:');  
      compareEverything(mainCallback);  
    }  
  });  
};
```

Comparisons

```
function compareEverything(mainCallback) {
  async.map(comparisons, (itemFunc, callback) =>
    runRequest(itemFunc(), (err, res) => {
      if (res.backend === res.essence) {
        callback(null, null); // no differences
      } else {
        const formatDiff = formatter.formatDiff({
          backend: JSON.parse(res.backend),
          essence: JSON.parse(res.essence)
        });
        callback(null, formatDiff);
      }
    }),
    (err, results) => {
      const nonmatching = results.filter(x => x);
      mainCallback(nonmatching.length
        ? 'Backend and Essence differ in their data' : null);
    });
}
```

The Main Loop

```
const requests = [resets[0]()]; // initial reset

let count = 0;

while (count < 50) {
  count++;
  requests.push(chooseFrom(modifyingRequestGenerator()));
}

async.mapSeries(requests, requestAndCompare, (err, results) => {
  results.map(result => console.log(result));
  if (err) {
    console.log(err);
  }
});
```

Questions – and Answers

- ▶ Completeness
 - ▶ Did we really capture all requests (+ responses) in our contract?
 - ▶ All possible combinations with different backend states?

Questions – and Answers

- ▶ Completeness
 - ▶ Did we really capture all requests (+ responses) in our contract?
 - ▶ All possible combinations with different backend states?
- ▶ CDCT:

Questions – and Answers

- ▶ Completeness
 - ▶ Did we really capture all requests (+ responses) in our contract?
 - ▶ All possible combinations with different backend states?
- ▶ CDCT:
 - ▶ We must write all tests ourselves

Questions – and Answers

- ▶ Completeness
 - ▶ Did we really capture all requests (+ responses) in our contract?
 - ▶ All possible combinations with different backend states?
- ▶ CDCT:
 - ▶ We must write all tests ourselves
 - ▶ We are responsible for completeness

Questions – and Answers

- ▶ Completeness
 - ▶ Did we really capture all requests (+ responses) in our contract?
 - ▶ All possible combinations with different backend states?
- ▶ CDCT:
 - ▶ We must write all tests ourselves
 - ▶ We are responsible for completeness
- ▶ Beyond CDCT:

Questions – and Answers

- ▶ Completeness
 - ▶ Did we really capture all requests (+ responses) in our contract?
 - ▶ All possible combinations with different backend states?
- ▶ CDCT:
 - ▶ We must write all tests ourselves
 - ▶ We are responsible for completeness
- ▶ Beyond CDCT:
 - ▶ QuickCheck approach: We don't write tests

Questions – and Answers

- ▶ Completeness
 - ▶ Did we really capture all requests (+ responses) in our contract?
 - ▶ All possible combinations with different backend states?
- ▶ CDCT:
 - ▶ We must write all tests ourselves
 - ▶ We are responsible for completeness
- ▶ Beyond CDCT:
 - ▶ QuickCheck approach: We don't write tests
 - ▶ We only specify the possible routes

Questions – and Answers

- ▶ Completeness
 - ▶ Did we really capture all requests (+ responses) in our contract?
 - ▶ All possible combinations with different backend states?
- ▶ CDCT:
 - ▶ We must write all tests ourselves
 - ▶ We are responsible for completeness
- ▶ Beyond CDCT:
 - ▶ QuickCheck approach: We don't write tests
 - ▶ We only specify the possible routes
 - ▶ Completeness is established over time

Questions – and Answers

▶ State Validity

- ▶ What are valid states in our stub?
- ▶ Did we always establish a valid state in our stub?
- ▶ How do we establish them (technically) before the request?
- ▶ How do we validate them after the (modifying) request?

Questions – and Answers

- ▶ State Validity

- ▶ What are valid states in our stub?
- ▶ Did we always establish a valid state in our stub?
- ▶ How do we establish them (technically) before the request?
- ▶ How do we validate them after the (modifying) request?

- ▶ CDCT:

Questions – and Answers

- ▶ State Validity
 - ▶ What are valid states in our stub?
 - ▶ Did we always establish a valid state in our stub?
 - ▶ How do we establish them (technically) before the request?
 - ▶ How do we validate them after the (modifying) request?
- ▶ CDCT:
 - ▶ We establish the state ourselves for each test

Questions – and Answers

- ▶ State Validity
 - ▶ What are valid states in our stub?
 - ▶ Did we always establish a valid state in our stub?
 - ▶ How do we establish them (technically) before the request?
 - ▶ How do we validate them after the (modifying) request?
- ▶ CDCT:
 - ▶ We establish the state ourselves for each test
 - ▶ We are responsible for the state's correctness

Questions – and Answers

- ▶ State Validity
 - ▶ What are valid states in our stub?
 - ▶ Did we always establish a valid state in our stub?
 - ▶ How do we establish them (technically) before the request?
 - ▶ How do we validate them after the (modifying) request?
- ▶ CDCT:
 - ▶ We establish the state ourselves for each test
 - ▶ We are responsible for the state's correctness
- ▶ Beyond CDCT:

Questions – and Answers

- ▶ State Validity
 - ▶ What are valid states in our stub?
 - ▶ Did we always establish a valid state in our stub?
 - ▶ How do we establish them (technically) before the request?
 - ▶ How do we validate them after the (modifying) request?
- ▶ CDCT:
 - ▶ We establish the state ourselves for each test
 - ▶ We are responsible for the state's correctness
- ▶ Beyond CDCT:
 - ▶ The state is established through API calls

Questions – and Answers

- ▶ State Validity
 - ▶ What are valid states in our stub?
 - ▶ Did we always establish a valid state in our stub?
 - ▶ How do we establish them (technically) before the request?
 - ▶ How do we validate them after the (modifying) request?
- ▶ CDCT:
 - ▶ We establish the state ourselves for each test
 - ▶ We are responsible for the state's correctness
- ▶ Beyond CDCT:
 - ▶ The state is established through API calls
 - ▶ The state is always reachable and correct*

Questions – and Answers

- ▶ State Validity
 - ▶ What are valid states in our stub?
 - ▶ Did we always establish a valid state in our stub?
 - ▶ How do we establish them (technically) before the request?
 - ▶ How do we validate them after the (modifying) request?
- ▶ CDCT:
 - ▶ We establish the state ourselves for each test
 - ▶ We are responsible for the state's correctness
- ▶ Beyond CDCT:
 - ▶ The state is established through API calls
 - ▶ The state is always reachable and correct*

*Assuming no coding errors!

Questions – and Answers

- ▶ Maintenance

- ▶ How can we keep track of our contracts and avoid redundancies?
- ▶ How can we effectively maintain the contracts in case of changes?

Questions – and Answers

- ▶ Maintenance
 - ▶ How can we keep track of our contracts and avoid redundancies?
 - ▶ How can we effectively maintain the contracts in case of changes?
- ▶ CDCT:

Questions – and Answers

- ▶ Maintenance
 - ▶ How can we keep track of our contracts and avoid redundancies?
 - ▶ How can we effectively maintain the contracts in case of changes?
- ▶ CDCT:
 - ▶ As difficult as maintaining normal tests

Questions – and Answers

- ▶ Maintenance
 - ▶ How can we keep track of our contracts and avoid redundancies?
 - ▶ How can we effectively maintain the contracts in case of changes?
- ▶ CDCT:
 - ▶ As difficult as maintaining normal tests
 - ▶ Code coverage helps identify uncovered areas

Questions – and Answers

- ▶ Maintenance
 - ▶ How can we keep track of our contracts and avoid redundancies?
 - ▶ How can we effectively maintain the contracts in case of changes?
- ▶ CDCT:
 - ▶ As difficult as maintaining normal tests
 - ▶ Code coverage helps identify uncovered areas
- ▶ Beyond CDCT:

Questions – and Answers

- ▶ Maintenance
 - ▶ How can we keep track of our contracts and avoid redundancies?
 - ▶ How can we effectively maintain the contracts in case of changes?
- ▶ CDCT:
 - ▶ As difficult as maintaining normal tests
 - ▶ Code coverage helps identify uncovered areas
- ▶ Beyond CDCT:
 - ▶ We need to make sure that the driver knows all routes

Questions – and Answers

- ▶ Maintenance
 - ▶ How can we keep track of our contracts and avoid redundancies?
 - ▶ How can we effectively maintain the contracts in case of changes?
- ▶ CDCT:
 - ▶ As difficult as maintaining normal tests
 - ▶ Code coverage helps identify uncovered areas
- ▶ Beyond CDCT:
 - ▶ We need to make sure that the driver knows all routes
 - ▶ Code coverage helps identify missing routes

Questions – and Answers

- ▶ Maintenance
 - ▶ How can we keep track of our contracts and avoid redundancies?
 - ▶ How can we effectively maintain the contracts in case of changes?
- ▶ CDCT:
 - ▶ As difficult as maintaining normal tests
 - ▶ Code coverage helps identify uncovered areas
- ▶ Beyond CDCT:
 - ▶ We need to make sure that the driver knows all routes
 - ▶ Code coverage helps identify missing routes
 - ▶ Missing routes in Essence will be discovered because of errors

Questions – and Answers

- ▶ Maintenance
 - ▶ How can we keep track of our contracts and avoid redundancies?
 - ▶ How can we effectively maintain the contracts in case of changes?
- ▶ CDCT:
 - ▶ As difficult as maintaining normal tests
 - ▶ Code coverage helps identify uncovered areas
- ▶ Beyond CDCT:
 - ▶ We need to make sure that the driver knows all routes
 - ▶ Code coverage helps identify missing routes
 - ▶ Missing routes in Essence will be discovered because of errors
 - ▶ Missing logic in the Essence will be discovered

Questions – and Answers

- ▶ Maintenance
 - ▶ How can we keep track of our contracts and avoid redundancies?
 - ▶ How can we effectively maintain the contracts in case of changes?
- ▶ CDCT:
 - ▶ As difficult as maintaining normal tests
 - ▶ Code coverage helps identify uncovered areas
- ▶ Beyond CDCT:
 - ▶ We need to make sure that the driver knows all routes
 - ▶ Code coverage helps identify missing routes
 - ▶ Missing routes in Essence will be discovered because of errors
 - ▶ Missing logic in the Essence will be discovered
 - ▶ initially because of unexpected behaviour when prototyping

Questions – and Answers

- ▶ Maintenance
 - ▶ How can we keep track of our contracts and avoid redundancies?
 - ▶ How can we effectively maintain the contracts in case of changes?
- ▶ CDCT:
 - ▶ As difficult as maintaining normal tests
 - ▶ Code coverage helps identify uncovered areas
- ▶ Beyond CDCT:
 - ▶ We need to make sure that the driver knows all routes
 - ▶ Code coverage helps identify missing routes
 - ▶ Missing routes in Essence will be discovered because of errors
 - ▶ Missing logic in the Essence will be discovered
 - ▶ initially because of unexpected behaviour when prototyping
 - ▶ later because of comparison errors

A Word of Warning

- ▶ This is not an easy solution. The world remains complicated.

A Word of Warning

- ▶ This is not an easy solution. The world remains complicated.
- ▶ This is not a golden hammer. Don't apply it everywhere.

A Word of Warning

- ▶ This is not an easy solution. The world remains complicated.
- ▶ This is not a golden hammer. Don't apply it everywhere.
- ▶ This is rather at the top of the test pyramid.

Thank you very much!

Nicole Rauch

E-Mail info@nicole-rauch.de

Twitter [@NicoleRauch](https://twitter.com/NicoleRauch)

Web <http://www.nicole-rauch.de>

EventStorming · Domain-Driven Design
Training · Coaching · Facilitation
Software Craftsmanship
React.js and Redux
Functional Programming

Credits

Essence: Mark Morgan - Perfume

<https://www.flickr.com/photos/markmorgantrinidad/5959461561>