Does the camera model change the outcome?

A simulated RealSense D415 on aluminium parts, for pose estimation and suction grasping

Nicolo Iacobone · November 2026 · Code and results:
github.com/NicoloIacobone/synthetic-rgbd-manufacturing-perception

Summary. I built a pipeline that generates labelled synthetic RGB-D scenes of aluminium T-slot profiles and L-brackets, with a physics-based model of an Intel RealSense D415: rendered infrared stereo pairs with the projected dots, metal and matte materials, sensor noise and stereo matching. I then ran one experiment on 460 paired part views in 50 test scenes. CAD-based pose recall at 5 mm is 0.717 on ideal depth, 0.561 with noise matched to a published D415 measurement, 0.070 with the camera model on metal and 0.343 on matte parts. All three pre-specified comparisons reject. So the camera model changes the outcome, and additive noise does not stand in for it: even independent noise with the model's own error sizes gives 0.276 against 0.102 on the same scenes. The size of the effect on a real camera remains open: the metal result moves from 0.070 to 0.276 over a range of surface roughness I could not source, and against real images the model's disparity errors are compatible, while invalid pixels and infrared appearance differ.

Contents

1 Problem and scope 1
2 Related work 1
3 Reference camera 1
4 Synthetic data pipeline 2
5 Camera model 2
6 Experiment 3
7 Results 3
8 What did not work 5
9 Limitations 6
10 Reflection: the riskiest assumption 6
11 The first six months 7
12 AI-use note 7

1 Problem and scope

A robot that picks and assembles aluminium profiles and brackets needs depth on surfaces that are hard for active stereo, because smooth metal sends the projected pattern away from the camera or onto other parts. The D415 datasheet specifies depth on a white target and says nothing about metal [1]. My question is whether modelling this camera changes the result of a downstream step, compared with ideal depth and with noise of the size the camera is known to have. **Not in scope:** detection (ground-truth masks are given), grasp execution, a real robot, training networks, and replicating Intel's matching chip. **Results apply** to an active-stereo model with D415 geometry and to this ICP, not to a physical D415.

2 Related work

Depth simulation. A common route adds noise to ideal depth. Dex-Net 2.0 and 3.0 train grasp networks on rendered depth with multiplicative and Gaussian-process noise [2,3], and Dex-Net 3.0 lists objects with "specularities or transparencies that prevent the depth camera from sensing the object geometry" among its failure cases [3]. A second route simulates the sensing process. Landau et al. predict Kinect infrared and depth images from the projector, dot pattern and disparity processing [4], and DepthSynth extends this idea to more structured-light sensors, reporting that the data improves recognition and pose networks [5]. Two simulators target the D415 directly. Zhang et al. combine material acquisition, ray-traced infrared rendering, infrared noise and semi-global matching, and report perception and control policies that transfer to a real robot without fine-tuning; they also note that their specular, translucent and transparent real objects, unlike their matte 3D-printed ones, give "noisy and incomplete" depth, "more challenging to simulate" [6]. DREDS renders in Blender, randomises materials from specular to diffuse, and trains a depth-restoration network that raised real grasp success on specular and transparent objects from 38.8% to 96.2% (49 and 26 attempts) [7].

Reflective industrial parts. T-LESS provides thirty texture-less, industry-relevant objects [8]. ROBI gives D415 and Ensenso images of seven metal parts, with ground truth from anti-reflective spray, and reports "significant degradation" of D415 depth accuracy against the Ensenso [9]. XYZ-IBD, a preprint, records 15 metallic parts with three sensors including a D415 at 600–1000 mm, and reports a "stark performance degradation" of current pose methods compared with household benchmarks [10]. On general objects the BOP challenges point the other way: synthetic training has become competitive [11,12].

What this report adds. The studies above mostly evaluate networks trained on simulated depth, where training data, architecture and sensor model are mixed together. I use an untrained CAD-based harness, so depth is the only variable. On metal parts I compare the camera model with noise at a level measured on the real camera on a plane, with paired statistics over scenes. The price is that the result belongs to this ICP and says nothing about transfer to reality.

3 Reference camera

I chose the D415 for four reasons. It is an active infrared stereo camera, so material-dependent errors can emerge from rendering instead of being hand-written. It has an independent metrology study [13]. It has real recordings on metal parts with ground truth [9]. And it is still listed as a current product [14]. The geometry comes from the datasheet (Rev 017) [1]: baseline 55 mm; 1280×720; imager field of view 71°±1° × 44°±1° with no optical filter (pp. 43, 71); static 850 nm projector, 67°×41° (p. 71; p. 45 gives 64°); minimum range 450 mm (p. 91). The focal length follows from the imager field, $f_x = 640/\tan 35.5° = 897.25$ px. Depth accuracy is specified as ±2% within 2 m, on a white target at 150 mW with auto exposure (pp. 92–93).




Figure 1: One test view, chosen by a rule on part types only. On metal the flat bracket at the bottom almost disappears into the tray, and ICP ends far from the true poses.

4 Synthetic data pipeline

Parts and scenes. Parts are procedural: square T-slot-like profiles (side 30 mm, slot opening 8 mm, lengths 60, 100, 150 mm) and an L-bracket (legs 40 mm, width 30 mm, thickness 4 mm), with known symmetries. They are loosely based on 30-series extrusions, not on a vendor drawing. BlenderProc [15] and Cycles render a tray with 3–6 parts dropped by Bullet physics, seen from two views at 0.65–0.95 m with tilt up to 30°. I use 50 test scenes (seeds 0–49) and 5 separate development scenes (seeds 1000–1004), which never enter a reported result.

Labels. Each view is written in BOP format: RGB, ideal z-depth, visible and full masks, 6D poses, intrinsics and CAD models (Fig. 1). Two checks guard the labels: masked depth back-projected through the labelled pose lies on the CAD surface on all 460 part views (worst median 0.045 mm, no point beyond 1 mm), and rendered depth on a tilted plane matches the analytic plane within 0.002 mm, with the camera matrix returned within 10^{-6} px.

Cost. On an 8 GB Apple M2 a scene with all passes takes a median of 178 s; the 50 scenes take 2 h 28 and 1.4 GB, and the whole experiment 9 h 38. `scripts/setup.sh` installs from a lock file and runs 116 tests, and `scripts/quick_run.py` reproduces one scene's numbers without Blender in about 2 minutes (tested in a clean clone on macOS, and in a Linux container).

5 Camera model

The model follows the sensing chain, so effects emerge rather than being painted on.

1. **Projector.** A point spot light at the baseline midpoint casts a fixed semi-random pattern of 30 000 Gaussian dots ($\sigma = 0.7$ px). The D415's pattern is not published. This density puts a dot on 3.76% of lit pixels, inside the 1–10% that Intel's guidance calls near-ideal [16].
2. **Materials at 850 nm.** Metal is GGX with normal reflectance 0.868, computed from aluminium's optical constants at 848 nm [17], roughness 0.15 from fits to a measured aluminium BRDF in visible light [18], and a 1.5% diffuse lobe from the same fits. Matte parts are Lambertian, albedo 0.25, set on the development scenes so that mean exposed brightness on part pixels equals that of metal (16.0 DN each). On the test scenes the match is only approximate: 15.1 DN against 20.9 DN on average, with a per-view ratio from 0.09 to 4.35.
3. **Light transport.** Cycles path tracing with 32 samples, 3 glossy bounces and no denoiser. Both images are rendered 128 px wider, so the invalid left band comes from geometry and not from OpenCV's fixed margin. Linear radiance is stored, so exposure is applied later.
4. **Sensor.** A per-frame gain brings the mean of the metal left image to 20 DN (digital numbers, the 8-bit grey levels); the same gain applies to the right image and to the matte pass. Noise is shot plus read, $\mathrm{DN} + \sqrt{\mathrm{DN}/e + \sigma_r^2}\, n$, with n standard normal, an effective $e = 0.42$ electrons per DN, $\sigma_r = 1$ DN and draws shared by metal and matte. Images are then quantised to 8 bits, as in the D415's streams (p. 81).
5. **Matching.** OpenCV SGBM [19] with a 7×7 block, uniqueness 10, left-right check 1, speckle filter 100 px. The search is 128 px with disparities above 126 masked, the D415's range from [13,22]. No hole filling; invalid depth stays invalid.

Plane check. On a matte plane at 0.5–1.0 m with noise and auto exposure, bias stays within 0.31% of z, the central 80% of the image is 100% valid, and the left band is within 1.2 px of Bf/z. Plane-fit RMS is 0.42–2.66 mm, non-monotonic because of locking. For comparison the formula with $\varepsilon_d = 0.08$ px and my f gives 1.62 mm at 1 m [20,22], Carfagni et al. measured a standard deviation of 4.74 mm from a reference plane at 1 m [13], and the datasheet allows 2% of range. **This check is not independent:** e is set to bring the central-region RMS to 0.09 px, inside Intel's 0.07–0.11 px [16] (measured: 0.0897 px). It also says nothing about metal.

Table 1: Effects included and left out, and why.

Included	**How it arises**
Depth noise growing with z^2	Disparity error through $z = fB/d$ [20]
Invalid left band, occlusion shadows	Stereo and projector geometry; band within about 1 px of Bf/z
Minimum range	126 px search; simulated transition at 392 mm, see Section 8
Edge fattening, flying pixels	Matching window: in the matte condition 29.1% of edge pixels and 11.1% of interior pixels are off by more than 5 mm
Subpixel locking	SGBM's estimator. Comparable in size to the D4 chip at default firmware [21]; a different mechanism
Glints, dark faces, reflected dots, dependence on incidence angle	GGX and 3 glossy bounces in Cycles
Auto exposure, shot and read noise, 8 bits	Applied to linear radiance. A mean-brightness target is assumed; Intel's algorithm is not published
Unlit image margins	67° projector inside a 71° imager: 13.6% of the image, 0.064% of part pixels
Left out	**Why**
Ambient infrared	Indoor cell assumed, although the imagers have no filter [1], so I tested it once (Table 3)
Motion blur, rolling shutter	The scene is static at capture
Intel's matcher and post-processing	Proprietary; raw depth only. SGBM is cross-checked on real images (Section 7)
Calibration error, lens distortion, thermal drift	Assumed calibrated out, with constant temperature
Laser speckle, projector hot spot	Intel calls speckle "very detrimental" and its figure shows a hot spot [16]; no source quantifies them for the D415, and the datasheet is silent
Temporal noise	Single-frame setting
Anodising, machining marks, surface oxide	No source for extruded profiles at 850 nm; only roughness is varied (Table 3)
RGB imperfections	Neither task reads RGB. It is rendered from the left imager's viewpoint with a placeholder material, not modelled on the D415's RGB sensor

6 Experiment

Conditions, on identical scenes and poses. **C1** ideal depth. **C2a** and **C2b** ideal depth plus Gaussian noise $\sigma = z^2\varepsilon_d/(fB)$ [20], the naive baseline: $\varepsilon_d = 0.08$ px from Intel's guide [22], and $\varepsilon_d = 0.234$ px fitted to Carfagni's 4.74 mm at 1 m [13], which is deliberately generous. **C3** the camera model on metal. **C4** the camera model on matte parts, with brightness matched on the development scenes. C3 against C4 therefore contrasts the material, but brightness still differs from view to view on test scenes.

Task A, pose (primary). Ground-truth masks, eroded by 2 px, select depth points. Point-to-plane ICP [23] aligns them to 200 000 CAD samples with CAD normals, ray-cast visibility and coarse-to-fine stages. It starts 10 mm and 10° from the true pose, in random directions shared across conditions. Error is MSSD [11], which handles symmetries. **The primary endpoint is recall at MSSD < 5 mm.** The 5 mm threshold is my own, not sourced. Starts of 2, 5 and 20 mm and degrees are secondary.

Task B, suction. On the masked points, the planner takes the flattest point that fits a 10 mm-radius cup. Success is checked on the true mesh: within 2 mm of the surface, normal within 15°, and the whole disk planar within 1 mm on one part. With this cup no profile face can pass (largest flat disk: radius 9.76 mm), so I report brackets separately.

Statistics and pre-specification. The unit is a part in a view: 460 instance-views (342 profiles, 118 brackets), none excluded by the 10% visibility rule of BOP [11]. Endpoint, thresholds, conditions and the test/development split were frozen under a git tag before any data existed; the fixed sequence and C2b's level were added before any test data. Tests run in a fixed sequence at $\alpha = 0.05$, C1 vs C3, then C2b vs C3, then C3 vs C4. A comparison rejects only if the exact McNemar $p < 0.05$ and the 95% scene-bootstrap interval (10 000 resamples) excludes zero. Settings were fixed by rules declared in advance, each looking at one allowed statistic: sensor noise on a simulated plane, exposure and albedo on development scenes, material constants from sources. Camera settings never saw recall. The ICP variant was chosen on development recall, by its worst case across conditions and, on ties, the next worst. As a bug detector, ICP on C1 started at the true pose must keep at least 99% of views below 0.5 mm; it keeps 460/460.

Deviations I must disclose. Two matter most; all are logged with reasons in `docs/PLAN.md`. (i) The sanity check first failed on the test scenes because of a bug (Section 8). The fix changed the harness after the test render; only C1 at zero offset had been seen. (ii) **After all results had been seen**, a datasheet check showed that I had derived f_x from the 65° depth field, while the datasheet's formulas use the 71° imager field. I re-rendered and re-ran everything. The new run is primary whatever its direction, and it is the one reported here. Exposure, matte albedo and both noise levels that depend on f were re-derived by the same rules; material, matcher and harness were not touched. The 65° results appear only as a sensitivity (Table 2), and they were not used to choose settings.

7 Results

Confirmatory result. All three comparisons reject: C1−C3 +64.8 (59.6 to 70.0), $p = 3 \times 10^{-75}$, in percentage points; C2b−C3 +49.1 (42.5 to 55.9), $p = 6 \times 10^{-55}$; C3−C4 −27.4 (−33.0 to −21.7), $p = 5 \times 10^{-30}$. The widths of these intervals imply that effects of about 7–10 points are detectable at 80% power; even a worst-case bound that counts each scene as a single pair (33.2, 29.3, 22.2 points) lies below all three. The order {C1, C2a} > C2b > C4 > C3 holds at all four offsets. So **the camera model changes the outcome**: the generous naive noise gives recall a factor of eight above the model at my assumed roughness and a factor of two at roughness 0.4 (0.561 against 0.070 and 0.276), and I do not know the real value.

Table 2: Results on 460 instance-views (commit `7eca5f0`, clean tree; 95% intervals over scenes). Below the line: descriptive passes, outside the tests. Last column: the archived run with the earlier focal length, a sensitivity only.

	Recall, MSSD < 5 mm			Recall	Median	Suction,	Recall
Condition	all parts	profiles	brackets	< 2 mm	MSSD, mm	brackets	at 65°
C1 ideal depth	0.717 (0.671–0.761)	0.696	0.780	0.546	1.6	0.771	0.732
C2a noise 0.08 px	0.735 (0.684–0.783)	0.737	0.729	0.446	2.5	0.737	0.749
C2b noise 0.234 px	0.561 (0.498–0.621)	0.635	0.347	0.154	4.3	0.534	0.590
C3 metal, camera model	**0.070** (0.046–0.095)	0.079	0.042	0.000	16.8	0.110	0.085
C4 matte, camera model	0.343 (0.287–0.400)	0.380	0.237	0.059	7.3	0.381	0.386
Metal, roughness 0.2	0.139 (0.100–0.180)	0.167	0.059	0.007	12.4	0.136	0.159
Metal, roughness 0.4	0.276 (0.218–0.335)	0.345	0.076	0.033	9.4	0.229	0.288
Metal, reflections off	0.076 (0.054–0.100)	0.088	0.042	0.004	17.3	0.161	0.102
Matte, albedo 0.5	0.363 (0.302–0.427)	0.401	0.254	0.063	6.8	0.373	0.444




Figure 2: (a) Primary endpoint. (b) Recall by starting offset. (c) Depth on part pixels. (d) Recall by part distance, at 10 mm / 10°.

Metal fails silently. Only 2.3% of metal-part pixels are invalid, yet 44.1% of the valid ones are off by more than 5 mm (Fig. 2c). The error is one-sided: median +3.0 mm, 5th and 95th percentiles −5.2 and +29.2 mm, against a symmetric ±5.3 mm for C2b. C3's level is not a convergence limit. From a 2 mm / 2° start, where every view already has MSSD below 5 mm (largest 4.70 mm), C1 keeps 1.00 and C3 ends at 0.102, so ICP on C3 moves away from the truth. C1's own fall to 0.717 at 10 mm / 10° is a harness limit, so absolute recall belongs to this ICP, and the gaps between conditions are shown for this ICP only.

Size and layout matter, direction does not. I had assumed that ICP averages out zero-mean noise and fails on a one-sided bias, so I tested it on seeds 0–9, keeping each part's own errors and changing their structure, with the reading written down before the run (Table 3). Random signs make the errors zero-mean and independent but leave the large ones where they are: recall stays at 0.102. Permuting them among the part's pixels keeps the bias and spreads the large ones: 0.255. Both together give 0.276, no different from permuting alone (+2.0 points, −7.8 to +11.6). **So my assumption was wrong.** Most of the drop from C1 (0.704 on these seeds) comes from the size of the errors on metal, 44.1% of valid pixels beyond 5 mm against 11.2% in C2b, and the rest from their layout; my reading is that clustered errors leave whole faces without usable points. A plane measurement shows neither. With ten scenes these are indications, not estimates.

Stereo alone costs more than noise, in this model. C4 sits 21.7 points below C2b (17.5 to 26.1; descriptive) on matte parts. Part of this may come from how my images look rather than from stereo as such: they are bright dots on black, unlike real ones (see "Against real images"). No dot density I tried closes the gap: at 60 000 dots, on seeds 0–9, C4 still sits 24.5 points below C2b (16.0 to 34.3). C2a does not differ detectably from C1: −1.7 points (−4.1 to +0.7). Noise helps profiles (16 views gained, 2 lost, $p = 0.001$) and may hurt brackets (2 gained, 8 lost, $p = 0.11$); I did not trace why.

Distance matters. From below 0.7 m (46 views) to 0.9 m and beyond (141 views), C3 falls from 0.217 to 0.021 and C4 from 0.565 to 0.184, while C1 rises from 0.630 to 0.752. A fixed 5 mm shrinks in disparity: 0.305 px at 0.9 m.

Suction (descriptive) follows the same order on the 118 bracket views: C1 0.771 (0.673–0.864), C2a 0.737 (0.648–0.822), C2b 0.534 (0.436–0.635), C4 0.381 (0.280–0.484), C3 0.110 (0.046–0.178), with C1−C3 at +66.1 points (56.6 to 76.3). C3 plans a grasp on 44.1% of views and 25.0% of those succeed, against 85.6% and 90.1% for C1. Profiles never succeed, by

Table 3: What moves recall at 5 mm (descriptive, same scenes and offsets). Rows below the line use seeds 0–9 and read against their own baseline.

Change	Metal	Matte	Reading
Baseline, 50 scenes	0.070	0.343	
Roughness 0.15 → 0.2 → 0.4	0.139, 0.276		The largest lever, and the value is not sourced for real extrusions
Reflections off, same material	0.076		−0.7 points (−2.7 to +1.5), though correct pixels go 55 → 60%
Brighter matte, albedo 0.5		0.363	+2.0 points (−2.0 to +5.8): darkness is not the limit
Two new noise draws	0.061, 0.063		Spread 0.9 points; the primary draw is the highest of the three
ICP run again on identical depth	0.070	0.343	No view crosses 5 mm in 1840 comparisons (C1, C2b, C3, C4)
Baseline, seeds 0–9	0.102	0.265	
Less noise, e 0.42 → 1.0	0.102	0.286	Noise at 21 DN 7.1 → 4.7 DN does not explain metal
All three matcher filters off	0.112	0.245	No order flips; filters remove mostly wrong pixels
Ambient light added	0.031	0.224	Reaches 22 DN on metal, but metal gets worse; level and spectrum not sourced
Each part's errors, random signs	0.102		+0.0 points (−5.3 to +4.7): zero mean, large errors stay in place
Each part's errors, permuted	0.255		+15.3 points (+2.2 to +32.7): bias kept, large errors spread
Permuted, with random signs	0.276		+17.3 points (+6.7 to +28.6): the best per-part additive noise
Same 30 000 dots, rendered again	0.102	0.265	No view crosses 5 mm; the next two rows read against this
10 000 dots, new render	0.041	0.184	Metal −6.1 points (−11.5 to −1.0), matte −8.2 (−20.8 to +4.5)
60 000 dots, new render	0.031	0.235	Metal −7.1 points (−12.0 to −2.9), matte −3.1 (−9.8 to +4.3)




Figure 3: One development view, chosen by part-pixel count. Reflections add glints without changing the error pattern much.

geometry, yet the planner proposes a grasp on 0.3% of profile views in C1 and on 93.9% in C3. On a robot those would be false grasps. I did not trace the mechanism.

Mechanism: partly understood (Fig. 3). On 10 development views I did not isolate one cause. With metal blanked in both images, 98.7% of part pixels stay valid and only 2.5% are correct, so the matcher fills instead of invalidating. Faces whose mirror ray hits the scene are 35.7% correct, others 56.1%. When I shift the background of the right image by ±3 px, biased pixels do not follow it (slope 0.00), while with metal blanked the fill does (blanked control 0.77–0.94), so they are not simply copied from the tray; 86.1% lie between surface and tray. Low texture does not explain it: pixels with no texture above noise fell from 53.5% at 65° to 3.2% here, with lower noise, while correct pixels stayed near 50% (49.1, 50.5).

Against real images (Fig. 4). I compared with 26 ROBI Zigzag views at 0.32–0.41 m, one object at a different range from my parts (0.63–1.10 m). Signed disparity error is close: p5, p25, p50 are −2.07, −0.71, −0.19 px for the real D415 and −2.24, −0.68, −0.23 px for C3, while roughness 0.4 gives −0.98, −0.22, −0.04 px. But a pose-annotation error of 1 mm would shift disparity by 0.37 px at this range, more than the gaps between these quantiles, and ROBI states no annotation error, only a mean residual of 0.8 mm when fitting its RealSense camera poses [9]. Invalid pixels differ: 21% real, 2.3% in C3. SGBM on the real infrared pairs leaves 17% invalid, so the gap comes from the images and not from my matcher (inference). Those images differ too: 21 DN median and 4.6 DN local contrast on real parts, against 5 DN and 22.5 DN in C3. The background differs as well: 21 DN and 2.7 DN on ROBI, against 3 DN and 25.7 DN here, and my matte parts look like my metal ones (4 DN, 22.8 DN). Materials differ, but I infer that my whole image is bright dots on black, which may add to the cost of stereo in both C3 and C4. So the disparity match may be partly a coincidence. I read this as compatible, not validated.

8 What did not work

- **Wrong focal length for most of the project.** See the deviations above. The correction also opened a mismatch I could not close: with the 126 px search the depth transition falls at 392 mm, against the datasheet's 450 mm. Evidence is mixed, since 450 mm with 126 px would imply $f \approx 1031$ px and Intel's tuning guide computes with 65° [22], while ROBI's real camera has 905.9 px. No scene pixel is that close.
- **Sanity check failed.** First result 416/459 against the required 99%. Cause: a bug in AI-written code, where a ray-cast cache gave profiles the mesh of another length, culling end faces the camera sees. Development data (40 views) and 94




Figure 4: Against real D415 data on one ROBI object [9], in pixels, since 5 mm is 2.15 px at 0.34 m and 0.305 px at 0.9 m. Boxes: p5, p25, p50, p75, p95.

unit tests had missed it. After the fix and denser CAD sampling all variants pass. I chose the sample count after seeing C1 at zero offset on test scenes, which I disclose.

- **No reflections in the first renders.** BlenderProc defaults to zero glossy bounces, so early metal had no reflected dots. A figure checked before the test render exposed it, and every dependent setting was re-derived.
- **A robustness check that did nothing.** In OpenCV 5.0.0, `disp12MaxDiff` $= -1$ does not disable the left-right check. The first robustness run therefore left it on. I re-ran it with the check really off, and a unit test now pins this behaviour.
- **Fragile noise calibration.** The same rule gave $e = 0.087$ at 65° and 0.42 at 71°, because locking alone sets a no-noise floor (0.053, then 0.075 px) close to the 0.09 px target. The value is effective, not physical.
- **Not repeatable.** Renders with identical settings differ slightly, and in one development view 79% of metal pixels moved by more than 5 mm. A repeat render of seeds 0–9 was gentler: it changed 0.14% of metal depth pixels in the median view and moved no instance-view across 5 mm. ICP on bit-identical depth also varies on unstable views, with a source I did not trace. I measured what this costs: a full repeat of C1, C2b, C3 and C4 moved at most 6 of 460 views by more than 0.01 mm per condition (the largest by 33 mm), but no view crossed 5 mm, so recall is identical and the three tests reject again.
- **A depth overflow found in the final review.** Depth is stored as uint16 at 0.1 mm, so a match beyond 6.55 m (disparity below 7.5 px) wraps around to a false depth, as low as 26 mm. It touches 0.09% of image pixels but none of the 1 674 189 part pixels in C3 and C4, so recall and part metrics do not change. With all filters off (Table 3) it touches 0.04% of part pixels on seeds 0–9. I documented it rather than change the depth code just before submission.
- **Predictions I got wrong.** I expected the left-band check to fail at 71° because of the unlit margin, but the matcher fills that strip with plausible depth, itself an artefact. I expected texture loss to explain metal, and then a one-sided pull; neither does.
- **Not done:** global registration without an initial pose, parallel-jaw grasping, noise redraws on matte.

9 Limitations

Masks are ground truth, and real masks would degrade at edges. Scenes are sparse trays, not dense bins. The ICP variant was chosen on development data by a margin of one view. SGBM is not Intel's matcher, though on real ROBI pairs at close range it comes near the D4 chip (70% against 71% of pixels within 5 mm, invalid 17% against 21%). Roughness rests on a visible-light fit to an aluminium sample of unstated finish. Zero ambient light is a primary-run assumption that the datasheet weakens. The dot density is also assumed, because the pattern is not published. On seeds 0–9 metal recall falls with both fewer and more dots, from 0.102 to 0.041 and 0.031 (Table 3), so the metal level depends on the pattern. Changing the count also moves every dot, so I cannot separate density from layout, and my 30 000 dots may be a favourable draw. The order C3 < C4 < C2b holds at all three densities. At 60 000 dots the images are still far from real ones: background 11 DN, local contrast 16.4 DN, against 21 DN and 2.7 DN on ROBI. Infrared images use 32 samples: on one development scene at the earlier focal length, 128 samples moved correct pixels by 1.95 points (my limit was 2), but lit-metal radiance differed by a median of 47–53%, so the images are not converged. Parts are procedural. Detectable effects are about 7–10 points on 50 scenes and larger on ten, so small differences among descriptive rows mean little. Above all, nothing here was measured on a real profile.

10 Reflection: the riskiest assumption

The assumption. *That the simulated sensor errs in the same way as the real one, on the parts that matter.* Appearance gets most of the attention in sim-to-real work, and there the evidence is encouraging: in BOP 2022 a pose method trained only on BlenderProc images reached 82.7 ARC (BOP's average-recall score), and the gap to methods also trained on real images shrank [12]. Depth on reflective metal is a different problem, for three reasons that come out of this work.

- **The error is not what a plane measurement suggests.** Noise at a level measured on the real camera predicts 0.561 where the camera model predicts 0.070. Part of the gap is size: on metal 44% of valid pixels are off by more than 5 mm,

against 11% with that noise. Part is layout: independent noise of the model's own sizes still gives 0.276 against 0.102 on the same scenes. None of this shows on the flat white target on which cameras are specified. A network trained on the wrong errors learns the wrong correction.

- **It fails silently.** In my model only 2.3% of metal pixels are flagged invalid while 44% of the rest are off by more than 5 mm, and nothing in the depth map reveals which. Validation in simulation cannot catch a wrong error model, because the same model produces the training and the test data. The first evidence comes from the robot.
- **Nothing I could find pins it down.** Metal recall moved nearly fourfold across roughness values, and I found no source for extruded profiles at 850 nm. My model is compatible with a real D415 on disparity error but differs on invalid pixels (2.3% against 21%) and on infrared appearance. A network trained on it might learn to expect a bias where the real camera leaves holes. XYZ-IBD reports stark degradation on metal parts in cluttered bins [10], and Zhang et al. note that specular and transparent real objects are harder to simulate than matte 3D-printed ones [6].

Two other candidates are real but show themselves sooner: appearance randomisation that misses factory surfaces [24] fails visibly in the first real images, and pose error that does not predict pick success appears in the first trials. A wrong sensor error model can stay hidden until grasps fail on one surface finish at one distance.

11 The first six months

The aim is to measure this gap on real parts, then decide from evidence how much sensor realism is worth.

- **Month 1, no hardware.** Repeat my comparison on the D415 depth of XYZ-IBD [10], which is at my working range (600–1000 mm) and covers 15 metal objects, unlike the single ROBI object at 0.32–0.41 m used here. Extend the ROBI comparison to its other six objects, whose infrared pairs let me separate the images from the matcher.
- **Months 1–2, calibration set.** Record real extruded profiles and brackets, mill-finish and anodised, 20–30 scenes at 0.6–1.0 m, with a D415 and a structured-light reference on a robot arm for repeatable views. Take ground truth from anti-reflective spray, as ROBI and XYZ-IBD do. Depth and both infrared streams together are supported only for calibration (datasheet p. 84), so record them in succession.
- **Months 2–3, measure effect by effect.** Build a digital twin of the same poses. Compare infrared appearance first, then invalid share and signed disparity error, by material, incidence angle and distance. Add ambient light with a measured spectrum.
- **Months 3–4, fix by evidence.** Measure the BRDF of the real parts at 850 nm instead of assuming roughness. Learn a residual only for what physics leaves over, and randomise only what stays unmodelled, within measured bounds. Hold out one part family and one finish. **Gate, fixed in advance:** on held-out scenes, invalid share within 5 points and disparity quantiles within 0.25 px of real (5 mm is 0.305 px at 0.9 m). If it fails, the model stays labelled as unvalidated.
- **Months 5–6, does it matter?** Train one pose and one suction network on ideal depth, naive noise, the fitted model and randomised depth, then test all four on real parts in closed-loop pick and assembly, with thresholds and a minimum useful gain declared in advance. If the fitted model does not beat naive noise by that margin, effort should go elsewhere, and that is a result worth publishing.

Outputs: an open real-and-simulated dataset on aluminium parts, a validated sensor model with stated limits, and a measured answer to how much sensor realism a factory perception model needs.

12 AI-use note

I used Claude Code (Claude Opus 5.5) as planning partner, literature searcher and programmer: it wrote most of the code, ran the experiments, and produced the first draft of this report from the project's records. I took the decisions, set the rules for what could be tuned on what, and checked the results and this text. A log of corrections is in `docs/AI_USE_LOG.md`. **Where I disagreed:** when the assistant found the focal-length error, it recommended disclosing it as a limitation without re-rendering, because the estimated effect was small and the value was frozen. I rejected that and had the render and the whole experiment re-run as a logged deviation. **Where checking mattered:** when the sanity check failed, the assistant's first explanation (numerical conditioning) did not hold; the diagnosis I asked for, why fitness was low on ideal depth, confirmed the real cause, a bug in its own cache code. My rule that every source be checked against the primary text also caught errors in its earlier citations.

References

[1] Intel. RealSense D400 Series Product Family Datasheet, Rev 017, doc. 337029-017, Sep 2023.

[2] Mahler et al. Dex-Net 2.0: Deep learning to plan robust grasps with synthetic point clouds and analytic grasp metrics. RSS 2017.

[3] Mahler et al. Dex-Net 3.0: Computing robust vacuum suction grasp targets in point clouds using a new analytic model and deep learning. ICRA 2018.

[4] Landau, Choo, Beling. Simulating Kinect infrared and depth images. IEEE Trans. Cybernetics 46(12), 2016.

[5] Planche et al. DepthSynth: Real-time realistic synthetic data generation from CAD models for 2.5D recognition. 3DV 2017.

[6] Zhang et al. Close the optical sensing domain gap by physics-grounded active stereo sensor simulation. IEEE Trans. Robotics 39(3), 2023.

[7] Dai et al. Domain randomization-enhanced depth simulation and restoration for perceiving and grasping specular and transparent objects. ECCV 2022.

[8] Hodaň et al. T-LESS: An RGB-D dataset for 6D pose estimation of texture-less objects. WACV 2017.

[9] Yang et al. ROBI: A multi-view dataset for reflective objects in robotic bin-picking. IROS 2021.

[10] Huang et al. XYZ-IBD: Benchmarking robust 6D object pose estimation under real-world industrial complexity. arXiv:2506.00599v3, 2026.

[11] Hodaň et al. BOP Challenge 2020 on 6D object localization. ECCV Workshops 2020.
[12] Sundermeyer et al. BOP Challenge 2022 on detection, segmentation and pose estimation of specific rigid objects. arXiv:2302.13075, 2023.
[13] Carfagni et al. Metrological and critical characterization of the Intel D415 stereo depth camera. Sensors 19(3):489, 2019.
[14] RealSense. Products page, realsenseai.com/products, and spin-out notice (Intel Capital, Jul 2025).
[15] Denninger et al. BlenderProc2: A procedural pipeline for photorealistic rendering. JOSS 8(82):4901, 2023.
[16] Grunnet-Jepsen et al. Projectors for Intel RealSense depth cameras D4xx. Intel white paper, Rev 1.0, 2019.
[17] Rakić et al. Optical properties of metallic films for vertical-cavity optoelectronic devices. Appl. Opt. 37, 1998.
[18] Bieron, Peers. An adaptive BRDF fitting metric. Computer Graphics Forum 39(4), 2020, and GGX supplement.
[19] Hirschmüller. Stereo processing by semiglobal matching and mutual information. IEEE TPAMI 30(2), 2008; OpenCV `StereoSGBM` implements a modified version.
[20] Keselman et al. Intel RealSense stereoscopic depth cameras. CVPR Workshops 2017.
[21] Grunnet-Jepsen et al. Subpixel linearity improvement for Intel RealSense depth camera D400 series. Intel white paper, Rev 1.3, 2019.
[22] Grunnet-Jepsen et al. Best-known-methods for tuning Intel RealSense D400 depth cameras for best performance. Intel white paper, Rev 2.0.
[23] Rusinkiewicz, Levoy. Efficient variants of the ICP algorithm. 3DIM 2001.
[24] Tobin et al. Domain randomization for transferring deep neural networks from simulation to the real world. IROS 2017.