## .h .cpp多文件项目

.h 实际是class对外暴露的接口

## const pointer & iterators

```
//constant pointer to a non-constant int
int * const p;

//non-constant pointer to a constant int
const int* p;
int const* p;

//constant pointer to a constant int
const int* const p;
int const int* const p;
int const* const p;
something on the heap so this is again how Const interacts with the pointers is
cultimage heap so this is again how Const interacts with the pointers is
cultimage heap so this is again how Const interacts with the pointers is
cultimage heap so this is again how Const interacts with the pointers is
cultimage heap so this is again how Const interacts with the pointers is
cultimage heap so this is again how Const interacts with the pointers is
cultimage heap so this is again how Const interacts with the pointers is
cultimage heap so this is again how Const interacts with the pointers is
cultimage heap so this is again how Const interacts with the pointers is
cultimage heap so this is again how Const interacts with the pointers is
cultimage heap so this is again how Const interacts with the pointers is
cultimage heap so this is again how Const interacts with the pointers is
cultimage heap so this is again how Const interacts with the pointers is
cultimage heap so this is again how Const interacts with the pointers is
cultimage heap so this is again how Const interacts with the pointers is cultimage heap so this is again how Const interacts with the pointers is cultimage heap so this is again how Const interacts with the pointers is cultimage heap so this is again how Const interacts with the pointers is cultimage heap so this is again how Const interacts with the pointers is cultimage heap so this is again heap so this is a
```

```
vector v{1,2312};

const vector<int>::iterator itr = v.begin();

++itr; // doesnt compile

*itr = 15; // compiles

we have to define a new type called a Const iterator so if you've been looking 我们必须定义一个称为a 的新类型常量迭代器,所以如果你一直
```

```
const vector<int>::iterator itr = v.begin();
*itr = 5; //OK! changing what itr points to
++itr; //BAD! can't modify itr

vector<int>::const_iterator itr = v.begin();
*itr = 5; //BAD! can't change value of itr
++itr; //OK! changing v
int value = *itr; //OK! reading from itr
```

## **Challenge Mode:**

```
const int* const myClassMethod(const int* const & param) const;
```

