```
192.168.1.2 192.168.1.1

Fa0 Gig0/0/0

PC-PT ISR4321
PC0 Router0
```

```
Router>enable
Router#config t
Enter configuration commands, one per line. End with CNTL/Z.
Router(config)#hostname Rl
R1(config) #enable secret hello
R1(config)#interface g0/0/0
R1(config-if) #ip address 192.168.1.1 255.255.255.0
Rl(config-if) #no shutdown
R1(config-if)#
%LINK-5-CHANGED: Interface GigabitEthernet0/0/0, changed state to up
%LINEPROTO-5-UPDOWN: Line protocol on Interface GigabitEthernet0/0/0, changed state to up
R1(config-if)#line vty 0 5
Rl(config-line)#login
% Login disabled on line 2, until 'password' is set
% Login disabled on line 3, until 'password' is set
% Login disabled on line 4, until 'password' is set
% Login disabled on line 5, until 'password' is set
% Login disabled on line 6, until 'password' is set
% Login disabled on line 7, until 'password' is set
Rl(config-line) #password pass
Rl(config-line)#end
R1#
%SYS-5-CONFIG I: Configured from console by console
                                                                                             ф Ва
R1#wr
Building configuration...
                                                                                            Batte
[OK]
R1#
```