AI Tutor: An Evidence-Based Adaptive Learning System with Deliberate Scaffolding Withdrawal

Submitted in partial fulfillment of the requirements for the award of the degree of

Master of Computer Applications

to

Guru Gobind Singh Indraprastha University, Delhi

Guide	Submitted by
Dr. Chetna Laroia	Ashwani Kumar Puri (04914004425)
	Aman Dogra (01614004425)
	Aditi Tanwar (01814004425)

JAGAN INSTITUTE OF MANAGEMENT STUDIES

3, Institutional Area, Sector-5, Rohini

Batch (2025–2027)

Certificate (Annexure-II)

We, 1. Ashwani Kumar Puri (04914004425), 2. Aman Dogra (01614004425) and 3. Aditi Tanwar (01814004425), certify that the Minor-III Project Report (MCA-269) entitled "AI Tutor: An Evidence-Based Adaptive Learning System with Deliberate Scaffolding Withdrawal" is done by us and it is an authentic work carried out by us at Jagan Institute of Management Studies, Rohini. The matter embodied in this project work has not been submitted earlier for the award of any degree or diploma to the best of our knowledge and belief.

Signature of the Students: _____ Date: _____

Certified that the Minor-III Project Report (MCA-269) entitled "AI Tutor: An Evidence-Based Adaptive Learning System with Deliberate Scaffolding Withdrawal" done by the above students is completed under my guidance.

Signature of the Guide: _____ Date: _____
Name of the Guide: Dr. Chetna Laroia
Designation: _____

Countersigned: Principal/Director _____

Acknowledgement

We are grateful to our guide, **Dr. Chetna Laroia**, for her guidance and feedback at every review of this project. We thank the faculty of the MCA department of Jagan Institute of Management Studies for the knowledge of databases, software engineering and web development this project is built on, and the institute for the facilities and the opportunity. We also thank the authors of the research papers listed in the references, whose findings on learning shaped the design of this system.

Ashwani Kumar Puri · Aman Dogra · Aditi Tanwar

Table of Contents

	Topic	Page
	Certificate · Acknowledgement · List of Tables/Figures/Symbols · Synopsis	2
1	**Problem Formulation**: 1.1 Introduction about the organisation · 1.2 Introduction about the problem · 1.3 Present state of the art · 1.4 Need of computerization · 1.5 Proposed software · 1.6 Importance of the work	10
2	**System Analysis**: 2.1 Feasibility study · 2.2 Analysis methodology and system planning (PERT) · 2.3 Choice of the platforms	15
3	**System Design**: 3.1 Design methodology · 3.2 UML modelling · 3.3 Database design (ERD, DFD) · 3.4 Input design · 3.5 Output design · 3.6 Code design and development	25
4	**Testing and Implementation**: 4.1 Testing methodology · 4.2 Test data and test cases · 4.3 Test reports and debugging · 4.4 Implementation manual · 4.5 Implementation · 4.6 Users training · 4.7 Post-implementation maintenance	59
5	**Conclusion and References**: 5.1 Conclusion · 5.2 System specifications · 5.3 Limitations · 5.4 Future scope · 5.5 References	78
6	**Annexures**: A-1 Menu flow · A-2 Structure chart · A-6 Decision tables · A-7 Data dictionary · A-8 Test reports · A-9 Sample inputs · A-10 Sample outputs · A-11 Coding	84

List of Tables

No	Title
1	Problems with the existing (manual) way of learning
2	Functional modules and their users
3	Feasibility summary with measured costs
4	Software and hardware used
5	Verdicts and how each one is decided
6	Mastery formula factors
7	Fade stages
8	Automated test suites and results
9	Defects found and fixed during testing
10	Data dictionary (key tables)
11	Placement test rules
12	Hint ladder and where each hint comes from

No	Title
13	Exercise generation: how a job runs
14	Data rights: what each request does, and what erasure keeps
15	Lessons: what each one holds and the gates it passes
16	Speed tests in the DSA exercise bank

List of Figures

No	Title
1	System architecture
2	Use case diagram
3	Class diagram: domain model
4	Class diagrams: services and adapters (running code and mastery; the AI and the placement test)
5	Sequence diagram: register, then log in
6	Sequence diagram: submit code
7	State diagram: submission
8	Activity diagram: next-step selection
9	Table groups (overview); ER diagrams: attempts and submissions, and execution
10	DFD level 0, level 1 (in two parts), and level 2 (execute and grade)
11	System planning (PERT/Gantt)
12	Deployment diagram
13	Menu flow diagram
14	Sequence diagram: request a hint
15	Activity diagram: placement test
16	Sequence diagram: forgot and reset password
17	Sequence diagram: delete an account
18	Sequence diagram: open a lesson
19	Activity diagram: verify an exercise with generated speed tests

List of Symbols and Abbreviations

Symbol	Meaning
AC, WA, CE, RE, TLE, MLE, SE	Verdicts: accepted, wrong answer, compile error, runtime error, time limit exceeded, memory limit exceeded, sandbox error
λ (lambda)	Decay rate of a skill per day
e	Euler's number; effective mastery = score × e^(−λ × days)
Rung	Exercise difficulty level 1–5 (Predict → Build)
API, JWT, ORM	Application programming interface, JSON Web Token, object-relational mapper
DPDP	Digital Personal Data Protection Act, 2023 (India)
E2B	Cloud sandbox service that runs learner code in isolated micro-VMs
Brevo	Email delivery service that sends the password-reset and account-deletion emails
SHA-256	One-way hash; the database stores only this fingerprint of each token
LLM	Large language model (Google Gemini in this project)

Synopsis

1. Title of Project. AI Tutor: An Evidence-Based Adaptive Learning System with Deliberate Scaffolding Withdrawal. In one line: a tutor whose objective is to make itself unnecessary.

2. Problems with the Existing System. Today a self-taught programmer learns "manually": they pick a video course, watch it in order, copy the instructor's code, tick lessons as complete and, when stuck, ask an AI assistant for the answer. Nothing records what they can actually *write*. Completion is measured instead of capability, the order is the same for everyone, help is unlimited and never withdrawn, and nothing schedules revision before a skill is forgotten.

3. Description of the Proposed System. A web-based, online system that keeps a separate **reading** and **writing** mastery score for every skill, updates them **only from code that was actually executed and graded**, chooses the next step from a prerequisite graph, teaches each skill with a short lesson written for the learner's level, and **withdraws help on a schedule** until the learner can work alone. Learner code runs in an isolated cloud sandbox. Every lesson and exercise is proven in that sandbox and frozen before any learner sees it. An LLM writes hints and can add content, but never grades and never decides what comes next. Two courses are built: C++ basics (20 skills) and Data Structures and Algorithms (49 skills, from the basics to advanced).

4. Functional Modules and Users. Users: **Learner**, **Author** (maintains the skill graph and templates), **Admin** (analytics). Thirteen modules: M1 Accounts, consent and data rights, M2 Skill graph, M3 Diagnostic, M4 Mastery model, M5 Recommender, M6 Exercises and lessons, M7 Execution and grading, M8 Hint ladder, M9 Sessions, M10 Revision, M11 Progress, M12 Scaffolding fade, M13 Analytics.

5. Tools/Platforms.

- **5.1 Hardware:** development on a laptop with a 4-core or better processor, 8–16 GB RAM, 256 GB SSD. Production for the pilot: Vercel for the web app, Render (Singapore) for the API and its queue, and Supabase (Mumbai) for PostgreSQL, all on free plans, plus managed sandboxes; an older laptop takes the nightly backups.
- **5.2 Software:** Windows 11 / Ubuntu 24.04; front end Next.js 16, React 19, TypeScript, Monaco editor; back end Node.js 22, Express 5, TypeScript; database PostgreSQL (16 locally, 17 on Supabase) with Drizzle ORM; Redis 7 with BullMQ; E2B sandboxes with clang 19 (C++20); Google Gemini API; Brevo email API; Docker, pnpm, Git/GitHub, Vitest.

6. Methodology. 6.1 Incremental and iterative development. 6.2 It suits a system whose correctness is partly statistical: each increment produces a working system whose predictions can

be checked against real learner performance, and the design decisions are recorded as they are made (architecture decision records), so later increments build on settled ground.

7. Future Scope. More courses (Java, Python, frontend, backend), a mobile app, colleges as institutional customers, live calibration of the mastery model from real learners, and spoken explanation assessment.

CHAPTER 1: PROBLEM FORMULATION

1.1 Introduction about the Organisation

The project is carried out at **Jagan Institute of Management Studies (JIMS), Rohini**, as the MCA-269 Minor Project of the 2025–2027 batch, under the guidance of Dr. Chetna Laroia. It is not built for an outside company. The team (Ashwani Kumar Puri: backend, architecture and database; Aman Dogra: frontend; Aditi Tanwar: frontend and UI/UX) intends to continue it as a product under the name **Nidanos** after the course, which is why commercial concerns (licensing, data protection law, running cost) were treated as real requirements from the start.

1.2 Introduction about the Problem

Learning to program has become easy to *start* and hard to *finish*. A learner can watch hours of video and follow along successfully, yet face a blank editor and be unable to write a working function. The problem was first observed by a team member while learning a web stack under time pressure, and later measured on a pilot learner (Learner A, anonymised): **10 of 11** on reading code, **0 of 4** on writing it. A single "progress" number would have averaged these into about 65% and hidden the real situation completely.

Three causes stand out:

1. **Completion is measured instead of capability.** Platforms record what was watched or ticked, not what the learner can produce.
2. **Help is unlimited and never withdrawn.** An AI assistant asked for code gives code; productivity rises, capability does not.
3. **Nobody keeps a model of the learner.** Without one, the next step is chosen by playlist order, not by what this learner needs.

1.3 Present State of the Art

Kind of system	Examples	What it does well	What it lacks for our problem
Video course platforms	Coursera, Udemy, free video courses	Wide content, low cost	No learner model; completion measured, not capability

Kind of system	Examples	What it does well	What it lacks for our problem
Interactive coding platforms	Codecademy, Scrimba	Learner types code	Fixed sequence, heavy scaffolding that never fades
Practice and assessment	LeetCode, HackerRank, Exercism	Real graded code	No teaching, no learner model, no adaptive path
Spaced repetition	Anki, Quizlet	Schedules revision	Recall of facts, not writing code
General AI assistants	ChatGPT, GitHub Copilot	Explain anything	Give answers freely; no memory of what the learner can do
AI tutoring products	Khanmigo, Duolingo Max	Guided hints	Not focused on writing code; no separate reading/writing model

The research behind our design:

- **Bloom (1984)**: one-to-one tutoring with mastery learning lifts the average student about two standard deviations, so we aim at mastery-based progression.
- **Roediger & Karpicke (2006)**: recall builds memory and re-reading builds false confidence, so mastery moves only on produced evidence.
- **Bjork & Bjork**: desirable difficulties, so help is limited on purpose.
- **Cepeda et al. (2006)**: the spacing effect, so mastery decays and revision is scheduled.
- **Sweller**: worked examples help beginners, but the effect reverses with expertise, so support fades rung by rung.
- **Corbett & Anderson (1994)**: knowledge tracing. We keep its idea of estimating hidden skill from noisy evidence, but use two scores and add forgetting.
- **VanLehn (2011)**: step-level tutoring works best, so hints respond to the current attempt.
- **Bastani et al. (2025)**: unrestricted AI help made students score 17% lower once the AI was removed; restricted, hint-only help did not.

1.4 Need of Computerization

The "manual" way (a learner, a playlist and an unrestricted AI chat) cannot do what the problem needs:

- **Grading real code** needs a compiler, hidden tests and time and memory limits, applied identically every time. Done by hand, it is slow and inconsistent.

- **Keeping two mastery scores per skill**, decaying them daily and adjusting them after every submission, is arithmetic over hundreds of events per learner.
- **Choosing the next step** from a prerequisite graph and current mastery is a query, not a guess.
- **Enforcing limits on help** (hint ceilings that fade) only works if the server, not the learner, holds the rules.

1.5 Proposed Software / Project

A web application in which the learner:

1. takes a short adaptive placement test, so that skills they already know are fast-tracked;
2. is given the next step (skill, level and exercise) by fixed rules, in study sessions they can pause and resume;
3. reads that skill's lesson, written for their level (new, building or strong): an explanation, a diagram, a worked example with its exact output, common mistakes and a predict-the-output check;
4. opens an exercise matched to their level (five rungs, from *predict the output* to *build from a blank page*);
5. writes code in an in-browser editor and submits it;
6. has it compiled and run in an isolated sandbox against hidden tests, getting one of seven verdicts; in the DSA course, large hidden tests also check that the solution is fast enough;
7. sees their reading and writing mastery change from that evidence;
8. asks for hints one level at a time, and gets less help over time as they succeed with few hints;
9. can correct, download or delete their own data at any time, and switch the optional AI-training and research uses on and off.

Two courses are seeded: **C++ basics** (20 skills, from a first program to the standard library) and **Data Structures and Algorithms** (49 skills in 8 groups, from complexity analysis to network flow and advanced dynamic programming, building on the C++ course).

The system is **deterministic where it matters**: grading, mastery, placement and next-step choice are fixed rules in code. Content is proven before use: lessons and exercises are run in the sandbox and frozen, stored hints are verified, and live hints about the learner's own code pass a filter that blocks anything resembling the solution.

1.6 Importance of the Work

- **For learners**, especially students preparing Data Structures and Algorithms in C++ for placements: an honest picture of what they can write, and practice that builds independence instead of dependence.
- **For institutions**: a measure of real coding ability rather than course completion.
- **Technically**, the project combines several areas from the semester: database design (a 44-table schema with integrity constraints), software engineering (layered modules, ADRs, automated tests), security (authentication, sandboxing, India's DPDP Act 2023) and AI (LLM content under strict guardrails).

CHAPTER 2: SYSTEM ANALYSIS

2.1 Feasibility Study

2.1.1 Technical Feasibility

The hard technical parts were proven early by building them, not just by planning them.

Risk	How it was settled	Evidence
Running untrusted C++ safely	E2B cloud sandboxes (Firecracker micro-VMs), **one fresh offline sandbox per submission**, killed after use	All six verdict types reproduced on the real service (section 4.3)
Judging memory and time limits	Our own judge: `timeout` for time, `prlimit` for address space, GNU `time` for peak memory	MLE, TLE and RE detected correctly
Speed	Measured each step and cut the network round trips from 2 per test to 3 per submission	5–15 s down to about 6 s per submission
Data integrity	PostgreSQL constraints: CHECK ranges, partial unique indexes, foreign keys	16 database-rule tests
Placing learners fairly	A placement walk over the skill graph with a check question after a possible slip	All 711 possible C++ knowledge states, and 300 random DSA learners, placed exactly in simulation (section 4.2)
Keeping the AI from giving answers	A filter compares every hint with the reference solution; caps per learner and per month	Unit tests with real leak attempts (section 4.2)
Trusting AI-written exercises	Stored only after the sandbox proves them: the reference passes, the starter fails, and 3 wrong answers fail	Tests with a fake model and sandbox, including weak tests being rejected (section 4.2)
Account recovery without revealing accounts	The same reply for every email, with all the work done after it; a one-use, 30-minute link stored only as a hash; at most one email per account every 5 minutes	9 tests and an independent security review (section 4.3)

Risk	How it was settled	Evidence
Deleting an account without losing what the law keeps	Each module erases its own rows, children first; consent proof and a year of sign-in records stay under an anonymous ID; a test lists every table that points at a learner and fails on a new one	19 tests, a run on the real database and a second security review (section 4.3)
Lessons that are correct	Both programs of every lesson run in the real sandbox and must print exactly the output the lesson states; a leak filter stops a lesson from solving its skill's exercises; a generated lesson also passes a claim-by-claim fact check	207 lessons frozen this way; the sandbox caught every wrong stated output before freezing (section 4.3)
Speed tests that tell fast from slow	Large tests built from a seed, with the expected output taken from the reference; a brute-force solution must agree on a medium test and time out on a large one	All 245 DSA exercises and the 98 DSA placement items verified on the real sandbox (section 4.2)
Team skills	The stack (TypeScript, React, Node, SQL) matches the semester courses	Working code in the repository

2.1.2 Economic Feasibility

The budget is a student budget, so every running cost was measured or quoted, not assumed.

Item	Choice	Cost
Hosting (API, worker, queue)	Render free web service and Key Value, Singapore. Oracle Cloud Always Free was the plan, but Mumbai had no capacity in 63 tries (ADR-0024)	₹0 per month
Database	Supabase free plan, Mumbai: 500 MB	₹0 per month
Web hosting	Vercel free plan during the college phase, at tutor.nidanos.com	₹0
Backups	An older laptop we own, as a home server: nightly encrypted dump, 14 days kept	₹0
Code execution	E2B, billed per second while a sandbox runs; $100 starting credit	about ₹0.01 per submission
Exercise generation	Gemini 3.8 Flash (3.1 Pro on a third try), once per exercise, then frozen; its own cap of ₹300 per month	about ₹1.5 per exercise; skills 6–20 were hand-written instead, saving about ₹110–150

Item	Choice	Cost
Lessons	207 hand-written for both courses and frozen; generation with a fact check is ready for later courses, with its own cap of ₹300 per month	₹0 so far; about ₹0.6 per generated lesson plus ₹0.15 for its check
Live tutor hints and lesson notes	Gemini 3.5 Flash Lite, capped at 20 per learner per day and ₹500 per month in total	about ₹0.08 per hint (₹0.01 measured on short test prompts)
Account emails (password reset, deletion notice)	Brevo free plan: 300 emails a day	₹0

One cost was found only when paying: a new Google Cloud billing account in India must prepay **₹3,000** in total before the paid Gemini tier activates (₹500 paid on 18 October, ₹2,500 due on 7 November). Until then the key stays on the free tier, where prompts may be used by Google, so live hints are switched off by a setting until billing is active (7 November 2026, section 4.5). The free tier also turned out to allow only 20 Flash calls a day and no Pro calls, about 9 lessons a day. So all the lessons were written by hand, which also kept them in the repository, reviewable and identical in every environment (ADR-0019).

One design decision is a direct result of this study. The first design kept one sandbox alive for a whole learner session. Because E2B bills every second a sandbox is alive, that would cost about **₹4.60** for a 30-minute session. Creating a fresh sandbox per submission costs about **₹0.25** for the same session, roughly 18 times less, so the design was changed (ADR-0003).

2.1.3 Operational Feasibility

- **Learners** need only a browser. There's no installation; the code editor and compiler run online.
- **The team** can run the whole system locally with three commands (section 4.4). The server is the same Docker Compose setup, so operating it needs no special skills.
- **Authors** add skills, lessons and exercises as data (seed files), not code changes. A lesson is a Markdown file, and an exercise a short C++ template.

2.1.4 Other Feasibility Dimensions

- **Legal.** The system stores personal data, so it is designed for India's **Digital Personal Data Protection Act, 2023**:
    - consent at sign-up, recorded with the policy version;
    - separate opt-ins for AI training and research, adults only;

    - during the pilot, sign-up is for adults only, because a child's account needs a parent's approval and that flow comes later;
    - learner code is never sent to the AI with a name or email, and is deleted once the learner clears that skill;
    - account emails (password reset, deletion notice) go through Brevo (EU), which receives only the email address;
    - learners can correct, download or delete their data, and switch the opt-ins on and off; a deletion waits 7 days (logging in cancels it), then keeps anonymous numbers only for learners who opted in;
    - the Terms of Service and Privacy Policy are published at `/terms` and `/privacy`, built from the same texts learners accept;
    - data is stored in India (Supabase, Mumbai), and processed in Singapore while the API handles a request (ADR-0024).
- **Licensing.** No third-party course content is copied. Skill names, descriptions, lessons and exercises are our own, and external references appear only as links. The source code is published under the PolyForm Noncommercial License 1.0.0: anyone may study and run it, but commercial use needs the team's permission.
- **Schedule.** All 33 endpoints (the 23 planned, plus forgot and reset password, six for data rights and two for lessons) were live by Review 3 (section 4.5). The DSA exercise bank and placement test were finished on 21–22 October, ahead of plan. On 23 October calibration was added, and the deployment files, the pilot data export and the pilot survey were written; the frontend, running the deployment, the first live AI runs (once billing is active on 7 November) and the pilot are planned up to 10 November 2026.

2.2 Analysis Methodology

Model: incremental and iterative. Each increment adds one working, tested capability on top of the previous one:

1. Schema and authentication.
2. Consent and data protection.
3. Sandbox and judge.
4. Submissions and queue.
5. Mastery engine.
6. Exercises and attempts.

7. Help fading.
8. Template exercise bank, verified in the sandbox.
9. Next-step recommender.
10. Placement test.
11. Study sessions and the progress view.
12. Admin analytics.
13. LLM adapter and hints.
14. Exercise generation.
15. Password reset by email, and per-IP limits that trust only our own proxy.
16. Data rights (correct, download, delete), skill details with each exercise, and the Terms and Privacy pages.
17. The DSA course's skill graph, with prerequisites that reach into the C++ course.
18. Personalised lessons: three frozen levels per skill and a short live note, with all 207 lessons written and proven in the sandbox.
19. The DSA exercise bank: generated speed tests and a brute-force check (all 245 exercises).
20. The DSA placement test: a reading item and a code task for each of the 49 skills (98 items), under the C++ test's rules.
21. Calibration from each first try (ADR-0021); the review queue recorded as worked out on read (ADR-0022); generation kept to C++ basics for the pilot (ADR-0023).
22. Deployment files checked locally, the pilot data export and the pilot survey.
23. Pilot hosting on Vercel, Render and Supabase after Oracle had no capacity, with nightly backups to the home server (ADR-0024).

Every increment ended with automated tests and a real end-to-end run before the next one began. Larger designs (the placement test, hints, generation) were also reviewed by adversarial checks that tried to break them, and the holes they found were fixed before the code was committed (Table 9).

Analysis tools used:

- **Requirements:** the SRS from Phase 1, numbered as FR-Mx-yy and NFR-xx.
- **Decisions:** each one recorded as an Architecture Decision Record (ADR-0001 to ADR-0024), with the options compared and the reason for the choice. For example, ADR-0003

compares Judge0, Piston and E2B on compiler version, memory-limit support, network isolation and cost.

- **Measurement before optimisation:** timings were measured step by step before anything was changed.


Pilot baseline. The planned "Phase 0" (running the whole loop on paper with a learner before coding) was **not carried out**. It was replaced by a measured baseline of one anonymised pilot learner (Learner A: reading 10/11, writing 0/4), which confirmed the central design choice of separate reading and writing scores. A pilot with real learners on the finished system is planned before the final report.

System Planning (PERT)

Activity	Depends on	Dates	Status
A. Synopsis, problem analysis, literature survey, SRS	–	7–24 Sep	Done (Review 1)
B. System design: DFD, ER, UML, ADRs	A	25 Sep–15 Oct	Done (Review 2)
C. Database schema and migrations	B	13 Oct	Done
D. Authentication and DPDP consent	C	13–14 Oct	Done
E. Sandbox and judge	C	15 Oct	Done
F. Submissions, queue, mastery	D, E	15 Oct	Done
G. Exercises, attempts, help fading	F	16 Oct	Done
H. Frontend screens	D	16–31 Oct	In progress (team; due 31 Oct)
J. Template bank, recommender, placement test	G	17–18 Oct	Done
L. Sessions, progress, analytics	J	19 Oct	Done
I1. LLM adapter and hints	G	19 Oct	Done (live calls wait for billing)
I2. Exercise generation	I1	19 Oct	Done (live runs wait for billing)
N. Password reset by email	D	19 Oct	Done (real emails once the Brevo account is set up)
O. Data rights, skill details, Terms and Privacy pages	D	19 Oct	Done (the Settings screens are part of H)

Activity	Depends on	Dates	Status
P. CI, code purge, adults-only pilot sign-up, guided demo walk	O	20 Oct	Done
Q. DSA course: skill graph of 49 skills	J	20 Oct	Done
R. Personalised lessons: 3 levels per skill, live note, 207 hand-written lessons	Q, I1	20 Oct	Done (live notes wait for billing)
S. DSA exercise bank: 245 exercises with speed tests	R	20–21 Oct	Done (planned to 2 Nov)
T. DSA placement test: 98 items	S	22 Oct	Done (planned for 3–5 Nov)
U. Calibration; review-queue and generation-scope decisions	T	23 Oct	Done
V. Deployment files, pilot data export, pilot survey	U	23 Oct	Done (deployed with K, on Vercel, Render and Supabase: ADR-0024)
M. Gemini billing activation	–	7 Nov	Planned (₹2,500 of the ₹3,000 prepayment left)
I3. First live AI runs: frozen hints, live notes, extra generated exercise variants	I2, R, M	7–8 Nov	Planned
K. Deployment, pilot, final report	H, I3, L, V	5–10 Nov	Planned

Critical path: A → B → C → E → F → G → J → Q → R → S → T → K. The sandbox and grading chain was the riskiest part, so it was built first. With the DSA content written, the frontend (H) is now the longest chain, and the billing activation (M) the one outside dependency.



2.3 Choice of the Platforms

2.3.1 Software Used

Layer	Choice	Why this, for this project
Language	TypeScript (end to end)	One language for frontend and backend; shared types catch contract mistakes at compile time
Front end	Next.js 16, React 19, Monaco editor	The same editor as VS Code; a built-in proxy to the API means the same origin, so no CORS issues and httpOnly cookies work
Back end	Node.js 22, Express 5	Most backend work is waiting on the database, sandbox or LLM, which Node's event loop handles cheaply. Express 5 forwards async errors to one handler
Validation	zod 4	Every request body is checked against one schema, and types are inferred from it
Database	PostgreSQL 16 with Drizzle ORM	Constraints, transactions and row locks keep mastery consistent; Drizzle gives typed queries and versioned migrations
Queue	Redis 7, BullMQ	Running code is slow, so it is queued: retries, rate limits, and the API stays fast

Layer	Choice	Why this, for this project
Code execution	E2B sandboxes, Debian 13, clang 19, C++20	Managed isolation with internet off; a current compiler; per-second billing
AI	Google Gemini (paid tier)	Cheapest capable models; paid-tier data is not used for training; hidden behind one adapter
Email	Brevo transactional email API (plain `fetch`, no SDK)	The free plan covers the pilot (300 emails a day); EU-hosted, with a data processing agreement in its terms
Security	argon2id, jose (JWT), httpOnly cookies, express-rate-limit, helmet	Passwords hashed, short-lived tokens, CSRF origin check, rate limits
Testing	Vitest, Supertest	Fast unit tests and HTTP-level integration tests on a separate test database
Tooling	pnpm workspaces, Docker Compose, Git/GitHub	One repository for web, API and shared types; identical local setup for every team member

2.3.2 Hardware Used

Purpose	Specification
Development machine	Windows 11 laptop, multi-core processor, 8–16 GB RAM, SSD
Backup server	Older laptop running Ubuntu Server 24.04 LTS (AMD Ryzen 5 4600H, 8 GB RAM): nightly encrypted backups of the pilot database
Production (pilot)	Render free web service (512 MB, 0.1 CPU, Singapore) for the API and queue; Supabase free PostgreSQL (500 MB, Mumbai); Vercel for the web app
Sandboxes	E2B micro-VMs: 2 vCPU, 512 MiB RAM each, created per submission
Learner's device	Any modern browser; no installation

CHAPTER 3: SYSTEM DESIGN

3.1 Design Methodology


The system is a **modular monolith**: one backend, divided into 13 modules (M1–M13). Each module has the same four layers:

```
routes → controllers → services → repositories → database
(URL)    (HTTP in/out)  (rules)    (SQL only)
```

Five rules hold the design together:

1. **Modules talk through services, never through each other's tables.** For example, the execution module (M7) asks the exercises module (M6) for an exercise through `getRunnableExercise()`; it never reads M6's tables.
2. **One writer per state.** Only M4 writes mastery, and only M12 writes fade stages.
3. **Deterministic core, LLM at the edge.** Grading, mastery and next-step choice are fixed code. The LLM only produces content, which is verified and frozen first.
4. **Server-owned state.** Hint level, hint ceiling, fade stage, mastery and verdicts live only in the database, so the client can't tamper with them.
5. **Slow work is queued.** The API answers in milliseconds; running code happens in a background worker.

Figure 1: System architecture




3.2 UML Modelling

3.2.1 Use Case

The learner registers, takes a diagnostic, reads the lesson for their level, solves exercises, asks for hints, views progress, can reset a forgotten password by email, and can correct, download or delete their own data. The author maintains the skill graph, the lessons and the template exercises; the admin views analytics. Two non-human actors matter: the **scheduler** (mastery decays with time, not only with clicks, and a deleted account is erased once its 7 days are over) and the **sandbox, LLM and email services**.

Figure 2: Use case diagram



3.2.2 Sequence Diagrams

Figure 5: Register, then log in. Registration does not log the user in. The user logs in separately and receives a 15-minute access token plus a rotating 30-day refresh token.




Figure 16: Forgot and reset password, as built (ADR-0017). The reply is the same for every email and all the work happens after it, so neither the reply nor its timing shows who has an account. The token travels in the link's `#fragment`, which browsers never send to a server, and only its SHA-256 hash is stored. The reset is one transaction: it marks the link used (only if it is still unused), ends the account's other links, saves the new argon2id hash and revokes every session.




Figure 17: Delete an account, as built (ADR-0018). The password is asked again, so a stolen session alone can't delete the account. Every login ends at once, and nothing is erased for 7 days: logging in again cancels the request. Then the hourly job closes the account, so no name, email, password or date of birth is left, and each module erases its own rows, children first. With an opt-in to research or AI training only anonymous numbers stay; without one every learning row goes. Consent records, and a year of sign-in records, stay under the anonymous ID, as the law asks.





Figure 6: Submit code. This is the central flow of the system. The API saves the submission and answers `202` at once; a worker grades it in a fresh sandbox and saves the verdict, the mastery evidence and any fade advance in **one database transaction**.



3.2.3 Activity and State Diagrams

Figure 7: State of a submission. A sandbox failure is retried with a fresh sandbox; after the last try the verdict is SE, which never counts against the learner.




Figure 8: Activity diagram, next-step selection, as built (recommender m5-v1, ADR-0011). No LLM is involved; every pick is saved with its reasons.




Figure 14: Request a hint, as built (ADR-0015). One level per request, never above the fade stage's ceiling. The live tutor comes first; the frozen hint is the fallback.




Figure 15: Placement test, as built (ADR-0012). Reading questions walk the skill graph easiest-first; code tasks are asked only on the frontier of what was read correctly.




Figure 18: Open a lesson, as built (ADR-0019). The lesson is frozen and chosen by the learner's level today. The short live note over it uses the learner's results, never their code, and is reused until they practise the skill again.





Figure 19: Verify an exercise with generated speed tests, as built (ADR-0020). Large tests are built from a seed in the harness, so nobody writes their answers by hand: the reference supplies them, and a slow but correct brute force checks the reference.



3.2.4 Class Diagrams

Figure 3: Domain model (attribute names only; their types are in the ER diagrams and the data dictionary, A-7)




Figure 4: Services and adapters, as built (method parameters left out for space), in two parts. Two interfaces keep the outside services replaceable: `SandboxProvider` (only one class

knows about E2B) and `LlmProvider` (only one class knows about Gemini). Tests replace both with fakes. Modules call each other's services, never each other's tables.

Figure 4a: Running code and moving mastery. The submission flow and the content verifier both reach the sandbox only through `SandboxProvider`.





Figure 4b: The AI and the placement test. Hints and lesson notes reach Gemini only through `LlmProvider`; the placement test writes its results through the same mastery and fade services as practice.



3.3 Database Design

Design rules applied:

- **Ledger plus snapshot.** Every mastery change appends an `evidence_events` row that is never edited; `mastery_records` holds today's value. Both are written in one transaction,

so the history always explains the number.

- **Compute on read.** Effective mastery (after forgetting) and "review is due" are calculated when read, never stored, because they change every second.
- **Frozen content.** An exercise is identified by its content key (skill, language, rung, variant, content version). Its secret parts (harness, reference solution) live in a separate table, `exercise_secrets`, that no learner-facing query touches.
- **Normalisation.** Tables are in third normal form: each non-key column depends only on its table's key. There are two deliberate, documented exceptions. `submissions.user_id` is copied from the attempt to make per-learner queries simple. `mastery_records` is a snapshot of the ledger, kept consistent by always writing both in one transaction.

Validations enforced by the database itself:

Rule	How it is enforced
Scores between 0 and 1; rungs 1–5; hint level 0–5	CHECK constraints (`inRange` helper)
A hint level never above the attempt's ceiling	CHECK `hint_level <= hint_ceiling`
One active attempt per learner and exercise	Partial unique index `WHERE status = 'active'`
A submission never runs twice	UNIQUE `idempotency_key`
Evidence never counted twice	UNIQUE `(submission_id, dimension)`
One live consent of each kind	Partial unique index `WHERE revoked_at IS NULL`
Email unique in any letter case	`citext` column type
A skill can only sit on a stage its schedule has	Composite foreign key
Each reset link is unique, stored only as its hash, and used once	UNIQUE `token_hash`; the reset marks it used only `WHERE used_at IS NULL`
An erased account keeps its consent proof	`consents` has no cascade: the user row is anonymised (status `deleted`), never deleted

The schema has **44 tables in 9 groups**: 41 are built (16 migrations), and 3 come later with their features. The two newest, `lessons` and `lesson_notes`, came with the personalised lessons (ADR-0019). `lessons` holds no personal data. A lesson note is written about one learner, so it is personal data: it is in the learner's download and is always erased with the account.

3.3.1 ERD

Figure 9a: Overview of the table groups. Each box is one group of tables and the module that owns it; an arrow points from a group to the groups that refer to it. The full ERD is in the Phase 2 design document (section 5).




Figure 9b: Attempts and submissions, the tables the submit flow writes first





Figure 9c: Execution, one sandbox run per submission (or verification) and one result per test



3.3.2 DFD

Figure 10a: Level 0 (context)




Figure 10b: Level 1, part 1 of 2: the learning loop (processes 3, 4, 5, 6, 7, 9, 10 and 12)




Figure 10b: Level 1, part 2 of 2: accounts, content, hints and reports (processes 1, 2, 8, 11 and 13). A data store shown in both parts is the same store. Dashed lines: process 1 erases a deleted account's rows (each module erases its own).





Figure 10c: Level 2, process 7 (execute and grade)



3.4 Input Design

All input enters through the REST API, and **every request body is validated by a zod schema before any logic runs**. Invalid input returns `400 VALIDATION_ERROR` with a message per field.

Input	Fields	Validation
Register	email, password, displayName, dateOfBirth, acceptTerms, acceptPrivacy, aiTraining?, research?	Email ≤ 254 characters, case-insensitive; password 8–128 characters (NIST: no forced symbols); name 1–80; date of birth a real date, not in the future; both acceptances must be `true`; under-18s refused during the pilot (shown next to the date of birth); `.invalid` addresses refused (erased accounts use them); unknown fields such as `role` are stripped
Login	email, password, client (web or mobile)	Same email rules; failed logins throttled per email and per IP
Forgot password	email	Same email rules; the same reply whether or not the account exists; 5 requests per IP per 15 minutes, and at most one email per account every 5 minutes
Reset password	token, password	Token 20–200 characters; password as for sign-up; a used, expired or replaced link gives `400 RESET_LINK_INVALID`; 10 per IP per 15 minutes
Correct profile	displayName?, timezone?	At least one; name 1–80 after trimming; a real IANA time zone; email and date of birth can't be changed here
Opt in or out	kind, in the path	Only `ai_training` or `research_study` (the required consents end with the account); opting in for adults only (`403 ADULTS_ONLY`); 30 changes an hour
Delete account	password	The account's own password again (`403 WRONG_PASSWORD`); 5 tries per 15 minutes
Submit code	attemptId, answer, idempotencyKey	attemptId must be a UUID of *your own* active attempt; answer ≤ 64 KB; key 8–100 characters; 10 submits per minute per learner
Read mastery / fade state / progress	`language` (and `course`) query parameters	Optional, 1–20 (60) characters; the course must be offered in that language
Placement answer	itemId, then answer or dontKnow	Only the current question is accepted (`409 ITEM_NOT_CURRENT` otherwise); answer ≤ 64 KB with no NUL character; 30 calls per minute
Session change	status: active, paused or ended	An ended session refuses changes
Hint request	code (optional)	≤ 64 KB; the level is decided by the server, never the client; 10 per minute

Input	Fields	Validation
Lesson and its note	skill id in the path, `language` query parameter	The skill must exist (`404 SKILL_NOT_FOUND`); the level comes from the server's scores, never the client; a note request shares the hint limit (10 a minute) and the 20 live calls a day
Analytics	days (1–365), course, language	Admin role only (`403 FORBIDDEN` otherwise)

Screen input (frontend, in progress): sign-up form with a date picker and two separate required tick boxes, with the optional opt-ins shown only when the date of birth makes the user 18+; login form; forgot-password and set-new-password forms; Settings (to build): profile, privacy switches, download and delete; lesson page, where the check's answer stays hidden until the learner has typed a guess; exercise page with the Monaco editor (a plain text box for rung-1 "predict the output"). The same rules are applied in the browser to show errors before submitting, but the server is always the authority.

3.5 Output Design

Every response has **one envelope**:

```
{ "success": true, "data": { } }
{ "success": false, "error": { "code": "ATTEMPT_CLOSED", "message":
"This attempt is already finished" } }
```

The client branches on `error.code` and shows `error.message`.

The submission result shows a sample test in full, and a hidden test as its verdict only:

```
{ "verdict": "WA", "testsPassed": 1, "testsTotal": 4,
  "tests": [
    { "seq": 1, "name": "Example", "visibility": "sample", "verdict":
"WA",
      "input": "123", "expectedOutput": "6", "output": "3\n" },
      { "seq": 2, "name": "Zero", "visibility": "hidden", "verdict":
"AC", "timeMs": 0 } ] }
```

A placement question carries the program or the task, never its answer key, its tests or whether earlier answers were right:

```
{ "itemId": "…", "dimension": "reading", "skill": { "slug":
"operators", "name": "Operators" },
  "promptMd": "Read the program carefully. **What does it print?**",
"code": "#include <iostream>\n…" }
```

A hint is one level only, with where it came from:

```
{ "level": 2, "ceiling": 5, "source": "live", "bodyMd": "Look at the
line that returns the result: which variable does it use?" }
```

A lesson is the frozen one for the learner's level today, or the nearest level written. Its live note comes from a separate request and is `null` when there's nothing personal to say yet:

```
{ "level": "building",
    "lesson": { "level": "building", "explanationMd": "### A quick
recap…", "diagramMermaid": "flowchart TB…",
                "example": { "code": "#include <iostream>…", "output":
"…", "walkthroughMd": "1. …" },
              "mistakesMd": "- **Forgetting the end mark.** …",
                          "check": { "code": "…", "output": "9 1 0",
"explanationMd": "…" } } }
```

The password-reset email has a subject, a button and the plain link (`/reset-password#token=…`), and no name: the email provider may receive only the address (privacy policy §5).

The account-deletion email gives the date in the learner's own time zone and says that logging in before then cancels the deletion. It has no name either.

The data download (`GET /me/data`) is a file to keep, so it is the one reply without the envelope: `ai-tutor-my-data.json`, never cached. It starts with a summary, the purposes and the five named providers (what each one receives), then holds every row each module keeps about the learner. It never contains a password or token hash, or a hidden test.

Skill details come with every exercise and in the progress view: the skill's own one-line description and its further-reading links, in the learner's language.

The Terms and Privacy pages (`/terms`, `/privacy`) are built from the same text files the learner accepts; the build fails if a draft line or an unfilled blank is left.

Mastery output always shows reading and writing **separately**, each as a stored `score` and an `effective` score after forgetting. They are never blended into one number, because a 10/11 versus 0/4 profile averages into a misleading 65%.

3.6 Code Design and Development

```
apps/api/src/
  config/env.ts                settings, validated at startup
  infrastructure/
     database/  schema/ seed/    Drizzle tables, migrations, seed data
(both courses' skills, lessons
                                          as Markdown, exercises as C++
templates)
    sandbox/                   SandboxProvider interface, E2B adapter,
template
```

```
    llm/                          LlmProvider interface, Gemini adapter,
cost log
    queue/                       BullMQ queues and workers: submissions,
generation, hourly erasure
    mail/                          Brevo email (printed locally when no
key is set)
   shared/                               errors, response envelope, auth
helpers, middlewares, India time
  modules/                      each: routes → controllers → services →
repositories
      m1_auth   m2_skills   m3_diagnostic   m4_mastery   m5_recommender
m6_exercises
          m7_execution     m8_socratic     m9_sessions     m11_progress
m12_scaffolding  m13_analytics
  scripts/                       sandbox build and smoke test, exercise
verification, lesson seeding and
                                       generation, hint generation, make-
admin, the guided demo walk
```

Key pieces of logic are pure functions, which means no database and no network, so they are fully unit-tested:

- `judge.ts`: turns sandbox readings into a verdict (Table 5).
- `mastery-formula.ts`: the M4 formula and decay (Table 6).
- `age.ts`: whole-year age, used for the under-18 rule.
- `recommend.ts`: the next-step rules (Figure 8).
- `placement.ts`: the placement walk and estimates (Table 11, Figure 15).
- `session-clock.ts`: idle pause after 15 minutes, end after 24 hours paused, study time.
- `solution-filter.ts`: blocks hints that resemble the solution (Table 12).
- `exercise-draft.ts`: what the model must write for a new exercise, the prompt, and the conversion into the hand-written bank's format (Table 13).
- `verify-exercise.ts`: the proof every exercise passes in the sandbox, including generated speed tests and the brute-force check (Table 16, Figure 19). It talks to the sandbox only through `SandboxProvider`, so its rules are unit-tested with a fake.
- `freeze-lesson.ts`: the gates every lesson passes before it is stored (Table 15).

Table 5: Verdict rules. These are checked in this order for each test; the first failing test decides.

Verdict	Rule
CE	The compiler exits non-zero, or takes longer than 10 s
TLE	The test was killed by the time limit (2 s by default)

Verdict	Rule
MLE	Peak memory above the limit (256 MB), or a `std::bad_alloc` crash
RE	Any other non-zero exit (crash, divide by zero)
WA	Output differs from the expected output (trailing spaces and line endings ignored)
AC	All tests pass
SE	The sandbox itself failed; retried, never counted

Table 6: Mastery formula v1. Rung 1 moves reading; rungs 2–5 move writing.

Event	Update
AC	new = old + 0.40 × weight × (1 − old); weight = rung/5 × (1 − 0.15 per hint; 0 if the solution was shown) × time factor (0.7–1)
WA or RE	new = old × (1 − 0.15 × (6 − rung)/5); **only the first failure in an attempt** is penalised
TLE or MLE	Penalty starts at 1/20 of a WA, doubles on each consecutive one, capped at a WA; only an AC resets it
Compile error, sandbox error	No change
Decay (on read)	effective = score × e^(−λ × days since evidence)

About five good solves (rungs 2 → 5) take a new skill from 0 to 0.72, just past the 0.7 prerequisite threshold.

Table 7: Fade stages. Help is withdrawn per skill.

Stage	Easiest rung	Max hints	Moves on after solving
1	1	5	rung 2 (or harder) with ≤ 1 hint
2	3	4	rung 3 with ≤ 1 hint
3	4	3	rung 4 with ≤ 1 hint
4	5	2	rung 5 with ≤ 1 hint → skill cleared

Table 11: Placement test rules (ADR-0012). All 20 C++ skills are covered by 40 frozen, sandbox-verified items: one predict-the-output reading item and one small function per skill. The 49 DSA skills have 98 more under the same rules (22 October), none of them a copy of a practice exercise; DSA code tasks carry speed tests (Table 16).

Rule	Detail
Order	Fewest transitive prerequisites first, then difficulty, then name

Rule	Detail
Reading walk	A skill is asked only if no prerequisite was missed. A right answer passes the skill and all its prerequisites
Slip check	"I don't know" is a miss. A typed wrong answer is only *suspect* until its first dependent is answered: right rescues it, wrong confirms both
Code tasks	Only on the frontier (passed skills nothing else passed builds on); an AC vouches for everything below. Run in the background
Estimate	Passed → 0.85 for reading; proven in code → 0.85 for writing; confidence 0, 0.5 or 1 by what was observed
Seeding	One transaction: mastery raised only if higher than today's value; skills proven in code start on the last fade stage; skills cleared in practice untouched
Length	C++: 1 question for a novice, 6 for a beginner, 18 for a mid learner, 26 (about 28 minutes) for an expert, instead of 40. DSA: 17 for a learner who knows 4 skills; 49 reading and 20 code tasks for an expert (about 2½ hours, with pause and resume)
Retakes	Up to 3 per course; a retake can lift a placement but never lowers it

Table 12: Hint ladder and where each hint comes from (ADR-0015).

Level	Content	Source
1 Concept	The idea or C++ feature needed, in words	Live tutor first; frozen hint if capped, failed or blocked
2 Location	Where in the learner's own code the problem is	Same
3 Mechanism	How to fix it, in words	Same
4 Worked example	A different, smaller problem using the same technique	Same
5 Answer	The reference solution, or the program's output for rung 1	Always frozen; logged as a bottom-out; the attempt earns no credit

Table 13: Exercise generation: how a job runs (ADR-0016). Started by an admin or author, or queued automatically by the recommender when a learner's best next skill has no exercise.

Step	Rule
Queue	One active job per skill and rung; a second request gets the same job. Run one at a time in the background
Tries	Up to 3: Gemini 3.8 Flash, Flash, then Gemini 3.1 Pro. Each retry is told why the last draft was rejected

Step	Rule
Draft	JSON checked against a schema: title, prompt, function signature, the call each test makes, starter, reference, 3–6 test cases, and 3 wrong solutions (rung 1: a program and its claimed output)
Prompt	The skill, the only other skills it may use (its prerequisites), the rung's rule, the frozen harness, an example from the hand-written bank, and the titles to avoid
Proof	In the real sandbox: the reference passes every test, the starter compiles but fails one, and each wrong solution compiles but fails one. A rung-1 program must print exactly the output it claims
Store	Only proven content is stored, ready to serve; its frozen hints follow
Failure	Every failed try is logged with its stage. After 3 tries, or when this month's ₹300 is spent, the job falls back to the hand-written exercise for that skill and rung

A live hint is blocked if it holds 25 % or more of the code only the solution has (5-token fingerprints, not counting the starter or the learner's own code), shows a code block longer than 6 lines, or gives away a rung-1 output.

Table 14: Data rights: what each request does, and what erasure keeps (ADR-0018). Every request needs a login and acts only on the learner's own data.

Request	Endpoint	Rule
Correct	`PATCH /me`	Name and time zone; the hidden personal organisation, named after the learner, is renamed too
Opt in or out	`PUT` / `DELETE /me/consents/:kind`	AI training and research only, adults only; a withdrawn consent is kept, revoked, as proof
Download	`GET /me/data`	One JSON file: summary, purposes, the 5 named providers, then each module's rows; 5 an hour
Delete	`DELETE /me`	The password again; every login ends; an email gives the date; logging in within 7 days cancels
Erase	hourly job	Name, email, password, date of birth and all code go. With an opt-in to research or AI training, the anonymous numbers stay (verdicts, scores, timings); without one, every learning row goes. Consents, and a year of sign-in records, stay under the anonymous ID


Table 15: Lessons: what each one holds and the gates it passes (ADR-0019). Each skill has three frozen lessons, one per level: **new** (no score yet), **building** (some score) and **strong** (cleared, or writing ≥ 0.7). The learner gets the lesson for today's level, or the nearest level written, and a short live note over it.

Part	Rule
Contents	An explanation (300–700 words), one Mermaid diagram, a worked example with its exact output and a walkthrough, 3–5 common mistakes, and a check: a short program whose output the learner predicts
Shape	Checked against a schema: example program at most 45 lines, check at most 20, a diagram type the web app can draw
Exercises kept safe	The hint leak filter compares the whole lesson with each verified exercise of the skill, so a lesson never solves one
Programs proven	Both programs run in the real sandbox and must print exactly the output the lesson states
Written by	Hand for both courses (207 lessons). Generation is ready for later courses: Gemini drafts, then the same model checks **each technical claim one by one**; asked only for "errors" in general, it missed a wrong claim that the claim-by-claim check caught
Live note	2–4 sentences from the learner's level, last 5 results and weak prerequisites, never their code; reused until they practise again; counts against the hint caps; a reply with code or over 100 words is dropped

Table 16: Speed tests in the DSA exercise bank (ADR-0020). Five hand-written exercises per skill (245 in all). A task with a slow but correct solution gets large tests; a task without one keeps small tests that wrong answers fail.

Part	Rule
Generated tests	A test without an expected output calls a seeded generator in the harness, such as a million random 0s and 1s. The reference's output becomes its answer, stored at verification
Order	The hand-written tests first (the first is the sample), then a medium generated test, then a large one: the sandbox stops at the first failing test
Reference	Passes every hand-written test, and its slowest test takes at most a third of the 2-second limit
Brute force	Required with generated tests: it passes the hand-written tests, **agrees** on at least one generated test and then **times out**. Disagreeing or crashing rejects the exercise, and finishing every test in time means the tests can't tell fast from slow
Starter	Must fail a test. A slow starter fails by timing out, which makes "make it fast enough" a natural rung-2 task

Figure 12: Deployment, as decided for the pilot (ADR-0024; ADR-0010's own VM comes later)



CHAPTER 4: TESTING AND IMPLEMENTATION

4.1 Testing Methodology

Tests are automated with **Vitest** and **Supertest** and run against a **separate test database** (`ai_tutor_test`), which is rebuilt from the migrations on every run. That way the tests prove the real migrations, not a hand-made copy. Each test creates its own users and data with random names, so tests never depend on each other. **GitHub Actions** runs the type checks, all these tests on a fresh database and the web build on every push and pull request (`.github/workflows/ci.yml`), so nothing that breaks them reaches `main` unnoticed.

4.1.1 Unit Testing

Pure functions are tested with constructed inputs:

- **judge:** each verdict rule, rule order (TLE wins over a crash exit code), output normalisation, and an empty test list giving SE, never AC;
- **mastery formula:** the approved learner journey to the exact numbers, the hint and solution-shown rules, TLE doubling and its cap, and decay to half after $\ln 2 / \lambda$ days;
- **age:** turning 18 exactly on the birthday;
- **skill graph:** cycle detection, plus checks that both seeded courses have unique names, only known prerequisites and no cycles, and that every DSA skill builds on C++ basics and is never easier than what it builds on;
- **recommender:** candidates, review urgency, rung bands clamped to the fade stage, and the journey from rung 1 to rung 5;
- **placement:** every one of the **711 knowledge states** the 20-skill graph allows, answered with "I don't know" and with wrong guesses, is placed exactly, in at most 20 reading and 7 code questions; on the real DSA graph, an expert gets 49 reading and 20 code questions, and 300 random learners are each placed exactly, with one code task per skill on their frontier; slips, missing items and cleared skills;
- **session clock:** the idle pause, the 24-hour end, and study time that never counts idle gaps;
- **leak filter:** prose and fragments pass; the solution, whole or in its key lines, fenced or not, is blocked; the learner's own code is not counted; a rung-1 output is never given away;

- **exercise drafts:** the schema's rules (the test call must take the test's arguments; exactly 3 wrong solutions), the conversion into the bank's format, and what the prompt contains;
- **exercise banks:** both courses have rungs 1–5 once per skill; every DSA exercise shows a sample with its output, and one with generated tests has at least two, last, and a brute force; the DSA placement bank has one reading item and one code task per skill, none reusing a practice exercise's title or function;
- **lessons:** the level rule (new, building, strong), the lesson schema, and all 207 hand-written lessons covering every skill of both courses at all three levels.

4.1.2 Module Testing

Database-rule tests, one per schema group, try to break each constraint on purpose and expect the database to refuse. Examples: a duplicate email in different letter case, a hint level above the ceiling, a second active attempt, a second open session, a duplicate idempotency key, evidence with no source.

4.1.3 Integration Testing

HTTP-level tests call the real Express app with real requests:

- **auth:** register, login, refresh, logout, theft detection, throttling, CSRF, consent, and per-IP limits that trust only our own proxy;
- **submissions:** submit, idempotency, ownership, judging, retries, and deleting a cleared skill's code (privacy policy §2);
- **exercises:** secrets never leak; attempts, enrollment and fade start; the skill's description and reading links;
- **exercise verification:** a reference that fails or a starter that passes is rejected; generated tests take their outputs from the reference only when the brute force agrees and then times out; a brute force that never times out or disagrees, and a reference slower than a third of the limit, are rejected;
- **lessons:** the lesson for the learner's level or the nearest one; a generated lesson proven and frozen, or refused when the fact check finds it false, when it gives an exercise away, or when its programs don't print what it states; the ₹300 monthly stop; hand-written lessons through the same gates;
- **lesson notes:** a note from the learner's recent results and weak prerequisite, reused until they practise again; nothing without live AI, past the daily limit or when the reply has code;
- **mastery and fade:** read views, the decay maths, stage advance;

- **recommender:** first step, moving up rungs, skipping skills without content, naming the other course's skills a learner must finish first, course complete;
- **placement test:** no answer key in any response, only the current question accepted, replays, code tasks queued once, the 202 grading wait, seeding, fast-track to the last stage, retakes, and a cheat attempt with a borrowed idempotency key;
- **sessions and progress:** steps from the recommender, pause/resume at the same step, idle and timeout, statuses that match the recommender's unlock rule;
- **analytics:** admin only, counts only, never a learner's email;
- **hints:** live hint, a leaky reply replaced by the frozen hint, a failed call, the fade ceiling, the answer at level 5, the daily and monthly caps;
- **exercise generation:** a proven draft stored ready to serve; a retry after a bad reply; tests a wrong answer passes, rejected three times, ending on the Pro model and the hand-written fallback; a rung-1 program's claimed output checked; the budget stop; admin-only endpoints; automatic queueing by the recommender;
- **password reset:** the same reply for unknown and inactive accounts, and an email, without the name, only for real ones; the token stored only as a hash; at most one email per account every 5 minutes; one use, even with two resets at once; expiry; only the newest link works; every login ended; the per-IP limit;
- **data rights:** correction and its limits; opt-ins on and off, adults only, 30 an hour; the download holds every module's rows and no secrets; deletion needs the password, ends every login (even one refreshed seconds before), emails the date and is cancelled by logging in; erased accounts' addresses can't be taken;
- **account erasure:** without an opt-in every learning row goes, with one only anonymous numbers stay; accounts still in their grace period, or cancelled, are left alone; every table that points at a learner is accounted for.

The sandbox, Gemini and the email service are replaced by **fake providers** in these tests: same interfaces, fixed results. That makes them fast, free and repeatable.

4.1.4 System Testing

1. **Sandbox smoke test** (`pnpm sandbox:smoke`): six real C++ programs run on the real E2B service, and each must produce its intended verdict (AC, WA, CE, RE, TLE, MLE).
2. **Content verification** (`pnpm exercises:verify`): every seeded exercise runs in the real sandbox; the reference must pass and the starter must fail. **483 of 483 verified** (100 C++ practice exercises, 40 C++ placement items, 245 DSA exercises, 98 DSA placement

items). The 74 hand-written for C++ skills 6–20 were also each run against a common wrong answer first, which had to fail. The 245 DSA exercises cover all 49 skills, five rungs each; their **speed tests**, and those of the DSA placement code tasks, were proven too: on each, the reference took at most a third of the 2-second limit and the slow brute force agreed and then timed out (Table 16).

3. **Lesson verification** (`pnpm lessons:seed`): every hand-written lesson passes the gates of Table 15, with both its programs run in the real sandbox. **207 of 207 frozen** (60 for C++ basics, 147 for DSA).
4. **End-to-end learner loop** on a running server: register → log in → open exercise → submit → poll → read mastery → reopen the exercise.
5. **End-to-end placement test** on real E2B, then the first recommendation and the fade stages; **sessions** (start, pause, resume, end); **progress**; **hints** (the whole ladder); **analytics** with a promoted admin; **generation** refused correctly while billing is off.
6. **Password reset in a real browser:** the forgot-password form, the emailed link (printed locally), a new password, then logging in with it; the old password and the used link are refused.
7. **Data rights on the running server:** correct, opt in, download, then delete with the password (the email printed locally), and the erasure of that account as the hourly job does it (A-10). The server registers the hourly job once, and its first run completes.
8. **Guided walk** (`pnpm demo:walk`): one new learner through sign-up, the placement test, an exercise on the real sandbox (a wrong then a right answer), a hint, progress, the data download and deletion (A-10). It is also the smoke test after a deploy.
9. **Manual API tests** with curl, for authentication and consent, by a team member.
10. **Load check** (23 October, real E2B): 20 learners submit code at the same moment, half of it DSA with speed tests, plus 5 predict-the-output answers. All 25 came back AC, with no sandbox error. The last code verdict arrived after 27–30 s (median 17 s) and the predict answers within about 1 s, after the two changes in defect 43; the rest of the wait is E2B Hobby's limit of one new sandbox per second.

4.1.5 White-Box and Black-Box Testing

- **White box:** unit tests cover every branch of the judge and formula, and database-rule tests target specific constraints.
- **Black box:** integration and system tests use only the public API and check visible behaviour. For example, "a hidden test's input never appears in any response" is checked by searching the whole response body.

4.1.6 Acceptance Testing

The acceptance criteria are the SRS requirements, traced in the Phase 2 design document (section 9). For example:

- **FR-M4-02**, "mastery changes only from executed evidence": tested by "records no evidence for SE or an early compile error".
- **FR-M12-02**, "the help limit is enforced on the server": tested by "never lets the hint level pass the fade ceiling" and "refuses a level above the fade stage's ceiling, and logs it".
- **FR-M8-04**, "block any reply that looks like the solution": tested by "blocks a reply that gives the solution away and serves the frozen hint instead".
- **FR-M3-01**, "an adaptive test estimates reading and writing": tested by "places all 711 possible learners exactly".
- **FR-M13-01**, "compare predicted mastery with results": tested by "saves a calibration record for a learner's first counted try at an exercise only".
- **FR-M1-05**, "reset a forgotten password": tested by "sets the new password, ends every login, and works only once".
- **DPDP Act s.11**, the right of access: tested by "downloads everything held about the learner, from every module, with who it was shared with".
- **DPDP Act s.12**, erasure: tested by "anonymises the person and deletes every learning row, keeping the consents as proof".

Learner acceptance testing is planned for the pilot before the final report, with an anonymous survey (`DOCS/phase-3/pilot-survey.md`): the System Usability Scale and ten statements, each paired with a number from the pilot's logs.

4.2 Test Data and Test Cases

Table 8: Automated test suites (248 tests in 43 files, all passing on 23 Oct 2026)

Level	Suite	Tests	What it proves
Unit	judge	7	Each verdict rule, order, normalisation, excerpts
Unit	mastery formula v1	8	Approved journey 0 → 0.16 → 0.33 → 0.53 → 0.72; hints; TLE doubling; decay
Unit	skill graph	7	Cycle detection; both seeded graphs valid; DSA builds on C++ basics and is never easier than its prerequisites

Level	Suite	Tests	What it proves
Unit	recommender rules	7	Candidates, reviews, rung bands, journey from rung 1 to 5
Unit	placement rules	13	All 711 C++ knowledge states and 300 random DSA learners placed exactly; slip check; frontier code tasks
Unit	session clock	5	Idle pause, timeout end, study time
Unit	leak filter	5	Solution-like hints blocked, learner's own code ignored
Unit	exercise banks	11	Practice and placement banks of both courses complete and well-formed; DSA generated tests last, with a brute force; no placement item reuses a practice exercise
Unit	exercise drafts	5	Draft rules, conversion to the bank's format, prompt contents
Unit	lesson drafts, lesson files	7	Level rule; lesson schema; all 207 hand-written lessons cover both courses at three levels and fit the schema
Module	9 schema suites	17	Every key constraint refuses bad data; a prerequisite from another course must already be seeded
Integration	auth + consent	17	Login flows, token theft, throttling, CSRF; DPDP consent; under-18s refused during the pilot; client IP only from our own proxy
Integration	password reset	10	Same reply for every email; token stored as a hash; one email per 5 minutes; one use, even at once; expiry; newest link only; every login ended, even one under way during the reset; per-IP limit
Integration	data rights	15	Correction; opt-ins on and off, adults only; the download from every module, no secrets; deletion with the password, every login ended, cancelled by logging in; limits
Integration	account erasure	4	Every learning row erased, or only anonymous numbers kept with an opt-in; grace period respected; every table pointing at a learner accounted for
Integration	submissions	15	202 + polling, idempotency tied to its attempt, hidden tests private, CE/SE rules, predict-the-output graded at once, a cleared skill's code deleted; a calibration record on the first counted try only, even with two graded at once

Level	Suite	Tests	What it proves
Integration	exercises API + verification	16	No secrets or rung-1 answers in responses; skill details; bad content rejected; wrong solutions must fail; generated tests' outputs from the reference; brute force must agree then time out; reference within a third of the limit
Integration	mastery API, scaffolding fade	7	Reading and writing apart; decay on read; stage advance
Integration	recommendations API	5	First step, rung up, skip skills without content, the other course's skills first, course done
Integration	placement test API	19	No answer key, current question only, background grading, seeding, retakes, cheat refused, a prerequisite from another course
Integration	sessions, progress	9	Steps advance, pause/resume, idle, statuses
Integration	analytics	6	Admin only, counts only; Brier score and reliability table
Integration	pilot data export	1	Research opt-ins only, under aliases; no name, email, birth date, code or free text in any file
Integration	hints, budget, frozen hints	10	Live, blocked, failed, ceiling, answer, daily and monthly caps
Integration	exercise generation, budget, API	11	Proven drafts stored; retries; weak tests rejected; Pro then fallback; budget stop; admin only; automatic queueing; DSA left hand-written
Integration	lessons API, lesson notes	11	Lesson for the level or the nearest; generated lessons proven or refused (false claim, exercise given away, wrong output); ₹300 stop; notes reused, capped, dropped with code
System	sandbox smoke (real E2B)	6	All six execution verdicts on real infrastructure
System	content verification (real E2B)	483	Every seeded exercise: reference passes, starter fails; DSA speed tests tell fast from slow
System	lesson verification (real E2B)	207	Every lesson's programs print exactly what it states; no exercise given away

Sample test case: a generated exercise whose tests can't catch a mistake is rejected

Field	Value
Input	The (fake) model writes a correct exercise, but one of its 3 "wrong" solutions is actually correct, so it passes every test; it does this on all 3 tries

Field	Value
Expected	Each try is rejected at stage `tests_too_weak`; the third uses the Pro model; the job ends `fell_back`, pointing at the hand-written exercise of the same skill and rung; nothing is stored
Result	Pass

Sample test case: a hint never gives the solution away

Field	Value
Input	A learner at hint level 1 asks for level 2; the (fake) tutor replies with the whole reference solution in a code block
Expected	The reply is blocked and logged as `blocked`; the learner gets the frozen level-2 hint instead (`source: "frozen"`); the level moves to 2
Result	Pass

Sample test case: judging hides hidden tests

Field	Value
Input	Exercise with 1 sample test (input `123`, expected `6`) and 1 hidden test; the learner's run outputs `6` and `27`
Expected	Verdict AC, 2 of 2 passed; the sample test shows input, expected and actual output; **the hidden test shows only `{ seq, name, visibility, verdict, timeMs }`**
Result	Pass

Sample test case: a reset link works only once, even when used twice at the same moment

Field	Value
Input	One reset link; two "set new password" requests are sent with it at the same moment
Expected	Exactly one gets `204` and the other `400 RESET_LINK_INVALID`: the reset marks the link used only if it is still unused, in one transaction
Result	Pass

Sample test case: a deleted account keeps only what the law asks

Field	Value
Input	A learner with rows in all 16 tables of learning data, and no opt-in, asked to delete the account 8 days ago; the hourly job runs

Field	Value
Expected	Email `deleted-<id>@deleted.invalid`, name "Deleted learner", no date of birth, status `deleted`; all 16 tables empty for that learner; both consents revoked but kept; the sign-in record ended but kept; an old access token gets `401`
Result	Pass

**Test data for the starter exercise "Sum of digits" (`int sumOfDigits(int n)`):

Test	Visibility	Input	Expected
Example	sample	123	6
Zero	hidden	0	0
All nines	hidden	999999999	81
Largest input	hidden	1000000000	1

4.3 Test Reports and Debugging

Results: 248 of 248 automated tests pass, the 6 of 6 real-sandbox verdicts are correct, 483 of 483 seeded exercises and 207 of 207 lessons verify on the real sandbox, and the end-to-end runs pass (A-8, A-10).

Debugging followed one rule: **measure, find the cause, fix the cause, add a test.** These are the defects found:

Table 9: Defects found and fixed

#	Symptom	Cause found	Fix
1	The memory-hog test program got **AC** instead of MLE	The C++ optimiser legally removed an allocation that was never used	Test program now writes to the memory (`volatile`), so it can't be removed. Judge unchanged
2	A submission took **5–15 s**	Timing each step showed compiling took only 0.5 s; each network round trip to the sandbox cost 1–2 s	Compile + all tests in **one** command; template pre-warms the compiler; sandbox killed in the background. Now about 6 s
3	Any non-zero exit **crashed the runner**	The SDK throws an exception on a non-zero exit	The script always exits 0 and reports each exit code as data
4	Learner output could **break or forge** the result format	Results were read from text the program could also print	Each result line is written by our script *after* the program ends, with output base64-encoded

#	Symptom	Cause found	Fix
5	**Cheating hole:** printing "PASS" could pass	The first design let the harness inside the sandbox decide pass or fail	Expected outputs never enter the sandbox; the judge compares outside it
6	Migration 0011 **failed** on existing data	Shrinking an enum fails while rows still use a removed value	The migration deletes those rows first (it had never been applied anywhere, so editing it was safe)
7	Register returned **400** in manual tests	The JSON was quoted for PowerShell but run in Git Bash; one field was called `name` instead of `displayName`	Shell-specific commands in the guide; field names checked against the API
8	New tests failed with "`expect` is not a function"	An `async` helper returning a Supertest request was awaited automatically	The helper now takes the expected status itself
9	**Cheating hole:** a learner could be placed without writing code	A practice submission sent under the placement task's predictable idempotency key was returned as the placement answer	A key now returns only a submission made on the same attempt, otherwise `409` (this also protects practice)
10	A learner who had practised **once** lost their placement, and the skills built on it stayed locked	Seeding skipped any skill with a counted attempt	Only cleared skills are skipped; seeding is raise-only, so practice gains are never lowered
11	Risk of the API **freezing** under load	Inside the completion transaction, a skill lookup asked the pool for a second connection; with 10 such transactions at once, all would wait forever	The lookup now runs on the transaction's own connection (also fixed in grading)
12	The answer to a **rung-1** exercise was visible	Its only test was marked "sample", and sample tests are shown with the exercise	Rung-1 exercises never show sample tests
13	Git showed a source file as **binary**	A script wrote a raw NUL byte instead of the `\0` escape	Replaced with the escape; every changed file is now scanned for NUL bytes
14	Live hints would have sent learner code to Google's **free tier**	The Gemini key's project had not activated billing	A `GEMINI_PAID` setting must be `true` before any live call; until then hints fall back to frozen ones

#	Symptom	Cause found	Fix
15	The set-new-password page said the link was **missing**, though it had one	In development React runs a page's effects twice; the first run had removed the token from the address bar, so the second found none	The token stays in the address bar. That is safe: the `#fragment` never reaches a server, and the link works once, for 30 minutes
16	The reply could reveal, by its **timing**, whether an account exists	The new link was saved before replying, and only for real accounts	All the work now happens after the reply
17	The reset email included the learner's **name**	The privacy policy lets the email provider receive only the address	The email now starts with "Hi,"; a test checks that the name never appears
18	Anyone could **block** someone's password reset (security review)	Three requests an hour for a victim's email filled a per-email limit, so the victim's own request got `429`	No per-email limit: each account gets at most one email every 5 minutes, and asking sooner sends nothing while the link already sent still works
19	Two requests at the same moment could leave **two working links** (security review)	Both deleted the old links before either saved its own	A reset now ends every unused link of the account
20	In production, a missing email key would have **silently** stopped all reset emails (security review)	The key was optional everywhere	The API now refuses to start in production without it
21	A caller could choose their own **IP address** for the per-IP limits (security review)	The API trusted one proxy hop, so a request reaching it directly, or through the local web proxy that passes the header on, could set `X-Forwarded-For`	Only our own proxy (this machine or its private network) is trusted; local development trusts nobody. The per-email login limit also checks the email's type and caps its length
22	The full placement check **timed out** when the whole suite ran	Its 1,422 runs take about 3 s alone, over the 5 s default once 35 other files run beside it	That one test has a 30 s limit

#	Symptom	Cause found	Fix
23	A login at the moment of erasure could open a **session on an erased account** (security review)	The login checked the account, the job then closed it, and the login went on	The login now fails unless its own update still finds the account active
24	After a deletion request, a token refreshed **seconds before** could start a new 30-day session (security review)	A just-replaced token has a 20-second grace and was already marked revoked, so ending every login skipped it	A refresh is refused while a deletion is pending
25	Erasure deleted the **sign-in records** the privacy policy keeps for a year (security review)	The internal DPDP checklist said "delete tokens", unlike its own retention rule	The records are ended and kept under the anonymous ID; the security-log job will delete them after a year
26	Switching an opt-in on and off in a loop added **proof rows without end** (security review)	Each switch keeps a row, and nothing limited them	30 switches an hour per learner
27	Generating the 207 lessons would have taken **over three weeks**	Until billing activates, the free tier allows 20 Flash calls a day and no Pro calls; each lesson needs a draft and a fact check	All lessons hand-written, through the same gates as a generated one; generation kept for later courses
28	The fact check **passed a wrong lesson**	Asked for "any errors", the model missed that an inner `int i` hid the outer one, so the stated output was wrong	The check now lists each technical claim and judges them one by one; it caught the same error
29	The leak filter **flagged correct lessons** as giving exercises away	Matching lines were generic C++ (`std::cout`, `(v.begin(), v.end())`, `[](int x)`) and shared variable names	Lessons reworded with their own names; the filter stays strict, since a missed leak costs more than a rewrite
30	**Five lessons stated a wrong output**	Outputs worked out by hand	Caught by the sandbox gate or review and fixed before freezing. This is why no lesson is stored without its programs being run

#	Symptom	Cause found	Fix
31	A slow brute force **finished in time**, so a speed test could not tell slow from fast	The tests were too small, or the slow version not slow enough (saddle points, factor counts, a tree rebuild)	Larger generated tests, or a brute force that is really quadratic; `tests_too_weak` now catches this before an exercise is stored
32	A correct **reference was too slow** for its own speed test	`std::set` and `std::map` at a million items took over a third of the 2-second limit	Those tests use 300,000 items; the rule stays, so a learner's good solution has room to spare
33	Some DSA tests **didn't compile**	A braced list such as `{{1, 5}}` was ambiguous between a list of pairs and a list of numbers, and a variadic helper can't take braced lists	Overloads for braced lists; tests with pairs use at least two
34	Generated tests that **said nothing**: every answer of a test was -1	At 30% walls or more, a random grid usually walls in its start; a sparse random graph usually leaves a town cut off	Densities and seeds chosen by printing the generated answers first, and a generator that always builds a connected graph; each speed test now keeps one "impossible" case on purpose
35	A brute force passed the timing check **on one run and failed it on the next**	It finished in about 2 s, right at the limit, and the compiler vectorised some simple loops	Brute forces made clearly slower (at least 10 times over the limit), for example scanning every pile instead of shifting a sorted list
36	Six DSA placement items were **too close to practice exercises**	Written for the same skills, four code tasks and one reading program repeated a practice task, and one shared a practice exercise's title: practice would have taught the test's answers	Replaced or renamed; a unit test now fails if a placement item shares a title or a function with any practice exercise, and it found the last two
37	Verification **stopped part-way** on a network timeout	One failed connection to the sandbox service ends `pnpm exercises:verify`	Verified items are saved as they pass, so a rerun finishes the rest (73 then 25 here). Since 23 October each item is tried 3 times, then skipped and left for the next run

#	Symptom	Cause found	Fix
38	The web framework had **two critical security advisories** (remote code execution)	A dependency audit before deployment: Next.js 16.4.0, and an old DOMPurify inside the code editor	Next.js 16.4.2, and DOMPurify 3.4.17 pinned; the audit fell from 12 advisories to 1 moderate one, in a development-only tool
39	The calibration summary **failed** in Postgres	The same bin expression was sent twice with separate parameters, so Postgres couldn't match the SELECT to the GROUP BY	Grouped by column position; a test checks the Brier score and every bin exactly
40	A scripted edit **emptied a test file**	Python on Windows used the local code page and stopped at a character it couldn't encode, after opening the file for writing	Restored from Git; scripted edits now read and write UTF-8 explicitly
41	The export test **timed out**, but only in the full suite	It starts a second Node process, which took over 5 s while 42 other files ran	That test has a 30 s limit, as in defect 22
42	In the server image, `pnpm` **downloaded itself** on every command	It had been fetched at build time into the root user's folder, and the container runs as an unprivileged user	pnpm is stored in a shared folder at build time, so commands work offline
43	Under load, a **predict-the-output answer waited over a minute**, and the queue ran below its limit (load check)	Rung-1 answers need no sandbox but queued behind code runs; 5 workers left E2B's one-start-a-second unused, since a run takes 5–10 s	A rung-1 answer is graded in the request (about 1 s); up to 10 runs at once, of the 20 E2B allows; a retry whose answer just solved the attempt gets its submission back instead of `409`
44	A login or refresh **under way during a password reset** could keep its session (security review, 19 October)	It checked the account just before the reset, then saved its new token just after the reset had ended every login	A reset raises the user's session version; a refresh token from an older version is refused and its login ended

The password reset and the data rights each had an independent security review (19 October), with no critical or high issues in either: defects 18–21 came from the first, and 23–26 from the second. The second also led to a test that fails when a new table points at a learner's data without being exported and erased. One smaller finding, a login already in progress at the moment of a password reset, was closed on 23 October (defect 44). Defects 27–37 came from the lessons,

the DSA bank and the DSA placement test (20–22 October): each was caught by a gate or a test before any learner saw the content, which is the gates' purpose. Defects 38–43 came from the 23 October work: the dependency audit, calibration, the export, the local deployment run and the load check. Defect 44 closes the last finding of the 19 October review.

4.4 Implementation Manual

Run the system locally:

```
docker compose up -d                  # PostgreSQL 16 + Redis 7
pnpm install
cd apps/api && cp .env.example .env   # fill DATABASE_URL, JWT_SECRET,
WEB_ORIGIN, E2B_API_KEY, GEMINI_API_KEY, BREVO_API_KEY
pnpm db:migrate && pnpm db:seed       # 18 migrations; C++ basics (20
skills) and DSA (49 skills); 345 practice exercises, 138 placement
items
pnpm exercises:verify                 # runs every new exercise in the
real sandbox before it can be served
pnpm lessons:seed                     # freezes the 207 hand-written
lessons through their gates (real sandbox)
pnpm dev                                    # API + queue worker on
http://localhost:3001
pnpm test                             # 248 automated tests (CI runs
them on every push)
pnpm demo:walk                        # one learner through the whole
loop on a running API
pnpm sandbox:smoke                    # real-sandbox check of all six
verdicts
pnpm user:admin <email>                  # make the first admin (for
analytics)
pnpm pilot:export --since=… --until=… # de-identified pilot data for
the report (research opt-ins only)
pnpm hints:generate                         # once billing is active
(GEMINI_PAID=true): freeze hints 1-4
```

Build the sandbox template once: `pnpm sandbox:build` creates the `ai-tutor-cpp` machine (Debian 13, clang 19) on E2B.

Deploy: `deploy/README.md` is the runbook: Supabase, the Render Blueprint (`render.yaml`), Vercel with the tutor.nidanos.com domain, the checks after deploying, and the nightly encrypted backup on the home server. The Compose file (Caddy, API, Postgres, Redis) for an own VM is kept for later (ADR-0010).

4.5 Implementation

Status at Review 3 (23 October 2026):

Module	Built	Endpoints live
M1 Accounts, consent and data rights	Register, login, refresh, logout, me; forgot and reset password by email; date of birth; consent kinds; adults only during the pilot; correct, opt in and out, download, delete (7-day grace, hourly erasure)	13
M2 Skill graph	C++ basics: 20 skills, 23 prerequisites. DSA: 49 skills in 8 groups, 97 prerequisites (19 of them C++ basics skills). Further-reading links; each skill's description and links shown with its exercises and progress	–
M3 Placement test	Adaptive reading walk with a slip check, frontier code tasks, seeding, retakes; 40 verified C++ items and 98 DSA items	3
M4 Mastery	Formula v1 inside the grading transaction; read views with decay; raise-only seeding; the prediction before each first try kept for calibration	2
M5 Recommender	Next skill, rung and exercise by fixed rules, saved with reasons; names the other course's skills a learner must finish first	1
M6 Exercises and lessons	Learner view; 100 verified C++ practice exercises (20 skills × 5 rungs) and 245 verified DSA exercises with speed tests (all 49 skills × 5 rungs), all hand-written; generation proven in the sandbox, by admins and automatically (C++ basics only for the pilot, ADR-0023); 207 frozen lessons (3 levels per skill, both courses) and the live note	5
M7 Execution	Fresh offline sandbox per submission, judge, queue, retries, polling; a cleared skill's code deleted	2
M8 Hints	Five-level ladder, live tutor with leak filter and caps, frozen fallback	1
M9 Sessions	Start or resume, pause, resume, end; steps from the recommender; idle rules	3
M10 Reviews	Due when a cleared skill's writing decays below 0.5, worked out on read and served by the recommender (ADR-0022)	–
M11 Progress	Every skill, reading and writing apart, fade stage, status	1
M12 Fade	Stage start, advance on solve, fast-track from the placement test, state endpoint	1
M13 Analytics	Admin overview: learners, code runs, outcomes, content coverage, hardest exercises, hints, AI spend, and calibration (Brier score and reliability table, ADR-0021); the de-identified pilot export	1

Module	Built	Endpoints live
Total		**all 33 endpoints**

Real runs at this stage: a placement test on real E2B placed a learner who knew 3 skills with 6 questions (5 reading, 1 code), graded the code in about 6 seconds and fast-tracked those 3 skills to the last fade stage; the first recommendation was then the next new skill. Sessions, progress, hints, analytics and generation were each run against the development database, the password reset was walked through in a real browser, and the data rights on the running server, including the erasure of that test account (A-10). A DSA placement test through the running API placed a learner who knew 4 skills exactly, with 17 questions: 14 reading, and 3 code tasks run on real E2B with their speed tests (A-8). The 207 lessons and 483 exercises were each proven on real E2B. On the web, the sign-in pages (with the password reset) and the Terms and Privacy pages are built. The production stack ran locally on 23 October: the image builds, migrations and the seed run inside it, HTTPS works through Caddy, a made-up `X-Forwarded-For` is ignored unless it comes with Vercel's secret header, and an encrypted backup restores into a scratch database.

Planned for the MVP (10 November): Gemini billing activation (7 November), then the first live AI runs: live hints, lesson notes, the frozen hints, and extra generated exercise variants; frontend screens (in progress, due 31 October), including the Settings screens for data rights; the Brevo account and sending domain for real account emails; running the deployment on Vercel, Render and Supabase (ADR-0024; its files are written and checked locally); and a pilot with real learners, with the data export and the survey ready.

4.6 Users Training

- **Learners** need no training beyond the interface. Every verdict has a plain-language message ("Too slow on test 3: limit 2 s"), and the fade state tells the learner what unlocks the next stage.
- **The frontend team** works from a written API guide (`DOCS/api/FRONTEND-GUIDE.md`) with exact request and response types, error codes, and what to show for each verdict.
- **Authors** add skills, exercises and lessons as seed data; a test checks the skill graph for cycles on every run, `pnpm exercises:verify` checks every new exercise in the real sandbox, and `pnpm lessons:seed` freezes a lesson only after its gates pass.
- **Admins** are created with `pnpm user:admin <email>` and see one overview page; it shows counts only, never who.

4.7 Post-Implementation Maintenance

- **Schema changes** always go into a new migration; applied migrations are never edited.
- **Decisions** are recorded as ADRs, so the reason for each choice survives the people who made it.
- **The mastery formula is versioned** (`m4-v1` is stored on every evidence row), so it can be tuned later from calibration data without making old numbers unexplainable.
- **Costs are watched:** every LLM call is logged with its estimated cost, with hard monthly caps; sandboxes are billed per second and killed after each run.
- **Data protection:** account erasure runs every hour, and a learner's code is deleted once they clear its skill (both built); the other retention jobs come next (3 years inactive with a 48-hour warning, deleting sign-in records after a year). A test fails if a new table points at a learner without being exported and erased. A breach-response plan sets the 6-hour CERT-In and 72-hour Board deadlines, and an encrypted backup runs nightly (`deploy/backup.sh`, restored in a test).
- **Every push and pull request** runs the type checks, the tests on a fresh database and the web build (GitHub Actions).
- **Dependencies** are pinned to exact versions; upgrades are deliberate and tested. A dependency audit runs before each deployment (on 23 October it led to the Next.js and DOMPurify upgrades, defect 38).

CHAPTER 5: CONCLUSION AND REFERENCES

5.1 Conclusion

The project set out to measure what a learner can *write*, not what they have watched, and to withdraw help as they improve. At Review 3, the core of that idea works end to end on real infrastructure:

1. A learner opens an exercise, and an attempt starts with a help limit taken from the skill's fade stage.
2. The learner's C++ code is compiled and tested in a fresh, offline sandbox.
3. A deterministic judge gives the verdict.
4. In the same transaction, the writing score moves by the approved formula and the skill moves to less help when solved with at most one hint.

In a real run, a correct submission was judged **AC (4 of 4 tests) in about 6 seconds**, and the learner's writing mastery for that skill moved from **0 to 0.24**, exactly as the formula predicts.

Around that core, the rest of the learner's journey now works too: an adaptive **placement test** that asks an expert 26 questions instead of 40 and fast-tracks what they prove, a **recommender** that chooses the next skill, rung and exercise by explainable rules, **study sessions** that resume at the same step, an honest **progress** view, an **admin overview**, a **hint ladder** whose live tutor can never hand over the solution, **exercise generation** that stores nothing the sandbox hasn't proven, a **password reset** that never reveals who has an account, and **data rights**: learners can correct, download and delete their own data, and only those who opted in leave anonymous numbers behind. Each learner's first try at an exercise also records what the mastery model predicted beforehand (**calibration**), so the pilot measures how far the scores can be trusted.

The platform now teaches two courses. **C++ basics** (20 skills) is complete, and **Data Structures and Algorithms** (49 skills) builds on it. Every skill of both has **three frozen lessons**, one per level, each with a diagram, a worked example and a check, all **207** proven in the sandbox before storing. In the DSA course, **speed tests** tell a fast solution from a slow one: all 245 exercises, each proven so that its reference finishes well inside the limit and a slow but correct solution times out. Both courses have a **placement test**, 138 items in all.

All 33 endpoints are live, backed by 248 automated tests run on every push, 483 exercises verified in the real sandbox (100 C++ and 245 DSA practice exercises covering every skill and rung of both courses, and 138 placement items), 207 verified lessons, and a written decision record (ADR-0001 to ADR-0023) for every major choice. The deployment files are written and were checked locally.

5.2 System Specifications

5.2.1 H/W Requirement

- **Server:** none of our own for the pilot: Render's free service gives the API 512 MB and 0.1 CPU, and Supabase's free plan 500 MB of database. An own VM later needs 2+ CPU cores, 4 GB+ RAM and 20 GB disk.
- **Client:** any device with a modern browser.

5.2.2 S/W Requirement

- **Server:** Render runs the API's Docker image (Node.js 22), with Key Value for the queue; PostgreSQL 17 on Supabase. An own VM later: Ubuntu 24.04, Docker, PostgreSQL 16, Redis 7.
- **Accounts:** an E2B account (sandboxes), a Gemini API key, and a Brevo account (account emails) with the sending domain authenticated.
- **Client:** Chrome, Edge, Firefox or Safari (current versions).

5.3 Limitations of the System

- **No web interface yet.** The frontend is in progress (due 31 October); this draft's sample outputs are API responses, and screen snapshots will be added in the final report.
- **One practice exercise per rung.** Every skill has five hand-written exercises, one per rung, so a learner who needs more practice at a rung retries the same task or moves up; generated variants add more for C++ basics once billing is active. DSA stays hand-written for the pilot, because its speed tests and brute forces aren't in the generation prompt yet (ADR-0023). The placement tests cover every skill of both courses.
- **The DSA placement test is long for an expert.** It follows the C++ rules, so an expert answers all 49 reading questions and 20 code tasks, about 2½ hours with pause and resume; a beginner is done in a few questions. A walk that tries the hardest skills first would be shorter for experts and longer for beginners.

- **Lessons are fixed per level.** The 207 lessons are hand-written, so a lesson does not change for one learner; the live note that personalises it waits for billing. A lesson's correctness rests on its gates and on review: the sandbox proves its programs' outputs, not every sentence.
- **Live AI waits for billing.** Live hints and exercise generation are built and tested with a fake model, but stay off until the ₹3,000 prepayment is complete and activates the paid tier (the remaining ₹2,500 on 7 November); until then learners get frozen hints or a general nudge, and lessons come without their live note.
- **Account emails wait for setup.** Real reset and deletion emails need the Brevo key and the sending domain; until then they are printed in the API terminal (in development only: production refuses to start without the key).
- **Client IP.** The per-IP limits trust only our own proxy; the API takes the visitor's real address from Vercel only with the origin secret Vercel adds (ADR-0024). It was checked locally and is checked again on the live servers.
- **Data rights screens and the rest of retention.** The data-rights API is built, but not yet the Settings screens. The email address and date of birth are changed by email, not in the app. The 3-year inactivity job and the yearly clean-up of sign-in records are still to build. After a deletion request, an access token still works on the learning endpoints until it expires (at most 15 minutes).
- **Adults only during the pilot.** Under-18s can't sign up until the parent-approval flow is built.
- **Legal pages carry working values.** The company name, the domain and the Grievance Officer's postal address are placeholders until Nidanos is registered, and a lawyer-reviewed version replaces both texts before public launch.
- **The judge sees only output.** A determined learner can sometimes avoid a prerequisite (for example by rewriting a struct to use a vector); the tasks are designed so the natural solution uses it.
- **Placement length.** An expert answers 26 questions (about 28 minutes); a placement seed unlocks the next skills for about 4 days (syntactic skills) before one Build per skill confirms them.
- **Latency:** about 6 s per submission, mostly network round trips to the sandbox provider, whose servers are outside India. When 20 learners submit at the same moment the last waits about 30 s, because E2B's Hobby plan starts one sandbox a second; the Pro plan starts five.

- **Sandbox trust:** learner code runs as the same user as our runner script, so a determined learner could tamper with result lines. That's acceptable for practice; the fix is a separate run user.
- **Formula constants are starting values.** Each first try now records the model's prediction (ADR-0021), so the pilot shows how well they predict, but tuning them needs more learners than a three-day pilot. The recommender picks exercises near the learner's level, so predictions bunch in the middle.
- **Reviews are simple.** A cleared skill is due for review when its writing decays below 0.5; nothing is stored, and the interval doesn't grow after a good review (ADR-0022). The first review comes about a week after clearing, so the pilot will see few.
- **Pilot:** the planned manual "Phase 0" validation was replaced by a single-learner baseline.

5.4 Future Scope for Modification

- More languages (Java, Python) on the same language-independent engine, and more courses (frontend, backend), whose lessons the generator with its fact check can write.
- Generated variants of the DSA exercises, with their own speed tests; and a shorter DSA placement walk for experts.
- The parent-approval flow for under-18 learners, with identity verification as the DPDP Rules require, and a parent acting on a child's data rights.
- The remaining retention jobs: 3 years inactive, and a year's sign-in records.
- Changing the password, email address or date of birth while logged in, and verifying the email address at sign-up.
- Tuning the mastery formula from the calibration records, a held-out exercise bank for a cleaner measure, and spaced-revision intervals (M10, ADR-0022).
- A mobile app (the API already supports Bearer tokens), and colleges as institutional customers.
- Spoken explanation assessment, and a portable learner profile.

5.5 References / Bibliography

1. Bloom, B. S. (1984). The 2 Sigma Problem. *Educational Researcher*, 13(6), 4–16.
2. Roediger, H. L., & Karpicke, J. D. (2006). The Power of Testing Memory. *Perspectives on Psychological Science*, 1(3), 181–210.

3. Bjork, E. L., & Bjork, R. A. (2011). Making Things Hard on Yourself, But in a Good Way. In *Psychology and the Real World*, 56–64.

4. Cepeda, N. J., Pashler, H., Vul, E., Wixted, J. T., & Rohrer, D. (2006). Distributed Practice in Verbal Recall Tasks. *Psychological Bulletin*, 132(3), 354–380.

5. Sweller, J., & Cooper, G. A. (1985). The Use of Worked Examples as a Substitute for Problem Solving in Learning Algebra. *Cognition and Instruction*, 2(1), 59–89.

6. Corbett, A. T., & Anderson, J. R. (1994). Knowledge Tracing. *User Modeling and User-Adapted Interaction*, 4(4), 253–278.

7. VanLehn, K. (2011). The Relative Effectiveness of Human Tutoring, Intelligent Tutoring Systems, and Other Tutoring Systems. *Educational Psychologist*, 46(4), 197–221.

8. Bastani, H., et al. (2025). Generative AI Without Guardrails Can Harm Learning. *Proceedings of the National Academy of Sciences*.

9. Government of India (2023). *The Digital Personal Data Protection Act, 2023*; and (2025) *Digital Personal Data Protection Rules, 2025*.


10. Technical documentation: Node.js, Express 5, PostgreSQL 16, Drizzle ORM, BullMQ, E2B, Google Gemini API, Next.js, Brevo (official documentation, accessed October 2026).

11. Project documents: Phase 1 synopsis, problem analysis, literature survey and SRS (24 Sep 2026); Phase 2 system design (15 Oct 2026, updated 20 Oct); ADR-0001 to ADR-0023; frontend API guide; deployment runbook (`deploy/README.md`); pilot survey; Terms of Service, Privacy Policy and DPDP checklist (draft v0.1).

CHAPTER 6: ANNEXURES

A-1 Menu Flow Diagram


Figure 13: Planned screen flow




A-2 Structure Chart

The chart is in two parts: what handles a request, and what runs in the background. A module used by several callers is drawn under each of them.

Part 1: handling a request



Part 2: background jobs



A-6 Decision Tables

Sign-up consent

Age ≥ 18?	Accepted Terms and Privacy?	Opt-in ticked?	Result
any	No	any	400, sign-up refused
Yes	Yes	No	Active account; consents: data processing, terms
Yes	Yes	Yes	Active account; also the chosen opt-ins
No	any	any	400 next to the date of birth: the pilot is adults only, and **nothing is saved**

Does a submission count, and what does it do?

Verdict	Counts as attempt	Mastery	Fade
AC	Yes	Gain (weighted)	Advances if the rung and hints qualify
WA / RE	Yes	Penalty, only the first in the attempt	–
TLE / MLE	Yes	Small penalty, doubling	–
CE (1st, 2nd)	No	–	–
CE (3rd+)	Yes	No change	–

Verdict	Counts as attempt	Mastery	Fade
SE	No	–	–

Which hint does the learner get? (levels 1–4; level 5 is always the answer)

Above the ceiling?	Under the daily and monthly caps, billing on?	Gemini answered?	Filter passed?	Result
Yes	any	–	–	`409 HINT_LIMIT`, logged `denied_ceiling`
No	Yes	Yes	Yes	Live hint, logged `delivered` with its cost
No	Yes	Yes	No	Logged `blocked`; frozen hint (or general nudge)
No	Yes	No (error)	–	Frozen hint (or general nudge)
No	No	–	–	Frozen hint (or general nudge), no call made

Is a generated draft stored?

Valid JSON matching the schema?	Reference passes every test?	Starter compiles and fails?	Every wrong solution compiles and fails?	Result
No	–	–	–	Logged `schema`; next try
Yes	No	–	–	Logged `compile` or `reference`; next try
Yes	Yes	No	–	Logged `compile` or `tests_too_weak`; next try
Yes	Yes	Yes	No	Logged `compile` or `tests_too_weak`; next try
Yes	Yes	Yes	Yes	**Stored, ready to serve**; frozen hints follow

After the third failed try (or when the month's budget is spent), the job falls back to the hand-written exercise.

What happens to a deleted account?

Logged in within 7 days?	Live opt-in to research or AI training?	Result
Yes	any	Request cancelled; nothing erased
No	Yes	Person erased; code and the learner's own words emptied; anonymous numbers kept; consents revoked and kept
No	No	Person erased; every learning row deleted; consents revoked and kept

A-7 Data Dictionary

Table 10: Key tables (all 42 are described in the Phase 2 design document)

Table	Key columns	Constraints
users	id (UUIDv7), org_id, email (citext), display_name, password_hash (argon2id), role, status (active, disabled, pending_parent, deleted), date_of_birth, deletion_requested_at, session_version (raised by a password reset)	email unique in any case; name 1–80 characters; an erased row stays, anonymous
consents	user_id, kind (data_processing, terms, parental, ai_training, research_study), policy_version, granted_at, revoked_at	one live consent per kind; revoked, never deleted
password_reset_tokens	user_id, token_hash (SHA-256 of the emailed token), expires_at, used_at, created_at	token hash unique; a link works once; kept a year as a security record
exercises	id, skill_id, language_code, rung, variant_seed, content_version, status, title, prompt_md, starter_code, time_limit_ms, memory_limit_mb	content key unique; rung 1–5; limits in range
exercise_secrets	exercise_id, harness_code, reference_solution	never read by learner-facing queries

Table	Key columns	Constraints
exercise_attempts	id, user_id, exercise_id, status, hint_level, hint_ceiling, ce_count, submission_count	one active per learner and exercise; hint_level ≤ hint_ceiling
submissions	id, attempt_id, answer (≤ 64 KB, deleted once the skill is cleared), answer_sha256, idempotency_key, status, verdict, tests_passed, counts_as_attempt	idempotency key unique
sandbox_runs / run_test_results	run status, verdict, compile output, wall time, peak memory; per-test verdict, time, memory, output excerpt	one result per run and test
mastery_records	(user_id, skill_id, language_code), reading_score, writing_score, evidence times, cleared_at, limit_streak, decay_lambda	scores 0–1; row locked while updated
evidence_events	user, skill, dimension, submission_id, verdict, rung, hints_used, weight, score_before, score_after, formula_version	exactly one source; never counted twice
skill_scaffolding / fade_stage_changes	current stage per learner and skill; every move with its cause (solved, or the placement test)	stage must exist in its schedule
diagnostic_items / attempts / responses / results	item (skill, reading or writing, verified exercise); attempt number and status; each answer; one estimate per skill	one test in progress per enrollment; one answer per item
recommendations	skill, rung, reason, score breakdown, top-5 snapshot, algorithm version, exercise served	rung 1–5
learning_sessions / session_steps	status, last activity, study time; ordered steps from recommendations	one open session per learner; one active step per session
generation_jobs / generation_failures	skill, rung, variant, trigger (admin or automatic), status, tries, model, the exercise made or the fallback; each failed try with its stage and reason	one active job per skill and rung; tries 0–3
hint_events / llm_calls	each hint request (delivered, blocked, refused, bottomed out) with its text or stored hint; each Gemini call with tokens and estimated cost	hint level 1–5

A-8 Test Reports

Full test run of 23 October 2026: **43 test files, 248 tests, 248 passed.**

- ✓ account-api.test.ts > PATCH /me > corrects the name and time zone, and renames the hidden personal organisation with the name
- ✓ account-api.test.ts > PATCH /me > rejects an unknown time zone, a blank name, an empty body and other fields
- ✓ account-api.test.ts > PATCH /me > needs a login, and an account that can still log in
- ✓ account-api.test.ts > opt-ins > turns AI training and research on and off, keeping every grant as proof
- ✓ account-api.test.ts > opt-ins > is for adults only
- ✓ account-api.test.ts > opt-ins > allows 30 switches an hour
- ✓ account-api.test.ts > opt-ins > won't switch off a consent the account needs, or a kind that doesn't exist
- ✓ account-api.test.ts > GET /me/data > downloads everything held about the learner, from every module, with who it was shared with
- ✓ account-api.test.ts > GET /me/data > lists sign-ins and consents, and allows 5 downloads an hour
- ✓ account-api.test.ts > GET /me/data > needs a login
- ✓ account-api.test.ts > DELETE /me > needs the password again, then ends every login and emails when the account goes
- ✓ account-api.test.ts > DELETE /me > ends even a login refreshed seconds before, and every token until the next login
- ✓ account-api.test.ts > DELETE /me > is cancelled by logging in again
- ✓ account-api.test.ts > DELETE /me > keeps the address erased accounts get for them alone
- ✓ account-api.test.ts > DELETE /me > allows 5 password tries in 15 minutes
- ✓ analytics-api.test.ts > GET /analytics/overview > is for admins only
- ✓ analytics-api.test.ts > GET /analytics/overview > counts new learners, opt-ins, code runs, sessions and clears in the window
- ✓ analytics-api.test.ts > GET /analytics/overview > reports one course's content coverage and per-skill averages exactly
- ✓ analytics-api.test.ts > GET /analytics/overview > scores calibration per dimension: the Brier score and predicted against observed, in fifths

- ✓ analytics-api.test.ts > GET /analytics/overview > lists the hardest practice exercises, lowest solve rate first
- ✓ analytics-api.test.ts > GET /analytics/overview > accepts a window of 1 to 365 days
- ✓ attempts.test.ts > attempts schema > rejects a double-submit with the same idempotency key
- ✓ attempts.test.ts > attempts schema > never lets the hint level pass the fade ceiling
- ✓ auth.test.ts > auth > registers, logs in with cookies, and returns the profile without secrets
- ✓ auth.test.ts > auth > ignores a role sent at sign-up
- ✓ auth.test.ts > auth > rejects the same email in any letter case with 409
- ✓ auth.test.ts > auth > answers a wrong password and an unknown email identically
- ✓ auth.test.ts > auth > rotates refresh tokens, and revokes the whole login when an old one is reused
- ✓ auth.test.ts > auth > ends the session on logout
- ✓ auth.test.ts > auth > blocks cookie-carrying writes from another site
- ✓ auth.test.ts > auth > throttles the 6th failed login for one email
- ✓ auth.test.ts > auth > counts a too-long email by its first 254 characters, so junk can't grow the limiter's memory
- ✓ auth.test.ts > auth > answers 400, not 500, when the email isn't a string
- ✓ auth.test.ts > client IP for the per-IP limits > comes from our own proxy, never from a caller on the internet
- ✓ auth.test.ts > consent at sign-up > records the required consents plus only the opt-ins chosen
- ✓ auth.test.ts > consent at sign-up > refuses sign-up without accepting the Terms
- ✓ auth.test.ts > consent at sign-up > refuses a date of birth in the future
- ✓ auth.test.ts > consent at sign-up > refuses under-18s during the pilot, next to the date of birth, and saves nothing
- ✓ auth.test.ts > consent at sign-up > still keeps an account waiting for a parent from logging in
- ✓ auth.test.ts > consent at sign-up > counts age in whole years, turning 18 on the birthday
- ✓ curriculum.test.ts > curriculum schema > rejects a skill that requires itself

- ✓ curriculum.test.ts > curriculum schema > rejects a duplicate edge even when it applies to every language (null)
- ✓ curriculum.test.ts > curriculum schema > seeds a prerequisite from another course, and refuses one that isn't seeded yet
- ✓ diagnostic-api.test.ts > POST /diagnostic/start > asks a skill whose prerequisite comes from another course
- ✓ diagnostic-api.test.ts > POST /diagnostic/start > starts with the first skill's program to read, never its answer, and resumes the same test
- ✓ diagnostic-api.test.ts > POST /diagnostic/start > is unavailable until items are verified, and 404 for an unknown course
- ✓ diagnostic-api.test.ts > POST /diagnostic/:id/answers > grades reading on the spot without saying so, and accepts only the current question
- ✓ diagnostic-api.test.ts > POST /diagnostic/:id/answers > rejects an answer Postgres can't store as a 400, not a 500
- ✓ diagnostic-api.test.ts > POST /diagnostic/:id/answers > re-queues a code task whose first queueing failed when the answer is retried
- ✓ diagnostic-api.test.ts > POST /diagnostic/:id/answers > ends after an "I don't know" on the first skill, with nothing asked on top of it
- ✓ diagnostic-api.test.ts > POST /diagnostic/:id/answers > queues a code task once, in a diagnostic attempt with no hints and no fade stage
- ✓ diagnostic-api.test.ts > POST /diagnostic/:id/complete > waits for the code task, then seeds mastery and fast-tracks the skills it proves
- ✓ diagnostic-api.test.ts > POST /diagnostic/:id/complete > starts a skill only read correctly at rung 2: Predict is skipped, writing still starts at 0
- ✓ diagnostic-api.test.ts > POST /diagnostic/:id/complete > raises a practised skill without lowering it, so the skills built on it unlock
- ✓ diagnostic-api.test.ts > POST /diagnostic/:id/complete > leaves a skill cleared in practice alone, and doesn't ask it
- ✓ diagnostic-api.test.ts > POST /diagnostic/:id/complete > won't let a practice submission stand in for the code task
- ✓ diagnostic-api.test.ts > POST /diagnostic/:id/complete > moves a skill opened before the test (stage 1, never submitted) up to the last stage

- ✓ diagnostic-api.test.ts > POST /diagnostic/:id/complete > stops waiting for a code task the sandbox never ran, and counts it as unobserved
- ✓ diagnostic-api.test.ts > retake > starts a new test only when asked, up to three, never lowering earlier results
- ✓ diagnostic-api.test.ts > retake > lifts a placement on a retake after a failed code task, reusing the open attempt
- ✓ diagnostic-api.test.ts > retake > finishes cleanly for a learner who has already cleared every skill
- ✓ diagnostic-api.test.ts > retake > refreshes only a seed that has faded below the new estimate
- ✓ diagnostic.test.ts > diagnostic schema > allows only one diagnostic in progress per enrollment
- ✓ enrollment-fade.test.ts > enrollment and fade schema > rejects an enrollment in a language the course doesn't offer
- ✓ enrollment-fade.test.ts > enrollment and fade schema > rejects a skill sitting on a fade stage its schedule doesn't have
- ✓ erasure.test.ts > account erasure (DPDP doc §4) > knows every table that points at a learner: a new one must join the export and erasure first
- ✓ erasure.test.ts > account erasure (DPDP doc §4) > anonymises the person and deletes every learning row, keeping the consents as proof
- ✓ erasure.test.ts > account erasure (DPDP doc §4) > keeps the anonymous numbers of a learner who opted in to research, but never their code or words
- ✓ erasure.test.ts > account erasure (DPDP doc §4) > leaves accounts still in their grace period, and requests cancelled by logging in
- ✓ exercise-draft.test.ts > exercise drafts > become templates the bank's harness can run, with the standard closing instruction
- ✓ exercise-draft.test.ts > exercise drafts > turn a predict draft into a rung-1 template whose program is its own reference
- ✓ exercise-draft.test.ts > exercise drafts > refuse a call statement that doesn't take the test's arguments
- ✓ exercise-draft.test.ts > exercise drafts > prompt with the skill, what it may use, the existing titles and the last failure
- ✓ exercise-draft.test.ts > exercise drafts > give Gemini a schema without the dialect tag

- ✓ exercise-templates.test.ts > cpp-basics template bank > covers rungs 1–5 for every course skill, once each
- ✓ exercise-templates.test.ts > cpp-basics template bank > only uses skills that exist in the course
- ✓ exercise-templates.test.ts > cpp-basics template bank > gives rung 1 a program to read and no harness; rungs 2–5 a function to write
- ✓ exercise-templates.test.ts > DSA practice bank > has rungs 1–5 once each for every skill it covers, all of them DSA skills
- ✓ exercise-templates.test.ts > DSA practice bank > shows a sample with its output; generated tests come last, at least two, with a brute force
- ✓ exercise-templates.test.ts > cpp-basics placement test bank > has exactly one reading item and one code task per course skill
- ✓ exercise-templates.test.ts > cpp-basics placement test bank > asks reading as a program to read, showing only the code
- ✓ exercise-templates.test.ts > cpp-basics placement test bank > asks code tasks as a rung-5 function with hidden tests beyond the shown example
- ✓ exercise-templates.test.ts > DSA placement test bank > has exactly one reading item and one code task per course skill
- ✓ exercise-templates.test.ts > DSA placement test bank > asks reading as a program to read, and code as a rung-5 function with a shown example
- ✓ exercise-templates.test.ts > DSA placement test bank > never reuses a practice exercise, so practice can't teach the test's answers
- ✓ exercise-verification.test.ts > exercise verification > verifies when the reference passes and the starter fails
- ✓ exercise-verification.test.ts > exercise verification > rejects an exercise whose reference doesn't pass
- ✓ exercise-verification.test.ts > exercise verification > rejects an exercise whose tests can't tell the starter from a solution
- ✓ exercise-verification.test.ts > exercise verification > runs only the program itself for rung 1 (there is no starter to try)
- ✓ exercise-verification.test.ts > exercise verification > checks content before it is stored: a starter that won't compile, and wrong solutions that slip through

- ✓ exercise-verification.test.ts > generated tests and the brute force > takes generated tests' outputs from the reference when the brute force agrees and then times out
- ✓ exercise-verification.test.ts > generated tests and the brute force > rejects a brute force that is missing, never times out, disagrees, never agrees or fails a small test
- ✓ exercise-verification.test.ts > generated tests and the brute force > rejects a reference that takes more than a third of the time limit
- ✓ exercise-verification.test.ts > generated tests and the brute force > stores the generated outputs when a draft is verified
- ✓ exercises-api.test.ts > GET /exercises/:id > shows the exercise and its sample test, never secrets or hidden tests
- ✓ exercises-api.test.ts > GET /exercises/:id > shows what the skill is about and its active reading links for the exercise's language, in order
- ✓ exercises-api.test.ts > GET /exercises/:id > starts one attempt, enrolling the learner and starting the skill at fade stage 1
- ✓ exercises-api.test.ts > GET /exercises/:id > returns a solved attempt as solved instead of starting a new one
- ✓ exercises-api.test.ts > GET /exercises/:id > hides exercises that aren't verified
- ✓ exercises-api.test.ts > GET /exercises/:id > never shows a predict-the-output exercise's answer
- ✓ exercises-api.test.ts > GET /exercises/:id > never opens a placement-test exercise as practice
- ✓ exercises.test.ts > exercises schema > rejects a second exercise with the same content key
- ✓ exercises.test.ts > exercises schema > rejects a rung outside 1 to 5
- ✓ export-pilot.test.ts > pilot data export (pnpm pilot:export) > exports an opted-in learner's activity under an alias, and nothing that identifies anyone
- ✓ freeze-hints.test.ts > frozen hints > stores levels 1–4 once, and leaves an exercise that already has hints alone
- ✓ freeze-hints.test.ts > frozen hints > asks again when a hint gives the solution away, and skips the exercise if it happens twice
- ✓ generate-exercise.test.ts > exercise generation > stores a draft the sandbox proves, verified and ready to serve

- ✓ generate-exercise.test.ts > exercise generation > tries again after a bad reply, telling the model what was wrong
- ✓ generate-exercise.test.ts > exercise generation > rejects tests a wrong solution passes, tries Pro last, then falls back to the hand-written exercise
- ✓ generate-exercise.test.ts > exercise generation > checks a predict-the-output draft's claimed output by running the program
- ✓ generate-exercise.test.ts > exercise generation > does nothing for a job that has already finished
- ✓ generation-api.test.ts > POST /exercises/generate > queues one job per skill and rung for an author, and returns the same job while it runs
- ✓ generation-api.test.ts > POST /exercises/generate > is for admins and authors only, and refuses while billing is off
- ✓ generation-api.test.ts > POST /exercises/generate > leaves DSA hand-written: no job on request or for a skill with nothing to serve (ADR-0023)
- ✓ generation-api.test.ts > POST /exercises/generate > 404s for an unknown skill or job
- ✓ generation-api.test.ts > automatic generation > queues an exercise when the learner's next skill has none, once
- ✓ generation-budget.test.ts > generation budget > stops before calling the model once ₹300 is spent this month, and falls back
- ✓ hints-api.test.ts > POST /exercises/:id/hints > gives the live tutor's hint for the next level only, and moves the level
- ✓ hints-api.test.ts > POST /exercises/:id/hints > blocks a reply that gives the solution away and serves the frozen hint instead
- ✓ hints-api.test.ts > POST /exercises/:id/hints > falls back to a general nudge when the tutor fails and nothing is stored
- ✓ hints-api.test.ts > POST /exercises/:id/hints > refuses a level above the fade stage's ceiling, and logs it
- ✓ hints-api.test.ts > POST /exercises/:id/hints > shows the answer at level 5 without the tutor, and marks the bottom-out
- ✓ hints-api.test.ts > POST /exercises/:id/hints > stops calling the tutor after 20 live hints in a day
- ✓ hints-api.test.ts > POST /exercises/:id/hints > needs an open attempt on a practice exercise

- ✓ hints-budget.test.ts > hint budget > serves frozen hints without calling the tutor once ₹500 is spent this month
- ✓ identity.test.ts > identity schema > treats email as unique and case-insensitive
- ✓ identity.test.ts > identity schema > deletes a user's refresh tokens with the user
- ✓ judge.test.ts > judge > accepts the right output, ignoring line endings and trailing spaces
- ✓ judge.test.ts > judge > gives WA for different output, including an early exit that prints nothing
- ✓ judge.test.ts > judge > gives RE for a crash or a non-zero exit
- ✓ judge.test.ts > judge > gives MLE above the memory limit or on std::bad_alloc
- ✓ judge.test.ts > judge > gives TLE when the time limit killed the test, whatever else happened
- ✓ judge.test.ts > judge > lets the first failing test decide, and calls an empty test list a setup error
- ✓ judge.test.ts > judge > cuts long output to a readable excerpt
- ✓ lesson-draft.test.ts > lesson level > is new before any evidence, building with some, and strong once the skill is written well or cleared
- ✓ lesson-draft.test.ts > lesson draft > accepts a complete lesson, and refuses a diagram the web can't draw or a program without main
- ✓ lesson-draft.test.ts > lesson draft > asks for the learner's level, builds on what they know, and avoids the skill's exercises
- ✓ lesson-files.test.ts > cpp-basics hand-written lessons > cover every skill of the course, with all three levels each
- ✓ lesson-files.test.ts > cpp-basics hand-written lessons > fit the lesson schema, as a generated one must
- ✓ lesson-files.test.ts > dsa hand-written lessons > cover every skill of the course, with all three levels each
- ✓ lesson-files.test.ts > dsa hand-written lessons > fit the lesson schema, as a generated one must
- ✓ lesson-notes-api.test.ts > POST /lessons/:skillId/note > writes a note from the learner's recent results and weak prerequisite, then reuses it until they practise again
- ✓ lesson-notes-api.test.ts > POST /lessons/:skillId/note > says nothing without live AI, past the daily limit, or when the reply has code

- ✓ lesson-notes-api.test.ts > POST /lessons/:skillId/note > makes no call when there's nothing personal to say yet
- ✓ lessons-api.test.ts > lesson generation > writes, proves and freezes a lesson for one level
- ✓ lessons-api.test.ts > lesson generation > refuses a lesson the fact-check finds false, and tells the next try what is true
- ✓ lessons-api.test.ts > lesson generation > refuses a lesson that gives a practice exercise away, and tells the next try why
- ✓ lessons-api.test.ts > lesson generation > refuses programs that don't print what the lesson states, and gives up after three tries
- ✓ lessons-api.test.ts > lesson generation > stops before calling the model once this month's ₹300 is spent
- ✓ lessons-api.test.ts > hand-written lessons > pass the same gates, are frozen as hand-written, and fill their level for the generator
- ✓ lessons-api.test.ts > GET /lessons/:skillId > serves the lesson for the learner's level, or the nearest one written so far
- ✓ lessons-api.test.ts > GET /lessons/:skillId > is null until a lesson is written, 404 for an unknown skill, and needs a login
- ✓ mastery-api.test.ts > mastery API > lists skills with reading and writing apart, decayed on read
- ✓ mastery-api.test.ts > mastery API > shows one skill in detail, and zeros for a skill never practised
- ✓ mastery-api.test.ts > mastery API > answers 404 for a skill that doesn't exist
- ✓ mastery-formula.test.ts > mastery formula v1 > follows the approved journey: about five good solves pass 0.7
- ✓ mastery-formula.test.ts > mastery formula v1 > gives no credit for an AC after the solution was shown
- ✓ mastery-formula.test.ts > mastery formula v1 > penalises only the first WA or RE of an attempt, more on easy rungs
- ✓ mastery-formula.test.ts > mastery formula v1 > starts TLE/MLE tiny, doubles each time, caps at a WA, and lets only AC reset the streak
- ✓ mastery-formula.test.ts > mastery formula v1 > leaves a counted compile error's score alone

- ✓ mastery-formula.test.ts > mastery formula v1 > gives less credit when much slower than usual, but never below 70%
- ✓ mastery-formula.test.ts > mastery formula v1 > counts rung 1 as reading and rungs 2–5 as writing
- ✓ mastery-formula.test.ts > mastery formula v1 > halves effective mastery after ln 2 / λ days, and never decays without evidence
- ✓ mastery.test.ts > mastery schema > rejects evidence that has no source
- ✓ mastery.test.ts > mastery schema > never counts the same evidence twice
- ✓ password-reset-api.test.ts > forgot password > emails a 30-minute link with the token in the #fragment, storing only its hash
- ✓ password-reset-api.test.ts > forgot password > answers unknown and inactive accounts exactly like a real one, and mails only the real one
- ✓ password-reset-api.test.ts > forgot password > sends one email per account every 5 minutes; asking sooner keeps the link already sent
- ✓ password-reset-api.test.ts > forgot password > limits each IP to 5 requests per 15 minutes
- ✓ password-reset-api.test.ts > reset password > sets the new password, ends every login, and works only once
- ✓ password-reset-api.test.ts > reset password > ends a login or refresh that was under way during the reset, even one saved just after it
- ✓ password-reset-api.test.ts > reset password > lets only one of two simultaneous resets through
- ✓ password-reset-api.test.ts > reset password > refuses an expired link, and an older link once a newer one was sent
- ✓ password-reset-api.test.ts > reset password > ends the account's other links too (two requests at once can each make one)
- ✓ password-reset-api.test.ts > reset password > asks for a password of 8 to 128 characters
- ✓ placement.test.ts > placement order > puts every prerequisite before the skills built on it, easiest first
- ✓ placement.test.ts > placement walk > ends after one item for a novice who doesn't know, and after the check for one who guesses

- ✓ placement.test.ts > placement walk > asks writing only on the frontier of what was read correctly
- ✓ placement.test.ts > placement walk > places all 711 possible learners exactly, within 20 reading and 7 writing items
- ✓ placement.test.ts > placement walk > rescues a typed slip when the next skill is right, and confirms it when that is wrong too
- ✓ placement.test.ts > placement walk > checks a suspect skill once: its other dependents wait for that check
- ✓ placement.test.ts > placement walk > never lets a writing verdict change which item comes next
- ✓ placement.test.ts > placement walk > infers a skill with no reading item from its dependents, and moves the frontier below a missing writing item
- ✓ placement.test.ts > placement walk > never asks or estimates skills already cleared in practice, but builds on them
- ✓ placement.test.ts > placement estimate > lets one frontier AC vouch for every skill below it, at lower confidence
- ✓ placement.test.ts > placement estimate > treats a pending or failed-to-run task as unobserved, and gives unreached skills nothing
- ✓ placement.test.ts > placement walk, DSA course > asks an expert all 49 reading items and the 20 skills nothing else in the course builds on
- ✓ placement.test.ts > placement walk, DSA course > places 300 random learners exactly, with one code task per skill on their frontier
- ✓ progress-api.test.ts > GET /progress > shows every skill's reading and writing apart, as they are today, with a status
- ✓ progress-api.test.ts > GET /progress > names prerequisites from another course, and holds a skill back until they are met
- ✓ progress-api.test.ts > GET /progress > 404s for a course that doesn't exist in that language
- ✓ recommendations-api.test.ts > GET /recommendations/next > starts a new learner on the first skill at rung 1, enrolls them, and saves the reasons
- ✓ recommendations-api.test.ts > GET /recommendations/next > moves to rung 2 after the rung-1 exercise is solved

- ✓ recommendations-api.test.ts > GET /recommendations/next > names the next skill without an exercise when it has no content yet
- ✓ recommendations-api.test.ts > GET /recommendations/next > names the other course's skills a learner must finish first, instead of saying the course is done
- ✓ recommendations-api.test.ts > GET /recommendations/next > returns null when every skill is cleared and fresh, and 404 for an unknown course
- ✓ recommender.test.ts > recommender rules v1 > starts a new learner on the first skill only
- ✓ recommender.test.ts > recommender rules v1 > unlocks the next skill once a prerequisite is cleared, even if it has decayed a little
- ✓ recommender.test.ts > recommender rules v1 > finishes the skill in progress before a due review, and does due reviews before new skills
- ✓ recommender.test.ts > recommender rules v1 > prefers the learner's goal skill among equals, and reports nothing when the course is done
- ✓ recommender.test.ts > recommender rules v1 > follows the approved journey: rung 1 → 2 → 3 → 4 → 5 in five good solves
- ✓ recommender.test.ts > recommender rules v1 > never goes below the fade stage's easiest rung
- ✓ recommender.test.ts > recommender rules v1 > picks the unfinished attempt first, then unseen at the rung, then harder, then easier
- ✓ research.test.ts > research schema > allows one live consent of each kind, and a new one after revoking
- ✓ scaffolding-api.test.ts > scaffolding fade > moves a skill on when the stage's rung is solved with at most 1 hint, and logs why
- ✓ scaffolding-api.test.ts > scaffolding fade > stays put with too many hints or on an easier rung, and moves one stage at a time
- ✓ scaffolding-api.test.ts > scaffolding fade > never moves past the last stage
- ✓ scaffolding-api.test.ts > scaffolding fade > shows each skill's stage and limits
- ✓ session-clock.test.ts > session clock > leaves a recently active session alone
- ✓ session-clock.test.ts > session clock > pauses after 15 idle minutes, from the moment it went idle
- ✓ session-clock.test.ts > session clock > ends a session paused for over 24 hours, whether paused by hand or by going idle

- ✓ session-clock.test.ts > session clock > counts time between activities as study, but never while paused
- ✓ session-clock.test.ts > session clock > pauses, resumes and ends on request, and does nothing for the same state
- ✓ sessions-api.test.ts > POST /sessions > starts a session on the recommender's first step, and resumes it on the next call
- ✓ sessions-api.test.ts > POST /sessions > ends as completed when the course is done, and 404s for an unknown course
- ✓ sessions-api.test.ts > GET /sessions/active > moves to the next step once the current exercise is solved
- ✓ sessions-api.test.ts > GET /sessions/active > pauses a session idle for 15 minutes without counting the gap, and ends one paused for a day
- ✓ sessions-api.test.ts > PATCH /sessions/:id > pauses, resumes at the same step, and ends for good
- ✓ sessions-api.test.ts > PATCH /sessions/:id > hides other learners' sessions and rejects unknown states
- ✓ sessions.test.ts > sessions schema > allows only one open session per learner
- ✓ sessions.test.ts > sessions schema > allows only one active step per session
- ✓ skill-graph.test.ts > skill graph > finds a cycle
- ✓ skill-graph.test.ts > skill graph > accepts a graph where skills share prerequisites
- ✓ skill-graph.test.ts > skill graph > cpp-basics seed data > has unique slugs and only known prerequisites
- ✓ skill-graph.test.ts > skill graph > cpp-basics seed data > has no cycles
- ✓ skill-graph.test.ts > skill graph > dsa seed data > has unique slugs and names, and only known prerequisites, its own or C++ basics'
- ✓ skill-graph.test.ts > skill graph > dsa seed data > has no cycles, even counting C++ basics, and builds on C++ basics from every root
- ✓ skill-graph.test.ts > skill graph > dsa seed data > is never easier than what it builds on
- ✓ solution-filter.test.ts > solution filter > passes a hint in words, and a small fragment of a different idea
- ✓ solution-filter.test.ts > solution filter > blocks the solution, whole or in its key lines, fenced or not

- ✓ solution-filter.test.ts > solution filter > doesn't count code the learner already has
- ✓ solution-filter.test.ts > solution filter > blocks more than a fragment of code, even unrelated code
- ✓ solution-filter.test.ts > solution filter > blocks a predict-the-output hint that gives the output away
- ✓ submissions.test.ts > submissions > saves and queues a submission, answering 202
- ✓ submissions.test.ts > submissions > grades a predict-the-output answer at once, without the queue, and a repeat gives the same result
- ✓ submissions.test.ts > submissions > returns the same submission for a repeated idempotency key, counted once
- ✓ submissions.test.ts > submissions > refuses a key already used on another attempt, so no attempt can borrow another's verdict
- ✓ submissions.test.ts > submissions > hides other learners' attempts and submissions
- ✓ submissions.test.ts > submissions > judges a run, shows the sample test in full and the hidden test as a verdict only
- ✓ submissions.test.ts > submissions > shows compiler output for CE, and doesn't count it before the third
- ✓ submissions.test.ts > submissions > retries a sandbox failure, then gives SE without counting it
- ✓ submissions.test.ts > submissions > turns an AC into writing mastery, saved with its ledger row
- ✓ submissions.test.ts > submissions > penalises only the first wrong answer of an attempt
- ✓ submissions.test.ts > submissions > records no evidence for SE or an early compile error
- ✓ submissions.test.ts > submissions > saves a calibration record for a learner's first counted try at an exercise only (ADR-0021)
- ✓ submissions.test.ts > submissions > calibrates only one of two first tries graded at the same time
- ✓ submissions.test.ts > submissions > predicts from today's scores, decayed since their last evidence
- ✓ submissions.test.ts > submissions > deletes the learner's code for a skill once it is cleared, keeping every verdict (privacy policy §2)

Real-sandbox smoke test:

```
ok   AC  → AC   5866 ms
ok   WA  → WA   5341 ms
ok   CE  → CE   3565 ms
ok   RE  → RE   5118 ms
ok   TLE → TLE  6965 ms
ok   MLE → MLE  5424 ms
All six verdicts correct.
```

Content verification on the real sandbox (18 October 2026), placement items:

```
Verifying 40 draft exercise(s)…
ok       rung 1 · What does it print? Comments and line breaks
ok       rung 1 · What does it print? Implicit conversions
…        (36 more)
ok       rung 5 · Sort by distance, split near from far
ok       rung 5 · Own a heap array inside a struct
40 verified, 0 rejected.
```

Content verification on the real sandbox (20 October 2026), the five DSA exercises of one skill (prefix sums). Each line shows the reference's time per test in ms; the last two tests of rungs 2–5 are generated, so their outputs are printed as a size and a hash and stored as the expected output:

```
rung 1 ok    What does it print? Reading sums off a prefix array
ref ms: 10
rung      2      ok                  Fix      the      range      sums
ref ms: 20,0,0,0,0,10
               out: 9 -2 4 13 | 5 |  | 3000000000 | size 2000, hash
12174026465321784153 | size 500000, hash 14448745048033150881
rung     3     ok               Complete     the     balance     point
ref ms: 30,0,0,0,0,0,0
rung  4  ok       Extend  coverage  to  weights  and  a  threshold
ref ms: 10,0,0,0,0,0,40
rung  5  ok       The  longest  stretch  with  equal  0s  and  1s
ref ms: 10,0,0,0,0,0,10
```

The development database after seeding and verification (22 October 2026):

```
pnpm exercises:verify   → Verifying 0 draft exercise(s)… 0 verified, 0
rejected.   (every exercise already proven)
pnpm lessons:seed       → 0 added, 207 already there, 0 failed.
exercises: cpp-basics 140 verified, dsa 343 verified    (483; none
rejected or waiting)
placement items: cpp-basics 20 reading + 20 code, dsa 49 reading + 49
code   (all verified)
lessons:   207   (C++ basics 20 × 3 levels, DSA 49 × 3 levels)
```

A DSA placement test through the running API (22 October 2026, real E2B). A learner who knows complexity, binary search, prefix sums and two pointers answers those reading items

with the right output, says "I don't know" to the rest, and submits each frontier code task's reference solution (R: reading, W: code task):

```
asked 17: R:complexity R:recursion R:binary-search R:elementary-sorts
R:graph-basics R:hashing R:matrices
               R:prefix-sums R:queues R:stacks R:two-pointers R:bit-
manipulation R:linked-lists
              R:binary-search-on-answer W:binary-search W:prefix-sums
W:two-pointers
status completed, 49 skills
  complexity: reading 0.85, writing 0.85, confidence 0.5      (vouched
for by the code tasks above it)
  binary-search: reading 0.85, writing 0.85, confidence 1
  prefix-sums: reading 0.85, writing 0.85, confidence 1
  two-pointers: reading 0.85, writing 0.85, confidence 1
  (the other 45 skills: 0)
```

A-9 Sample Inputs

```
# Register (adult)
curl -X POST http://localhost:3001/api/v1/auth/register -H "Content-
Type: application/json" \
                                                                    -d
'{"email":"adult@test.com","password":"password123","displayName":"Adul
t","dateOfBirth":"2000-05-
01","acceptTerms":true,"acceptPrivacy":true,"aiTraining":true}'

# Submit code for an attempt
curl    -X    POST    http://localhost:3001/api/v1/submissions    -H
"Authorization: Bearer <token>" -H "Content-Type: application/json" \
   -d '{"attemptId":"<attempt id>","answer":"int sumOfDigits(int n) {
int s = 0; for (; n > 0; n /= 10) s += n % 10; return s;
}","idempotencyKey":"try-001"}'

# Placement test: start, then answer the current question (or say "I
don't know")
curl   -X   POST   http://localhost:3001/api/v1/diagnostic/start   -H
"Authorization: Bearer <token>" -H "Content-Type: application/json" -d
'{}'
curl -X POST http://localhost:3001/api/v1/diagnostic/<id>/answers -H
"Authorization: Bearer <token>" -H "Content-Type: application/json" \
  -d '{"itemId":"<item id>","dontKnow":true}'

# Ask for the next hint, sending the current code
curl -X POST http://localhost:3001/api/v1/exercises/<exercise id>/hints
-H "Authorization: Bearer <token>" -H "Content-Type: application/json"
\
  -d '{"code":"int sumOfDigits(int n) { return n % 10; }"}'

# Forgot password, then set a new one with the token from the emailed
link
curl   -X   POST   http://localhost:3001/api/v1/auth/forgot-password   -H
"Content-Type: application/json" -d '{"email":"adult@test.com"}'
```

```
curl -X POST http://localhost:3001/api/v1/auth/reset-password -H
"Content-Type: application/json" \
    -d '{"token":"<token from the link>","password":"a brand new
passphrase"}'

# Correct the profile, switch research on, download the data
curl -X PATCH http://localhost:3001/api/v1/me -H "Authorization: Bearer
<token>" -H "Content-Type: application/json" \
  -d '{"displayName":"Asha K","timezone":"Europe/London"}'
curl -X PUT http://localhost:3001/api/v1/me/consents/research_study -H
"Authorization: Bearer <token>"
curl -OJ http://localhost:3001/api/v1/me/data -H "Authorization: Bearer
<token>"

# Delete the account (the password again)
curl -X DELETE http://localhost:3001/api/v1/me -H "Authorization:
Bearer <token>" -H "Content-Type: application/json" \
  -d '{"password":"correct horse battery"}'
```

A-10 Sample Outputs

Real responses captured during testing (IDs shortened):

```
// Register (adult)
{"success":true,"data":{"user":
{"email":"adult@test.com","displayName":"Adult","role":"LEARNER",
 "dateOfBirth":"2000-05-01","status":"active"}}}

// Register (15 years old) during the pilot: refused, next to the date
of birth, and nothing saved
{"success":false,"error":{"code":"VALIDATION_ERROR","message":"Invalid
request",
  "details":[{"code":"custom","path":["dateOfBirth"],"message":"AI-Tutor
is open to adults (18 and over) for now"}]}}

// Submission result: wrong answer (return n % 10)
{"verdict":"WA","testsPassed":1,"testsTotal":4,"tests":[

{"seq":1,"name":"Example","visibility":"sample","verdict":"WA","input":
"123","expectedOutput":"6","output":"3\n"},

{"seq":2,"name":"Zero","visibility":"hidden","verdict":"AC","timeMs":0}
,
                                                    {"seq":3,"name":"All
nines","visibility":"hidden","verdict":"WA","timeMs":0},
                                                {"seq":4,"name":"Largest
input","visibility":"hidden","verdict":"WA","timeMs":0}]}

// Submission result: correct answer
{"verdict":"AC","testsPassed":4,"testsTotal":4}

// An exercise's skill details (reading-link titles and addresses
shortened)
{"skill":{"name":"Arrays","slug":"arrays",
```

```
 "description":"Fixed-size sequences of values, indexing them, and what
happens when an index goes out of bounds.",
                  "resources":[{"kind":"article","title":"…","url":"…"},
{"kind":"docs","title":"…","url":"…"}]}}
```

```
End-to-end learner loop (16 Oct 2026)
GET exercise:   Sum of digits | rung 3 | skill Functions | sampleTests
1 | attempt active, ceiling 5
verdict:        AC 4/4
GET mastery:    Functions | writing 0.240 effective 0.240 | attempts 1
reopen attempt: solved
```

```
Placement test on real E2B (18 Oct 2026): a learner who knows the first
3 skills
start: attempt 1, first question: reading program-structure    (the
answer is not in the response)
  reading program-structure      → answers
  reading variables-and-types    → answers
  reading operators              → answers
  reading conditionals           → I don't know
  reading bitwise-operators      → I don't know
   writing operators                    → answers (code, run in the
background)
answered 6 in 621 ms; complete → 202 grading, retry in 5000 ms →
completed after 5676 ms
  program-structure      reading 0.85 writing 0.85 confidence 0.5
  variables-and-types    reading 0.85 writing 0.85 confidence 0.5
  operators              reading 0.85 writing 0.85 confidence 1
next step: conditionals, rung 1
fade: program-structure = stage 4, variables-and-types = stage 4,
operators = stage 4
```

```
Session and progress (19 Oct 2026)
start:  active | step 1 Your first program, rung 1
pause:  paused | resume: active, same step
progress summary: total 20, locked 19, ready 1, in progress 0, cleared
0, review due 0
end:    user | active session after end: none
```

```
Hint ladder with live AI switched off (19 Oct 2026), a rung-1 exercise
200 level 1/5 generic: Re-read the task and list what goes in and what
must come out…
200 level 2/5 generic: Run the example by hand, line by line…
200 level 3/5 generic: Change one thing at a time and run again…
200 level 4/5 generic: Solve a tiny version of the task first…
200 level 5/5 answer:  It prints: Hello World / 3. Trace it again line
by line…
409 HINT_LIMIT
```

```
Admin overview, last 30 days (19 Oct 2026, development database, before
the full practice bank was seeded)
```

```
learners: total 9, joined 9, ran code 4, waiting for a parent 1, AI-training opt-ins 1
runs:     5 submissions (AC 4, WA 1), median run 50 ms, sandbox error rate 0
content:  14 of 20 skills have no practice exercises yet; Your first program has one per rung
```

```
Exercise generation with live AI switched off (19 Oct 2026), as an admin
POST /exercises/generate { skill: "vectors", rung: 2 } → 503 GENERATION_UNAVAILABLE
```

```
Password reset in a real browser (19 Oct 2026; development, so the email is printed instead of sent)
POST /auth/forgot-password → 202 "If an account uses that email, a reset link is on its way. It works for 30 minutes."
[mail not sent: no BREVO_API_KEY] to reset-check-…@test.dev: Reset your AI-Tutor password
  link: http://localhost:3000/reset-password#token=…
POST /auth/reset-password → 204; log in with the new password → dashboard; old password → 401
same link again → 400 RESET_LINK_INVALID "This reset link is invalid or has expired. Ask for a new one."
```

```
Guided walk on the running server, real E2B (20 Oct 2026; pnpm demo:walk)
▶ Sign up: 15 years old → 400 "AI-Tutor is open to adults (18 and over) for now"; adult → 201 active; log in → 200
▶ Placement test: question 1 reading, Your first program; "I don't know" → completed, all 20 skills from the beginning
▶ What next: Your first program, rung 1 of 5 (new_skill)
▶ Open "Sum of digits" (Functions, rung 3): 1 sample test shown, hidden tests stay on the server, up to 5 hints
▶ Wrong answer: WA, 1 of 4 tests; sample "Example" expected "6", got "0"; hidden "Zero" AC, "All nines" WA, "Largest input" WA
▶ Hint: level 1 of 5 (generic): Re-read the task and list what goes in and what must come out…
▶ Right answer: AC, 4 of 4 tests; Functions reading 0.00, writing 0.20 (one hint used, so less credit)
▶ Progress: total 20, locked 19, ready 1, in progress 0, cleared 0, review due 0
▶ Download my data: 200, attachment; filename=ai-tutor-my-data.json, 11 sections, 5 named providers
▶ Delete my account: 202, erased after 7 days; the same token now → 401
```

```
Data rights on the running server (19 Oct 2026; development, so the email is printed instead of sent)
PATCH /me → 200 Asha K, Europe/London; time zone "Mars/Olympus" → 400 VALIDATION_ERROR "Unknown time zone"
PUT /me/consents/research_study → 204; GET /me/consents → data_processing, terms, research_study (v0.1)
DELETE /me/consents/terms → 400 (the required consents end only with
```

```
the account)
GET /me/data → 200, Content-Disposition: attachment; filename=ai-tutor-
my-data.json, Cache-Control: no-store
    sections: exportedAt, about, account, courses, placementTests,
mastery, recommendations,
            practice, hints, sessions, scaffolding
  shared with: Oracle Cloud (India region); Vercel; E2B; Google Gemini
(paid, no-training terms); Brevo
  a password or token hash anywhere in it: no
DELETE /me, wrong password → 403 WRONG_PASSWORD; right password → 202
{"eraseAfter":"2026-10-26T18:05:47.799Z"}
[mail not sent: no BREVO_API_KEY] to rights-check-…@test.dev: Your AI-
Tutor account will be deleted
  "It will be deleted after 26 October 2026 at 6:05 pm GMT. … Log in
before then and nothing is deleted"
GET /auth/me with the same token → 401

The same account erased as the hourly job does it, 8 days later:
  user:     deleted-<id>@deleted.invalid | Deleted learner | no date of
birth | Asia/Kolkata | deleted
   consents: research_study, data_processing, terms: all revoked, kept
as proof
  logins:   mobile, ended, kept a year as a security record
  log in with the old email and password → 401
```

The provider list above is from 19 October. Since ADR-0024 the download names Supabase (India region), Render (Singapore) and Vercel in place of Oracle Cloud.

Screen snapshots of the web interface will be added here in the final report.

A-11 Coding (selected)

The verdict judge (`apps/api/src/modules/m7_execution/services/judge.ts`)

```
import          type          {          verdict          }          from
"../../../infrastructure/database/schema/index.js";
import       type       {       Limits,       TestRun       }       from
"../../../infrastructure/sandbox/sandbox-provider.js";

//  Turns  raw  sandbox  readings  into  verdicts  (ADR-0003,  "Verdict
mapping"). Pure: no sandbox, no database.
export type Verdict = (typeof verdict.enumValues)[number];

const EXCERPT_CHARS = 4000;

// Same output once line endings, trailing spaces and blank lines at
the end are ignored.
const normalise = (text: string) =>
  text
    .replace(/\r\n/g, "\n")
    .split("\n")
    .map((line) => line.trimEnd())
    .join("\n")
```

```
    .trimEnd();

export const sameOutput = (actual: string, expected: string) =>
normalise(actual) === normalise(expected);

export function judgeTest(run: TestRun, expected: string, limits:
Limits): Verdict {
  if (run.timedOut) return "TLE";
      if (run.peakMemoryKb > limits.memoryLimitMb * 1024 ||
run.stderr.includes("std::bad_alloc")) return "MLE";
  if (run.exitCode !== 0) return "RE";
  return sameOutput(run.stdout, expected) ? "AC" : "WA";
}

// The first failing test decides. No tests means a broken setup, never
the learner's fault.
export const overallVerdict = (testVerdicts: Verdict[]): Verdict =>
  testVerdicts.length ? (testVerdicts.find((v) => v !== "AC") ?? "AC")
: "SE";

// Compiler output and test output are stored and shown cut to a
readable size.
export const excerpt = (text: string) =>
   text.length > EXCERPT_CHARS ? `${text.slice(0, EXCERPT_CHARS)}\n…
(truncated)` : text;
```

The mastery formula (`apps/api/src/modules/m4_mastery/services/mastery-formula.ts`)

```
import type { Verdict } from "../../m7_execution/services/judge.js";

// The M4 formula, v1 (ADR-0004, approved 15 Oct). Pure: no database.
Every evidence row stores
//  FORMULA_VERSION, so old numbers stay explainable when these
constants are tuned.
export const FORMULA_VERSION = "m4-v1";
const GAIN = 0.4; // AC moves the score 40% of the way to 1, scaled by
weight
const PENALTY = 0.15; // WA/RE take 15% of the score, scaled by
failWeight
const HINT_COST = 0.15; // each hint used cuts the AC credit by 15%
const BOTTOM_OUT_LEVEL = 5; // hint 5 shows the solution: no credit
const LIMIT_START = PENALTY / 20; // TLE/MLE start at 1/20 of a WA,
doubling, capped at a WA
const USUAL_MINUTES = [5, 8, 12, 15, 20]; // per rung; placeholders
until real timings exist
const SLOWEST_TIME_FACTOR = 0.7;

export type Evidence = {
  verdict: Verdict;
  rung: number;
  hintsUsed: number;
   activeMs: number; // 0 until sessions track active time; then time
counts
```

```
  isRepeatFailure: boolean; // an earlier WA/RE in the same attempt was
already penalised
};

export type Update = { score: number; weight: number; limitStreak:
number };

// Rung 1 is "predict the output", so it's evidence about reading code;
rungs 2–5 about writing it.
export const dimensionOf = (rung: number) => (rung === 1 ? "reading" :
"writing");

export function applyEvidence(before: number, limitStreak: number, e:
Evidence): Update {
  const unchanged = { score: before, weight: 0, limitStreak };
  const failWeight = (6 - e.rung) / 5; // failing an easy exercise says
more than failing a hard one

  switch (e.verdict) {
    case "AC": {
      const hints = e.hintsUsed >= BOTTOM_OUT_LEVEL ? 0 : 1 - HINT_COST
* e.hintsUsed;
      const weight = (e.rung / 5) * hints * timeFactor(e);
       return { score: before + GAIN * weight * (1 - before), weight,
limitStreak: 0 };
    }
    case "WA":
    case "RE":
       return e.isRepeatFailure ? unchanged : { score: before * (1 -
PENALTY * failWeight), weight: failWeight, limitStreak };
    case "TLE":
    case "MLE": {
      const penalty = Math.min(LIMIT_START * 2 ** limitStreak, PENALTY)
* failWeight;
        return { score: before * (1 - penalty), weight: failWeight,
limitStreak: limitStreak + 1 };
    }
    default:
      return unchanged; // a counted CE: it shows in attempt totals but
doesn't move the score
  }
}

// Slower than the rung's usual time lowers credit, never below 0.7. No
time tracked = full credit.
function timeFactor({ rung, activeMs }: Evidence) {
  if (!activeMs) return 1;
  const usualMs = USUAL_MINUTES[rung - 1] * 60_000;
     return Math.min(1, Math.max(SLOWEST_TIME_FACTOR, usualMs /
activeMs));
}

const DAY_MS = 86_400_000;

// FR-M4-03: what the learner can still do today. Stored scores never
```

```
decay; this is computed on read.
export const effectiveScore = (score: number, decayLambda: number,
evidenceAt: Date | null, now = new Date()) =>
    evidenceAt ? score * Math.exp((-decayLambda * (now.getTime() -
evidenceAt.getTime())) / DAY_MS) : score;
```

The hint leak filter (`apps/api/src/modules/m8_socratic/services/solution-filter.ts`)

```
// FR-M8-04: every generated hint is checked before a learner sees it.
Pure, so it is unit-tested.
// Code is compared as overlapping runs of 5 tokens ("fingerprints"). A
hint is blocked when it
// carries too many of the fingerprints only the solution has (not the
starter, not the learner's
// own code), when it shows more than a fragment of code, or when it
gives away a rung-1 output.
const RUN = 5;
const MAX_SHARED = 0.25; // share of the solution's own fingerprints a
hint may contain
const MAX_CODE_LINES = 6; // a hint may show a fragment, never a
program
const MIN_OUTPUT_CHARS = 4; // shorter outputs ("3") appear in prose by
chance

export type FilterContext = { reference: string; starter: string;
learnerCode?: string; output?: string };
export type FilterResult = { passed: boolean; shared: number;
longestCode: number; givesOutput: boolean };

const TOKEN = /[A-Za-z_]\w*|\d+|"(?:\\.|[^"\\])*"|'(?:\\.|
[^'\\])*'|\S/g;
const tokens = (code: string) => code.replace(/\/\/.*$/gm,
"").replace(/\/\*[\s\S]*?\*\//g, "").match(TOKEN) ?? [];
const fingerprints = (text: string) => {
  const t = tokens(text);
  return new Set(Array.from({ length: Math.max(0, t.length - RUN + 1)
}, (_, i) => t.slice(i, i + RUN).join(" ")));
};
const codeBlocks = (reply: string) =>
[...reply.matchAll(/```[^\n]*\n([\s\S]*?)```/g)].map((m) => m[1]);
const squash = (text: string) => text.replace(/\s+/g, " ").trim();

export function checkHint(reply: string, { reference, starter,
learnerCode = "", output }: FilterContext): FilterResult {
    const known = new Set([...fingerprints(starter),
...fingerprints(learnerCode)]);
    const own = [...fingerprints(reference)].filter((f) =>
!known.has(f));
  const inReply = fingerprints(reply);
  const shared = own.length ? own.filter((f) => inReply.has(f)).length
/ own.length : 0;
  const longestCode = Math.max(0, ...codeBlocks(reply).map((c) =>
c.trim().split("\n").length));
```

```
  const answer = output ? squash(output) : "";
     const givesOutput = answer.length >= MIN_OUTPUT_CHARS &&
squash(reply).includes(answer);
  return { passed: shared < MAX_SHARED && longestCode <= MAX_CODE_LINES
&& !givesOutput, shared, longestCode, givesOutput };
}
```

The password reset transaction (`apps/api/src/modules/m1_auth/repositories/auth.repository.ts`)

```
// The new password, the spent link and the end of every login,
together: a session stolen with the
// old password dies with it. Other unused links go too (two requests
at once can each make one).
// False if the link was just used (a double click: the first one won).
export const resetPassword = (tokenId: string, userId: string,
passwordHash: string) =>
  db.transaction(async (tx) => {
    const [spent] = await tx
      .update(passwordResetTokens)
      .set({ usedAt: new Date() })
                    .where(and(eq(passwordResetTokens.id, tokenId),
isNull(passwordResetTokens.usedAt)))
      .returning({ id: passwordResetTokens.id });
    if (!spent) return false;
                                                                  await
tx.delete(passwordResetTokens).where(and(eq(passwordResetTokens.userId,
userId), isNull(passwordResetTokens.usedAt)));
      await tx.update(users).set({ passwordHash }).where(eq(users.id,
userId));
        await tx.update(refreshTokens).set({ revokedAt: new Date()
}).where(and(eq(refreshTokens.userId,                          userId),
isNull(refreshTokens.revokedAt)));
    return true;
  });
```

Account erasure, step by step (`apps/api/src/modules/m1_auth/services/erasure.service.ts`)

```
export const DELETION_GRACE_DAYS = 7;

const graceStart = () => new Date(Date.now() - DELETION_GRACE_DAYS *
86_400_000);

// DPDP doc §4. Code and the learner's own words always go. With an
opt-in to research or AI training,
// the anonymous numbers (verdicts, scores, timings) stay; without one,
every learning row goes.
export async function eraseAccount(userId: string) {
  const keepNumbers = await repo.hasOptIn(userId);
  // A hash of a password nobody knows: the account can never be logged
in to again.
      if (!(await repo.closeAccount(userId, graceStart(), await
```

```
hashPassword(randomToken()))))) return; // logged in again: cancelled
   const enrollmentIds = (await learnerEnrollments(userId)).map((e) =>
e.id);
  // Rows that point at other modules' rows go first. review_items has
no writer yet: M10 adds its
  // step here when it gets one.
  await eraseCalibration(userId, keepNumbers);
  await eraseMastery(userId, keepNumbers);
  await eraseScaffolding(userId, keepNumbers);
  await erasePlacements(userId, keepNumbers);
  await eraseHints(userId, keepNumbers);
  await erasePractice(userId, keepNumbers);
  await eraseSessions(userId, keepNumbers);
  await eraseRecommendations(enrollmentIds, keepNumbers);
  await eraseEnrollments(userId, keepNumbers);
  await repo.finishErasure(userId);
}

// The hourly job. Every step can run twice, so an account that fails
is simply tried again next hour,
// and doesn't hold up the others.
export async function eraseDueAccounts() {
  for (const { id } of await repo.dueForErasure(graceStart())) {
        await  eraseAccount(id).catch((err)  =>  console.error(`Erasing
account ${id} failed`, err));
  }
}
```

The speed-test check (`apps/api/src/modules/m6_exercises/services/verify-exercise.ts`, ADR-0020)

```
// The brute force must pass the small tests, agree with the reference
on at least one generated test,
// and then time out: proof that the reference is right on generated
data and that the large tests need speed.
async function bruteForceProblem(content: Content, expected: string[],
provider: SandboxProvider) {
      if   (!content.bruteForceSolution)   return   fail("brute_force",
"generated tests need a brute force to check the reference against");
    const  result  =  await  run(content,  content.bruteForceSolution,
provider);
   if  (!result.compile.ok)  return  fail("compile",  "the  brute  force
doesn't compile");
  let agreed = 0;
  for (const [i, testRun] of result.tests.entries()) {
    const verdict = judgeTest(testRun, expected[i], content.limits);
    const { seq, expectedOutput } = content.tests[i];
        if  (expectedOutput  !==  null  &&  verdict  !==  "AC")  return
fail("brute_force", `the brute force gets ${verdict} on test ${seq}`);
    if (expectedOutput === null && verdict === "TLE")
      return agreed ? undefined : fail("brute_force", "the brute force
times out on every generated test, so none checks the reference");
        if  (expectedOutput  ===  null  &&  verdict  !==  "AC")  return
fail("brute_force", `the brute force gets ${verdict} on generated test
```

```
${seq}`);
    if (expectedOutput === null) agreed++;
  }
    return fail("tests_too_weak", "the brute force finishes every generated test in time, so the tests can't tell fast from slow");
}
```