

Software Categories

- ▶ Operating System
 - ▶ controls all machine activities
 - ▶ provides the user interface to the computer
 - ▶ manages resources such as CPU and memory
 - ▶ Examples??
- ▶ Application program

generic term for any other kind of software

examples: word processors, missile control systems, games, software development tools (or Kits)
- ▶ Most operating systems and application programs have a graphical user interface (GUI)

Software Development Kits/Tools

- ▶ SDKs are specialized application programs that allow programmers to write and test programs
- ▶ Experienced programmers generally prefer an Integrated Development Environment (IDE)
- ▶ Examples: Sun's Java SDK (JDK), Dr Java IDE, NetBeans, Eclipse

User Interface Styles

- ▶ Mainly 2 styles for any type of program:
 - ▶ Command Line Interface (CLI)
 - ▶ Graphical User Interface (GUI)
- ▶ As a computer programmer, you must be able to use and/or write programs for both styles of user interface

Command Line Interface (CLI)

- ▶ Computer types a Prompt requesting input
- ▶ User types a Command with parameters
- ▶ An old style of interaction that does not require a lot of computer power, but still in use today in some O/S and applications
- ▶ Not user friendly, but is very efficient when combined with scripting
- ▶ Example: DOS prompt, command & parameter

```
C:\> type file.txt
```

(display the contents of the file)

Graphical User Interface (GUI)

- ▶ Computer displays a combination of text and graphical symbols offering options to the user
- ▶ User manipulates mouse and uses keyboard to select from the offered options (hot keys) or to enter text
- ▶ More common now (computer power is cheap)
- ▶ Considered by most to be user friendly
- ▶ Examples: M/S Windows/Office or MAC O/S

Programming Languages

- ▶ A programming language specifies the words and symbols that we can use to write a program
- ▶ Has a set of rules that dictate how the words and symbols can be put together to form valid program statements
- ▶ Some languages are better for one type of program or one style of user interface than for others
- ▶ Examples??
- ▶ A programming language has both syntax and semantics

Syntax & Semantics

- ▶ The syntax rules of a language define how we can put together symbols, reserved words, and identifiers to make a valid program
- ▶ The semantics of a program statement define what that statement means (its purpose or role in a program)
- ▶ A program that is syntactically correct is not necessarily logically (semantically) correct
- ▶ A program will always do what we tell it to do, not what we meant to tell it to do
- ▶ Example: $5 + 3$

Program Translation

- ▶ A program must be translated into machine language before it can be executed
- ▶ A compiler is a software tool which translates source code into a specific target language. Target language is the machine language for a particular CPU type
- ▶ The Java approach is somewhat different

Java History

- ▶ The Java programming language was created by James Gosling at Sun Microsystems, Inc.
- ▶ Was introduced in 1995 and it's popularity has grown quickly since
- ▶ Is a high-level language

Java Properties

- ▶ Object-oriented
- ▶ Simple
- ▶ Automatic garbage collection
- ▶ Portable
- ▶ Multi-threaded programming
- ▶ Secure
- ▶ Internet aware
- ▶ Distributed
- ▶ Architecture neutral
- ▶ Dynamic

Java Translation

- ▶ The Java compiler translates Java source code into a special representation called bytecode
- ▶ Java bytecode is not the machine language for any traditional CPU
- ▶ Another software tool, called an interpreter, translates bytecode into machine language and executes it. Implies the Java compiler is not tied to any particular machine
- ▶ Java is considered to be architecture-neutral


JDK Editions

- ▶ Java Standard Edition (J2SE): used to develop client-side standalone applications or applets.
- ▶ Java Enterprise Edition (J2EE): used to develop server-side applications such as Java servlets and Java ServerPages.
- ▶ Java Micro Edition (J2ME): used to develop applications for mobile devices such as cell phones.

Java Development Environments

- ▶ There are many programs that support the development of Java software, including:
 - Sun Java Development Kit (JDK)
 - Sun NetBeans
 - IBM Eclipse
 - Borland JBuilder
 - DrJava
- ▶ Though the details of these environments differ, the basic compilation and execution process is essentially the same

Sun Java's JDK



Sun Java's SDK

- ▶ programmer writes source code with files end in ".java" extension
- ▶ java compiler (javac) converts (compiles) source code into "bytecode" (files ending in ".class"). Bytecode is "machine code" for Java Virtual Machine (JVM)
- ▶ Example:


```
C:\> javac HelloWorld.java  
      >> HelloWorld.class  
C:\> java Hello
```

The Java Platform

- ▶ A platform: software or hardware environment in which a program runs.
- ▶ Java platform components:
 - Java Virtual Machine (JVM)
 - Java Application Programming Interface (API)
- ▶ Java API
 - a collection of ready-made software components that provide many useful capabilities including:
 - ▶ graphics
 - ▶ networking
 - ▶ database
 - ▶ input/output

Grouped into libraries of related classes and interfaces. These libraries are called packages.

Java Platform



Java Program Structure

In the Java programming language:

- ▶ A program is made up of one or more classes
- ▶ A class contains one or more methods
- ▶ A method contains program statements. A Java application always contains a method called main

These terms will be explored in detail throughout the course

Java Program Structure

```
class Welcome {  
    private static String my_name = "Arinda";  
  
    public static void main (String [] args){  
        System.out.print("Welcome " + my_name);  
    }  
}
```

The main Method

- ▶ Every program must contain a main method
- ▶ Is similar to the main function in C
- ▶ Its the entry point for your application and will subsequently invoke all the other methods required by your program.
- ▶ Accepts a single argument: an array of elements of type String
`public static void main(String [] args)`
- ▶ This array is the mechanism through which the runtime system passes information to your application. `java MyProgram arg1 arg2`
- ▶ Each string in the array is called a *command-line argument*. Command-line arguments let users affect the operation of the application without recompiling it. For example, a sorting program might allow the user to specify that the data be sorted in descending order with this command-line argument:
`-descending`

Command Line Example

```
public class Echo {  
    public static void main (String[] args) {  
        for (String s: args) {  
            System.out.println(s);  
        }  
    }  
}
```

Language Basics

- ▶ Variables
- ▶ Operators
- ▶ Expressions, Statements, and Blocks
- ▶ Control Flow Statements