

Module 1 Unit 2: Optical Fibres




Dr. Suren Patwardhan


Contents

0. Global fibre optic network
1. Structure of an optical fibre
2. Principle of working
3. Numerical aperture
4. Types of fibres
5. Modes of propagation
6. Attenuation and Dispersion
7. Fibre parameters

Global Fibre Optic Network




Structure of an Optical Fibre



- Main two parts: core and cladding
- Core has slightly higher refractive index
- Light is fed into the core region

Principle of Working – Total Internal Reflection



Total Internal Reflection and Acceptance Angle

But for TIR, $i \geq i_0$


$\Rightarrow \theta$ should have some “ceiling” value.

This value is called “acceptance angle”


condition for TIR:

$$\theta \leq \theta_c$$

At $\theta = \theta_c$, $i = i_0$ and $r = 90^\circ$




Optical Fibre – Cross Sections and Acceptance Cone



Sine of acceptance angle is called "Numerical Aperture" of optical fibre: $NA = \sin \theta_c$


Numerical Aperture of an Optical Fibre





$$NA = \sin \theta_c = \sqrt{n_1^2 - n_2^2}$$

$$NA \approx n_1 \sqrt{2\Delta}$$


Types of Fibres




Refractive Index Profile





Step Index






Graded Index



Ray Propagation in Different Types of Fibres




Single mode (Step index)



Mode of Propagation - Concept

- Defined as “allowed” directions for light entering optical fibre
- Fibre does not guide all light even though it is launched within acceptance cone
- Due to restricted space, light undergoes diffraction
- Light waves are in phase only along certain paths
- These paths are the “allowed” directions and called “modes of propagation”



V-number and Number of Modes

- An optical fibre is characterized by another important parameter called as the V-number or normalized frequency. It is given by,

$$V = \frac{2\pi a}{\lambda} \times \text{NA}$$

a: radius of core, λ : wavelength of light, NA: numerical aperture

- The maximum number of modes supported by the fibre is given by,

$$\begin{aligned} N_m &= \frac{V^2}{2}; & \text{SI} \\ &= \frac{V^2}{4}; & \text{GI} \end{aligned}$$

- From electromagnetic theory, it is deduced that

$$V < 2.405; \quad \text{SM}$$

Various Modes of Propagation





Figure of Merits for an Optical Fibres



Causes of Attenuation in Fibres

Absorption

- By impurities in fibre (Na, Fe, OH⁻, Cr)
- By fibre itself (intrinsic absorption)

Scattering

- Due to non-uniform density of glass (Rayleigh scattering)

Geometric

- Bending of fibre into tighter loops
- Micro-kinks inside fibre


Can be reduced
using a highly-
controlled
manufacturing
process

Causes of Dispersion in Fibres

Chromatic Dispersion

- Occurs if light of broad spectrum is used


Can be reduced using a laser source



Intermodal Dispersion

- Occurs due to loss synchronization between light waves


Can be reduced using GI or SM fibre



Waveguide Dispersion


- Occurs due to induced electric field in cladding

Can be reduced by increasing core diameter



Wavelength of the Internet

Attenuation coefficient: $\alpha = \frac{1}{L} 10 \log \left(\frac{P_{\text{in}}}{P_{\text{out}}} \right) \text{ dB/km}$



Pulse Dispersion and Bit Rate

Intermodal dispersion for SI: $\tau_i = \frac{n_1 L}{c} \Delta$


Intermodal dispersion for GI: $= \frac{n_2 L}{2c} \Delta^2$

Total dispersion (intermodal + material): $\tau = \sqrt{\tau_i^2 + \tau_m^2 + \tau_w^2}$

Usually, τ_w is small compared to other two and ignored

Bit Rate: $B \approx \frac{0.7}{\tau}$ usually expressed in “MBPS”

Fibre Optic Communication System



Fabrication of Optical Fibres



References

- Optics – Ghatak, 6th edition 2017, Mc-Graw Hill India
- Wikipedia (images on slide # 1, 3, 5, 11, 13, 18 and 20)