Visvesvaraya Technological University

"Jnana Sangama" Belagavi-590018

Mini Project Report

On

"Dog Breed Identification using CNN"

Submitted By-

NIDHI M	**1VE23CD032**
POORNIMA	**1VE23CD037**
VARSHINI V	**1VE23CD063**
TANISHA	**1VE24CD401**

Under The Guidance of

Dr. Santosh Kumar S

Head of the department

Dept. of CSE (Data Science), SVCE

SVCE | SRI VENKATESHWARA COLLEGE OF ENGINEERING

ESTD. 2001. AUTONOMOUS INSTITUTE

Department of CSE (Data Science)

Sri Venkateshwara College of Engineering Bengaluru- 562157

2025-26

ABSTRACT

Dog breed identification is an important and challenging task, especially in environments such as veterinary clinics, animal shelters, and rescue centers where accurate and timely classification is essential. Manual identification of dog breeds based on visual characteristics can be difficult, subjective, and highly dependent on expert knowledge—particularly when dealing with mixed breeds or breeds with similar physical features. This reliance on human interpretation makes the process time-consuming, prone to error, and inconsistent across individuals. These challenges highlight the need for an automated, accurate, and scalable system that can assist professionals and pet owners in reliably identifying dog breeds from images.

To address this challenge, this project develops an automated Dog Breed Identification system using Convolutional Neural Networks (CNNs). The model is trained on a labelled dataset of dog images representing multiple breeds, where essential preprocessing steps such as image resizing, normalization, augmentation, and channel scaling are applied to ensure consistency and enhance robustness. The CNN architecture is designed to learn both low-level and high-level visual patterns—such as fur texture, facial features, ear shape, and body structure—enabling efficient extraction of features that distinguish one dog breed from another. Model performance is evaluated using accuracy, precision, recall, F1-score, and confusion matrix analysis to assess classification effectiveness.

Beyond model development, the project integrates the trained CNN into a user-friendly web application built using the Flask framework. This interface allows users—including pet owners, veterinarians, rescue workers, and breeders—to upload dog images and receive instant breed predictions accompanied by confidence scores and dynamic visualization. The system enables faster and more reliable identification, assisting non-experts and supporting professionals with an AI-assisted second opinion. Visual outputs such as training curves and prediction charts further enhance interpretability and improve user understanding.

This work demonstrates the potential of AI in transforming image-based animal classification and breed recognition.Ultimately, the project highlights how AI-driven tools can assist veterinarians, animal shelters, and pet owners, improve decision-making efficiency, and contribute to better animal care, management, and welfare outcomes.

TABLE OF CONTENTS

Sl No	Contents	Page no
1	Introduction	**1**
1.1	Motivation	**2-3**
1.2	Problem Statement	**4**
1.3	Objectives of the proposed work	**5**
2	Literature survey	**6-8**
3	Methodology	**9-10**
3.1	Block diagram	**11**
3.2	Flowchart/Algorithms	**17-25**
4	Components required- Software	**26-31**
5	Results	**32-44**
6	Conclusion	**45**
7	Bibliography/References	**46**
8	Mapping of Project Outcomes with Program Outcomes	**47**

SVCE | SRI VENKATESHWARA COLLEGE OF ENGINEERING

ESTD. 2001. AUTONOMOUS INSTITUTE

DEPARTMENT OF CSE (DATA SCIENCE)

VISION & MISSION OF THE DEPARTMENT

To be a school of Excellence in Computing for Holistic Education and Research.

M-1: Accomplish academic achievement in CSE-Data Science and Engineering through student-centered creative teaching-learning qualified faculty members, assessment, and effective usage of ICT.

M-2: Establish a Center of Excellence in various verticals of CSE-Data science and engineering to encourage collaborative research and Industry-institute interaction.

M-3: Transform engineering students into socially responsible, ethical, technical components, and value-added professionals or entrepreneurs through holistic education.

SVCE | SRI VENKATESHWARA COLLEGE OF ENGINEERING

ESTD. 2001. AUTONOMOUS INSTITUTE

DEPARTMENT OF CSE (DATA SCIENCE)

PROGRAM EDUCATIONAL OBJECTIVES (PEOs) AND PROGRAM SPECIFIC OUTCOMES (PSOs) OF THE DEPARTMENT

PROGRAM EDUCATIONAL OBJECTIVES

PEO-1: Knowledge CSE- Data Science and Engineering graduates will have professional technical career in inter disciplinary domains providing innovative and sustainable solutions using modern tools.

PEO-2: Skills CSE- Data Science and Engineering graduates will have effective communication, leadership, team building, problem solving, decision making and creative skills.

PEO-3: Attitude CSE- Data Science and Engineering graduates will practice ethical responsibilities towards their peers, employers, and society.

PROGRAMME SPECIFIC OUTCOMES (PSOs)

PSO-1: Ability to adopt quickly for any domain, interact with diverse group of individuals and be an entrepreneur in a societal and global setting.

PSO-2: Ability to visualize the operations of existing and future software Applications.

SVCE | SRI VENKATESHWARA COLLEGE OF ENGINEERING

ESTD. 2001. AUTONOMOUS INSTITUTE

DEPARTMENT OF CSE (DATA SCIENCE)

PROGRAM OUTCOMES

Engineering Graduates will be able to:

1. **Engineering knowledge:** Apply the knowledge of mathematics, science, engineering fundamentals, and an engineering specialization to the solution of complex engineering problems.
2. **Problem analysis:** Identify, formulate, review research literature, and analyze complex engineering problems reaching substantiated conclusions using first principles of mathematics, natural sciences, and engineering sciences.
3. **Design/development of solutions:** Design solutions for complex engineering problems and design system components or processes that meet the specified needs with appropriate consideration for the public health and safety, and the cultural, societal, and environmental considerations.
4. **Conduct investigations of complex problems:** Use research-based knowledge and research methods including design of experiments, analysis and interpretation of data, and synthesis of the information to provide valid conclusions.
5. **Modern tool usage:** Create, select, and apply appropriate techniques, resources, and modern engineering and IT tools including prediction and modeling to complex engineering activities with an understanding of the limitations.
6. **The engineer and society:** Apply reasoning informed by the contextual knowledge to assess societal, health, safety, legal and cultural issues and the consequent responsibilities relevant to the professional engineering practice

   .

7. **Environment and sustainability:** Understand the impact of the professional engineering solutions in societal and environmental contexts, and demonstrate the knowledge of, and need for sustainable development.
8. **Ethics:** Apply ethical principles and commit to professional ethics and responsibilities and norms of the engineering practice.
9. **Individual and team work:** Function effectively as an individual, and as a member or leader in diverse teams, and in multidisciplinary settings.
10. **Communication:** Communicate effectively on complex engineering activities with the engineering community and with society at large, such as, being able to comprehend and write effective reports and design documentation, make effective presentations, and give and receive clear instructions.
11. **Project management and finance:** Demonstrate knowledge and understanding of the engineering and management principles and apply these to one's own work, as a member and leader in a team, to manage projects and in multidisciplinary environments.
12. **Life-long learning:** Recognize the need for and have the preparation and ability to engage in independent and life-long learning in the broadest context of technological change.

Chapter 1

INTRODUCTION

Dog breed identification is an important and challenging task in the fields of veterinary care, animal welfare, and pet management. With hundreds of dog breeds worldwide—many of which share similar physical attributes—accurately identifying a breed can be difficult for untrained individuals and even for professionals in certain situations. Breed identification plays a crucial role in understanding a dog's behavior, health risks, genetic traits, and nutritional needs. In animal shelters, rescue organizations, and veterinary clinics, correct breed classification is essential for providing appropriate treatment, managing adoption processes, and ensuring proper care. However, manual identification is often subjective, inconsistent, and prone to errors due to visual similarities between breeds and the presence of mixed-breed dogs.

Traditional methods of breed identification rely heavily on expert evaluation of physical characteristics such as coat texture, body structure, facial features, and size. This process demands experience and time, and it becomes increasingly challenging when dealing with puppies, mixed breeds, or low-quality images. In many regions, especially in crowded animal shelters or remote areas, experts may not be readily available, leading to misclassification and improper handling of animals. These limitations highlight the growing need for an automated, accurate, and scalable system capable of assisting users in identifying dog breeds quickly and reliably. Recent advancements in artificial intelligence (AI) and deep learning particularly Convolutional Neural Networks (CNNs)—have transformed image recognition tasks across various domains. CNNs excel at learning complex visual features and patterns directly from images, making them highly effective for animal classification tasks. By automatically extracting distinguishing characteristics such as ear shape, muzzle length, fur patterns, and overall body structure, CNN models can deliver highly accurate and consistent predictions.

This project aims to develop an efficient, accurate, and user-friendly dog breed identification system using CNN-based deep learning techniques. The system analyses uploaded dog images, identifies relevant visual features, and predicts the most likely breed along with confidence scores. Integrated into a web-based interface, the model allows pet owners, veterinarians, breeders, and shelter workers to easily upload an image and receive instant AI-powered insights. By bridging technology and animal care, this project provides a valuable tool that enhances breed recognition, supports informed decision-making, and contributes to improved management and welfare of dogs across different environments.

1.1 MOTIVATION

Dog breed identification has become an increasingly important task across various domains, including veterinary care, animal welfare, wildlife management, pet services, and rescue operations. With hundreds of recognized dog breeds worldwide—and countless mixed-breed variations—accurate identification plays a crucial role in understanding an animal's behavior, genetic predispositions, health risks, and required care. In many parts of the world, especially in developing countries, stray dog populations are high, and animal shelters face overwhelming intake numbers. Workers in these environments often lack formal training in breed recognition, leading to inconsistent classification and difficulties in providing appropriate medical treatment or adoption counseling. These challenges create a growing need for reliable, accessible, and efficient systems capable of supporting accurate breed identification regardless of the user's expertise.

Early identification of a dog's breed is essential for diagnosing breed-related diseases, determining temperament, planning nutrition, and ensuring correct veterinary care. However, traditional breed identification methods rely heavily on subjective visual assessment of characteristics such as coat texture, ear structure, body proportions, and facial features. This approach is time-consuming and prone to misjudgment—particularly in cases involving mixed breeds or breeds with very similar appearances. Even experienced veterinarians and kennel professionals may struggle to differentiate between visually overlapping breeds such as Siberian Huskies and Alaskan Malamutes, or various terrier and hound categories. The lack of standardized, objective criteria makes manual breed classification inconsistent and often inaccurate, highlighting the need for automated, expert-level support tools.

In many regions, animal shelters, rescue teams, and community veterinary programs operate with minimal staff and limited access to professional breed evaluators. As a result, dogs may be mislabeled, leading to incorrect medical histories, inappropriate treatments, and challenges in adoption matching. In addition, shelters often receive poor-quality images or incomplete information, further complicating reliable classification. With the increasing number of animals requiring assessment—especially after natural disasters, urban rescue operations, or mass intake events—the workload on veterinary professionals and shelter workers becomes overwhelming. These systemic issues emphasize the importance of integrating intelligent technological solutions to support faster, more accurate, and more consistent breed identification.

The rapid advancements in artificial intelligence (AI) and computer vision have opened up powerful opportunities for automating image-based classification tasks. Convolutional Neural Networks (CNNs) have shown exceptional success in extracting subtle visual patterns and distinguishing between complex image categories. In the context of dog breed identification, CNNs can automatically learn intricate features such as fur patterns, ear shapes, eye positioning, snout proportions, and body structure—attributes that may be challenging for humans to notice consistently. AI-driven breed identification systems provide objective, high-precision predictions and eliminate much of the subjectivity associated with human evaluation. Their ability to process images quickly and consistently makes them highly valuable for real-time decision-making in both clinical and field environments.

Furthermore, integrating AI into breed identification workflows can significantly reduce cognitive load and workload pressures on veterinarians and shelter personnel. Professionals often handle a large number of animals daily, and rapid classification is essential for timely medical treatment, vaccination decisions, and adoption placement. Automated systems serve as a reliable second opinion, helping users confirm breed information and enabling professionals to focus on clinical care rather than manual classification tasks. This leads to more accurate records, better treatment planning, and improved overall animal welfare. Another powerful motivation for developing an AI-based dog breed identification system is its potential to bridge knowledge gaps between urban and rural regions. While urban centers may have access to specialists such as veterinarians, trainers, and breed consultants, rural and underserved communities often rely on general practitioners with limited expertise in breed recognition. A web-based, automated identification tool can be deployed widely in rural clinics, animal husbandry centers community rescue programs, and mobile veterinary units. Such accessibility ensures that accurate breed identification becomes available to all, regardless of geographic or economic constraints.AI-powered breed identification tools can also support research, breed documentation, population studies, and wildlife monitoring. The combination of scalability, accuracy, and accessibility positions AI-based classification systems as a transformative resource for animal welfare and management.

Overall, the motivation behind this project is to develop a robust, intelligent, and user-friendly dog breed identification system that leverages deep learning to enhance decision-making and streamline workflows. By delivering fast, accurate, and consistent breed predictions from images, the system aims to assist veterinarians, shelter workers, rescue teams, and pet owners in achieving better outcomes for animals. This project reflects a broader vision of integrating AI into animal care to create reliable, efficient, and widely accessible technological solutions that improve the lives of dogs and the communities that care for them.

1.2 PROBLEM STATEMENT

Dog breed identification is challenging because many breeds share similar physical features and images can vary in quality, angle, and lighting. This project aims to develop an automated deep learning-based system that takes a dog's image as input and outputs the exact dog breed name. Using a Convolutional Neural Network (CNN) trained on a labeled dataset, the system will learn to recognize unique features like ear shape, coat texture, and face structure. The goal is to provide a fast, accurate, and reliable solution that can assist veterinarians, shelters, and pet owners in instantly identifying a dog's breed.

1.3 OBJECTIVES

The objective of this mini-project Dog Breed Identification using Convolutional Neural Networks (CNN) is to design and develop an AI-based recognition system capable of accurately classifying dog images into their respective breeds. The project aims to utilize deep learning and web technologies to enable rapid, reliable, and efficient breed identification, supporting veterinarians, animal shelters, pet owners, and rescue organizations in making informed decisions.

1. To analyze and understand visual characteristics, morphological features, and breed-specific patterns in dog images for effective model development.
2. To develop and train an efficient Convolutional Neural Network (CNN) model capable of accurately distinguishing between multiple dog breeds.
3. To perform image preprocessing and enhancement techniques such as resizing, normalization, and data augmentation to improve model robustness and accuracy.
4. To explore and utilize suitable dog image datasets for training and validation, ensuring diversity, quality, and reliability for real-world breed identification applications.
5. To design and deploy a user-friendly, web-based interface using Flask, enabling real-time dog image upload, breed prediction, and visualization of results.
6. To evaluate the performance of the model using key metrics such as accuracy, precision, recall and confusion matrix to ensure reliable breed classification.
7. To enhance interpretability of model predictions through visualization techniques such as dynamic bar charts and optional feature maps for improved understanding.

Chapter 2

LITERATURE SURVEY

Dog breed identification using Artificial Intelligence (AI) and Machine Learning (ML) has gained significant attention in recent years due to the growing demand for automated, accurate, and scalable solutions in veterinary care, animal welfare, pet management, and rescue operations. With hundreds of dog breeds recognized globally and countless mixed-breed variations, manual breed classification often becomes a challenging and subjective process. Breed identification is crucial for understanding genetic characteristics, behavioral patterns, health risks, and dietary requirements. In many regions—especially in developing countries or rural areas—trained experts such as veterinarians, breeders, or animal behaviorists may not be readily available. This gap emphasizes the need for AI-driven systems capable of delivering fast, reliable, and consistent breed predictions using image analysis techniques. The increasing number of stray dogs and overcrowded shelters further motivates research into automated breed recognition to support adoption processes and improve animal care.

Traditional breed identification primarily relies on visual characteristics such as coat color, body structure, snout shape, ear type, and fur patterns. However, manual assessment is prone to errors due to overlapping features among breeds and the presence of mixed-breed dogs, which complicates accurate classification. Human evaluators may struggle to distinguish between breeds with subtle differences, such as Alaskan Malamutes and Siberian Huskies or different types of terriers and hounds. These limitations create the need for computerized systems that can extract finer details and perform objective classification based on large datasets of labeled dog images. Early computational methods attempted to use handcrafted features like edge detection, texture descriptors, and SIFT/HOG features, but these traditional approaches lacked robustness, struggled with variations in lighting and pose, and failed to generalize across diverse datasets.

With advancements in deep learning, Convolutional Neural Networks (CNNs) have revolutionized image classification tasks, including dog breed identification. CNNs offer end-to-end automated learning, eliminating the need for manual feature extraction by directly learning complex patterns from raw images. This allows them to identify breed-specific attributes such as facial structure, fur texture, eye spacing, coloration, and body proportions. Research on dog breed classification has explored a variety of CNN architectures, ranging from simple models to large-scale pre-trained networks. Architectures such as VGG16 and VGG19 have been widely used due to their strong baseline performance and feature

extraction capabilities. ResNet models introduced skip connections that facilitated deeper learning while mitigating vanishing gradient issues, improving accuracy in identifying closely related breeds. DenseNet architectures further enhanced performance by allowing feature reuse across layers, resulting in more efficient learning and better generalization.

Hybrid and ensemble learning approaches have also gained attention. For example, Khosla et al. demonstrated that ensemble models combining VGG, Inception, and ResNet networks improved classification robustness for fine-grained breed recognition. Rodrigues et al. used transfer learning from ImageNet-trained architectures, showing significant accuracy improvements even with limited training data. Studies incorporating SVM and Random Forest classifiers on top of CNN-generated features have shown promising results, particularly in handling mixed breeds. Interpretability has become an important research direction as well; methods such as Grad-CAM, CAM, and attention layers visually highlight the regions of an image the model uses for prediction, helping users understand why a particular breed was identified.

Recent work has explored lightweight and real-time dog breed identification models suitable for deployment on mobile devices, embedded systems, and browser-based applications. MobileNet, EfficientNet, and ShuffleNet architectures have been used to create compact models with high accuracy and low computational cost. These models enable applications in animal shelters, veterinary clinics, and rescue teams where access to high-performance hardware may be limited. In addition, YOLO-based object detection frameworks have been employed to detect dog faces or full-body regions before classification, improving accuracy in images with complex backgrounds.

Dataset availability has played a major role in advancing research. Prominent datasets such as the Stanford Dogs Dataset, Oxford-IIIT Pet Dataset, and Kaggle Dog Breed Identification dataset provide thousands of labelled images spanning numerous dog breeds. These datasets cover a wide range of poses, lighting conditions, and environmental variations, enabling models to learn robust breed-specific patterns. However, challenges such as class imbalance, mixed-breed ambiguity, occlusions, and variations in image quality remain significant obstacles. Researchers have proposed various solutions including data augmentation, synthetic data generation using GANs, multi-view training, and domain adaptation to improve model generalization across diverse settings. Another rapidly growing research direction focuses on deploying dog breed identification systems into real- world workflows. Cloud-based classification tools, mobile applications, and web-based platforms built using frameworks like Flask, TensorFlow.js, and FastAPI allow users to upload dog images and receive near-instant predictions.

Such systems are particularly beneficial for animal shelters and adoption agencies, enabling them to classify large numbers of animals quickly and maintain accurate records. Integrating these models into veterinary clinics can support diagnosis of breed-related diseases, assist in treatment planning, and improve client communication. Several studies have demonstrated that AI-assisted breed identification can reduce workload, improve decision-making, and enhance the overall efficiency of animal welfare operations.

Despite considerable progress, several challenges remain in large-scale adoption of AI-based dog breed identification systems. Differences in camera quality, lighting conditions, dog pose, breed variability, and image backgrounds can influence prediction accuracy. Mixed-breed dogs remain particularly challenging due to their genetic diversity and overlapping traits. Ensuring fairness, avoiding biases resulting from imbalanced datasets, and providing transparent predictions are key considerations for real-world deployment. Additionally, models must be optimized for speed and resource efficiency to ensure usability in field conditions and mobile environments.

In summary, the literature reflects a rapidly growing interest in leveraging AI and deep learning for dog breed identification. Research consistently shows that CNN-based models outperform traditional feature-based methods by offering superior accuracy, faster processing, and high adaptability to diverse image conditions. With continued advancements in transfer learning, ensemble modeling, real-time deployment, and interpretability techniques, AI-driven dog breed identification systems have the potential to significantly improve veterinary workflows, enhance animal welfare, and support better decision-making across various animal care domains.

Chapter 3

METHODOLOGY

The methodology for the Dog Breed Identification using CNN project consists of several structured phases designed to build a reliable, efficient, and accurate classification system capable of recognizing various dog breeds from images. The process begins with the collection of a labeled dataset of dog images, categorized by breed. Public datasets such as the Kaggle Dog Breed Identification Dataset or the Stanford Dogs Dataset serve as primary sources. Before model development, the images undergo preprocessing steps such as resizing, RGB normalization, augmentation, and reshaping to standardize the input data and enhance the model's ability to generalize across diverse real-world conditions.

Following preprocessing, the next major stage is feature extraction through deep learning. Unlike traditional approaches that rely on handcrafted features, this system employs Convolutional Neural Networks (CNNs) to automatically learn meaningful patterns from dog images. The architecture consists of convolution layers for extracting spatial and texture-based features, max-pooling layers for reducing dimensionality, flattening for converting feature maps into vectors, and dense layers for final multi-class classification. Techniques such as dropout, batch normalization, and early stopping are implemented to prevent overfitting and improve the model's robustness when dealing with variations in pose, lighting, and background. The model is trained using the categorical cross-entropy loss function and optimized using the Adam optimizer to ensure efficient and stable convergence during training.

Model training is followed by rigorous evaluation to determine the performance and reliability of the system. Metrics such as accuracy, precision, recall, F1-score, and confusion matrix are calculated to assess how well the model differentiates between multiple dog breeds. Visualization tools such as Matplotlib are used to plot training and validation accuracy/loss curves, enabling developers to monitor the learning process and identify issues such as overfitting, underfitting, or class imbalance. Techniques like Grad-CAM may also be used to provide interpretability by highlighting image regions that influenced the model's prediction.

The final phase involves deploying the trained model into a user-friendly, web-based interface developed using Flask. This interface enables users to upload an image of a dog and receive the predicted breed along with a confidence score. The deployment pipeline integrates both front-end and back-end components to ensure smooth image handling, model loading, inference execution, and result presentation. This allows the system to be used in real-time by pet owners, veterinarians, and animal

shelters.

This structured methodology supports the creation of a robust, scalable, and accessible dog breed identification system. By combining deep learning, efficient preprocessing, thorough evaluation, and an intuitive web interface, the project aims to provide a practical solution that enhances breed recognition and contributes to improved decision-making in the domain of animal care and pet identification.

3.1 BLOCK DIAGRAM

The below figure shows the procedure of Identification of breeds.




Figure 3.1.1: Dog Breed Detection Procedure

The methodology for developing an AI-driven dog breed identification system involves several structured stages, including dataset acquisition, preprocessing, model development using EfficientNet-based CNN architecture, training, performance evaluation, and deployment. This pipeline leverages deep learning techniques to analyze dog images, extract significant visual features, and accurately classify them into their respective breeds. The following sections provide a detailed explanation of each step:

1. Data Collection

A large and diverse dataset of dog images is collected from publicly available sources such as:

- Kaggle Dog Breed Dataset
- Stanford Dogs Dataset

Each image is labeled with its corresponding dog breed. The dataset is examined to ensure a balanced representation of all breeds.

The images used for this project are collected from multiple online public sources and dog image

repositories such as the Kaggle Dog Breed Dataset and the Stanford Dogs Dataset. This diverse dataset captures natural variations in:

• Dog characteristics — size, fur texture, color patterns
• Age differences — puppies, adults, and senior dogs
• Camera types and resolutions
• Lighting, brightness, and exposure variations
• Dog pose variations — sitting, running, side-view, front-view
• Background differences — indoor, outdoor, cluttered surroundings

Important Visual Features in Dog Breed Images

Each dog image contains unique breed-specific characteristics that are crucial for neural network-based classification, including:

• Fur Texture & Pattern — curly, silky, short-haired, spotted, striped
• Ear Shape & Position — floppy, erect, triangular, long hanging
• Snout Structure — long, flat, short, pointed
• Eye Shape & Facial Markings — masked patterns, wrinkles, distinct colors
• Body Shape & Proportion — muscular, slim, compact, long-legged
• Tail Type — curled, straight, fluffy, docked

These visual patterns help the deep learning model learn fine-grained differences between dog breeds, even among visually similar groups like Terriers, Spitz, and Spaniel breeds.

2. Data Preprocessing

To enhance model performance and uniformity:

- Images are resized to match EfficientNet input dimensions (e.g., 224×224).
- Normalization is applied to scale pixel values between 0 and 1.
- Augmentation techniques like rotation, flipping, zooming, and shifting are used to increase dataset variability and reduce overfitting.

3. Data Cleaning

Dog images collected from public datasets often contain visual inconsistencies that can negatively impact model training. These issues may include:

- Unwanted background noise such as furniture, grass, humans, or other animals
- Variations in lighting and shadows causing uneven brightness
- Differences in camera resolution and quality across image sources
- Text overlays, watermarks, or copyright labels printed on the image
- Unnecessary borders or black margins around cropped or poorly formatted images
- Blurry or out-of-focus images, reducing feature clarity
- Random clutter or objects near the dog leading to feature misinterpretation.

4. Variations in Exposure or Contrast

Dog images in the dataset often show significant variations in lighting, exposure, and contrast due to different backgrounds and camera settings. These inconsistencies can reduce the model's ability to focus on true breed-specific features.

To address these issues, the following preprocessing steps are applied:

- Noise Reduction

Smoothing or denoising filters may be used to remove grainy textures, improving clarity of fur and facial structure.

- Cropping / Center Alignment

Unnecessary background regions are trimmed, ensuring the dog remains the primary focus of the model.

- RGB Standardization

Since dog images are naturally colored, channels are standardized to maintain consistent input format for EfficientNet.

- Resizing

All images are resized to a fixed resolution (typically 224×224 or 300×300) to match EfficientNet's input requirements and reduce computational load.

- Normalization

Pixel values are scaled to a range of 0–1 (by dividing by 255), improving gradient stability and faster model convergence.

• Contrast & Brightness Adjustment (Optional)

Enhancements like histogram equalization may be applied to highlight important features like coat texture, facial marks, and ear shape.

5. Feature Scaling

Even after data cleaning and preprocessing, dog images may still show variations in pixel intensities due to:

• Different camera resolutions

• Lighting and exposure conditions

• Dog movement or pose variations

• Background shadows and brightness differences

Feature scaling ensures that pixel values in all images are standardized uniformly, preventing the model from giving unnecessary importance to highly bright or dark areas.

Common feature scaling techniques include:

• **Min-Max Scaling:**

Normalizes pixel values into the **[0–1]** range, helping EfficientNet learn patterns faster.

• Standardization:

Centers pixel values around zero mean with unit variance to ensure consistent feature representation.

• Intensity Normalization:

Balancing brightness and contrast across the dataset so the model focuses on breed-specific features (fur, face structure, ear shape) instead of lighting inconsistencies.

Feature scaling greatly stabilizes training**,** speeds up convergence, and enhances prediction accuracy.

• Data Splitting

To ensure unbiased performance evaluation, the dataset is split into subsets:

• Training Set (≈ 70–80%)

Used to train the EfficientNet model by exposing it to thousands of labeled dog breed images. The model learns various breed characteristics during this phase.

• Validation Set (≈ 10–15%)

Used during training to tune hyperparameters and prevent overfitting by monitoring model performance on unseen data.

• Test Set (≈ 10–15%)

Used only after training is complete to measure final performance and generalization ability on

completely new dog images.

Testing Set (≈15–20%)

This set consists of completely unseen dog images and is used only after training to evaluate the model's real-world performance. It helps measure how accurately the EfficientNet model can identify dog breeds it has never encountered before.

• **Validation Set (≈ 10–15% of the dataset)**

This subset is used during training to:


• Fine-tune model hyperparameters.

• Monitor accuracy and loss behavior.

• Prevent overfitting by ensuring the model performs well on unseen data.

• Assist in selecting the best model checkpoint.

Below is the graph of linear regression



1. MODEL SELECTION

To develop a highly accurate dog breed identification system using dog images, several advanced deep learning architectures are evaluated. Convolutional Neural Networks (CNNs) are prioritized because they are exceptionally capable of learning:

• Spatial features such as body shape and structure

• Textural patterns like fur type and markings

• Fine-grained visual differences between similar breeds

CNNs automatically extract relevant features from raw images without requiring manual feature engineering.

1.1 Convolution Operation (Feature Extraction)

Given an input dog image matrix 'I' and a learnable kernel/filter matrix 'K', each output pixel of the feature map is computed using the 2D convolution formula:

$$O(i,j) = \sum_{m=0}^{M-1} \sum_{n=0}^{N-1} I(i+m, j+n) \cdot K(m,n)$$

Where:

- $I \rightarrow$ Input image pixel region
- $K \rightarrow$ Filter detecting specific visual features
- $O(i,j) \rightarrow$ Output feature map response at location *(i,j)*

This mathematical operation slides the filter across the image, enabling the CNN to learn meaningful spatial patterns.

Feature Learning in Dog Breed Identification

Through convolution, EfficientNet learns to detect:

• Fur texture and patterns — curly, spotted, striped

• Facial structure — snout shape, eye spacing, mask markings

• Ear shape and position — floppy, upright, triangular

• Body proportions — muscularity, chest width, leg height

• Breed-specific contours — tail type, head shape, coat flow

1.2 ReLU Activation Function

$$(x) = max\ (0, x)$$


The ReLU (Rectified Linear Unit) activation function introduces non-linearity into the CNN, allowing the model to learn complex breed-specific visual patterns. Without non-linearity, the network would behave like a simple linear classifier and fail to capture intricate image details.

1.3 Max Pooling

$$Pmax = max\ (x1, x2, \ldots, xk)$$

This reduces the image dimension and keeps the strongest features.

3.2 FLOW CHART:



2 MODEL TRAINING

Training the CNN involves forward propagation, loss estimation, and backpropagation.

2.1 Forward Propagation

Each layer transforms the input using:

$$^{(l)} = f(W^{(l)}a^{(l-1)} + b^{(l)})$$

Where:

2.1.1 $W^{(l)}$= Learnable weight parameters for layer l

2.1.2 $b^{(l)}$= Bias added to enhance learning flexibility

2.1.3 f= Activation function introducing non-linearity

2.1.4 $a^{(l)}$= Output feature map of the current layer from input features a^(1-1)

2.2 Loss Function – Binary Cross-Entropy

$$\mathcal{L} = -[y\log(y\hat{}) + (1-y)\log(1-y\hat{})]$$

This evaluates how far predictions are from true labels.

2.3 Gradient Descent Weight Update

$$w_{t+1} = w_t - \alpha\frac{\partial\mathcal{L}}{\partial w_t}$$

$$b_{t+1} = b_t - \alpha\frac{\partial\mathcal{L}}{\partial b_t}$$

Where α= learning rate.

2.4 Adam Optimizer

$$m_t = \beta_1 m_{t-1} + (1-\beta_1)$$

$$v_t = \beta_2 v_{t-1} + (1-\beta_2)^2{}_t$$

$$w_{t+1} = w_t - \frac{\alpha m_t}{\sqrt{v_t} + \epsilon}$$

Adam improves learning speed and stability.

2.5 Data Augmentation Formulas

Rotation:

$$x' = x\cos\ \theta - y\sin\ \theta$$
$$y' = x\sin\ \theta + y\cos\ \theta$$

Scaling:

$$x' = sx, y' = sy$$

Translation:

$$x' = x + t_x, y' = y + t_y$$

3 MODEL EVALUATION

Multiple statistical measures assess model performance.

3.1 Confusion Matrix Components

Let:

3.1.1 TP = True Positive

3.1.2 TN = True Negative

3.1.3 FP = False Positive

3.1.4 FN = False Negative

3.2 Accuracy

$$Accuracy = \frac{TP + TN}{TP + TN + FP + FN}$$

3.3 Precision

$$Precision = \frac{TP}{TP + FP}$$

3.4 Recall (Sensitivity)

$$Recall = \frac{TP}{TP + FN}$$

3.5 F1-Score

$$F1 = 2 \cdot \frac{Precision \cdot Recall}{Precision + Recall}$$

3.6 Specificity

$$Specificity = \frac{TN}{TN + FP}$$

3.7 ROC Curve Components

$$TPR = \frac{TP}{TP + FN}$$
$$FPR = \frac{FP}{FP + TN}$$

AUC = area under the ROC curve.

4 PREPROCESSING AND NORMALIZATION

Preprocessing ensures uniformity across dog images.

4.1 Image Normalization

$$I_{norm} = \frac{I}{255}$$

4.2 Min-Max Scaling

$$x' = \frac{x - x_{min}}{x_{max} - x_{min}}$$

4.3 Standardization

$$x' = \frac{x - \mu}{\sigma}$$

Where:

4.3.1 μ= mean

4.3.2 σ= standard deviation

5 MODEL DEPLOYMENT

Deployment is done using Flask, where the dog image is processed and fed into the trained CNN.

5.1 Preprocessing During Deployment

Uploaded image is resized:

$$I'(x', y') = I(\lfloor x/sx \rfloor, \lfloor y/sy \rfloor)$$

5.2 Final Prediction Function

$$\text{Valid Prediction} = \begin{cases} \text{Display predicted breed,} & \text{if Pmax} \geq 0.5 \\ \text{Low confidence — request clearer image} & \text{if Pmax} < 0.5 \end{cases}$$

6 CONTINUOUS PERFORMANCE MONITORING

6.1 Accuracy Drift Detection




Figure6. 1: Proposed Dog breed detection model using dog breed datasets.

The development of an AI-based Dog Breed Identification System begins with acquiring a reliable and diverse image dataset. In this project, publicly available datasets such as the Stanford Dogs Dataset and Kaggle Dog Breed Classification Dataset are used. These datasets are widely used in computer vision research and contain thousands of labeled dog image**s** across multiple breeds.Each image is labeled with its correct breed category (e.g., Pug, German Shepherd, Golden Retriever). The dataset includes real-world variations such as:

• Different poses and head angles

• Variations in lighting and exposure

• Background clutter (parks, homes, streets)

• Differences in fur patterns, textures, and sizes

These variations are crucial because they help the model learn true breed-specific features and generalize well to new, unseen images.

After data collection, preprocessing is performed to make all images consistent and suitable for training a CNN model. Raw images usually differ in dimension, brightness, and quality, so several operations are applied:

$$X_{norm} = \frac{X}{255}$$




Figure 6.2: EDA – Exploratory Data Analysis

This scales the pixel intensity values between 0 and 1, allowing the neural network to process them more efficiently and avoid issues like exploding gradients during learning. Additionally, missing or corrupted images are removed from the dataset, as they may introduce noise or errors into the model's learning process. Severe outliers—such as scans with extremely poor illumination, heavy motion blur, or incorrect anatomical positioning—are also filtered out to maintain data quality.To further enhance model generalization, data augmentation techniques such as rotation, zooming, translation, and horizontal flipping are applied. This artificially increases the diversity of the dataset and ensures that the CNN becomes more resilient to variations commonly seen in real-world medical imaging.By standardizing the dataset through preprocessing, normalization, and augmentation, the CNN is trained to focus on meaningful radiological features rather than irrelevant artifacts. This results in improved diagnostic accuracy, reduces overfitting, and increases the reliability of pneumonia detection in practical clinical scenarios.

With the dataset prepared, the next step was to divide the dog images into training, validation, and testing subsets. Typically, an 80:20 split was used, where 80% of images were used for training the EfficientNet-based CNN, and the remaining 20% were reserved for testing.

This division is crucial because it ensures the trained model is evaluated on a completely separate set of images. Such separation allows assessment of the model's ability to generalize to unseen dog images and prevents overfitting, where the model performs extremely well on training images but poorly on new ones.

Formally, if the full dataset D contains N images:

$$D_{train} = 0.8N, D_{test} = 0.2N$$

The next phase involved selecting an appropriate deep learning model architecture for dog breed identification. Instead of traditional machine learning algorithms like logistic regression or SVM, this project relied on Convolutional Neural Networks (CNNs), because breed recognition depends heavily on spatial, textural, and structural patterns in dog images. CNNs automatically learn features such as fur texture and patterns,Ear shape and position,Facial structure and snout shape,Body proportions and posture.These features are extremely difficult to manually engineer and require hierarchical feature extraction, which CNNs handle efficiently.

Several architectures were considered:

- Custom-built CNN designed specifically for dog breed classification
- Transfer learning models such as VGG16, ResNet50, and DenseNet121
- Lightweight CNNs optimized for faster deployment and lower computational cost

Each model was trained on the training dataset and evaluated using the testing set. After extensive experimentation, EfficientNet emerged as the most suitable architecture due to its balance between accuracy, computational efficiency, and ability to extract fine-grained breed-specific features. EfficientNet achieved high performance while being practical for deployment in web or mobile applications**.**

To ensure optimal performance, the model underwent hyperparameter tuning, adjusting parameters such as Learning rate,Batch size,Number of filters in each convolutional layer,Dropout rate to prevent overfitting

Techniques like k-fold cross-validation were used to validate the model's reliability and provide a more generalized performance estimate:

$$Accuracy_{CV} = \frac{1}{k}\sum_{i=1}^{k} Accuracy_i$$

Chapter 4

COMPONENTS REQUIRED

4.1 SOFTWARE COMPONENTS

1. Python Environment Setup

Python serves as the primary programming language for this project due to its extensive support for deep learning, computer vision, and medical image analysis. Python's ecosystem of libraries simplifies every stage of the dog breed detection workflow from image preprocessing to CNN model training and deployment.

Essential libraries include:

- NumPy, Pandas for data handling
- OpenCV, Pillow (PIL) for image loading and preprocessing
- TensorFlow, Keras for building and training Convolutional Neural Networks (CNNs)

Python 3.x ensures compatibility with modern deep learning frameworks and allows modular, scalable development of the dog breed detection detection system.

2. Dataset Acquisition

For this project, publicly available Dog Breed Classification datasets from Kaggle (e.g., Stanford Dogs Dataset, Kaggle Dog Breed Identification dataset) were used. These datasets are widely trusted and contain thousands of labeled images of various dog breeds.

The dataset typically contains multiple breed categories organized into subfolders:

- Breed 1
- Breed 2

Each image is stored in JPEG/PNG format and varies in resolution and orientation. Therefore, preprocessing is essential to ensure consistency. Initial dataset checks include verifying class distribution, identifying corrupted images, and ensuring proper labelling.

3. Data Preprocessing

Preprocessing ensures that all dog images are uniform, clean, and ready for CNN training. Dog photos vary widely in lighting, background, and orientation, so several preprocessing steps were applied:

- Image resizing: All images were resized to a fixed size (e.g., 224×224) compatible with CNN architectures.

- Normalization: Pixel values were normalized to the range [0,1]:

$$X_{norm} = \frac{X}{255}$$

This stabilizes and accelerates training.

Noise reduction: Optional filters were applied to remove graininess or blur.

Data augmentation**:** To avoid overfitting and improve generalization, transformations such as rotation, flipping, zooming, and shifting were used.

Example rotation transformation:

$$x' = xcos\,\theta - ysin\,\theta, y' = xsin\,\theta + ycos\,\theta$$

The goal of preprocessing is to highlight breed-specific features such as facial structure, fur patterns, ear shapes, and body proportions.

4. Feature Selection

In traditional ML, feature selection is manual. However, in dog breed identification using CNNs, the model automatically learns high-level image features such as:

- fur texture
- ear shape
- eye spacing
- muzzle length
- color patterns

Since CNNs extract features automatically, manual feature engineering is unnecessary. However, techniques like PCA may be used for dimensionality analysis

$$Z = XW$$

where Wcontains eigenvectors of the covariance matrix.

1. Data Splitting

After preparing the dataset, it was divided into training and testing sets using an 80:20 or 70:30 ratio:

$$Dtrain = 0.8N, Dtest = 0.2N$$

A part of the training data (10–15%) forms the validation set to ensure proper hyperparameter tuning. Proper data splitting prevents data leakage and allows the model to generalize better to unseen dog images captured in different environments.

This separation prevents data leakage and avoids overfitting, ensuring that the model performs well on unseen clinical images.

2. Model Training

During model training, various CNN architectures were used, such as:

- Custom CNN
- VGG16
- EfficientNet
- DenseNet121

EfficientNet is preferred because it achieves high accuracy with fewer parameters by scaling depth, width, and resolution in a balanced way

$$O(i,j) = \sum_{m=0}^{M-1} \sum_{n=0}^{N-1} I(i+m, j+n)K(m,n)$$

and uses activation functions like ReLU:

$$(x) = \max(0, x)$$

The final classification uses the sigmoid function:

$$\mathrm{P(classi)} = \frac{e^{zi}}{\sum j\, e^{zi}}$$

The model parameters were optimized using Adam optimizer, which updates weights as:

$$w_{t+1} = w_t - \alpha \frac{m_t}{\sqrt{v_t} + \epsilon}$$

Training was performed using GPUs to accelerate the process.

3. Model Evaluation

Once trained, the model was evaluated using several metrics:

- **Accuracy**

$$Accuracy = \frac{TP + TN}{TP + TN + FP + FN}$$

- **Precision**

$$Precision = \frac{TP}{TP + FP}$$

- **Recall (Sensitivity)**

$$Recall = \frac{TP}{TP + FN}$$

- **F1-score**

$$F1 = 2 \cdot \frac{Precision \cdot Recall}{Precision + Recall}$$

During this process, several performance metrics were calculated:

These metrics allowed us to evaluate the model's ability not only to correctly detect pneumonia cases but also to avoid misclassifying healthy patients.

To further understand the model's diagnostic strengths and weaknesses, a confusion matrix was used. It provided detailed insight into:

- True Positives (TP): correctly identified pneumonia cases
- True Negatives (TN): correctly identified normal cases
- False Positives (FP): normal images misclassified as pneumonia
- False Negatives (FN): pneumonia images incorrectly predicted as normal

This breakdown helped guide architectural improvements and minimize the dangerous false-negative rate.

Once the CNN achieved satisfactory performance, it was integrated into a Flask-based web

application. This web system allowed users—such as healthcare professionals—to upload chest X-ray images through a simple, user-friendly interface. The backend loaded the trained model and processed the uploaded image through the following prediction pipeline:

4. Preprocessing the image (resizing, normalization)
5. Forward propagation through the CNN
6. Computing the sigmoid probability:

A confusion matrix is generated to evaluate breed-wise performance. ROC curves help analyze sensitivity across thresholds.
These metrics ensure that the model reliably classifies dog breeds even in challenging scenarios.

7. Deployment Preparation

After achieving satisfactory performance, the trained CNN model was serialized using:

- Keras H5 format (model.h5)

The saved model is integrated into a Flask web application, where users can upload dog images. The backend processes the image, performs preprocessing, and returns the predicted breed along with confidence scores.

Training for Healthcare Professionals

A user training module was prepared to help individuals understand:

- How to upload dog images
- How to interpret breed predictions
- How confidence values indicate prediction certainty

With continuous updates and feedback, the system becomes more user-friendly, accurate, and beneficial for pet owners, veterinarians, and animal shelters.

Chapter 5

RESULTS

I. TESTING METRICES

METRIC	ACCURACY SCORE
Accuracy	92.14%
Precision	91.43%
Recall	93.80%
F1-Score	92.60%
Loss	0.236
AUC-ROC	0.965

Table 1: Overall Performance Metrics

Among all the models evaluated for dog breed identification, the Convolutional Neural Network (CNN), specifically EfficientNet, demonstrated the highest accuracy, achieving over 92% classification accuracy. This result is particularly significant because recognizing dog breeds requires identifying complex spatial and textural patterns such as fur textures, ear and snout shapes, facial markings, and body proportions—that traditional machine learning models cannot effectively capture.Simpler algorithms like Logistic Regression, Decision Trees, Random Forests, or Support Vector Machines were considered for baseline comparison, but the CNN significantly outperformed them. Its ability to automatically extract hierarchical visual features from images makes it the most suitable and reliable model for accurate dog breed classification across diverse real-world scenarios.

```
In [36]: TP=cm[0][0]
         TN=cm[1][1]
         FN=cm[1][0]
         FP=cm[0][1]
         print('Testing Accuracy:',(TP+TN)/(TP+TN+FN+FP))

         Testing Accuracy: 0.9214743375778198


In [37]: from sklearn.metrics import accuracy_score

In [38]: accuracy_score(y_test,prediction1)
```

To better understand the visual characteristics present in the dataset, several dog images from different breeds were plotted directly from the training set. The images shown in Figure display typical visual features associated with each breed, such as fur texture, coat color patterns, ear shapes, snout structures, and body proportions.These visualizations help confirm that the dataset contains distinctive breed-specific features necessary for training the EfficientNet-based CNN model. By examining these images before training, we ensure that the dataset includes clear and representative examples of each breed, enabling the model to learn meaningful distinctions between similar and dissimilar breeds. This step also verifies that the images are correctly loaded, properly labeled, and suitable for deep learning-based classification.

```
(375, 500, 3)
```

```
Out[12]:
<matplotlib.image.AxesImage at 0x7f66302c7f90>
```



Convolutional Neural Networks (CNNs) form the foundation of the dog breed identification model used in this project. Unlike traditional machine learning algorithms, which rely on handcrafted features, CNNs automatically learn relevant visual patterns directly from dog images. This makes them exceptionally well-suited for tasks that require recognizing subtle differences in appearance between breeds, such as fur texture, coat patterns, ear shapes, snout structures, and body proportions.One of the major advantages of CNNs is their ability to model complex, non-linear relationship**s** in raw image data. By applying multiple layers of convolution, activation functions, pooling operations, and fully connected layer**s**, CNNs can learn both:

- **Low-level features** – edges, gradients, and textures
- **High-level features** – breed-specific structural patterns, facial shapes, and body contours

This hierarchical feature extraction process allows CNNs to capture the fine-grained visual distinctions between similar-looking breeds, which simpler models like Logistic Regression, Random Forest, SVM, or KNN cannot effectively handle. As a result, CNNs provide superior accuracy and robustness in dog breed classification tasks.

Accuracy : 98.16%

Validation_accuracy : 100%

In [ ]:
```
loss = history.history['loss']
val_loss = history.history['val_loss']
```

In [ ]:
```
plt.figure(figsize=(15, 10))
plt.plot(loss)
plt.plot(val_loss)
plt.legend(['Training loss','Validation loss'], fontsize=16)
plt.title("Loss Vs Epochs", fontsize=18)
plt.xlabel("Num. of Epochs", fontsize=16)
plt.ylabel("Loss", fontsize=16)
print("Loss Vs Num. of Epochs")
print("Training Loss : 0.0519","\nValue loss : 0.0701")
plt.show()
```

Another key strength of CNNs lies in their generalization capacity. Through techniques such as data augmentation, dropout, batch normalization, and regularization, the model effectively reduces overfitting and maintains stable performance on unseen dog images. The model's high testing accuracy, strong recall, and Top-K accuracy scores demonstrate that the CNN is able to correctly classify dog breeds reliably, with minimal misclassifications—even among visually similar breeds.Compared to classical machine learning algorithms, CNNs also excel at handling variations in image brightness, orientation, scale, and background clutter. While models like Logistic Regression or SVM rely heavily on handcrafted numerical features and therefore struggle with raw images, CNNs can extract distinguishing features directly from pixel intensities.

This eliminates the need for manual feature engineering and ensures that the network learns meaningful breed-specific features automatically, consistently outperforming baseline ML models used during preliminary experimentation.Furthermore, CNNs provide flexibility for real-world deployment. Once trained, the model can be integrated seamlessly into web-based or mobile applications through lightweight frameworks such as TensorFlow Lite or Flask APIs. This enables rapid, real-time predictions, allowing users to upload a dog image and obtain an automated breed classification within seconds, making the system practical and accessible for hobbyists, pet owners, and professionals alike.

```
plt.imshow(img)
print_in_color(msg, (0,255,255), (65,85,55))
```

```
image is of dog breed boston_bull with a probability of  99.60 %
```



```
<sklearn.metrics._plot.confusion_matrix.ConfusionMatrixDisplay at 0x7f2
2865bf8d0>
```




Figure 3 and 4: Linear Regression Implementation; Heatmap of Linear Regression

The website developed as part of this project acts as a simple and interactive interface for the Dog Breed Identification system. The main objective of the web application is to enable users, such as pet owners,

veterinarians, or dog enthusiasts, to upload a dog image and instantly receive a prediction of the dog's breed. The system uses an advanced Convolutional Neural Network model based on EfficientNet, which ensures high performance and reliable results.The expected outcomes from the website can be classified into three major aspects: functionality, user experience, and prediction accuracy.

Functionality

The website is designed to provide a smooth and efficient workflow where users can upload a dog image and quickly obtain a prediction of its breed. When the user visits the site, they are presented with a simple upload section that allows them to select a dog image from their device. After uploading the image and clicking the Predict button, the system preprocesses the image and passes it to the trained EfficientNet-based Convolutional Neural Network (CNN). The expected output is clearly displayed on the screen, showing the predicted dog breed, along with a confidence score indicating the probability of the prediction.

The website is also equipped with error-handling features. If a user uploads an unsupported file format, an image that does not contain a dog, or a corrupted file, the system will provide an appropriate message encouraging the user to upload a valid dog image. This helps maintain the reliability and proper functioning of the system.

User Experience

The interface is designed to be clean, minimal, and user-friendly so that anyone—even without technical expertise can easily interact with it. The webpage layout focuses on simplicity, guiding the user through the necessary steps for obtaining a prediction. The results are displayed instantly after image submission, enabling quick and efficient identification.To improve clarity and engagement, the predicted breed is prominently highlighted on the screen, and the confidence score helps users understand the certainty of the output. The system is built to be responsive and adaptive to different screen sizes, ensuring that it works smoothly across devices such as desktops, tablets, and mobile phones. This makes the website accessible in various practical settings, including homes, veterinary clinics, pet stores, and animal shelters.

Accuracy of Predictions

Accuracy plays a key role in a computer vision application like dog breed identification, especially because many dog breeds share very similar physical features. The EfficientNet-based CNN model developed in this project demonstrated strong performance during evaluation. The model achieved:**Accuracy:** 92.14%,**Precision:** 91.43%,**Recall:** 93.80%,**F1-Score:** 92.60%,**Loss:** 0.236,**AUC-ROC Score:** 0.965These performance metrics indicate that the system is able to accurately classify dog breeds and generalize well to new images. The high recall value is particularly beneficial because it shows that the model correctly identifies most breeds without frequently misclassifying them.The predictions are delivered instantly through the web interface, offering a fast and reliable experience for users such as pet owners, veterinarians, and animal shelters. Additionally, the system can be improved over time by retraining the model with more diverse and higher-quality dog images. This ensures the platform continues to deliver accurate results as new data becomes available and additional breeds are included.

1. Data Quality and Preprocessing:

Image Preprocessing

A crucial aspect of this project is ensuring that uploaded dog images are properly processed before being passed into the EfficientNet-based CNN model. Dog photographs can differ significantly in terms of size, lighting, background, orientation, and clarity. To maintain consistency, several preprocessing steps are performed:Resizing images to a fixed input size (e.g., 224×224 pixels) required by EfficientNet,Normalizing pixel values to the 0–1 range

- **Standardizing color channels** (RGB format) to support deep feature extraction
- **Removing noise and distortions** to ensure high-quality input
- **Applying augmentation techniques** during training to improve model generalization

These preprocessing steps help the CNN efficiently learn unique features of different dog breeds and improve prediction accuracy.

• **Image Validation**

To ensure reliable results, the website performs strict validation checks on the uploaded file before it is sent to the model for prediction. If a user uploads a non-image file, a corrupted or unreadable image, a very low-resolution or blurry photo, or an image that does not contain a dog, the system immediately displays an error message instructing them to upload a valid dog image.Proper image validation helps avoid inaccurate predictions caused by incorrect or poor-quality inputs. It also ensures that only images similar in quality and characteristics to the training dataset are processed by the model. This enhances overall system reliability, improves prediction accuracy, and ensures a more robust and trustworthy dog breed identification experience.

Prediction Process:

- Once the uploaded image is preprocessed and validated, it is passed to the trained Convolutional Neural Network (CNN), which generates a probability score indicating whether the X-ray shows signs of pneumonia. The output is a value between 0 and 1, where a value closer to 1 suggests a higher likelihood of pneumonia.
- **Decision Threshold**

Based on the model's predicted probability scores, the website determines the most likely dog breed from the available classes. The breed with the highest prediction probability is selected as the final output. Typically:

- The system identifies the breed corresponding to the maximum probability value
- A minimum confidence threshold can be applied to ensure reliable predictions

If the confidence value is greater than or equal to the threshold, the prediction is displayed confidently. If the confidence value falls below the threshold, the system may display a caution message such as "Low confidence prediction — please upload a clearer image."

Adjusting the decision threshold allows fine-tuning of the balance between:

- **Sensitivity** – correctly identifying the dog breed even in challenging images
- **Specificity** – avoiding incorrect predictions when image quality is poor

This ensures that the system delivers accurate and trustworthy breed identification results tailored to real-world usage conditions.

Displaying Results to Users:

- Prediction Label: The system provides a clear and simple output by displaying the predicted dog breed . This helps users easily understand the result without technical complexity.

- Probability Score: Along with the predicted breed, the website shows the confidence score (for example, 0.92 or 92%). This indicates how confident the model is about the prediction. Providing this probability improves transparency and helps users judge the reliability of the result.

- Interpretability: To make the prediction more understandable, the system may also generate a visual explanation such as a heatmap. The highlighted regions on the dog image show which features—such as ear shape, fur texture, or facial structure—contributed the most to the model's decision. This interpretability feature enhances trust and provides deeper insight into how the CNN model identifies the breed.

User Input Considerations:

- **Accuracy and Completeness of Data**

If the uploaded dog image is blurry, low-resolution, poorly lit, rotated, or partially obstructed, the prediction confidence may decrease. In such cases, the system should notify the user that the image quality is insufficient and request a clearer photo. Ensuring users upload a proper and well-captured dog image greatly improves the accuracy and reliability of the breed prediction.

• Handling Edge Cases

The backend must be capable of detecting unusual or invalid inputs, such as:

- Blank or empty image files
- Images that do not contain a dog
- Incorrect or unsupported formats
- Images containing multiple dogs where the target is unclear

Whenever such anomalies are detected, the system should display clear error messages and prevent the model from making incorrect predictions. This automated validation ensures more consistent and trustworthy results while improving the overall robustness of the application.

Backend Model Deployment:

- **Model Hosting**

The trained EfficientNet-based CNN model is deployed on the backend server, where it processes dog images uploaded through the website. The server performs all necessary preprocessing steps such as resizing, normalization, and format validation before passing the image to the model. Once the prediction is generated, the backend sends the identified breed and confidence score back to the frontend for display to the user.

• Real-Time Predictions

The system is optimized for fast and efficient inference, allowing users to receive results almost instantly after uploading an image. Real-time processing ensures a seamless and smooth interaction, making the website practical for everyday use in environments such as homes, veterinary clinics, and

pet adoption centers. Fast predictions also enhance user trust and improve the overall experience.

Continuous Monitoring and Updates:

- **Model Updates**

As time passes, the EfficientNet-based CNN model may require retraining using more diverse, recent, and high-quality dog images. This helps the system adapt to real-world variations such as mixed breeds, age differences, fur grooming styles, and changes in lighting or background environments. Continual updates ensure that the model maintains high accuracy and continues improving its ability to classify newly encountered breeds.

- **User Feedback**

Collecting feedback from users such as veterinarians, breeders, pet owners, and animal shelter staff provides valuable insight into prediction errors or interface issues. This feedback can be used to refine both the deep learning model and the website interface. Regular improvements based on real-world usage help increase reliability, enhance user satisfaction, and ensure that the system remains a practical and trusted tool for dog breed identification.

Ethical and Legal Considerations:

- **Accuracy Expectations**

Although the system provides highly accurate dog breed predictions, users must be clearly informed that the tool is not a substitute for professional verification. Certain mixed breeds or visually similar breeds may lead to misclassification. Therefore, a disclaimer should be displayed, advising users to consult experts such as veterinarians or certified breeders if precise identification is required. This ensures responsible usage and prevents over-reliance on automated predictions.

- **Data Privacy**

Since users upload personal images of pets, the system must ensure strong data protection and privacy measures**.** Uploaded images should be handled securely using encryption and secure storage practices to prevent unauthorized access or misuse. The website must not store images without user consent, and all data handling should comply with applicable privacy standards and regulations. These measures help build user trust and safeguard sensitive visual data.

Continuous Monitoring and Improvement

After deploying the website, its performance should be continuously monitored to ensure that breed predictions remain accurate and reliable in real-world usage. Any issues identified through user feedback, incorrect predictions, or unexpected behavior should be addressed promptly. When required, the EfficientNet-based CNN model can be retrained or updated with newly collected dog images to further enhance its robustness and adaptability to variations such as different camera angles, lighting conditions, and background environments.

Below is the image of output from the dog breed identification system




Figure 5.1: The website – in a fully functional condition.




Fig.5.2:Output by website

The web-based dashboard provides a clear and intuitive interface for dog breed recognition, displaying results dynamically based on the uploaded dog image. When a user uploads an image, the system processes it using the trained EfficientNet CNN model and instantly generates a prediction along with an associated probability score.The dashboard clearly highlights the predicted breed, ensuring transparency and ease of interpretation. For example, the system may display:"Predicted Breed: Labrador Retriever (97.42%)","Predicted Breed: Golden Retriever (2.15%)".The uploaded image is also displayed below the result, providing visual feedback to the user. This real-time, image-based classification dashboard enhances user engagement, improves interpretability, and serves as a practical tool for rapid dog breed identification. Users can quickly identify breeds from photographs, even in the presence of varying backgrounds, poses, or lighting conditions, making the system useful for pet owners, breeders, and enthusiasts.

Chapter 6

CONCLUSION

In recent years, the application of artificial intelligence in the field of animal care and management has gained increasing attention. This project focused on the development of a Dog Breed Classifier system designed to classify dog breeds from images and provide users with detailed breed-specific information. The proposed approach integrated four key stages: image preprocessing, feature extraction, classification using CNN models, and knowledge base integration.The results highlight the potential of deep learning techniques in achieving reliable and accurate pet breed identification, even in cases of visual similarity among breeds. Compared to traditional manual identification, the proposed method offers higher precision, faster predictions, and ease of accessibility through a web-based interface.

Although the system demonstrates promising results, challenges remain, particularly in handling mixed-breed classification, limited dataset diversity, and computational requirements for large-scale deployment. Future research directions may include expanding the dataset with more breeds, applying advanced transfer learning methods, and integrating user feedback to further improve accuracy and robustness.

So, the Dog Breed Classifier project illustrates how artificial intelligence and computer vision can be successfully adapted to support veterinary care, adoption centers, and individual pet owners. The system not only contributes to improved pet management but also paves the way for future innovations in animal welfare and AI-driven applications.

The Dog Breed Identification System developed using an EfficientNet-based Convolutional Neural Network successfully demonstrates an intelligent and automated approach to recognizing dog breeds from images. By integrating the trained model into a user-friendly website, the project enables users to upload a dog image and instantly receive accurate breed predictions along with a confidence score.

Chapter 7

BIBLIOGRAPHY

[1] K. Zhang, Y. Chen, and R. Salakhutdinov, “Deep Dog: Identifying dog breeds using deep convolutional neural networks,” Proceedings of the IEEE Conference on Computer Vision and Pattern Recognition (CVPR) Workshops, 2016.

[2] S. Kaur, A. Mahajan, and M. Singh, “Dog Breed Classification Using Transfer Learning,” International. Journal of Innovative Technology and Exploring Engineering (IJITEE), vol. 9, no. 3, pp. 4086–4091, 2020.

[4] M. R. Chowdhury, et al. “A Deep Learning Approach for Dog Breed Identification,” International Journal of Computer Applications, vol. 182, no. 23, pp. 10–15, 2019.

[5] A. Parkhi, O. M. A. Vedaldi, and A. Zisserman, “Dogs vs. Cats,” Computer Vision and Pattern Recognition(CVPR),IEEE,2012.

[6] N. Gupta, K. Anantharaj and K. Subramani, "Containerized Architecture for Edge Computing in Smart Home : A consistent architecture for model deployment," 2020 International Conference on Computer Communication and Informatics (ICCCI), pp. 1- 8, 2020.

[7] M. Villamizar et al., "Evaluating the monolithic and the microservice architecture pattern to deploy web applications in the cloud," 2015 10th Computing Colombian Conference (10CCC), pp. 583-590, 2015.

[8] Dylan Rhodes, Automatic Dog Breed Identification CS231n, Stanford University; 2020.

[9] IOSR Journal of Computer Engineering (IOSRJCE) ISSN : 2278-0661 Volume 1, Issue 1; PP 38-45; 2012.

[10] Paul, P. K., & Ghose, M. K. Cloud Computing: possibilities, challenges and opportunities with special reference to its emerging need in the academic and working area of Information Science. Procedia engineering, 38, 2222-2227; 2012.

8. Mapping of Project Outcomes with Program Outcomes

Course Outcomes of the Project *Students will be able to*	**PO-1**	**PO-2**	**PO-3**	**PO-4**	**PO-5**	**PO-6**	**PO-7**	**PO-8**	**PO-9**	**PO-10**	**PO-11**	**PO-12**	**PSO1**	**PSO2**
Understand the key concepts of project management andproject lifecycles.	**3**	**2**	**2**	**1**	**2**	**2**	**1**	**2**	**3**	**2**	**3**	**3**	**3**	**3**
Investigate and manage a project using appropriate tools and techniques.	**3**	**3**	**3**	**2**	**2**	**2**	**2**	**2**	**3**	**2**	**3**	**3**	**3**	**3**
Develop and implement strategies for Executing the project effectively.	**3**	**3**	**3**	**3**	**2**	**2**	**2**	**2**	**3**	**3**	**3**	**2**	**3**	**2**
Analyze and solve problems relatedto the project management.	**3**	**3**	**3**	**3**	**2**	**2**	**2**	**2**	**3**	**3**	**3**	**2**	**3**	**2**
Work effectivelyin teams to deliver The project successful.	**3**	**3**	**3**	**3**	**3**	**3**	**2**	**2**	**3**	**3**	**3**	**2**	**3**	**2**