```
nidhi@NidhiDB:~/spark-4.1.1-bin-hadoop3$ nano wc2.txt
nidhi@NidhiDB:~/spark-4.1.1-bin-hadoop3$ spark-shell
WARNING: Using incubator modules: jdk.incubator.vector
Using Spark's default log4j profile: org/apache/spark/log4j2-defaults.proper
ties
26/05/02 13:40:23 WARN Utils: Your hostname, NidhiDB, resolves to a loopback
 address: 127.0.1.1; using 10.255.255.254 instead (on interface lo)
26/05/02 13:40:23 WARN Utils: Set SPARK_LOCAL_IP if you need to bind to anot
her address
Using Spark's default log4j profile: org/apache/spark/log4j2-defaults.proper
ties
Setting default log level to "WARN".
To adjust logging level use sc.setLogLevel(newLevel). For SparkR, use setLog
Level(newLevel).
Welcome to
      ____              __
     / __/__  ___ _____/ /__
    _\ \/ _ \/ _ `/ __/  '_/
   /___/ .__/\_,_/_/ /_/\_\   version 4.1.1
      /_/

Using Scala version 2.13.17 (OpenJDK 64-Bit Server VM, Java 17.0.18)
Type in expressions to have them evaluated.
Type :help for more information.
26/05/02 13:40:36 WARN NativeCodeLoader: Unable to load native-hadoop librar
y for your platform... using builtin-java classes where applicable
Spark context Web UI available at http://10.255.255.254:4040
Spark context available as 'sc' (master = local[*], app id = local-177772923
9053).
Spark session available as 'spark'.
```

```
scala> val textFile = sc.textFile("file:///home/nidhi/spark-4.1.1-bin-hadoop
3/wc2.txt")
val textFile: org.apache.spark.rdd.RDD[String] = file:///home/nidhi/spark-4.
1.1-bin-hadoop3/wc2.txt MapPartitionsRDD[1] at textFile at <console>:1

scala> val counts = textFile
     |   .flatMap(_.split(" "))
     |   .map(word => (word, 1))
     |   .reduceByKey(_ + _)
val counts: org.apache.spark.rdd.RDD[(String, Int)] = ShuffledRDD[4] at redu
ceByKey at <console>:4

scala> val sorted = counts.sortBy(_._2, ascending = false)
     |
     | println(sorted.collect().mkString("\n"))
     |
     | for ((k, v) <- sorted.collect()) {
     |   if (v > 4) {
     |     println(k + "," + v)
     |   }
     | }
[Stage 0:>                                                          (0 + 2)
[Stage 0:==============================>                          (1 + 1)

(data,5)
(hello,5)
(test,5)
(spark,3)
(world,2)
(hadoop,1)
data,5
hello,5
test,5
val sorted: org.apache.spark.rdd.RDD[(String, Int)] = MapPartitionsRDD[9] at
 sortBy at <console>:1
```