

```
cqlsh> CREATE KEYSPACE Employee With replication = {'class': 'SimpleStrategy','replication_factor':1};
cqlsh> Describe keyspaces;
```

```
employee  system_auth      system_schema  system_views
system    system_distributed  system_traces  system_virtual_schema
```

```
cqlsh> Use employee;
cqlsh:employee> CREATE TABLE Employee_Info( Emp_id INT PRIMARY KEY, Emp_Name TEXT, Designation TEXT, Date_of_Joining DATE, Salary FLOAT, Dept_Name TEXT);
cqlsh:employee> Describe table employee_info
```

```
CREATE TABLE employee.employee_info (
  emp_id int PRIMARY KEY,
  date_of_joining date,
  dept_name text,
  designation text,
  emp_name text,
  salary float
) WITH additional_write_policy = '99p'
AND bloom_filter_fp_chance = 0.01
AND caching = {'keys': 'ALL', 'rows_per_partition': 'NONE'}
AND cdc = false
AND comment = ''
AND compaction = {'class': 'org.apache.cassandra.db.compaction.SizeTieredCompactionStrategy', 'max_threshold': '32', 'min_threshold': '4'}
AND compression = {'chunk_length_in_kb': '16', 'class': 'org.apache.cassandra.io.compress.LZ4Compressor'}
AND memtable = 'default'
AND crc_check_chance = 1.0
AND default_time_to_live = 0
AND extensions = {}
AND gc_grace_seconds = 8640000
AND max_index_interval = 2048
AND memtable_flush_period_in_ms = 0
AND min_index_interval = 128
AND read_repair = 'BLOCKING'
AND speculative_retry = '99p';
```

```
cqlsh:employee> Begin batch
... Insert into employee_info (Emp_id, emp_name, designation, Date_of_joining, salary, dept_name) Values(1,'Priya','Developer','2026-03-03',100000,'Engineering')
... Apply batch;
cqlsh:employee> Begin batch Insert into employee_info (Emp_id, emp_name, designation, Date_of_joining, salary, dept_name) Values(1,'Priya','Developer','2026-03-03',100000,'Engineering'); Apply batch;
```

```
cqlsh:employee> Begin batch insert into employee_info(emp_id,emp_name, designation,date_of_joining, salary, dept_name) values(2,'krisha','Developer','2026-03-04',120000,'Engineering'); insert into employee_info(emp_id,emp_name, designation,date_of_joining, salary, dept_name) values(3,'mohit','Consultant','2026-03-05',130000,'Engineering'); apply batch;
cqlsh:employee> select*from employee_info
```

```
cqlsh:employee> select*from employee_info;

emp_id | date_of_joining | dept_name | designation | emp_name | salary
-----+-----+-----+-----+-----+-----
1 | 2026-03-03 | Engineering | Developer | Priya | 1e+05
2 | 2026-03-04 | Engineering | Developer | krisha | 1.2e+05
3 | 2026-03-05 | Engineering | Consultant | mohit | 1.3e+05
```

```
cqlsh:employee> Update employee_info SET emp_name = 'Rachana', dept_name = 'HR' WHERE emp_id = 1;
cqlsh:employee> select*from employee_info;
```

```
emp_id | date_of_joining | dept_name | designation | emp_name | salary
-----+-----+-----+-----+-----+-----
1 | 2026-03-03 | HR | Developer | Rachana | 1e+05
2 | 2026-03-04 | Engineering | Developer | krisha | 1.2e+05
3 | 2026-03-05 | Engineering | Consultant | mohit | 1.3e+05
```

(3 rows)

```
cqlsh:employee> select* from employee_info allow filtering;
```

```
emp_id | date_of_joining | dept_name | designation | emp_name | salary
-----+-----+-----+-----+-----+-----
1 | 2026-03-03 | HR | Developer | Rachana | 1e+05
2 | 2026-03-04 | Engineering | Developer | krisha | 1.2e+05
3 | 2026-03-05 | Engineering | Consultant | mohit | 1.3e+05
```

```
cqlsh:employee> Alter table employee_info ADD Projects SET<TEXT>;
cqlsh:employee> select*from employee_info;
```

```
emp_id | date_of_joining | dept_name | designation | emp_name | projects | salary
-----+-----+-----+-----+-----+-----+-----
1 | 2026-03-03 | HR | Developer | Rachana | null | 1e+05
2 | 2026-03-04 | Engineering | Developer | krisha | null | 1.2e+05
3 | 2026-03-05 | Engineering | Consultant | mohit | null | 1.3e+05
```

```

cqlsh:employee> UPDATE EMPLOYEE_INFO SET PROJECTS = {'PROJECT A','PROJECT B'} WHERE EMP_ID = 1;
cqlsh:employee> UPDATE EMPLOYEE_INFO SET PROJECTS = {'PROJECT B','PROJECT C'} WHERE EMP_ID = 2;
cqlsh:employee> UPDATE EMPLOYEE_INFO SET PROJECTS = {'PROJECT C'} WHERE EMP_ID = 3;
cqlsh:employee> SELECT EMP_ID,EMP_NAME,PROJECTS FROM EMPLOYEE_INFO;

```

emp_id	emp_name	projects
1	Rachana	{'PROJECT A', 'PROJECT B'}
2	krisha	{'PROJECT B', 'PROJECT C'}
3	mohit	{'PROJECT C'}

```

cqlsh:employee> UPDATE EMPLOYEE_INFO USING TTL 15 SET SALARY = 0 WHERE EMP_ID = 1;
cqlsh:employee> SELECT*FROM EMPLOYEE_INFO;

```

emp_id	date_of_joining	dept_name	designation	emp_name	projects	salary
1	2026-03-03	HR	Developer	Rachana	{'PROJECT A', 'PROJECT B'}	0
2	2026-03-04	Engineering	Developer	krisha	{'PROJECT B', 'PROJECT C'}	1.2e+05
3	2026-03-05	Engineering	Consultant	mohit	{'PROJECT C'}	1.3e+05

(3 rows)

```

cqlsh:employee> SELECT*FROM EMPLOYEE_INFO;

```

emp_id	date_of_joining	dept_name	designation	emp_name	projects	salary
1	2026-03-03	HR	Developer	Rachana	{'PROJECT A', 'PROJECT B'}	null
2	2026-03-04	Engineering	Developer	krisha	{'PROJECT B', 'PROJECT C'}	1.2e+05
3	2026-03-05	Engineering	Consultant	mohit	{'PROJECT C'}	1.3e+05