

Business or Organizational Unit
Franchise or Department




Subgroup Benchmarking Framework


Sophie Sun, AEA/AMDS
Björn Bornkamp, SMC/AMDS
Yao Chen , SMC/AMDS
Jiarui Lu , SMC/AMDS
Kostas Sechidis , AEA/AMDS

Motivation

MOB




Causal Forest




FindIt

Causal Moderation: Heterogeneous Treatment Effect



Quint



Challenge

- There has been review work to compare subgroup methods (Lipkovich et al. 2017, Huber et al. 2019, Zhang et al. 2018, Loh et al. 2019)
- Data: simulation data is not a good representation of the real clinical data
 - Mostly use variables generated from parametric distribution with simple dependent/independent covariates distributions (Lipkovich et al. 2017, Huber et al. 2019, Zhang et al. 2018)
 - Large subgroup effects (Loh et al. 2019)
- Methodology:
 - Only consider certain type of response (Loh et al. 2019, Huber et al. 2019)
 - Might tend to consider cases and metrics favoring the proposed methods
- Objective: Build objective & realistic benchmarking framework and considers metrics of practical importance, provide guidelines for subgroup analysis

Data generation: Prognostic and predictive structure

Generate data from: $f(X) = f_{prog}(X) + Trt * (\beta_0 + \beta_1 * f_{pred}(X))$

- Benchtm ([go/benchtm](#)) provides two covariate distributions:
 1. Synthetic data generated from a real clinical trials
 - Generated from real clinical trial data using “synthpop”
 - To ensure anonymization
 - Continuous covariates scaled to (0, 1)
 - Covariates relabeled to X_1, X_2, \dots, X_p
 2. Generated from parametric distribution with dependence/ independent covariates distributions
- User can provide the structure of $f_{prog}(X)$ and $f_{pred}(X)$ to account for different type of problems (e.g. linear/non-linear, step)

Data generation: different sets of parameters

Generate data from: $f(X) = f_{prog}(X) + Trt * (\beta_0 + \beta_1 * f_{pred}(X))$

Parameter	Setting
Sample size	100, 500, 1000
Number of predictors	30,100
Overall Effect size (determined by power)	Large (power = 0.9) Medium (power = 0.5) Small (power = 0.05)
Standard deviation of treatment effect	Small, medium, large (multiple)
Treatment effect structure	Step, linear
Number of variables defining subgroup	0 (no subgroup), 1, 2
Clinical endpoints	Continuous, binary, count, survival

List of methods for simulation

Non-ensembling methods

- Tree-based methods: (suggest subgroup)
 - ❑ Virtual Twins (Foster, Taylor, and Ruberg 2011)
 - ❑ SIDES (Lipkovich et al. 2011)
 - ❑ GUIDE (Loh and Zhou 2020)
 - ❑ Interaction Tree (Su et al. 2008)
 - ❑ MOB (Zeileis and Hothorn 2015)
 - ❑ QUINT (Dusseldorp and Van Mechelen 2014)
 - ❑ STIMA (Dusseldorp, Conversano, and Van Os 2010)
- Linear- Regression-based methods: (estimate interaction effect)
 - ❑ Lasso & Ridge, Glmnet (Hastie and Qian 2014)
 - ❑ FindIT (Imai, Ratkovic, and others 2013)
 - ❑ STIMA (Dusseldorp, Conversano, and Van Os 2010)
 - ❑ OWL (Fu, Zhou and Faries 2016, Yu et al. 2015)

Ensembling methods: (provide variable importance)

- ❑ Casual forest (Athey et al. 2019)
- ❑ GUIDE (Loh and Zhou 2020)
- ❑ MOBFOREST (Garge et al. 2019)
- ❑ Virtual Twins (Foster, Taylor, and Ruberg 2011)
- ❑ BART (Chipman et al. 2010)
- ❑ TSDT (Battioui et al. 2018)
- ❑ subtee (Bornkamp et al. 2017)

Performance Metrics

Ability to reliably determine subgroups with higher or lower (relative to overall) treatment effect (reproducible in new studies)

- Test for existence of differential treatment effects
 - Right/wrong decision
- Variable selection bias based on variable importance rankings (for differential treatment effect)
 - “True treatment effect modifying variates” are most important variables
 - Prognostic variables falsely identified among most important variables
- Estimation of individual treatment effects
 - Bias & MSE overall (and maybe in top 50%, top 20%, top 10% of predicted effects)

Performance Metrics: Treatment effect heterogeneity?


Setup:

- Continuous response
- Sample size $n = 500$
- power = 0.5
- Repeat on 1000


Methods to compare:

- CausalForest: Forest based
- MOB: MOBC with node fit $Y = Trt$, MOBI: $Y = \alpha Trt + \sum_j \beta_j X_j$, MobForest: ensemble MOBC
- GUIDE: tree-based
- Interaction test: Univariate interaction model
- HWVT: Holmes and Watson (2020) + virtual Twins implementation
- Oracle: true model

Probability of detecting heterogeneity




Performance Metrics: Variable selection bias



Performance Metrics: estimation of treatment effect

MSE of treatment effect



Subgroup identification method recommendation

- Benchmarking framework help us to better understand the performance of each methods for subgroup identification problems on:
 - Test for treatment effect heterogeneity
 - Variable selection bias (important variables are predictive)
 - Prediction bias (predicted treatment effect close to truth)
- Other than the performance part, whether a subgroup identification is recommended also depends on
 - Types of responses it can handle
 - Interpretability of the result
 - Computation cost
 - How easy it is to use the method (whether there is a package, how easy it is to use it in different systems)

Future work (go/subgroup)

Guideline:

- Objectives
- Preliminary steps
- Exploratory data-analysis
- Implementation of recommended subgroup methods
- Confirmatory analysis

Tools (funnel plot, forest plot, correlation plot)

Benchmarking
Simulation



Thank you


Reference

- [IT] Su, Xiaogang, et al. "Subgroup analysis via recursive partitioning." *Journal of Machine Learning Research* 10.Feb (2009): 141-158.
- [Quint] Dusseldorp, Elise, Lisa Doove, and Iven Van Mechelen. "Quint: An R package for the identification of subgroups of clients who differ in which treatment alternative is best for them." *Behavior research methods* 48.2 (2016): 650-663.
- [FindIt] Imai, Kosuke, and Marc Ratkovic. "Estimating treatment effect heterogeneity in randomized program evaluation." *The Annals of Applied Statistics* 7.1 (2013): 443-470.
- [VT] Foster, Jared C., Jeremy MG Taylor, and Stephen J. Ruberg. "Subgroup identification from randomized clinical trial data." *Statistics in medicine* 30.24 (2011): 2867-2880.
- [GUIDE] Loh, Wei-Yin, et al. "Identification of subgroups with differential treatment effects for longitudinal and multiresponse variables." *Statistics in medicine* 35.26 (2016): 4837-4855.[GUIDE]
- [SIDES] Lipkovich, Ilya, et al. "Subgroup identification based on differential effect search—a recursive partitioning method for establishing response to treatment in patient subpopulations." *Statistics in medicine* 30.21 (2011): 2601-2621.
- [IT] Su, Xiaogang, et al. "Interaction trees with censored survival data." *The international journal of biostatistics* 4.1 (2008).
- [STIMA] Dusseldorp, Elise, Claudio Conversano, and Bart Jan Van Os. "Combining an additive and tree-based regression model simultaneously: STIMA." *Journal of Computational and Graphical Statistics* 19.3 (2010): 514-530.
- [Holmes Watson] Watson, James A., and Chris C. Holmes. "Machine learning analysis plans for randomised controlled trials: detecting treatment effect heterogeneity with strict control of type I error." *Trials* 21.1 (2020): 156.
- [MOB] Zeileis, Achim, Torsten Hothorn, and Kurt Hornik. "Model-based recursive partitioning." *Journal of Computational and Graphical Statistics* 17.2 (2008): 492-514.

How to choose β_0 and β_1 in benchtm?

Generate data from: $f(X) = f_{prog}(X) + Trt * (\beta_0 + \beta_1 * f_{pred}(X))$

1. Can specify β_0 and β_1 (difficult in practice)
2. Derive β_0 and β_1 based on the *overall treatment effect power* and *the standard deviation of the treatment effect*
 - Derive β_1 based on sd_{TE} : $sd_{TE} = \beta_1 sd(f_{pred}(X))$
 - Find β_0 for a pre-specified overall power (for the naive unadjusted test)



- Depends on covariate distribution for X and structural form of $f_{pred}(X)$ as well as $f_{prog}(X)$

Acknowledge

AMDS: Janice Branson

- SMC: Mouna Akacha, Björn Bornkamp, Yao Chen, Jiarui Lu
- AEA: David Ohlssen, Kostas Sechidis, Sophie Sun
- SCC: Douglas Robinson, Ardalan Mirshani
- CTS: Mark Baillie

Collaborations:

- PMX: Chong Ma
- NIBR: Pablo Serrano
- DS&AI: Brian Buckley