

Stabilization of a Quadcopter

Michael Shell

School of Electrical and
Computer Engineering

Georgia Institute of Technology
Atlanta, Georgia 30332–0250

Email: <http://www.michaelshell.org/contact.html>

Homer Simpson

Twentieth Century Fox
Springfield, USA

Email: homer@thesimpsons.com San Francisco, California 96678–2391

James Kirk

and Montgomery Scott
Starfleet Academy

Telephone: (800) 555–1212
Fax: (888) 555–1212

Abstract—The abstract goes here.

I. INTRODUCTION

This demo file is intended to serve as a “starter file” for IEEE conference papers produced under L^AT_EX using IEEE-tran.cls version 1.8b and later. I wish you the best of success.




Figure 1: Location of the center of mass, where $\theta_1 = 0,043$ rad and $\theta_2 = 0,078$ rad.

Characteristics	Value [Unit]
Nominal output current	5 [A]
Peak current (<20 s)	15 [A]
Current control PWM frequency	53,6 [kHz]
Sample Rate of PI current controller	53,6 [kHz]

Table I: Important parameters of the motor control board.

A. Subsection Heading Here

Subsection text here.

1) *Subsubsection Heading Here*: Subsubsection text here.

II. MODEL

III. DISCUSSION

The conclusion goes here.

ACKNOWLEDGMENTS

The authors would like to thank...

REFERENCES

- [1] H. Kopka and P. W. Daly, *A Guide to L^AT_EX*, 3rd ed. Harlow, England: Addison-Wesley, 1999.

$$\mathbf{J}_F \ddot{\boldsymbol{\theta}}_F = -\mathbf{B}_F \dot{\boldsymbol{\theta}}_F + \mathbf{l}_F \times (\mathbf{m}_F \cdot \mathbf{g}) + \mathbf{l}_w \times \mathbf{F} - \boldsymbol{\tau}_m + \mathbf{B}_w \dot{\boldsymbol{\theta}}_w \quad [\text{N} \cdot \text{m}] \quad (1)$$

$$\begin{aligned} \tau_m[n] = & -8,314 \cdot e_\theta[n] + 7,422 \cdot e_\theta[n-1] + 8,3023 \cdot e_\theta[n-2] \\ & -7,434 \cdot e_\theta[n-3] + 1,382 \cdot \tau_m[n-1] - 0,3415 \cdot \tau_m[n-2] \\ & -0,001\,638 \cdot \tau_m[n-3] \end{aligned} \quad [\text{N} \cdot \text{m}] \quad (2)$$