

21/01/2024

Telecommunication Software

Report 4

Exemple 1-5 – Page 2 and Annex

Example 6 – Page 2

Annex – Page 4

Jehanne Sarrazin

230AEM053

For this whole practical exercise, you can find my work in the GitHub repository: <https://github.com/Niennaaa/TelecommunicationSoftware>

Example 1 to 5:

For this report, you can find my work on the example 1 to 5 and comments in the Annex page 4. You can also find it in the associated PDF file inside the same folder along with the corresponding notebook containing the python code.


Example 6:

For the Example 6, I chose to complete the University Ranking work. You can find the python project for it in the folder “scrapyWork” and run it by opening it in VSCode and running in its terminal:

```
cd scrapyWork
scrapy crawl uni
```

You will see that it will import the data from the university ranking and log it into a text file that will be automatically opened at the end of the run.

Here is the spider used:

The image shows a screenshot of the Visual Studio Code (VS Code) editor interface. On the left, the Explorer sidebar displays the project structure for 'scrapyWork'. The 'spiders' folder is expanded, showing 'mySpider.py' as the active file. The main editor area displays the code for 'UniSpider.py'. The code imports 'scrapy' and 'ScrapyworkItem' from '..items'. It defines a 'UniSpider' class that inherits from 'scrapy.Spider'. The class has a 'name' attribute set to 'uni' and a 'start_urls' list containing a URL from 'shanghairanking.com'. The 'parse' method iterates over the response's CSS selector 'tr[data-v-ae1ab4a8]', extracts the university name, rank, and score, and yields a 'ScrapyworkItem' object. A log statement is also present for each item.

```
1 import scrapy
2 from ..items import ScrapyworkItem
3
4 class UniSpider(scrapy.Spider): #Use "scrapy crawl uni" to run and create a txt file
5     name = "uni"
6     start_urls = ["https://www.shanghairanking.com/rankings/arwu/2023"]
7
8     def parse(self, response):
9         for row in response.css('tr[data-v-ae1ab4a8]'):
10             item = ScrapyworkItem()
11             #All the data we want :
12             item['univname'] = row.css('td.align-left div.global-univ span.univ-name::text').get()
13             item['rank'] = row.css('td div.ranking::text').get()
14             item['score'] = row.css('td:nth-child(5)::text').get()
15
16             #self.log(f"university name: {item['univname']}")
17             yield item
18
19
```

The pipeline.py file used to saved the result as a txt document:

```

9  from itemadapter import ItemAdapter
10
11
12  class ScrapyworkPipeline:
13      def process_item(self, item, spider):
14          return item
15
16  class TxtExportPipeline: #Create a txt file in which the data is saved
17      def __init__(self):
18          self.file = open('UnivRanking.txt', 'w')
19
20      def process_item(self, item, spider):
21          cleaned_univname = item['univname'].replace('\n', ' ')
22          cleaned_rank = item['rank'].replace('\n', ' ')
23          cleaned_score = item['score'].replace('\n', ' ')
24
25          line = f"University: {cleaned_univname}, Rank: {cleaned_rank}, Score: {cleaned_score}\n"
26          self.file.write(line)
27          return item
28
29      def close_spider(self, spider):
30          self.file.close()
31          #Open the file automatically to the user (optional) :
32          subprocess.run(['start', 'UnivRanking.txt'], check=True, shell=True)

```

And the result:

```

1  University: Harvard University , Rank: 1 , Score: 100.0
2  University: Stanford University , Rank: 2 , Score: 74.8
3  University: Massachusetts Institute of Technology (MIT) , Rank: 3 , Score: 69.1
4  University: University of Cambridge , Rank: 4 , Score: 67.9
5  University: University of California, Berkeley , Rank: 5 , Score: 63.4
6  University: Princeton University , Rank: 6 , Score: 60.1
7  University: University of Oxford , Rank: 7 , Score: 59.5
8  University: Columbia University , Rank: 8 , Score: 55.3
9  University: California Institute of Technology , Rank: 9 , Score: 54.5
10 University: University of Chicago , Rank: 10 , Score: 53.8
11 University: Yale University , Rank: 11 , Score: 52.2
12 University: Cornell University , Rank: 12 , Score: 50.5
13 University: University of California, Los Angeles , Rank: 13 , Score: 48.0
14 University: University of Pennsylvania , Rank: 14 , Score: 47.7
15 University: Paris-Saclay University , Rank: 15 , Score: 47.0
16 University: Johns Hopkins University , Rank: 16 , Score: 46.8
17 University: University College London , Rank: 17 , Score: 45.9
18 University: University of Washington , Rank: 18 , Score: 45.4
19 University: University of California, San Diego , Rank: 19 , Score: 44.8
20 University: ETH Zurich , Rank: 20 , Score: 44.1

```

Annex:

```

In [2]: #Exemple 1
#Test requests Python Library, including seven types of methods
#and 13 parameters to control access

"""
From the class :
7 METHODS
requests.request() constructs a request that supports the basic methods of the foll
requests.get() The main method for obtaining HTML pages corresponding to HTTP GET
requests.head() The method to obtain the header information of HTML pages, correspo
requests.post() Method for submitting POST requests to HTML pages, corresponding to
requests.put() The method of submitting a PUT request to an HTML page, correspondin
requests.patch() Submit a partial modification request to an HTML page, correspondi
requests.delete() Submit a delete request to the HTML page, corresponding to HTTP D

13 PARAMETERS
params: dictionary or byte sequence, added to the url as a parameter
data: dictionary, byte sequence or file object, as the content of the Request
JSON : data in JSON format, as the content of Request
headers: dictionary, HTTP custom headers
cookies: dictionary or CookieJar, cookies in Request
auth: tuple, support HTTP authentication function
files: dictionary type, transfer files
timeout: Set the timeout time in seconds
proxies: dictionary type, set the access proxy server, you can add login authentica
allow_redirects: True/False, the default is True, redirect switch
stream: True/False, the default is True, get the content immediately download switc
verify: True/False, the default is True, verify the SSL certificate switch
cert: local SSL certificate path

"""

#The 7 methods :
import requests
r1 = requests.request('GET',"http://httpbin.org/get")
r2 = requests.get("http://httpbin.org/get")
r3 = requests.head("http://httpbin.org/get")
r4 = requests.post("http://httpbin.org/post")
r5 = requests.put("http://httpbin.org/put")
r6 = requests.patch("http://httpbin.org/patch")
r7 = requests.delete("http://httpbin.org/delete")
r = [r1, r2, r3, r4, r5, r6, r7]
equi = ["REQUEST", "GET", "HEAD", "POST", "PUT", "PATCH", "DELETE"]
n = 0
for rr in r:
    try :
        rr.raise_for_status()
        rr.encoding = rr.apparent_encoding
        print("\n" + equi[n]+ " : ")
        print(rr.text[0:600])
        print(rr.status_code)
        print(rr.encoding)
        print("\n")
        n=n+1

```

```

except :
    print("Not this one :" + str(rr))
    n=n+1

url = "http://httpbin.org/get"
kv = {'key1':'value1', 'key2':'value2'}
body = "content"

#The 13 parameters :
r1 = requests.get(url, params = kv)
r2 = requests.get(url, data = kv)
r3 = requests.get(url, json = body)
r4 = requests.get(url, headers = kv)
r5 = requests.get(url, cookies = kv)
r6 = requests.get(url, auth = ('user', 'pass'))
r7 = requests.get(url, files = kv)
r8 = requests.get(url, timeout = 100)
r9 = requests.get(url, proxies = kv)
r10 = requests.get(url, allow_redirects = False)
r11 = requests.get(url, stream = False)
r12 = requests.get(url, verify = False)
#r13 = requests.get(url, cert = ('client.cert', 'client.key'))
r = [r1, r2, r3, r4, r5, r6, r7, r8, r9, r10, r11, r12]
equi = ["PARAMS", "DATA", "JSON", "HEADERS", "COOKIES", "AUTH", \
        "FILES", "TIMEOUT", "PROXIES", "ALLOW_REDIRECTS", "STREAM", "VERIFY", "CERT"]
n = 0
for rr in r:
    try :
        rr.raise_for_status()
        rr.encoding = rr.apparent_encoding
        print("\n" + equi[n] + " : ")
        print(rr.text[0:600])
        print(rr.status_code)
        print(rr.encoding)
        print("\n")
        n=n+1
    except :
        print("Not this one :" + str(rr))
        n=n+1

```

REQUEST :

```
{
  "args": {},
  "headers": {
    "Accept": "*/*",
    "Accept-Encoding": "gzip, deflate, br",
    "Host": "httpbin.org",
    "User-Agent": "python-requests/2.31.0",
    "X-Amzn-Trace-Id": "Root=1-65a7b2bf-26d8457035e0f3753fa23f80"
  },
  "origin": "85.254.221.245",
  "url": "http://httpbin.org/get"
}
```

200

ascii

GET :

```
{
  "args": {},
  "headers": {
    "Accept": "*/*",
    "Accept-Encoding": "gzip, deflate, br",
    "Host": "httpbin.org",
    "User-Agent": "python-requests/2.31.0",
    "X-Amzn-Trace-Id": "Root=1-65a7b2c0-635c5c5f71813c467bf73a62"
  },
  "origin": "85.254.221.245",
  "url": "http://httpbin.org/get"
}
```

200

ascii

HEAD :

200

None

POST :

```
{
  "args": {},
  "data": "",
  "files": {},
  "form": {},
  "headers": {
    "Accept": "*/*",
    "Accept-Encoding": "gzip, deflate, br",
    "Content-Length": "0",
    "Host": "httpbin.org",

```

```
    "User-Agent": "python-requests/2.31.0",
    "X-Amzn-Trace-Id": "Root=1-65a7b2c0-71303cbf6ddaccc03662c892"
  },
  "json": null,
  "origin": "85.254.221.245",
  "url": "http://httpbin.org/post"
}
```

200
ascii

PUT :

```
{
  "args": {},
  "data": "",
  "files": {},
  "form": {},
  "headers": {
    "Accept": "*/*",
    "Accept-Encoding": "gzip, deflate, br",
    "Content-Length": "0",
    "Host": "httpbin.org",
    "User-Agent": "python-requests/2.31.0",
    "X-Amzn-Trace-Id": "Root=1-65a7b2c0-04dec382eaac969034cf598"
  },
  "json": null,
  "origin": "85.254.221.245",
  "url": "http://httpbin.org/put"
}
```

200
ascii

PATCH :

```
{
  "args": {},
  "data": "",
  "files": {},
  "form": {},
  "headers": {
    "Accept": "*/*",
    "Accept-Encoding": "gzip, deflate, br",
    "Content-Length": "0",
    "Host": "httpbin.org",
    "User-Agent": "python-requests/2.31.0",
    "X-Amzn-Trace-Id": "Root=1-65a7b2c0-0f97d29c25ed5fc8000d6e28"
  },
  "json": null,
  "origin": "85.254.221.245",
  "url": "http://httpbin.org/patch"
}
```

200
ascii

DELETE :

```
{
  "args": {},
  "data": "",
  "files": {},
  "form": {},
  "headers": {
    "Accept": "*/*",
    "Accept-Encoding": "gzip, deflate, br",
    "Content-Length": "0",
    "Host": "httpbin.org",
    "User-Agent": "python-requests/2.31.0",
    "X-Amzn-Trace-Id": "Root=1-65a7b2c1-435216581805d3ec32235b5a"
  },
  "json": null,
  "origin": "85.254.221.245",
  "url": "http://httpbin.org/delete"
}
```

200
ascii

PARAMS :

```
{
  "args": {
    "key1": "value1",
    "key2": "value2"
  },
  "headers": {
    "Accept": "*/*",
    "Accept-Encoding": "gzip, deflate, br",
    "Host": "httpbin.org",
    "User-Agent": "python-requests/2.31.0",
    "X-Amzn-Trace-Id": "Root=1-65a7b2c1-6a18bea64395b5be20591cc0"
  },
  "origin": "85.254.221.245",
  "url": "http://httpbin.org/get?key1=value1&key2=value2"
}
```

200
ascii

DATA :

```
{
  "args": {},
  "headers": {
    "Accept": "*/*",
```



```
    "Accept-Encoding": "gzip, deflate, br",
    "Content-Length": "23",
    "Content-Type": "application/x-www-form-urlencoded",
    "Host": "httpbin.org",
    "User-Agent": "python-requests/2.31.0",
    "X-Amzn-Trace-Id": "Root=1-65a7b2c2-1d6d22e338d0d2fc33819d82"
  },
  "origin": "85.254.221.245",
  "url": "http://httpbin.org/get"
}
```

200
ascii

JSON :

```
{
  "args": {},
  "headers": {
    "Accept": "*/*",
    "Accept-Encoding": "gzip, deflate, br",
    "Content-Length": "9",
    "Content-Type": "application/json",
    "Host": "httpbin.org",
    "User-Agent": "python-requests/2.31.0",
    "X-Amzn-Trace-Id": "Root=1-65a7b2c2-19434aa4427922147ad84019"
  },
  "origin": "85.254.221.245",
  "url": "http://httpbin.org/get"
}
```

200
ascii

HEADERS :

```
{
  "args": {},
  "headers": {
    "Accept": "*/*",
    "Accept-Encoding": "gzip, deflate, br",
    "Host": "httpbin.org",
    "Key1": "value1",
    "Key2": "value2",
    "User-Agent": "python-requests/2.31.0",
    "X-Amzn-Trace-Id": "Root=1-65a7b2c2-1147fd977327c3f2398f43f7"
  },
  "origin": "85.254.221.245",
  "url": "http://httpbin.org/get"
}
```

200
ascii

COOKIES :

```
{
  "args": {},
  "headers": {
    "Accept": "*/*",
    "Accept-Encoding": "gzip, deflate, br",
    "Cookie": "key1=value1; key2=value2",
    "Host": "httpbin.org",
    "User-Agent": "python-requests/2.31.0",
    "X-Amzn-Trace-Id": "Root=1-65a7b2c2-619f18db286258f97e5cd17c"
  },
  "origin": "85.254.221.245",
  "url": "http://httpbin.org/get"
}
```

200

ascii

AUTH :

```
{
  "args": {},
  "headers": {
    "Accept": "*/*",
    "Accept-Encoding": "gzip, deflate, br",
    "Authorization": "Basic dXNlcjpwYXNz",
    "Host": "httpbin.org",
    "User-Agent": "python-requests/2.31.0",
    "X-Amzn-Trace-Id": "Root=1-65a7b2c3-27908f461e708adc7120354c"
  },
  "origin": "85.254.221.245",
  "url": "http://httpbin.org/get"
}
```

200

ascii

FILES :

```
{
  "args": {},
  "headers": {
    "Accept": "*/*",
    "Accept-Encoding": "gzip, deflate, br",
    "Content-Length": "254",
    "Content-Type": "multipart/form-data; boundary=73e3b624c4822ba47fadb8cd6ffa8a55",
    "Host": "httpbin.org",
    "User-Agent": "python-requests/2.31.0",
    "X-Amzn-Trace-Id": "Root=1-65a7b2c3-4f491ab302d79f146745264a"
  },
  "origin": "85.254.221.245",

```

```
"url": "http://httpbin.org/get"
}
```

```
200
ascii
```

TIMEOUT :

```
{
  "args": {},
  "headers": {
    "Accept": "*/*",
    "Accept-Encoding": "gzip, deflate, br",
    "Host": "httpbin.org",
    "User-Agent": "python-requests/2.31.0",
    "X-Amzn-Trace-Id": "Root=1-65a7b2c3-059f9b027ff33a4b17eb1b82"
  },
  "origin": "85.254.221.245",
  "url": "http://httpbin.org/get"
}
```

```
200
ascii
```

PROXIES :

```
{
  "args": {},
  "headers": {
    "Accept": "*/*",
    "Accept-Encoding": "gzip, deflate, br",
    "Host": "httpbin.org",
    "User-Agent": "python-requests/2.31.0",
    "X-Amzn-Trace-Id": "Root=1-65a7b2c3-796c0e0a4927d8cb41a0448a"
  },
  "origin": "85.254.221.245",
  "url": "http://httpbin.org/get"
}
```

```
200
ascii
```

ALLOW_REDIRECTS :

```
{
  "args": {},
  "headers": {
    "Accept": "*/*",
    "Accept-Encoding": "gzip, deflate, br",
    "Host": "httpbin.org",
    "User-Agent": "python-requests/2.31.0",
    "X-Amzn-Trace-Id": "Root=1-65a7b2c4-5a67cea645ca368b323ab8f9"
  },
}
```

```
"origin": "85.254.221.245",  
"url": "http://httpbin.org/get"  
}
```

```
200  
ascii
```

```
STREAM :  
{  
  "args": {},  
  "headers": {  
    "Accept": "*/*",  
    "Accept-Encoding": "gzip, deflate, br",  
    "Host": "httpbin.org",  
    "User-Agent": "python-requests/2.31.0",  
    "X-Amzn-Trace-Id": "Root=1-65a7b2c4-2bc46d3632957bfd753a0f33"  
  },  
  "origin": "85.254.221.245",  
  "url": "http://httpbin.org/get"  
}
```

```
200  
ascii
```

```
VERIFY :  
{  
  "args": {},  
  "headers": {  
    "Accept": "*/*",  
    "Accept-Encoding": "gzip, deflate, br",  
    "Host": "httpbin.org",  
    "User-Agent": "python-requests/2.31.0",  
    "X-Amzn-Trace-Id": "Root=1-65a7b2c5-6e699a1829675a4d60c46f85"  
  },  
  "origin": "85.254.221.245",  
  "url": "http://httpbin.org/get"  
}
```

```
200  
ascii
```

```
In [3]: #Exemple 2  
        #Search engine keyword submission interface with requests python Library.  
  
import requests  
keyword = "meme"  
try :  
    kv = {'q':keyword} #I followed the same logic as the one we've seen in the Lect  
    r = requests.get("http://www.bing.com/search", params = kv)  
    print(r.request.url)
```

```

    r.raise_for_status()
    print(len(r.text))
except :
    print("Abnormal detected")

print(r.status_code)
print(r.encoding)

```

<http://www.bing.com/search?q=meme>
 81755
 200
 utf-8

In [4]:

```

#Exemple 3
# Image crawling.
import requests
import os
url = "https://i.imgflip.com/2ghngj.jpg"
root = "C:/Users/Jehanne/Downloads/"
path = root+url.split("/")[-1]

#I followed the same logic as seen in class
if not os.path.exists(root):
    os.mkdir(root)
if not os.path.exists(path):#Get image
    r = requests.get(url)
    with open(path, "wb") as f :
        f.write(r.content) #Save it
        f.close()
        print("File saved")
else :
    print("File already exist")

```

File already exist

In [14]:

```

#Exemple 4
#University ranking print

"""

#Input: University ranking URL link
Link: https://www.shanghairanking.com/rankings/arwu/2023

#Output: Screen output of university ranking information (rank, #university name, t

#Technical route: requests-bs4 or requests-lxml

#Step 1: Obtain university ranking webpage content from the web
#Step 2: Extract the information in the web page content into a suitable data struc
#Step 3: Use data structures to display and output results

"""

import requests
from bs4 import BeautifulSoup
import bs4
import re

```

```

import pandas as pd

#We will output the result as a pandas dataframe
header = ["Rank", "University", "Score"]
result = pd.DataFrame(columns = header)
r = requests.get("https://www.shanghairanking.com/rankings/arwu/2023")
demo = r.text
soup = BeautifulSoup(demo, 'html.parser')

for tr in soup.find('tbody').children:
    if isinstance(tr, bs4.element.Tag):
        tds = tr('td')
        #First I get the data :
        rank = tds[0].find_all(string = re.compile(''))[-1].replace("\n", "")
        university = tds[1].find_all(string = re.compile(''))[-1]
        score = tds[4].find_all(string = re.compile(''))[-1].replace("\n", "")
        #Then I add it to my result
        result.loc[len(result)] = [rank, university, score]
print(result)

```

	Rank	University	Score
0	1	Harvard University	100.0
1	2	Stanford University	74.8
2	3	Massachusetts Institute of Technology (MIT)	69.1
3	4	University of Cambridge	67.9
4	5	University of California, Berkeley	63.4
5	6	Princeton University	60.1
6	7	University of Oxford	59.5
7	8	Columbia University	55.3
8	9	California Institute of Technology	54.5
9	10	University of Chicago	53.8
10	11	Yale University	52.2
11	12	Cornell University	50.5
12	13	University of California, Los Angeles	48.0
13	14	University of Pennsylvania	47.7
14	15	Paris-Saclay University	47.0
15	16	Johns Hopkins University	46.8
16	17	University College London	45.9
17	18	University of Washington	45.4
18	19	University of California, San Diego	44.8
19	20	ETH Zurich	44.1
20	21	University of California, San Francisco	44.0
21	22	Tsinghua University	40.3
22	23	Imperial College London	39.9
23	24	University of Toronto	39.7
24	25	Washington University in St. Louis	39.0
25	26	University of Michigan-Ann Arbor	37.8
26	27	The University of Tokyo	37.7
27	28	New York University	37.3
28	29	Peking University	36.7
29	30	Northwestern University	35.8

In [21]: *#Example 5:*
#Crawling of goods web pages and printing relevant numbers, goods names, and prices

```

import requests

```

```

from bs4 import BeautifulSoup
import bs4
import re
import pandas as pd

#I created this function to work with aliexpress.com
#It was a challenge because the place of the price changes based on the reductions
keyword = "plushie"
url = "https://www.aliexpress.com/w/wholesale-"+keyword+".html?spm=a2g0o.productlis

try :
    r = requests.get(url)
    print(r.request.url)
    soup = BeautifulSoup(r.text, 'html.parser')
    prettified= soup.prettify()

except :
    print("Abnormal detected")

soup0 = soup.find_all(class_="multi--content--11nFIBL")

alllist = []
index = 0
name = []
prices = []
rating = []
headers = ["Name", "Price", "Rating"]
results = pd.DataFrame(columns =headers)
for div in soup0:
    #I get all the data i need :
    alllist.append(div.get_text(separator=';', strip=True).split(";"))
    name.append(alllist[index][0])

    price = alllist[index][2]+alllist[index][3]+alllist[index][4]+alllist[index][5]
    prices.append(price)

    if len(alllist[index][-3])>3:
        rating.append(None)
    else :
        rating.append(alllist[index][-3])

    index+=1

    #And add it to my result

for i in range(len(name)):
    results.loc[i] = [name[i], prices[i], rating[i]]
print(results)

```

<https://www.aliexpress.com/w/wholesale-plushie.html?spm=a2g0o.productlist.search.0>

	Name	Price	Rating
0	Bat Plush Toy manta Kawaii Animal Creative Plu...	€0.63	93%
1	18cm FNAF Stuffed Plush Toys Freddy Fazbear Be...	€1.27	92%
2	Original Sanrio Plushies Hello Kitty Cinnamonr...	€3.08	75%
3	Skzoo Plush Toys 20cm Stray Kids Plush Wolf Ch...	€0.46	95%
4	Gaint White Goose Plush Toy Super Soft Goose S...	€20.7	None
5	40-50cm Sanrio Pompompurin Stuffed Plush Toys ...	€23.54	68%
6	Genshin Game Anime Figure Doll Fluffy Cat Plus...	€1.31	87%
7	20cm We Bare Bears Cartoon Plush Toys Standing...	€0.7	95%
8	Cuddly Little Cat Plush Pendant Toy Fluffy Kit...	€0.46	94%
9	Angry Blob Seal Pillow Popular Soft Chubby 3D ...	€3.2	59%

In []: *#Example 6:*

#See in project report, this was done in VScode