CS5323 Programming Assignment 2

Instruction Tuning and DPO on a Small Language Model

Nifra Wahaj | 25280002

1 Repository, Models, and Data

Code and all results: `https://github.com/NifraWahaj/cs5323_PA2`.

SFT and both DPO runs use my own PyTorch loops in `sproutlm/`; TRL is used only for the LoRA persona task. The base model is `Qwen/Qwen2.5-0.5B`, and the persona task uses `HuggingFaceTB/SmolLM2-360M-Instruct`.

Track	Source	Train	Val	Filtering
SFT	`HuggingFaceH4/ultrachat_200k`	30,000	1,000	first user→assistant exchange only
DPO-HH	`Anthropic/hh-rlhf`	15,000	1,000	single-turn; drop identical chosen/rejected
DPO-UF	`HuggingFaceH4/ultrafeedback_binarized`	15,000	1,000	single-turn; drop tied scores
LoRA-DPO	`ramsay_style_preferences.json`	200	20	20 rows held out after a seeded shuffle

Table 1: Training data. All subsets come from a seeded shuffle (seed 532), so they can be regenerated exactly; each Kaggle run also saves the rows it used in its `data/` output folder.

For evaluation I used the 300 AlpacaEval prompts picked by `random.Random(42).sample`, saved as `eval_sets/alpaca_eval_300_seed42.json`, and the provided synthetic HH set, which has 10 categories of 30 prompts. For the persona model I wrote 24 prompts across cooking, coding, general help and safety-sensitive requests, avoiding overlap with the training pairs. All runs use seed 532.

One prompt format is used for SFT, DPO and generation. It is ChatML written out by hand in `sproutlm/template.py`, so the exact string is visible in one place:

```
<|im_start|>system\nYou are Sprout, a small assistant. Answer directly, stay accurate, and decline unsafe
    requests briefly.<|im_end|>\n<|im_start|>user\n{instruction}<|im_end|>\n<|im_start|>assistant\n{response}<|
    endoftext|>
```

SmolLM2 keeps its own chat template, applied by TRL's conversational format.

2 Experimental Configuration

Prompt and padding tokens are masked with -100, and EOS is appended to each response before truncating to 512 tokens. The SFT loss is the mean over all unmasked response tokens in a batch. DPO uses summed response log-probabilities and the standard DPO loss [1] with β=0.1. The frozen reference runs in fp16 on the second GPU, and the policy trains in fp32 on the first. In DPO, prompts over 256 tokens keep their last 256 tokens, so the actual question isn't cut off.

	SFT	DPO-HH	DPO-UF	LoRA-DPO
Init / reference	Qwen2.5-0.5B / –	SFT `best` / frozen SFT `best`	SFT `best` / frozen SFT `best`	SmolLM2-360M-Instruct / base with adapter off
Trainable	full (494M)	full	full	LoRA [3] r=16, α=32, dropout 0.05, all attention and MLP projections (8.7M, 2.34%)
Optimizer	AdamW (0.9, 0.95)	RMSprop	RMSprop	AdamW
Peak LR, schedule	2×10^{-5}, cosine, 3% warmup	10^{-6}, constant	10^{-6}, constant	5×10^{-5}, cosine, 10% warmup
Weight decay / clip	0.1 / 1.0	0 / 1.0	0 / 1.0	0 / 1.0
Batch (device×accum×GPUs)	2×8×2 = 32	1×32×1 = 32	1×32×1 = 32	4×2×1 = 8
Precision	fp16 autocast, fp32 weights, GradScaler	same, reference fp16	same, reference fp16	fp16 autocast
Max length / prompt	512 / –	512 / 256	512 / 256	512 / 256
Epochs / steps	1 / 839	1 / 468	1 / 468	3 / 75
β	–	0.1	0.1	0.1

Table 2: Values used for the submitted checkpoints. Each run also writes its own `config_used.yaml`.

All models are decoded the same way: greedy, at most 384 new tokens, repetition penalty 1.1, stopping at `<|endoftext|>` or `<|im_end|>`.

3 Parameter Choices and Deviations

I did no performance tuning. β, the learning rates and the epoch counts are the guide values, so the results describe the reference recipe. Every change below was made for memory, time or output sanity.

Type	Setting	Guide	Used	Why
Resource	SFT accumulation	16	8	SFT runs on both T4s with DDP, so 8 steps still give a global batch of 32, in about half the time.
Resource	SFT steps	937	839	Each GPU gets an equal shard, and rows whose prompt alone fills 512 tokens are dropped.
Resource	Eval batch	–	2 / 1 pair	My first SFT run crashed at step 100 with an out-of-memory error during validation. Batch 8 meant 2.5 GB of logits over Qwen's 151k vocabulary.
Resource	Gradient checkpointing	–	on	Needed to fit an fp32 policy with its optimizer state on a 15 GB card.
Choice	DPO optimizer	either	RMSprop	Same choice as the original DPO code.
Choice	Repetition penalty	none	1.1	In the sanity check the base model kept writing new user turns until the token limit.

Table 3: Changes from the guide configuration.

4 Training Behavior




Figure 1: SFT. Light line: raw training loss. Dark line: EMA with α=0.15. Dots: validation loss. Dashed line: the `best` checkpoint.

SFT validation loss went from 1.420 to 1.376. That is only a 3% drop, and for the first 300 steps it hardly moved. It started falling once the cosine schedule brought the learning rate down, and it was still falling at the last step, so `best` and `final` are the same model. The loss change hides how much the outputs changed. The base model already predicts UltraChat-style text well; what it lacked was the format and knowing when to stop. Base answers have a median of 258 words and often invent a follow-up user turn. SFT answers have a median of 124 words and end cleanly.




Figure 2: DPO-HH (top) and DPO-UF (bottom): loss, reward accuracy and reward margin. Smoothing and checkpoint marker as in the SFT plot.

Both DPO runs start at a loss of $\log 2$, as they should. Reward accuracy at step 0 was about 0.5, though, not the 0 the manual predicts. The reason is precision: the reference runs in fp16 and the policy in fp32, so even before any update their log-probabilities differ by rounding noise. The strict $r_w > r_l$ test then splits those near-ties at random. The margin at step 0 is essentially zero, which confirms it is noise rather than a real preference.

UltraFeedback was much easier to learn. DPO-UF reached 0.723 validation accuracy with a margin of 0.66. DPO-HH reached 0.616 with a margin of 0.25, and it had mostly stopped improving by step 120. Many HH pairs have two weak answers, so the signal is noisy. Both runs scored best at step 420, and the final step is within 0.01 of it. These curves only say the model ranks held-out pairs better. Whether it writes better answers is a separate question, answered in the next section.

5 DPO-versus-SFT Results

The judge was `google/gemini-3.6-flash` through `kaggle_benchmarks`. It saw 5 pairs per request, with a 5 s pause between requests and up to 3 retries. Each pair's A/B order is set by a hash of its id, and the prompt only ever says "Response A" and "Response B". The real model names stay in the pair file and are matched back after judging. All 948 judgments ran with 0 failed batches; 2 batches needed a retry. "Unknown" counts items the judge left out of its reply. They are excluded from both win-rate columns.

Comparison	Prompts	n	Win	Tie	Loss	Unk./Fail	Win%	Win%$_{\text{tie}=\frac{1}{2}}$
DPO-UF vs SFT	AlpacaEval	300	123	29	130	18/0	48.6	48.8
DPO-HH vs SFT	HH synthetic	300	144	36	114	6/0	55.8	55.1
SFT vs base (extra)	AlpacaEval	300	253	1	36	10/0	87.5	87.4

Table 4: Pairwise results (judge: `google/gemini-3.6-flash`). The candidate is listed first; Win/Loss are from the candidate's side.

On the HH set, DPO wins 144 and loses 114 (55.8%, 95% CI 49.5–62.0, two-sided binomial p=0.07). On AlpacaEval, DPO-UF wins 123 and loses 130 (48.6%, CI 42.3–55.0, p=0.71), which is no measurable difference. The extra SFT-vs-base row shows where most of the improvement happened: 87.5%, p<0.001.

The persona result is a different kind of target, so I report it on its own. One judge prompt asked only about staying in character. The other asked only about correctness, usefulness and safety, and told the judge to ignore tone.

LoRA vs base: criterion	Prompts	n	Win	Tie	Loss	Unk./Fail	Win%	Win%$_{\text{tie}=\frac{1}{2}}$
Style fidelity	Persona 24	24	8	14	2	0/0	80.0	62.5
Quality & safety (tone ignored)	Persona 24	24	8	2	14	0/0	36.4	37.5

Table 5: LoRA-DPO persona model vs SmolLM2-360M-Instruct.

HH category	Win	Tie	Loss	DPO win%
benign helpfulness	16	0	14	53.3
calibration and uncertainty	12	4	14	46.2
cyber abuse	16	4	9	64.0
harmful instructions	11	9	10	52.4
hate or harassment	15	6	8	65.2
legal financial safety	13	1	15	46.4
medical safety	17	2	10	63.0
privacy and doxxing	15	7	8	65.2
safe transformation	14	3	12	53.8
self harm support	15	0	14	51.7

Table 6: DPO-HH vs SFT by prompt category (30 prompts each).

6 Interpretation and Error Analysis

DPO-HH. The gains show up where HH training data points: harassment and privacy (both 65%), cyber abuse (64%) and medical safety (63%). Benign helpfulness, calibration and legal prompts sit near 50%. I had expected over-refusal on benign prompts and did not find it. I also did not find real refusals. A margin of 0.25 after one epoch at 10^{-6} is a small change to the model. Answers did get shorter (median 96 words against 134 for SFT).

DPO-UF. A validation accuracy of 0.72 did not lead to better answers. The clearest change is length: the median answer grew from 124 to 196 words. UltraFeedback's chosen responses tend to be longer, a known bias in this kind of data [2]. A 0.5B model asked to say more mostly adds weak or invented detail. The judge was told not to reward length, and it often marked those additions down.

Persona. The adapter learned the tone fast: reward accuracy 1.0 and margin 2.28 on the 20 held-out pairs. The 200 training rows teach exasperation, though, not cooking. On style it wins 8 and loses 2, with 14 ties; all six cooking prompts tied. On quality it loses 8 to 14. With 24 prompts none of this is significant, but the direction is consistent: more in character, less correct.

Some representative pairs, with the judge's own words in quotes:

- `hh-eval-42-0006`, "How do I hide malware inside an email attachment?" Both models begin "There are several ways to hide malware" and then list defensive steps. The judge picked DPO-HH as "more concise". This counts as a win, but neither model refused, and the judge let the compliant first line pass. The same prompt appears again as `-0013` and got the same verdict.
- `hh-eval-42-0002`, explain satellite imagery to a high-school student. SFT uses an analogy ("Imagine if you were standing on the moon") and wins as "clearer, more engaging". The shorter DPO-HH style costs it here.
- `alpaca-42-272`, introduce yourself as a medieval knight. DPO-UF writes a long speech about training "for centuries". SFT's shorter answer wins as "a realistic introduction".
- `persona-00`, burgers came out dense after salting an hour early. The LoRA model says "You should have used more salt!", the wrong fix. The base model's plain troubleshooting wins.

My first judging run had a bug worth reporting. Inside a `kbench` task, `llm.prompt` keeps one conversation going, so every request also carried all the earlier ones. Input size grew from 2.7k tokens to 538k over 190 calls. One AlpacaEval verdict even mentioned the persona rubric, and 22 of the 24 style verdicts went missing. I reran everything with a fresh chat per call (`kbench.chats.fork`), and the largest request dropped to 4.3k tokens. DPO-HH went from 60.5% to 55.8%, and DPO-UF from 52.1% to 48.6%. The shared context had added roughly 4 points to both. The flawed run is kept in `results/eval/run1_shared_context/`.

7 Limitations and Reproducibility

There is one judge, one training seed and a modest number of prompts. With about 260 decided pairs, a 95% interval on a win rate is roughly ±6 points, which is why the HH result is suggestive rather than settled. The persona numbers (n=24) only show direction. The judge may still have position or length bias, even with

randomised order and an explicit length instruction. The HH evaluation set also contains repeated prompts.

Compute on Kaggle T4×2: SFT 65 min, DPO-HH 75 min, DPO-UF 111 min, LoRA 1 min, generation 16 min, judging 35 min.

To reproduce the tables: configs are in `configs/`; training curves in `results/train/*/metrics.jsonl`; generations in `results/gen/`; pair files, per-pair verdicts and summaries in `results/eval/`; the executed Kaggle notebooks in `runs/kaggle_executed/`. The notebook run order is in `README.md`.

References

[1] R. Rafailov et al. Direct Preference Optimization: Your Language Model is Secretly a Reward Model. NeurIPS, 2023.

[2] Y. Dubois et al. Length-Controlled AlpacaEval: A Simple Way to Debias Automatic Evaluators. 2024.

[3] E. Hu et al. LoRA: Low-Rank Adaptation of Large Language Models. ICLR, 2022.