Database ER diagram (crow's foot)

Jonathan Hirsch | December 10, 2020

bookings

PK	book_id	SERIAL PRIMARY KEY
FK	customer_id	integer NOT NULL
Key	book_date	timestamp
Key	card_no	integer NOT NULL
Key	total	float(10) NOT NULL
Key	taxes	float(7) NOT NULL

customers

PK	customer_id	SERIAL PRIMARY KEY
Key	customer_name	text NOT NULL
Key	customer_email	varchar(30) UNIQUE
Key	password	text NOT NULL
Key	city	char(20)

tickets

PK	ticket_id	SERIAL PRIMARY KEY
FK	flight_id	integer NOT NULL
FK	passenger_id	integer NOT NULL
Key	ticket_cost	integer
Key	waitlist_no	integer
FK	boarding_pass_id	integer

passengers

PK	passenger_id	SERIAL PRIMARY KEY
FK	book_id	integer NOT NULL
Key	passenger_name	text NOT NULL
Key	phone	char(15)
Key	email	varchar(30)

baggages

PK	bag_id	SERIAL PRIMARY KEY
FK	passenger_id	integer NOT NULL
Key	weight	float(7)

flights

PK	flight_id	SERIAL PRIMARY KEY
FK	aircraft_code	char(3) NOT NULL
Key	scheduled_departure	timestamp
Key	scheduled_arrival	timestamp
FK	departure_airport_id	char(3) NOT NULL
FK	arrival_airport_id	char(3) NOT NULL
FK	departure_gate_id	char(3) NOT NULL
FK	arrival_gate_id	char(3) NOT NULL
Key	status	character varying(20)
Key	waitlist_no	integer
Key	seats_available	integer
Key	movie	bool
Key	meal	bool
Key	flight_cost	float(7)

boarding_passes

PK	boarding_pass_id	SERIAL PRIMARY KEY
FK	boarding_gate	char(3) NOT NULL
Key	boarding_time	timestamp

aircrafts_in_service

PK	aircraft_code	char(3) NOT NULL
FK	model	char(25) NOT NULL

airports

PK	airport_id	char(3) NOT NULL
Key	airport_name	char(40) NOT NULL
Key	city	char(20) NOT NULL

aircraft_details

PK	model	char(25) NOT NULL
Key	max_seats	integer
Key	has_screens	bool
Key	has_kitchen	bool

gates

PK	gates	char(3) NOT NULL