

1. INSTRUCTION:


THIS SHEET IS THE STATEMENT OF THE LEAD-FREE THICK FILM CHIP RESISTORS SPECIFICATION THAT UNIOHMS' PRODUCTIONS CAN MEET.

2. RATING:

TYPE		0402	0603	0805	1206	1210	2010	2512
POWER RATING		1/16W	1/16W (1/10WS)	1/10W (1/8WS)	1/8W (1/4WS)	1/4W (1/3WS)	1/2W (3/4WS)	1W
MAX.WORKING VOLTAGE		50V		150V	200V			
MAX. OVERLOAD VOLTAGE		100V		300V	400V			
DIELECTRIC WITHSTANDING VOLTAGE		100V	300V	500V				
RESISTANCE RANGE	±0.5% ±1% ±2%	1Ω --- 1MΩ						
	±5%	1Ω --- 10MΩ						
TOLERANCE		±0.5%, ±1%, ±2%, ±5%						
RATED AMBIENT TEMP.		70℃						
TEMP.RANGE		-55℃ --- +155℃						

2.1 POWER RATING:

RESISTORS SHALL HAVE A POWER RATING BASED ON CONTINUOUS LOAD OPERATION AT AN AMBIENT TEMPERATURE OF 70°C. FOR TEMPERATURE IN EXCESS OF 70°C, THE LOAD SHALL BE DERATE AS SHOWN IN FIGURE 1

**2.2 VOLTAGE RATING:**

RESISTORS SHALL HAVE A RATED DIRECT-CURRENT (DC) CONTINUOUS WORKING VOLTAGE OR AN APPROXIMATE SINE-WAVE ROOT-MEAN-SQUARE (RMS) ALTERNATING-CURRENT (AC) CONTINUOUS WORKING VOLTAGE AT COMMERCIAL-LINE FREQUENCY AND WAVEFORM CORRESPONDING TO THE POWER RATING, AS DETERMINED FROM THE FOLLOWING FORMULA:

$$RCWV = \sqrt{P \times R}$$

WHERE: RCWV = RATED DC OR RMS AC CONTINUOUS WORKING VOLTAGE AT COMMERCIAL-LINE FREQUENCY AND WAVEFORM (VOLT.)


P = POWER RATING (WATT.)

R = NOMINAL RESISTANCE (OHM)

IN NO CASE SHALL THE RATED DC OR RMS AC CONTINUOUS WORKING VOLTAGE BE GREATER THAN THE APPLICABLE MAXIMUM VALUE.

LEAD-FREE THICK FILM CHIP RESISTORS


3. DIMENSION FOR CHIP:



DIMENSION: mm

TYPE	L	W	H	I ₁	I ₂
0402	1.00±0.10	0.50±0.05	0.35±0.05	0.20±0.10	0.25±0.10
0603	1.60±0.10	0.80 ^{+0.15} _{-0.10}	0.45±0.10	0.30±0.20	0.30±0.20
0805	2.00±0.15	1.25 ^{+0.15} _{-0.10}	0.55±0.10	0.40±0.20	0.40±0.20
1206	3.10±0.15	1.55 ^{+0.15} _{-0.10}	0.55±0.10	0.45±0.20	0.45±0.20
1210	3.10±0.10	2.60 ^{+0.15} _{-0.10}	0.55±0.10	0.50±0.25	0.50±0.20
2010	5.00±0.10	2.50 ^{+0.15} _{-0.10}	0.55±0.10	0.60±0.25	0.50±0.20
2512	6.35±0.10	3.20 ^{+0.15} _{-0.10}	0.55±0.10	0.60±0.25	0.50±0.20

4. STRUCTURE:



1: HIGH PURITY ALUMINA SUBSTRATE

(96% AL₂O₃、0.3±0.1%CaO、1.0±0.3%MgO、2.1±0.05%SiO₂)

2,3: PROTECTIVE COVERING

4: RESISTIVE COVERING

5: TERMINATION (INNER) Ag/Pd

6: TERMINATION (BETWEEN) Ni PLATING


7: TERMINATION (OUTER) Sn PLATING

LEAD-FREE THICK FILM CHIP RESISTORS

5. **MARKING:**


(1) FOR 0402 SIZE. DUE TO THE VERY SMALL SIZE OF THE RESISTOR'S BODY, THERE IS NO MARKING ON THE BODY.

EXAMPLE:



(2) $\pm 2\%$, $\pm 5\%$ TOLERANCE: THE FIRST TWO DIGITS ARE SIGNIFICANT FIGURES OF RESISTANCE AND THE THIRD DENOTES NUMBER OF ZEROS FOLLOWING


EXAMPLE:



33000 \rightarrow 33K Ω

(3) $\pm 2\%$, $\pm 5\%$ TOLERANCE: BELOW 10 Ω SHOW AS FOLLOWING, READ ALPHABET "R" AS DECIMAL POINT.


EXAMPLE:




2.2 Ω

(4) $\pm 0.5\%$, $\pm 1\%$ TOLERANCE: 4 DIGITS, FIRST THREE DIGITS ARE SIGNIFICANT, FOURTH DIGIT IS NUMBER OF ZEROS. LETTER R IS DECIMAL POINT.

EXAMPLE:



2700 \rightarrow 2.7K Ω



10.5 Ω

LEAD-FREE THICK FILM CHIP RESISTORS

(5) STANDARD E-96 SERIES VALUES ($\pm 0.5\%$, $\pm 1\%$ TOLERANCE) OF 0603 SIZE. DUE TO THE SMALL SIZE OF THE RESISTOR'S BODY, 3 DIGITS MARKING WILL BE USED TO INDICATE THE ACCURATE RESISTANCE VALUE BY USING THE FOLLOWING MULTIPLIER & RESISTANCE CODE.

MULTIPLIER CODE:



CODE	A	B	C	D	E	F	G	H	X	Y	Z
MULTIPLIER	10^0	10^1	10^2	10^3	10^4	10^5	10^6	10^7	10^{-1}	10^{-2}	10^{-3}

CODING FORMULA

FIRST TWO DIGITS-----RESISTANCE CODE

THIRD DIGIT-----MULTIPLIER CODE

EXAMPLE : $1.96K\Omega = 196 \times 10^1 \Omega$ -----29B $12.4\Omega = 124 \times 10^{-1} \Omega$ -----10X



STANDARD E-96 VALUES AND 0603 RESISTANCE CODE


Ω VALUE	CODE	Ω VALUE	CODE	Ω VALUE	CODE	Ω VALUE	CODE
100	01	178	25	316	49	562	73
102	02	182	26	324	50	576	74
105	03	187	27	332	51	590	75
107	04	191	28	340	52	604	76
110	05	196	29	348	53	619	77
113	06	200	30	357	54	634	78
115	07	205	31	365	55	649	79
118	08	210	32	374	56	665	80
121	09	215	33	383	57	681	81
124	10	221	34	392	58	698	82
127	11	226	35	402	59	715	83
130	12	232	36	412	60	732	84
133	13	237	37	422	61	750	85
137	14	243	38	432	62	768	86
140	15	249	39	442	63	787	87
143	16	255	40	453	64	806	88
147	17	261	41	464	65	825	89
150	18	267	42	475	66	845	90
154	19	274	43	487	67	866	91
158	20	280	44	499	68	887	92
162	21	287	45	511	69	909	93
165	22	294	46	523	70	931	94
169	23	301	47	536	71	953	95
174	24	309	48	549	72	976	96

LEAD-FREE THICK FILM CHIP RESISTORS

6. **CHARACTERISTICS:**

CHARACTERISTIC	LIMITS		TEST METHOD (JIS-C-5201)
TEMPERATURE COEFFICIENT	±0.5% ±1%	$1\Omega \text{ --- } 10\Omega \leq \pm 400\text{PPM}/^\circ\text{C}$ $11\text{---}100\Omega \leq \pm 200\text{PPM}/^\circ\text{C}$ $101\Omega \text{ --- } 1\text{M}\Omega \leq \pm 100\text{PPM}/^\circ\text{C}$	4.8 NATURAL RESISTANCE CHANGE PER TEMP. DEGREE CENTIGRADE $\frac{R_2 - R_1}{R_1(T_2 - T_1)} \times 10^6 \text{ (PPM}/^\circ\text{C)}$ R ₁ : RESISTANCE VALUE AT ROOM TEMP. (T ₁) R ₂ : RESISTANCE VALUE AT ROOM TEMP. +100°C (T ₂) TEST PATTERN: ROOM TEMP., ROOM TEMP. +100°C
	±2% ±5%	$1\Omega \text{ --- } 10\Omega \leq \pm 400\text{PPM}/^\circ\text{C}$ $11\Omega \text{ --- } 10\text{M}\Omega \leq \pm 200\text{PPM}/^\circ\text{C}$	
SHORT-TIME OVERLOAD	±0.5% ±1%	±(1%+0.1Ω) MAX.	4.13 PERMANENT RESISTANCE CHANGE AFTER THE APPLICATION OF 2.5 TIMES RCWV FOR 5 SECONDS.
	±2% ±5%	±(2%+0.1Ω) MAX	
INSULATION RESISTANCE	1,000 MΩ OR MORE		4.6 APPLY 500V DC BETWEEN PROTECTIVE COATING AND TERMINATION FOR 1 MINUTE, THEN MEASURE.
DIELECTRIC WITHSTANDING VOLTAGE	NO EVIDENCE OF FLASHOVER MECHANICAL DAMAGE, ARCING OR INSULATION BREAK DOWN.		4.7 RESISTORS SHALL BE CLAMPED IN THE TROUGH OF A 90 °C METALLIC V-BLOCK AND SHALL BE TESTED AT AC POTENTIAL RESPECTIVELY SPECIFIED IN THE GIVEN LIST OF EACH PRODUCT TYPE FOR 60-70 SECONDS.
TERMINAL BENDING	±(1%+0.05Ω) MAX		4.33 TWIST OF TEST BOARD: Y/X = 3/90 mm FOR 60 SECONDS
SOLDERING HEAT	RESISTANCE CHANGE RATE IS: ±(1%+0.05Ω) MAX		4.18 DIP THE RESISTOR INTO A SOLDER BATH HAVING A TEMPERATURE OF 260°C±3°C AND HOLD IT FOR 10±1 SECONDS.


LEAD-FREE THICK FILM CHIP RESISTORS

LEAD-FREE THICK FILM CHIP RESISTORS				
CHARACTERISTIC	LIMITS		TEST METHOD (JIS-C-5201)	
TEMPERATURE CYCLING	$\pm 0.5\%$ $\pm 1\%$	$\pm(0.5\%+0.05\ \Omega)\text{MAX}$	4.19 RESISTANCE CHANGE AFTER CONTINUOUS FIVE CYCLES FOR DUTY CYCLE SPECIFIED BELOW:	
			STEP	TEMPERATURE
	$\pm 2\%$ $\pm 5\%$	$\pm(1.0\%+0.05\ \Omega)\ \text{MAX.}$	1	-55°C $\pm 3^\circ\text{C}$
			2	ROOM TEMP.
			3	+155°C $\pm 2^\circ\text{C}$
			4	ROOM TEMP.
SOLDERABILITY	95% COVERAGE MIN.		WAVE SOLDER: TEST TEMPERATURE OF SOLDER: 245°C $\pm 3^\circ\text{C}$ DIPPING TIME IN SOLDER: 2-3 SECONDS.	
	GO UP TIN RATE BIGGER THAN HALF OF END POLE		REFLOW: 	
HUMIDITY (STEADY STATE)	$\pm 0.5\%$ $\pm 1\%$	$\pm(0.5\%+0.1\ \Omega)\ \text{MAX.}$	4.24 TEMPORARY RESISTANCE CHANGE AFTER 240 HOURS EXPOSURE IN A HUMIDITY TEST CHAMBER CONTROLLED AT 40 $\pm 2^\circ\text{C}$ AND 90-95% RELATIVE HUMIDITY,	
	$\pm 2\%$ $\pm 5\%$	$\pm(3.0\%+0.1\ \Omega)\ \text{MAX.}$		
LOAD LIFE IN HUMIDITY	RESISTANCE CHANGE RATE IS:		7.9 RESISTANCE CHANGE AFTER 1,000 HOURS (1.5 HOURS "ON", 0.5 HOUR "OFF") AT RCWV IN A HUMIDITY CHAMBER CONTROLLED AT 40°C $\pm 2^\circ\text{C}$ AND 90 TO 95% RELATIVE HUMIDITY.	
	$\pm 0.5\%$ $\pm 1\%$	$\pm(1\%+0.1\ \Omega)\text{MAX.}$		
	$\pm 2\%$ $\pm 5\%$	$\pm(3\%+0.1\ \Omega)\text{MAX.}$		
LOAD LIFE	RESISTANCE CHANGE RATE IS:		4.25.1 PERMANENT RESISTANCE CHANGE AFTER 1,000 HOURS OPERATING AT RCWV WITH DUTY CYCLE 1.5 HOURS "ON", 0.5 HOUR "OFF" AT 70°C $\pm 2^\circ\text{C}$ AMBIENT.	
	$\pm 0.5\%$ $\pm 1\%$	$\pm(1\%+0.1\ \Omega)\text{MAX.}$		
	$\pm 2\%$ $\pm 5\%$	$\pm(3\%+0.1\ \Omega)\text{MAX.}$		
RESISTANCE TO DISSOLUTION OF METALLIZATION TEST	INSPECT FOR ANY DISSOLUTION OF METALLIZATION ON COMPONENT ELECTRODES WITH MAGNIFIER OF ABOUT 20-30 MAGNIFICATION		TEST CONDITION: SOLDER TEMPERATURE 260°C $\pm 3^\circ\text{C}$ IMMERSION TIME 30 ± 1 SECOND IMMERSION DEPTH 2.0-2.5MM	

LEAD-FREE THICK FILM CHIP RESISTORS


7. **PACKAGING:**

7.1 **TAPPING DIMENSION:**



UNIT: mm


TYPE	A ± 0.2	B ± 0.2	C ± 0.05	ϕD + 0.1 - 0	E ± 0.1	F ± 0.05	G ± 0.1	W ± 0.2
0402	0.65	1.15	2.0	1.5	1.75	3.5	4.0	8.0



UNIT: mm

TYPE	A ± 0.2	B ± 0.2	C ± 0.05	ϕD + 0.1 - 0	E ± 0.1	F ± 0.05	G ± 0.1	W ± 0.2
0603	1.10	1.90	2.0	1.5	1.75	3.5	4.0	8.0
0805	1.65	2.40	2.0	1.5	1.75	3.5	4.0	8.0
1206	2.00	3.60	2.0	1.5	1.75	3.5	4.0	8.0
1210	2.80	3.50	2.0	1.5	1.75	3.5	4.0	8.0


LEAD-FREE THICK FILM CHIP RESISTORS



UNIT: mm

TYPE	A ± 0.2	B ± 0.2	C ± 0.05	ϕD $\begin{smallmatrix} +0.1 \\ -0 \end{smallmatrix}$	$\phi D1$ $\begin{smallmatrix} +0.25 \\ -0 \end{smallmatrix}$	E ± 0.1	F ± 0.05	G ± 0.1	W ± 0.2
2010	2.9	5.6	2.0	1.5	1.5	1.75	5.5	4.0	12
2512	3.5	6.7	2.0	1.5	1.5	1.75	5.5	4.0	12

7.2 DIMENSION:



UNIT: mm

TYPE	TAPING	SIZE	A ± 0.5	B ± 0.5	C ± 0.5	D ± 1	M ± 2	W ± 1
0402	PAPER	10,000 PCS REEL	2.0	13.0	21.0	60.0	178	10
0603	PAPER	5,000 PCS REEL	2.0	13.0	21.0	60.0	178	10
0805	PAPER	5,000 PCS REEL	2.0	13.0	21.0	60.0	178	10
1206	PAPER	5,000 PCS REEL	2.0	13.0	21.0	60.0	178	10
1210	PAPER	5,000 PCS REEL	2.0	13.0	21.0	60.0	178	10
2010	EMBOSSSED	4,000 PCS REEL	2.0	13.0	21.0	60.0	178	13.8
2512	EMBOSSSED	4,000 PCS REEL	2.0	13.0	21.0	60.0	178	13.8

PART NUMBER SYSTEM

EXPLANATION OF PART NUMBER SYSTEM (LEAD-FREE THICK FILM CHIP RESISTORS)

ORDERING PROCEDURE (EXAMPLE: 0402 1/16W 0.5% 100Ω T/R-10,000 LEAD-FREE):

0	4	0	2	W	G	D	1	0	0	0	T	C	E
---	---	---	---	---	---	---	---	---	---	---	---	---	---

PRODUCT TYPE:

FILL-IN THESE 4 DIGITS WITH THE CHIP RESISTOR TYPES AS FOLLOWS:

0402
0603
0805
1206
1210
2010
2512
4D03
10P8
16P8

WATTAGE:

FILL-IN THESE 2 DIGITS WITH THE CODES AS FOLLOWS:

NORMAL SIZE
WG=1/16W
WA=1/10W
W8=1/8W
W4=1/4W
W2=1/2W
1W=1W

SMALL SIZE
SA=1/10WS
S8=1/8WS
S4=1/4WS
S3=1/3WS
07=3/4WS

SPECIAL:
WH=1/32W

RESISTANCE VALUE:

1.E-24 SERIES: THE 1st DIGIT IS "0", THE 2nd & 3rd DIGITS ARE FOR THE SIGNIFICANT FIGURES OF THE RESISTANCE AND THE 4th INDICATE THE NUMBERS OF ZEROS FOLLOWING;
2.E-96 SERIES: THE 1st TO 3rd DIGITS ARE FOR THE SIGNIFICANT FIGURES OF THE RESISTANCE AND THE 4th DIGIT INDICATE THE NUMBERS OF ZEROS FOLLOWING.
J=10⁻¹; K=10⁻²; L=10⁻³

PACKING

QUANTITY:

1=1,000PCS
2=2,000PCS
3=3,000PCS
4=4,000PCS
5=5,000PCS
C=10,000PCS
D=20,000PCS

PACKAGING TYPE:

T=T/R PACKING
B=BUICK IN POLY-BAG
C=BUICK IN CASSETTE

TOLERANCE:

D=±0.5%

F=(1%

G=(2%

SPECIAL FEATURE:

0-NUM