B-Channel 1.25-W, 2.5-V MOSFET

PRODUCT SUMMARY		
V_{DS} (V)	$r_{DS(on)}$ (Ω)	I_D (A)
20	0.040 @ V_{GS} = 4.5 V	3.0
	0.060 @ V_{GS} = 2.5 V	2.0

TO-236
(SOT-23)



Top View
Si2302(A2)*
*Marking Code

ABSOLUTE MAXIMUM RATINGS (T_A = 25°C UNLESS OTHERWISE NOTED)				
Parameter		Symbol	Limit	Unit
Drain-Source Voltage		V_{DS}	20	V
Gate-Source Voltage		V_{GS}	±8	
Continuous Drain Current (T_J = 150°C)[b]	T_A= 25°C	I_D	3.0	A
Pulsed Drain Current[a]		I_{DM}	10	
Continuous Source Current (Diode Conduction)[b]		I_S	1.6	
Power Dissipation[b]	T_A= 25°C	P_D	1.25	W
Operating Junction and Storage Temperature Range		T_J, T_{stg}	–55 to 150	°C

THERMAL RESISTANCE RATINGS			
Parameter	Symbol	Limit	Unit
Maximum Junction-to-Ambient[b]	R_{thJA}	100	°C/W
Maximum Junction-to-Ambient[c]		166	

Notes
a. Pulse width limited by maximum junction temperature.
b. Surface Mounted on FR4 Board, t ≤ 5 sec.
c. Surface Mounted on FR4 Board.

SPECIFICATIONS (T_A = 25°C UNLESS OTHERWISE NOTED)

Parameter	Symbol	Test Conditions	Min	Typ	Max	Unit
Static						
Drain-Source Breakdown Voltage	$V_{(BR)DSS}$	V_{GS} = 0 V, I_D = 250 μA	20			V
Gate-Threshold Voltage	$V_{GS(th)}$	V_{DS} = V_{GS}, I_D = 250 μA	0.5		1.0	
Gate-Body Leakage	I_{GSS}	V_{DS} = 0 V, V_{GS} = ±8 V			±100	nA
Zero Gate Voltage Drain Current	I_{DSS}	V_{DS} = 16 V, V_{GS} = 0 V			50	nA
		V_{DS} =16 V, V_{GS} = 0 V, T_J = 55°C				
On-State Drain Current[a]	$I_{D(on)}$	V_{DS} ≥ 5 V, V_{GS} = 4.5 V	6			A
		V_{DS} ≥ 5 V, V_{GS} = 2.5 V	4			
Drain-Source On-Resistance[a]	$r_{DS(on)}$	V_{GS} = 4.5 V, I_D = 3.0 A			0.040	Ω
		V_{GS} = 2.5 V, I_D = 2.0 A			0.060	
Forward Transconductance[a]	g_{fs}	V_{DS} = 5 V, I_D = 3.0 A		10		S
Diode Forward Voltage	V_{SD}	I_S = 1.0 A, V_{GS} = 0 V			1.28	V
Dynamic						
Total Gate Charge	Q_g	V_{DS} = 10 V, V_{GS} = 4.5 V, I_D = 3.6 A		5.4	10	nC
Gate-Source Charge	Q_{gs}			0.65		
Gate-Drain Charge	Q_{gd}			1.60		
Input Capacitance	C_{iss}	V_{DS} = 10 V, V_{GS} = 0 V, f = 1 MHz		340		pF
Output Capacitance	C_{oss}			115		
Reverse Transfer Capacitance	C_{rss}			33		
Switching						
Turn-On Delay Time	$t_{d(on)}$	V_{DD} = 10 V, R_L = 5.5 Ω I_D ≅ 3.6 A, V_{GEN} = 4.5 V, R_G = 6 Ω		12	25	ns
Rise Time	t_r			36	60	
Turn-Off Delay Time	$t_{d(off)}$			34	60	
Fall-Time	t_f			10	25	

Notes
a. Pulse test: PW ≤300 μs duty cycle ≤2%..

VNLR02

TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)

Output Characteristics



Transfer Characteristics



On-Resistance vs. Drain Current



Capacitance



Gate Charge



On-Resistance vs. Junction Temperature



TYPICAL CHARACTERISTICS (25°C UNLESS NOTED)

Source-Drain Diode Forward Voltage



On-Resistance vs. Gate-to-Source Voltage



Threshold Voltage



Single Pulse Power



Normalized Thermal Transient Impedance, Junction-to-Ambient