

EXECUTIVE SUMMARY

7 Access points found	7 Open (unencrypted)	0 Evil twins detected	0 Deauth sources
--------------------------	-------------------------	--------------------------	---------------------

OVERALL THREAT LEVEL: CRITICAL

A passive 802.11 wireless survey was conducted at Bank HQ using the BLACK ICE v2 SIGINT platform. The survey detected 7 unique access points across the 2.4 GHz and 5 GHz bands.

CRITICAL: 7 access points were found operating without encryption ("**<hidden>**", "**<hidden>**", "**<hidden>**" and others). Unencrypted networks expose all traffic to passive interception and require immediate remediation.

All findings, coordinates, and evidence are detailed in the sections below.

Key Findings

- 7 unencrypted access points — immediate remediation required

ACCESS POINT INVENTORY

The following table lists all access points detected during the survey, ordered by signal strength (strongest first). Risk level is computed from encryption status, cipher suite, and proximity.

SSID	BSSID	SECURITY	SIGNAL	CH	VENDOR	RISK
<hidden>	E5:32:CB:56:6B:04	OPEN	-95 dBm	164	unknown	HIGH
<hidden>	0D:76:36:7A:A2:A7	OPEN	-95 dBm	145	unknown	HIGH
<hidden>	50:1F:0B:2C:B1:01	OPEN	-95 dBm	175	unknown	HIGH
<hidden>	8D:9E:DA:37:51:34	OPEN	-95 dBm	116	unknown	HIGH
<hidden>	7C:01:E4:E4:F5:71	OPEN	-95 dBm	171	unknown	HIGH
<hidden>	4C:DB:98:FA:0F:0C	OPEN	-95 dBm	211	unknown	HIGH
<hidden>	A4:DA:4D:A6:5E:8D	OPEN	-95 dBm	249	unknown	HIGH

HIGH	Open / rogue / WEP / TKIP
MEDIUM	WPA legacy / WPS enabled / TKIP
LOW	WPA2-CCMP or better

THREAT ANALYSIS

Open (Unencrypted) Networks — 7 found

CRITICAL: The following networks transmit all data without encryption. Any passive observer within radio range can capture and read all traffic, including passwords, session tokens, and sensitive documents.

OPEN NETWORK

<hidden>

E5:32:CB:56:6B:04

Ch 164 -95 dBm

-15.40390, 28.30140

All traffic is visible to passive observers. Disable this network or enable WPA2-CCMP immediately.

OPEN NETWORK

<hidden>

0D:76:36:7A:A2:A7

Ch 145 -95 dBm

-15.42030, 28.28500

All traffic is visible to passive observers. Disable this network or enable WPA2-CCMP immediately.

OPEN NETWORK

<hidden>

50:1F:0B:2C:B1:01

Ch 175 -95 dBm

-15.42641, 28.27889

All traffic is visible to passive observers. Disable this network or enable WPA2-CCMP immediately.

OPEN NETWORK

<hidden>

8D:9E:DA:37:51:34

Ch 116 -95 dBm

-15.42455, 28.28075

All traffic is visible to passive observers. Disable this network or enable WPA2-CCMP immediately.

OPEN NETWORK

<hidden>

7C:01:E4:E4:F5:71

Ch 171 -95 dBm

-15.40553, 28.29977

All traffic is visible to passive observers. Disable this network or enable WPA2-CCMP immediately.

OPEN NETWORK

<hidden>

4C:DB:98:FA:0F:0C

Ch 211 -95 dBm

-15.42483, 28.28047

All traffic is visible to passive observers. Disable this network or enable WPA2-CCMP immediately.

OPEN NETWORK

<hidden>

A4:DA:4D:A6:5E:8D

Ch 249 -95 dBm

-15.40835, 28.29695

All traffic is visible to passive observers. Disable this network or enable WPA2-CCMP immediately.

Evil Twin / Rogue Access Points — 0 found

No rogue access points detected during this survey.

Deauthentication Attacks — 0 source(s)

No deauthentication attacks observed during this survey.

Weak Cipher Suites (TKIP) — 0 found

No TKIP-only configurations detected.

RECOMMENDATIONS

The following recommendations are ordered by priority. Critical items should be resolved within 24 hours of this report. High items within 7 days. Medium items within 30 days.

PRIORITY	ACTION	EFFORT	DEADLINE
CRITICAL	Disable or secure all open networks Enable WPA2-CCMP on 7 unencrypted AP(s) immediately.	< 1 hour	24 hours
MEDIUM	Deploy 802.11w Protected Management Frames Enables encryption of deauth/disassoc frames, preventing injection attacks.	1–2 hours	30 days
MEDIUM	Schedule monthly wireless audits Recurring scans detect new rogue APs, configuration drift, and new open networks.	Ongoing	30 days
LOW	Enable wireless intrusion detection system (WIDS) Continuous passive monitoring integrated with SIEM for real-time alerting.	1–3 days	90 days

APPENDIX — TECHNICAL DETAIL

Survey Statistics

Total APs detected	7
Open (unencrypted) APs	7
WPA2 APs	0
WPA3 APs	0
TKIP-only APs	0
Evil twin detections	0
Deauth attack sources	0
GPS survey readings	0
Operator GPS position	-15.387500, 28.322800
GPS hardware lock	No (browser approximate)
Report generated	19 May 2026, 16:54:12
Platform	BLACK ICE v2 — NIGHTFALL35
Operator	Ishmael D. Tembo

Channel Distribution

Ch 116: 1 AP(s) Ch 145: 1 AP(s) Ch 164: 1 AP(s) Ch 171: 1 AP(s) Ch 175: 1 AP(s) Ch 211: 1 AP(s) Ch 249: 1 AP(s)

Methodology

This assessment was conducted using passive 802.11 frame capture (no active transmission). The BLACK ICE v2 platform operated in promiscuous monitor mode, capturing beacon frames, probe responses, and management frames across all available channels using an automated channel hopper with 150ms dwell time per channel. Geographic positions were resolved using on-device GPS hardware where available, falling back to Wigle.net geolocation and IP approximation. Evil twin detection uses a frequency-map algorithm comparing BSSID prefixes and SSID patterns across channels. All findings are based on passive observation only; no active exploitation was performed.

Legal Notice

This report was produced under written authorization from the site owner. Unauthorized use of wireless scanning tools may violate the Computer Misuse Act (Zambia), Computer Fraud and Abuse Act (USA), Computer Misuse Act (UK), and equivalent legislation in other jurisdictions. This report is confidential and intended solely for the authorized recipient. Distribution, reproduction, or disclosure to unauthorized parties is prohibited.