

**MITIGATING PUBLIC TRANSIT UNRELIABILITY THROUGH DEEP LEARNING
ANALYTICS AND RIDERSHIP FORECASTING**

YIP ZI XIAN

**RESEARCH REPORT SUBMITTED TO THE FACULTY OF EDUCATION,
UNIVERSITY OF MALAYA, IN PARTIAL FULFILMENT OF THE REQUIREMENTS
FOR THE DEGREE OF MASTER IN ARTIFICIAL INTELLIGENCE**

2026

UNIVERSITI MALAYA

ORIGINAL LITERACY WORK DECLARATION

Name of Candidate: **Yip Zi Xian**

(I.C/Passport No: **020709-08-1513**)

Registration/Matric No: **24202141**

Name of Degree: **Master of Artificial Intelligence (MAI)**

Title of Project Paper/Research Report/Dissertation/Thesis ("this Work"):

Mitigating Public Transit Unreliability through Deep Learning Analytics and Ridership Forecasting

Field of Study: **Artificial Intelligence**

I do solemnly and sincerely declare that:

- (1) I am the sole author/writer of this Work;
- (2) This Work is original;
- (3) Any use of any work in which copyright exists was done by way of fair dealing and for permitted purposes and any excerpt or extract from, or reference to or reproduction of any copyright work has been disclosed expressly and sufficiently, and the title of this Work and its authorship have been acknowledged in this Work;
- (4) I do not have any actual knowledge, nor do I ought reasonably to know that the making of this Work constitutes an infringement of any copyright work;
- (5) I hereby assign all and every rights in the copyright to this Work to the University of Malaya ("UM"), who henceforth shall be owner of the copyright in this Work and that any reproduction or use in any form or by any means whatsoever is prohibited without the written consent of UM having been first had and obtained;
- (6) I am fully aware that if in the course of making this Work I have infringed any copyright whether intentionally or otherwise, I may be subject to legal action or any other action as may be determined by UM.

Candidate's Signature

Date: **22nd June 2026**

Subscribed and solemnly declared before,

Witness's Signature

Date: **30th June 2026**

Name: **Prof. Ts. Dr. Rafidah binti Md Noor**

Designation: **Professor**

ABSTRACT

Predicting daily public transit ridership in Malaysia is challenged by complex spatiotemporal variables (e.g., population density, weather, and socio-economic activities) and extreme data anomalies driven by the Movement Control Order (MCO). This study identifies key ridership factors and introduces the Hybrid Multi-scale Temporal Spatio Feature (HMT-TSF) Forecaster. Utilizing a robust deep learning (DL) framework integrating General Transit Feed Specification (GTFS) schedules, historical weather, and Points of Interest (POIs), the proposed model is benchmarked against state-of-the-art architectures, including LSTM, BiLSTM, STGCN, and Informer. To evaluate pandemic-driven noise and predictive bias, the analysis is executed across two distinct dataset segmentations: "With MCO" (2019–2025) and "Without MCO" (2022–2025), utilizing MAE, RMSE, and R^2 evaluation metrics. Results indicate that incorporating exogenous variables significantly enhances DL predictive power over classical statistical models like ARIMA. The proposed HMT-TSF consistently outperforms baseline models across all lookback windows and dataset segmentations. Critically, training architectures on the MCO-inclusive dataset introduces severe predictive bias. Conversely, strategic data segmentation isolates these anomalies, enabling the model to accurately capture peak demands and standard urban mobility patterns. This paper provides transport authorities with an effective, data-driven methodology to optimize scheduling and close the infrastructure-to-ridership gap.

Keywords

Public Transit Reliability, Deep Learning Analytics, Ridership Forecasting, Urban Mobility Pattern Analysis

ABSTRAK

Ramalan jumlah penumpang harian pengangkutan awam di Malaysia amat mencabar disebabkan oleh pemboleh ubah ruang-masa yang rumit (seperti kepadatan penduduk, cuaca, dan aktiviti sosioekonomi) serta anomali data ekstrem akibat Perintah Kawalan Pergerakan (PKP). Kajian ini mengenal pasti faktor utama penggerak jumlah penumpang dan memperkenalkan model Hybrid Multi-scale Temporal Spatio Feature (HMT-TSF) Forecaster. Menggunakan rangka kerja pembelajaran mendalam (DL) teguh yang menyepadukan jadual General Transit Feed Specification (GTFS), corak cuaca sejarah, dan Tempat Menarik (POI), model yang dicadangkan ini ditanda aras berbanding seni bina terkini termasuk LSTM, BiLSTM, STGCN, dan Informer. Bagi menilai ralat (*noise*) dan bias ramalan akibat pandemik, analisis dilaksanakan merentasi dua segmentasi set data: "Dengan PKP" (2019–2025) dan "Tanpa PKP" (2022–2025), menggunakan metrik penilaian MAE, RMSE, dan R^2 . Keputusan kajian menunjukkan bahawa penggabungan pemboleh ubah eksogenus meningkatkan kuasa ramalan model DL secara signifikan berbanding kaedah statistik klasik seperti ARIMA. Model HMT-TSF yang dicadangkan konsisten mengatasi prestasi model garis dasar (*baseline*) merentasi semua tettingkap imbas kembali (*lookback windows*) dan kedua-dua segmen set data. Secara kritikal, latihan model menggunakan set data inklusif-PKP memperkenalkan bias ramalan yang besar. Sebaliknya, segmentasi data yang strategik berjaya mengasingkan anomali tersebut, sekali gus membolehkan model menangkap lonjakan permintaan waktu puncak dan corak mobiliti bandar yang normal dengan tepat. Kajian ini menyediakan metodologi berasaskan data yang berkesan untuk membantu pihak berkuasa pengangkutan mengoptimumkan penjadualan serta merapatkan jurang antara peluasan infrastruktur dan jumlah penumpang.

Kata Kunci

Kebolehpercayaan Transit Awam, Analitis Pembelajaran Mendalam, Ramalan Jumlah Penumpang, Analisis Corak Mobiliti Bandar

ACKNOWLEDGMENTS

Above all, I wish to extend my most sincere thanks to my highly respected supervisor, **Prof. Ts. Dr. Rafidah binti Md Noor**, for her excellent guidance, endless support, and boundless patience in the entire process of conducting this research. The extensive knowledge she possesses regarding smart transport systems, coupled with her continuous support and encouragement, was pivotal in completing this thesis work.

I would like to extend my immense gratitude towards my **family** members who loved me unconditionally and helped me in every possible way by making huge sacrifices. It was only because of their caring nature and belief in my capabilities that I could fully concentrate on my studies without any hindrance especially during the tough times of this research process.

To my fellow **friends** and **mates**, thank you very much for all the support and fun activities that made me feel relaxed in the middle of my tough academic life.

Lastly, to my **partner** who supported me throughout with her moral strength and patience, thank you very much for all the efforts.

To everyone who contributed directly or indirectly to the completion of this milestone, your kindness and support will always be remembered.

TABLE OF CONTENTS

ORIGINAL LITERACY WORK DECLARATION	II
ABSTRACT	III
ABSTRAK	IV
ACKNOWLEDGMENTS	VI
TABLE OF CONTENTS	VII
LIST OF FIGURES	XII
LIST OF TABLES	XIV
CHAPTER 1 INTRODUCTION	1
1.1 Research Background	1
1.2 Problem Statement	2
1.3 Research Questions	3
1.4 Research Objectives	3
1.5 Research Scope	4
1.6 Research Contribution	5
1.7 Thesis Organization	5
CHAPTER 2 LITERATURE REVIEW	7
2.1 Public Transport Reliability and Demand Dynamics	7
2.1.1 Defining Reliability: Metrics and User Perception	7
2.1.2 The Relationship between Ridership and Service Unreliability	8
2.1.3 The Landscape of Public Transit in Malaysia	9
2.2 Transit Data Ecosystems and Anomalies	10

2.2.1	Sources of Transit Data	10
2.2.2	Data Quality, Noise and Preprocessing Challenges	12
2.2.3	Extreme Anomalies in Spatiotemporal Data	13
2.3	Evolution from Traditional to DL Models	13
2.3.1	Traditional Architectures	13
2.3.2	Deep Learning Approaches in Spatiotemporal Transit Data	14
2.3.3	Benchmarking Methodologies and Evaluation Metrics	15
2.4	AI-Driven Operational Strategies and Sustainability	16
2.4.1	Proactive Scheduling and Resource Allocation	16
2.4.2	Deployment Challenges of AI in Transit Management	17
2.4.3	Sustainable Urban Mobility and Environmental Impact	18
2.5	Research Gap	19
CHAPTER 3 METHODOLOGY		24
3.1	Data Collection and Understanding	24
3.1.1	Primary Transit and Network Data	24
3.1.2	Administrative Geography and Spatial Connectivity	24
3.1.3	Economic and Temporal Indicators	25
3.1.4	Environmental and Geospatial Features	25
3.1.5	Data Segmentation and MCO Considerations	25
3.2	Feature Engineering	27
3.2.1	Data Cleaning	27
3.2.2	Feature Alignment	28

3.2.3	Sequence Building	29
3.3	Explanatory Data Analysis	29
3.3.1	MCO Collapse and Unequal Recovery	29
3.3.2	Northeast Monsoon Rainfall Pattern	31
3.3.3	Weather-Induced Ridership Surge under Heavy Rainfall	33
3.3.4	Fuel Price Elasticity and Modal Substitution	35
3.3.5	Holiday Anticipation and Return-Surge Effect	37
3.3.6	Lag Dominance and Static Near-Zero Signal	40
3.4	Baseline & Comparative Models	41
3.4.1	Spatiotemporal Models	42
3.4.2	Graph Models	42
3.4.3	Attention Models	43
3.5	Hybrid Multi-scale Temporal Spatio Feature (HMT-TSF)	44
3.5.1	Feature Selection	44
3.5.2	Key Architecture Components	46
3.5.2.1	Reversible Instance Normalisation (RevIN)	46
3.5.2.2	Multi-scale Temporal Convolution Network (TCN) – Temporal Encoder	46
3.5.2.3	Spatial Graph Encoder	47
3.5.2.4	Regime Gating Embedding	47
3.5.2.5	Gated Fusion	48
3.5.2.6	Dual Forecast Heads and Custom Loss	49
3.5.2.7	Future Temporal Projection – Known-Future Calendar Conditioning	49

3.5.3	Architecture Diagram	50
3.5.4	Design Trade-offs	51
3.6	Evaluation Metrics	51
3.6.1	Combined Accuracy Percentage (Combined %)	51
3.6.2	Constituent Metrics	52
3.7	Conclusion	53
CHAPTER 4 FINDINGS & RESULTS		55
4.1	Experimental Evaluation	55
4.2	Baseline Model Performance – Default Configuration (base_nomco_lb14)	56
4.2.1	LSTM Models	58
4.2.2	Graph Models	59
4.2.3	Attention Models	60
4.3	Effect of Hyperparameter Tuning	61
4.4	Lookback Window Sensitivity	62
4.5	MCO Structural Break Robustness	64
4.6	Generalisation and Overfitting Analysis	66
4.7	HMT-TSF Model Performance	68
4.8	SHAP Feature Importance Analysis	71
4.9	Feature-Reduced Variant: HMT-TSF-FR	72
4.10	Summary	73
CHAPTER 5 DISCUSSION & CONCLUSION		74
5.1	Discussion of Key Findings	74

5.2	Implications of the Study	75
5.3	Limitations of the Study	75
5.4	Future Works	75
5.5	Final Verdict	75
	REFERENCES	75
	APPENDICES	81
	APPENDIX A1 – HARDWARE SPECIFICATION	81
	APPENDIX A2 – DATA CONFIGURATION	82
	APPENDIX B1 – BASELINE MODELS HYPERPARAMETERS	82
	APPENDIX B2 – BASELINE MODELS TRAINING OPTIMIZATION	83
	APPENDIX C1 – SPATIOTEMPORAL MODELS	83
	APPENDIX C2 – GRAPH MODELS	93
	APPENDIX C3 – ATTENTION MODELS	100
	APPENDIX C4 – HMT-TSF TRAINING CONFIGURATIONS	105

LIST OF FIGURES

Figure 2.1 - Vicious Cycle of Transit Unreliability and Ridership Uncertainty	9
Figure 2.2 - Cause-and-effect of Resolving AI Deployment Challenges in Public Transit Systems	18
Figure 3.1 - Total Daily Transit Volume from 2019 to mid-2026, Featuring 6 Vertical Red Dashed Lines Pinpointing Specific Structural Shifts/Transition Points over Time	30
Figure 3.2 - Average Daily Usage Numbers Across Various Rail and Bus Lines Segmented into 3 Distinct Phases: Pre-MCO (blue), MCO (orange), and Post-MCO (green)	30
Figure 3.3 - Comparison of Total Counts of Wet Days ($\geq 10\text{mm}$), Very Wet Days ($\geq 30\text{mm}$), and Extreme Days ($\geq 50\text{mm}$) Across Various States with Terengganu Consistently Showing the Highest Counts	31
Figure 3.4 - Dashboard Visualizing the Trend and Breakdown of Extreme Rainfall Events over Time, Including Month/Annual Frequency Percentages, Annual Wet Day Counts by Category, and Extreme Event Frequency Aggregated by Month.....	32
Figure 3.5 - Dashboard Outlining General Rainfall Trends, Including Average Daily Rainfall by Month, Monthly Rainfall Anomalies, a 7-day Rolling Average Timeline, and Total Annual Rainfall from 2019 to 2026	33
Figure 3.6 - Advanced Behaviourial Analysis Focusing on Weather-driven Modal Shifts, Constrasting Heavy Rain Days against Normal Conditions through a Correlation Matrix, Monthly Trend Comparisons, and a Daily Percentage Change Surge Analysis	33
Figure 3.7 - Monthly Averages for Daily Rainfall against Total Ridership with Monthly Breakdown of Correlation Coefficients, r , with Corresponding Statistical Significance (p -values)	34
Figure 3.8 - Dashboard Analysis on Direct Impact of Wet Weather with Rainfall-vs-Ridership Scatterplot ($r = 0.1444$), Average Daily Ridership Comparison Bars, Total Rainy Day Sample Count ($n = 197$), and Historical Rainfall Time Series from 2019 to 2026.....	34

Figure 3.9 - Fuel Price Levels (RON95, RON97, Diesel) in MYR/Litre (top) and Weekly Price Changes for RON95 and Diesel (bottom), both from late 2018 to mid-2026	35
Figure 3.10 - Dashboard Analysis on Direct Relationship between Fuel Prices and Public Transit Ridership with Scatterplot with Trend Lines and Weekly Percentage Changes, and Bar Chart of Average Daily Ridership by Price Level	36
Figure 3.11 - Lagged correlation (from 0 to 7 days) between Changes in Fuel Prices (RON95 and Diesel) and Subsequent Changes in Transit Ridership	37
Figure 3.12 - Broad Seasonal and Weekly Overview Displaying Average Daily Ridership Across Day Types, Monthly Distribution of Public Holidays (peaking in May), Daily Breakdown by Day of the Week, General Ridership Fluctuations Across the Months of the Year.....	38
Figure 3.13 - Assessing How the Length of Holiday Influences Travel Patterns Showing that Short Holidays (less than 3 days) Experience the Most Severe Percentage Dip in Ridership from Normal Levels with Frequency Distribution and Day-of-Week Profile Broken Down by Holiday Duration	38
Figure 3.14 - Ridership Trends between Academic and Public Holidays highlighting Public Holidays See Sharp Drops in Both Overall Mean Volume and Daily Percentage Change with Breakdown of Mean Ridership Across Dozens of Individual Malaysian Calendar Events	39
Figure 3.15 - Dashboard Tracking Transit Demand around Holiday Periods, Showing Overall Mean Total Ridership Drops on Holidays, Day-of-Week Demand Dips (Most Pronounced on Tuesdays and Wednesdays), Distinct Weekday vs Weekend Response Gaps, and Percentage of Daily Ridership Change by Holiday Regime.....	40
Figure 3.16 - Detailed 6 x 6 Correlation Matrix of Key Demand Forecasting Inputs (left) with Standardized Coefficients of the Dominant Predictors of Ridership (right).....	40
Figure 3.17 - Large-scale, Lower-triangular Heatmap visualizing Complex Feature Correlation Matrix (79 x 79) for Full Demand Model.....	41
Figure 3.18 - HMT-TSF Architectural Flow Diagram	50

LIST OF TABLES

Table 1.1 Methodology, Metrics, Models, and Malaysia’s MCO Period Used in This Research	4
Table 2.1 Comparison of Technical Reliability Metrics and User Perception Factors	8
Table 2.2 Endogenous Data Sources: Examples, Applications, and Characteristics	11
Table 2.3 Exogenous Data Sources: Examples, Applications, and Characteristics	11
Table 2.4 Comparison of Traditional and DL Models	14
Table 2.5 Common Evaluation Metrics and Their Focus (Jiang et al., 2021; S.K.B et al., 2024; Mystakidis et al., 2025)	16
Table 2.6 Comparative Summary of Prior Forecasting Studies Supporting the Research Gap	20
Table 3.1 Independent Raw Data Sources: Coverage, Content, and Usage in This Study	25
Table 3.2 Primary Cleaning Operations Applied to Each Sources	27
Table 3.3 Merge Strategy and Null Handling	28
Table 3.4 79 Features Across 5 Semantic Groups	29
Table 4.1 Default-configuration (base_nomco_lb14) Performance of All 16 Baseline Variants, Ranked by Combined%	56
Table 4.2 Tuning Effect at tuned_nomco_lb14 Versus base_nomco_lb14	61
Table 4.3 Look-back Sensitivity (Combined%) Across lb14, lb28, and lb56 for All Baseline Variants (base_nomco)	63
Table 4.4 MCO Robustness at lb14 for All 16 Baseline Variants, Ranked by Combined% (Least to Most Degradation)	64

CHAPTER 1

INTRODUCTION

1.1 Research Background

By enhancing urban mobility where citizens prioritize public transports over private vehicles, countries can improve their economies while promoting environmental sustainability (Lu et al., 2020), aligning with United Nations Sustainable Development Goals (SDG). Malaysia, as a developing nation undergoing urbanisation, establishing an efficient public transit system is essential to achieve developed-country status (Wang et al., 2025). However, some suggested that citizens revert to private vehicles due to unreliable public transit predictions in public transit systems caused by uncertainties – weather conditions, socio-economic activities, and geopolitical events – thereby accelerates traffic congestion and air/sound pollution (Amir et al., 2025). Reliable public transit systems directly address the environmental and social challenges, enhancing residents' quality of life and mobility across metropolitan and rural areas (Wang et al., 2025).

Despite Malaysian government investments in major transit infrastructure such as mass rapid transit (MRT) Putrajaya, Shah Alam, and planned MRT Circle Line, ridership remains below average due to the uncertainties and service quality flaws (Amir et al., 2025). Prolonged travel times, untimely delays, and limited accessibility are primary causes of passenger dissatisfaction (Mee et al., 2022). These service deficiencies increase spatiotemporal complexity which conventional statistical models ARIMA fails to predict accurately. This emphasizes the important need for advanced predictive model to forecast public transit ridership accurately, consistently, and reliably.

Advancements in big data analytics and deep learning (DL) methodologies offer promising solutions in modelling intricate spatiotemporal relationships within public transit networks (Chen et al., 2022). Unlike traditional models like ARIMA, DL approaches such as LSTM and GCN integrate multiple data sources – General Transit Feed Specification (GTFS) data, historical weather patterns, Points of Interest (POIs) – to fully capture multidimensional relationships (Ge et al., 2021; Chen et al., 2022). Implementing state-of-the-art (SOTA) DL architectures addresses Malaysia’s current reliance on conventional models, enabling accurate ridership predictions for complex spatiotemporal data.

1.2 Problem Statement

One of the major issues with Malaysia’s transit management system is predicting daily ridership accurately due to the complex relationships existing between spatiotemporal factors affecting public transport services – including population density, weather, station/stop accessibility and socio-economic activities (Amir et al., 2025). Consequently, transit authorities face critical bottlenecks in terms of scheduling, routing, and service intervals during peak hours and holidays, undermining system reliability and passenger satisfaction. Addressing this requires a dual approach: (1) identify spatiotemporal factors influencing Malaysia’s ridership trends; (2) develop a robust predictive model capable of forecasting daily ridership based on these identified features.

Traditional statistical models struggle with highly fluctuating data compared to DL approaches. A critical barrier exists in historical ridership data: extreme anomalies from Malaysia’s Movement Control Order (MCO) enforcement (18th March 2020 to 31st December 2021) produced an 85-90% passenger drop, creating highly noisy patterns unrepresentative of normal operations (Amir et al., 2025). Training AI models on such

extreme outlier data introduces significant predictive bias, as pandemic-driven behaviour differs fundamentally from typical urban mobility patterns (Zhao & Lan, 2025). Models trained on contaminated datasets often struggle to recognize true ridership peaks once daily life normalizes (Lv et al., 2021). Therefore, this researcher strategically compare two datasets – one including and one excluding the MCO period – to determine whether this anomaly should be treated as noise before model training.

1.3 Research Questions

- 1) What are the primary spatiotemporal factors (e.g. weather, POIs, population density) that heavily affect public transit ridership trends in Malaysia?
- 2) How accurately and consistently can existing DL architectures (spatiotemporal-based, graph-based, and attention-based) compare against each other and proposed model in predicting Malaysia’s public transit ridership?
- 3) How does the inclusion of extreme data anomalies, specifically the Malaysia’s MCO period, impact the predictive accuracy and bias of existing DL models and proposed model?

1.4 Research Objectives

- To identify and categorize the primary spatiotemporal factors affecting Malaysian public transit ridership through a systematic analysis of historical performance data.
- To develop Hybrid Multi-scale Temporal Spatio Feature (HMT-TSF) Forecaster that integrates Malaysia’s spatiotemporal data to estimate future ridership trends.
- To benchmark the proposed model against existing baseline, spatiotemporal-based, graph-based and attention-based models using combined score and R^2 .

- To evaluate and compare model performance across two distinct dataset segmentations (with and without MCO period) to determine the impact of extreme outlier data on predictive bias.

1.5 Research Scope

Table 1.1

Methodology, Metrics, Models, and Malaysia's MCO Period Used in This Research

Aspect		Description
Models*	Baseline	LSTM
	Spatiotemporal	BiLSTM, ST-LSTM, CNN-LSTM, CNN-BiLSTM, TPA-LSTM
	Graph	STGCN, ASTGCN, PDR-STGCN, STSGCN, STFGNN, MTGNN
	Attention	Autoformer, Informer
	Proposed	Hybrid Multi-scale Temporal Spatio Feature (HMT-TSF) Forecaster
Evaluation Metrics	Combined MAE, RMSE and MAPE, and R^2	
Geographical Focus	Bus, urban rail, commuter transit networks with available data throughout whole Malaysia.	
MCO Period	Without MCO	1 st Jan 2022 to 31 st Dec 2025
Segmentation	With MCO	1 st Jan 2019 to 31 st Dec 2025

Note. *. Models full form refer to Appendix C.

1.6 Research Contribution

- Provide a detailed comparative analysis evaluating multiple deep learning models across distinct lookback windows, explicitly segmented by MCO periods.
- Introduce a predictive model that outperforms baseline SOTAs across all lookback windows and MCO inclusion/exclusion, accompanied by a reduced-feature variant based on SHAP-based feature importance ranking, to evaluate the removal of near-zero important spatiotemporal features toward ridership prediction.
- Develop a command-line interface (CLI) inference to predict 7-day ridership for 12 distinct transit networks based on historical distribution percentages with the proposed model.

1.7 Thesis Organization

Chapter 2: Literature Review

Reviews public transport reliability, ridership dynamics, and the Malaysian transit context. It covers transit data ecosystems, preprocessing challenges, and the shift from traditional models to deep learning for spatiotemporal forecasting and closes by identifying the research gap.

Chapter 3: Methodology

Describes the full pipeline: eight data sources, feature engineering, EDA, and sequence construction under MCO-inclusive and MCO-exclusive settings. It presents fourteen baseline models and the proposed HMT-TSF architecture, together with the Combined% evaluation framework.

Chapter 4: Findings & Results

Reports the comparative evaluation of fifteen architectures across default and tuned configurations, three look-back windows, and both MCO conditions. It covers baseline rankings, tuning and look-back sensitivity, MCO robustness, fit diagnostics, HMT-TSF performance, SHAP analysis, and the feature-reduced HMT-TSF-FR variant.

Chapter 5: Discussion & Conclusion

Interprets the findings, discusses implications for Malaysian transit planning, acknowledges study limitations, outlines future work, and concludes on the contribution of HMT-TSF to demand-responsive operations.

CHAPTER 2

LITERATURE REVIEW

2.1 Public Transport Reliability and Demand Dynamics

2.1.1 Defining Reliability: Metrics and User Perception

Public transport reliability is a multi-dimensional construct that integrates objective operational performance indicators with subjective passenger experience. A study defines travel time reliability as the calculated time gap between expected and actual travel times, citing route length, signalized intersections, and departure delays as primary structural causes of network unreliability (Mohamed et al., 2021). Conversely, some researchers also demonstrate that user satisfaction within the Klang Valley Light Rail Transit (LRT) system is mediated by “soft” reliability factors – the provision of accurate real-time information and the quality of station amenities (Ibrahim et al., 2022).

This divergence indicates that while transit agencies like RapidKL traditionally prioritize “hard” technical metrics such as headway adherence and on-time performance, the passenger’s psychological perception of reliability is shaped by the immediate physical environment and the mitigating effect of transparent communication. For instance, structural breakdowns and delays on the LRT Kelana Jaya line, alongside extreme disruptions like the derailment near Chan Sow Lin station on LRT Ampang-Sri Petaling line, highlight that operational unpredictable execution converts directly into acute user stress and anxiety.

Consequently, understanding the intersection of technical metrics and subjective factors is vital for establishing standardized evaluation criteria, as mapped in the comprehensive breakdown of operational, informational, and service quality parameters detailed in Table 2.1.

Table 2.1*Comparison of Technical Reliability Metrics and User Perception Factors*

Metric Category	Technical ^a	Subjective ^b
Temporal (Mohamed et al., 2021)	Headway adherence, Travel time variability	Punctuality, Wait time anxiety
Informational (Rezapour & Ferraro, 2021)	PIS accuracy, Real-time data latency	Certainty, Reduced stress
Service Quality (Ibrahim et al., 2022)	Vehicle cleanliness, Amenity availability	Comfort, Perceived safety
Operational (Sogbe et al., 2024)	Frequency, Route coverage	Accessibility, Convenience

Note. a. Operational Indicator.

b. User Perception

2.1.2 The Relationship between Ridership and Service Unreliability

Chronic service unreliability generates a severe demand-erosion cycle that fundamentally undermines public transit ridership. The absence of reliable predictions regarding traffic and weather variations causes citizens to abandon public transit in favour of private vehicles (Amir et al., 2025), supported with another finding which identifies prolonged travel times and untimely delays as the leading causes of passenger dissatisfaction in metropolitan areas like Kuala Lumpur and Manila (Mee et al., 2022).

When operational variance grows, passengers are forced to allocate substantial “buffer time” into their personal schedules to insure against systemic delays. For most commuters, this continuous temporal penalty quickly outweighs the financial savings of public transport, causing stagnant or declining modal shares even during periods of rising fuel

costs or high private vehicle ownership penalties, as observed in decentralized urban sectors such as Kota Samarahan. This behavioural shift establishes a self-reinforcing loop where transit unreliability drives private vehicular growth, thereby intensifying the road congestion that further degrades transit schedule adherence, as visually conceptualized in the behavioural cycle shown in Figure 2.1.




Figure 2.1 - Vicious Cycle of Transit Unreliability and Ridership Uncertainty

2.1.3 The Landscape of Public Transit in Malaysia

The Malaysian public transportation sector is currently defined by a sharp mismatch between extensive capital infrastructure investments and persistently low commuter modal shares. Despite massive government-funded transit expansions – including the Mass Rapid Transit (MRT) Putrajaya line, Shah Alam line, and the upcoming MRT3 Circle line – national public transport usage remains stagnant at approximately 20%,

falling significantly short of the 40% target established by the National Transport Policy (NTP) 2019 – 2030. Research highlights that in regions like Sarawak, private vehicle ownership remains exceptionally high due to the perceived inadequacy of bus service quality regarding tangibility and operational responsiveness (Ubaidillah et al., 2022).

This disparity proves that physical network expansion is sufficient on its own to shift commuter habits; infrastructure must be supported by localized reliability and data-driven operational optimizations to resolve localized service gaps. While programs like the MyBas initiative in Johor Bahru and Penang have successfully leveraged GTFS data to optimize networks and capture over 14.5 million trips, systemic barriers like the “first-mile-last-mile” (FMLM) connectivity gap continue to limit the efficacy of the broader national network. Resolving these localized structural inefficiencies requires transit management to pivot away from purely physical expansion toward DL methodologies capable of accurately forecasting spatiotemporal ridership to mitigate daily unreliability.

2.2 Transit Data Ecosystems and Anomalies

2.2.1 Sources of Transit Data

Modern transit data ecosystems combine diverse endogenous operational streams and exogenous environmental inputs to form a comprehensive foundation for urban mobility analysis. Two studies founded to classify core endogenous sources as Automated Fare Collection (AFC) systems for ridership tracking, Automated Vehicle Location (AVL) systems for real-time GPS tracking, Automated Passenger Counting (APC) sensors, and static GTFS schedules (Ge et al., 2021; Liu et al., 2025). Concurrently, another study also defines critical exogenous variables as real-time weather metrics, road network traffic data, POIs extracted via land-use profiles, and regional socio-economic demographics (Amir et al., 2025).

Synthesizing these multi-source streams into an integrated matrix – as categorized by the operational features, collection frequencies, and specific analytical applications outlined in Table 2.2 and 2.3 for endogenous and exogenous data, respectively – is a vital prerequisite for advanced predictive modeling.

Table 2.2

Endogenous Data Sources: Examples, Applications, and Characteristics

Specific Examples	Typical Applications	Key Characteristics
AFC Systems	Ridership analysis, origin-destination, revenue tracking	Transactional, passenger-centric
AVL Systems	Real-time tracking, schedule adherence, fleet management	Spatiotemporal, vehicle-centric
APC Systems	Occupancy rates, detailed ridership statistics	Discrete counts, vehicle-centric
Vehicle Sensors	Maintenance, operational efficiency	Real-time, diagnostic
GTFS Data	Route planning, schedule information, app development	Static, foundational

Table 2.3

Exogenous Data Sources: Examples, Applications, and Characteristics

Specific Examples	Typical Applications	Key Characteristics
Weather Data	Demand forecasting, operational adjustments	Environmental, dynamic

Traffic Data	Travel time prediction, congestion management	Real-time, network-wide
POIs	Demand modeling, urban planning	Static/dynamic, location- based
Demographic/Socio- economic	Long-term planning, demand forecasting	Static/slow-changing, population-centric

2.2.2 Data Quality, Noise and Preprocessing Challenges

Raw transit data ecosystems are highly vulnerable to fragmented quality issues and severe noise, demanding extensive preprocessing before deployment in DL models. One research points out that public transport agencies frequently collect disjointed and fragmented data streams that impede comprehensive system interpretation (Keller et al., 2022), while another identifies pervasive data quality threats such as sensor omissions, localized GPS telemetry errors, formatting inconsistencies across legacy systems, and extreme outliers (S.K.B et al., 2024).

These imperfections introduce major challenges during data cleaning, multimodal integration, feature transformation, and data reduction stages. For example, a missing data gap caused by an IoT network outage could generate significant downstream predictive bias if it left unaddressed, while the lack of alignment across spatial resolutions creates high noise that obscures actual demand signals. Because raw transit data is rarely usable in its initial state, implementing rigorous, automated preprocessing and feature engineering pipelines is essential to ensure data integrity and unleash the full potential of advanced analytics.

2.2.3 Extreme Anomalies in Spatiotemporal Data

Spatiotemporal transit profiles are sensitive to extreme, non-typical anomalies that degrade the reliability and generalization capabilities of predictive models. Extreme anomalies deviate drastically from standard mobility baselines, exemplified by Malaysia’s MCO during the COVID-19 pandemic, which caused an abrupt 85-90% ridership drop across all transit networks (Maria-Arribas et al., 2026). Training predictive models directly on these contaminated datasets introduces severe predictive bias because pandemic-era containment behaviours differ fundamentally from normal urban mobility patterns (Zhao & Lan, 2025).

When neural network architectures ingest uncorrected outlier sequences, they risk overfitting to anomalous troughs, confusing regular seasonal patterns, and failing to recognize normal ridership peaks once standard daily operations resume. Traditional anomaly detection methods relying on basic statistical thresholds often fail when applied to high-dimensional spatiotemporal data, driving the need for advanced techniques like ensemble DL or strategic dataset segmentation. This structural vulnerability underlines the necessity of this study’s approach: splitting the time-series data into distinct MCO-inclusive and MCO-exclusive segments to empirically evaluate and isolate the impact of extreme noise on DL architectures.

2.3 Evolution from Traditional to DL Models

2.3.1 Traditional Architectures

Traditional statistical and machine learning architectures offer strong model interpretability but are fundamentally limited by their inability to capture the non-linear, multi-dimensional complexities of modern transit data. Historically, forecasting models have relied on classical frameworks like ARIMA, Historical Average (HA), Vector

AutoRegressive (VAR) models, Support Vector Regression (SVR), and Random Forest Regression (RFR). These traditional statistical architectures demand strict data stationary and rigid distribution assumptions, which directly conflict with highly fluctuating, time-varying traffic data (Yin et al., 2022).

The structural limitations detailed in the comparative breakdown of data handling, assumptions, and scalability metrics in Table 4 emphasize the clear need to transition away from rigid classical models toward highly flexible DL frameworks (Sobrie et al., 2023).

Table 2.4

Comparison of Traditional and DL Models

Aspect	Traditional Models	DL Models
Data Handling	Small-scale, structured	Large-scale, multi-source
Dependencies	Linear, short-term	Non-linear, long-term
Complexity	Low (functional forms)	High (hierarchical features)
Assumptions	Strict (Stationarity, normality)	Minimal (Data-driven)
Interpretability	High	Lower (Black-box nature)
Scalability	Limited	High

2.3.2 Deep Learning Approaches in Spatiotemporal Transit Data

The main advantage of using DL architectures is that they can circumvent many restrictions posed by the conventional models by means of automatically capturing hierarchies of non-linear spatiotemporal features from transit multi-source data. The most efficient modern DL frameworks incorporate specially designed neural building blocks – Convolutional Neural Networks (CNNs) capture spatial correlations from grid structures,

Recurrent Neural Networks (RNNs) like LSTMs track sequential temporal dependencies, Graph Convolutional Networks (GCNs) model non-Euclidean network topologies, and attention mechanisms dynamically weigh feature significance. For instance, multi-model GeoSpatial-Temporal LSTM (GT-LSTM) that achieved a 15% reduction in MAPE and a 20% reduction in RMSE over traditional methods and standard DL baselines (S.K.B et al., 2024).

These architectures eliminate the necessity for explicit feature engineering through the learning of multi-dimensional interactions directly from the data. The use of transportation networks as connected graph nodes and environmental variables as dynamic weights, models like STGCN, ASTGCN, and TPA-LSTM can simultaneously process structured data (such as GTFS) and unstructured covariates (such as weather and POIs). Successful deployment of these diverse DL architectures requires establishing an equally rigorous benchmarking methodology to benchmark their respective accuracy and error.

2.3.3 Benchmarking Methodologies and Evaluation Metrics

Rigorous, standardized benchmarking methodologies and multi-metric validation frameworks are essential to verify the accuracy, consistency, and operational reliability of predictive models. In comprehensive DL surveys, some studies utilize MAE, RMSE, and MAPE as primary evaluation metrics (Jiang et al., 2021), while others emphasize the importance of pairing relative and absolute indices to validate SOTA results on benchmark datasets (Mystakidis et al., 2025).

Evaluating models through a single metric can mask critical performance flaws. A comprehensive benchmarking framework, as shown in Table 2.5, must combine comparative analysis against established baselines, sensitivity analysis under varying data

densities, and robustness testing across distinct geographical and anomalous contexts. Adhering to these structured metrics ensures a fair comparison between 14 baseline architectures evaluated in this study, providing a clear path to validating the performance gains of the proposed HMT-TSF forecaster.

Table 2.5

Common Evaluation Metrics and Their Focus (Jiang et al., 2021; S.K.B et al., 2024; Mystakidis et al., 2025)

Metric	Focus
MAE	Treats all errors equally and highly robust to outliers
RMSE	Heavily penalized large errors and sensitive to outliers
MAPE	Measures error relative to actual values, easy to understand
R^2	Explanatory power, how well model predict based on given data

2.4 AI-Driven Operational Strategies and Sustainability

2.4.1 Proactive Scheduling and Resource Allocation

Transitioning from reactive transit management to AI-driven predictive modelling enables transit agencies to implement proactive scheduling and highly optimized resource allocation. Public transport networks are evolving through AI’s capacity for data-driven optimization (Jevinger et al., 2024). A study proved that LSTM encoder-decoder architecture outperforms traditional rule-based business systems by 18% to 23% in real-time delay forecasting (Sobrie et al., 2023). Furthermore, reports also show that AI-powered planning platforms maximize bus schedule efficiency and fleet deployment by anticipating changing user demands (Levner, 2025; CCS Global Tech, 2026).

Traditional dispatch scheduling is reactionary in nature; changes in service frequencies are made only after delays or disruptions have occurred in the system due to overcrowding or other reasons. On the contrary, DL models can predict passenger surges and bottleneck formations well in advance, which allows for dynamic changes in service intervals as well as coach allocation based on future passenger demand. Their successful deployment depends on overcoming several technical and organizational barriers within transit agencies.

2.4.2 Deployment Challenges of AI in Transit Management

AI solution adoption into public transportation system framework is hampered by multiple obstacles including data quality, infrastructure scale, and organizational resistance. Fragmented corporate data structures and internal organizational silos frequently block the adoption of advanced data science methods (Keller et al., 2022), whereas two evidence shows that high upfront implementation costs, strict data privacy compliance, and stakeholder resistance to operational changes as major adoption barriers (Suwaidi et al., 2022; Hashimzai & Mohammadi, 2024).

DL approaches need large-scale, clean datasets, meaning there must be considerable long-term commitment in data governance and scalable computing infrastructure. Without clear data integration strategies and collaborative pipelines connecting software developers with transit operators, such complex predictive systems will just be theoretical endeavours. It is crucial to overcome these multifaceted organizational obstacles since addressing them will allow transit agencies to unlock the significant environmental benefits associated with such AI-based optimizations, as depicted in the cause-and-effect flow in Figure 2.2.




Figure 2.2 - Cause-and-effect of Resolving AI Deployment Challenges in Public Transit Systems

2.4.3 Sustainable Urban Mobility and Environmental Impact

Implementing AI optimizations within public transit networks directly supports sustainable urban mobility goals by reducing operational waste and mitigating environmental degradation. Transforming urban mobility is vital for lowering global transportation emissions (Son et al., 2025) whereas AI-driven regularizations of headways and schedule adherence minimize fuel waste, emergency maintenance costs, and operational inefficiencies (Vujadinovic et al., 2024).

If predictive models prove successful in improving transit efficiency and reducing waiting time, they will help expedite the modal shift that involves choosing public transits over private vehicles. The combination of this modal shift along with the improvement of bus idling and rail routes directly lowers urban emission rates and improves overall air quality (CCS Global Tech, 2026). The optimization of transit operations through AI-powered

forecasts serves as a vital tool for advancing comprehensive urban sustainability and improving the long-term quality of life for citizens.

2.5 Research Gap

Existing literature lacks a hybrid ridership forecaster that integrates multi-scale spatiotemporal features while explicitly isolating predictive bias from severe structural breaks such as Malaysia's MCO period. Although recent studies apply deep learning to public transport ridership (Farahmand et al., 2023; Amir et al., 2025), they rely on standard single-paradigm architectures that do not jointly model multi-scale temporal dynamics and multi-dimensional spatial interactions. Pandemic-era anomalies further confound model training (Maria-Arribas et al., 2026), yet no Malaysian study systematically quantifies how such breaks distort graph-based and attention-based state-of-the-art models. Excluding the MCO period disrupts series continuity; retaining it uncorrected introduces predictive bias — and without a unified benchmark across sequential, graph, and attention paradigms under both MCO conditions, operators lack evidence for selecting robust forecasters. Table 2.6 consolidates these limitations across prior work. This study addresses them through the Hybrid Multi-scale Temporal Spatio-Feature (HMT-TSF) Forecaster, enabling a shift from reactive to proactive, data-driven transit management.

Table 2.6*Comparative Summary of Prior Forecasting Studies Supporting the Research Gap*

Study	Scope & Target	Model & Data	Limitations	Gap Link
(Farahmand et al., 2023)	Netherlands (bus network); Daily bus ridership, weather-conditioned	Standard DL (CNN/LSTM family); Weather covariates only	X Single temporal scale; X No pandemic/MCO segmentation; X Single-model study	Applies baseline DL to ridership but not multi-scale spatiotemporal fusion or anomaly isolation
(Amir et al., 2025)	Malaysia (Rapid Bus Kuantan & Penang); Ridership prediction, multi-feature analysis	Standard DL (multi-feature, non-hybrid); Limited operator features	X No explicit multi-scale TCN/window sweep; X No MCO-included vs excluded evaluation; X No graph/attention SOTA comparison	Closest Malaysia DL ridership work, yet standard architecture without hybrid multi-scale design or systematic paradigm benchmark

(S.K.B et al., 2024)	Urban mobility (multi-modal); Urban mobility patterns	GeoSpatial-Temporal LSTM (GT-LSTM); Multi-modal geospatial + temporal streams	Partial (geo-temporal LSTM, not multi-scale TCN blocks); X No documented structural-break / MCO protocol; X GT-LSTM vs traditional baselines only	Shows multi-modal DL gains but not hybrid graph–attention fusion or anomaly-segmented benchmarking
(Sobrie et al., 2023)	European railways; Real-time delay prediction	DL (LSTM encoder–decoder); Operational delay features	X Single-scale sequential encoding; X No extreme-anomaly segmentation; X Single architecture vs rule-based systems	Demonstrates DL superiority for transit prediction but single-paradigm, non-Malaysia, no ridership–MCO analysis
(Yin et al., 2022)	Survey (traffic prediction); Traffic flow / speed forecasting	Review: CNN, RNN, GCN, attention; Discusses multi-source conceptually	Discusses multi-scale conceptually; Notes distribution shift; no MCO case study; Compares families conceptually, not empirically on one dataset	Establishes DL over traditional models but does not operationalise hybrid multi-scale ridership forecasting under anomalies

(Jiang et al., 2021)	Survey + traffic benchmarks; Urban traffic prediction	Review + benchmark of DL traffic models; Multi-source in benchmark datasets	Limited multi-scale discussion; $\times$ No pandemic-era ridership anomaly protocol; Partial (traffic DL families, not transit ridership paradigms)	Provides evaluation-metric framework (MAE, RMSE, MAPE) but not Malaysia transit or MCO-segmented multi-paradigm comparison
(Mystakidis et al., 2025)	Survey (traffic congestion); Congestion prediction	Review of emerging DL techniques; Multi-source discussed at survey level	Emerging multi-scale methods noted; $\times$ No empirical MCO / ridership anomaly study; $\times$ Survey only	Catalogues SOTA techniques but lacks Malaysia ridership empirical benchmark across sequential, graph, and attention models
(Maria-Arribas et al., 2026)	Traffic (graph-augmented dataset); Spatiotemporal traffic analysis / ML	Graph-augmented traffic dataset for DL; Graph + traffic sensor streams	Dataset supports multiple scales; Documents extreme mobility anomalies (85–90% drops); $\times$ Dataset paper, not ridership forecaster benchmark	Confirms anomaly severity but does not quantify distortion of graph/attention SOTAs on Malaysian national ridership

(Zhao & Lan, 2025)	USA (highway reliability); Travel-time reliability modelling	Statistical / reliability modelling; Highway route data	X Not multi-scale DL forecaster; Addresses non-typical travel patterns; X Not multi-architecture DL benchmark	Cited for confounding non- typical patterns; does not benchmark Malaysian transit DL paradigms under MCO segmentation
--------------------	--	---	--	---

Note. ✓ = explicitly addressed in the cited study.

X = not addressed

Surveys provide methodological context; empirical ridership gaps are concentrated in (Farahmand et al., 2023) and (Amir et al., 2025).

CHAPTER 3

METHODOLOGY

3.1 Data Collection and Understanding

This study integrates eight heterogeneous data sources — daily ridership, GTFS network supply, GADM administrative boundaries, retail fuel prices, public and school holidays, state-level rainfall, gridded population density, and OSM point-of-interest counts — into a single spatio-temporal forecasting dataset. Per-source coverage, content, and usage are summarised in Table 3.1.

3.1.1 Primary Transit and Network Data

Daily ridership counts for 12 Malaysian service lines (LRT, MRT, Monorail, KTM, and RapidBus) and static GTFS data were obtained from data.gov.my. Combining GTFS with spatial layers supports granular assessment of network efficiency and accessibility (Hassan et al., 2025). Real-time GTFS streams are excluded because the portal provides only vehicle positions as of early 2026; deriving metrics from raw coordinates would degrade inference efficiency.

3.1.2 Administrative Geography and Spatial Connectivity

GADM level-1 boundaries for Malaysia were standardised to WGS-84 to construct binary and border-length-weighted adjacency matrices. Graph-based spatial structures capture regional heterogeneity in transit demand (Jin et al., 2022).

3.1.3 Economic and Temporal Indicators

Weekly retail fuel prices (RON95, RON97, diesel) from data.gov.my were forward-filled to a daily index; Malaysian public and school holidays (2019–2026) were extracted from timeanddate.com. A significant positive correlation between fuel price increases and public transit ridership in developing countries (Ahmad et al., 2024).

3.1.4 Environmental and Geospatial Features

Gridded population density (worldpop.org), 7-category POI counts within a 500 m stop radius (OSM Overpass API), and sub-national daily rainfall (data.gov.my) were integrated as environmental covariates. Non-linear ridership relationships require joint semantic and spatial encoding (Shi et al., 2024).

3.1.5 Data Segmentation and MCO Considerations

The dataset (1 January 2019 – 31 December 2025) was split into MCO-inclusive and MCO-exclusive configurations to measure how atypical operational periods affect model generalisation. Table 3.1 summarises all eight sources.

Table 3.1

Independent Raw Data Sources: Coverage, Content, and Usage in This Study

Source (Coverage)	Content	Usage
Ridership (2019-01-01 – present)	Daily passenger counts for 12 transit services + total	Primary forecast target; provides the 13 output variables (12 service lines + total)

Fuel Price (2017-03-30 – present)	Weekly retail prices for 6 fuel types (level + weekly change)	Demand driver; capturing modal substitution behaviour
GTFS Static (Snapshot)	Standard GTFS files for Rapid Rail KL, RapidBus KL, RapidBus Penang, KTMB	Network topology; stop counts, route density and travel-time edges quantify transit supply
Rainfall (2019-01-01 – present)	Daily precipitation at state level; 9 metrics including accumulation and anomaly indices	Weather covariate; state-level daily precipitation captures external signals
GADM (2020)	GeoJSON polygons for 16 Malaysian states (Level 1 admin divisions)	Spatial structure; used to derive inter-state adjacency weights
POIs (Snapshot)	OSM POI extract; 7 categories (transport, food, retail, education, healthcare, leisure, other)	Land-use context within a 500m catchment of each stop
Population Density (2020)	~1km ² gridded raster of population density across Malaysia	Spatial context; static proxy for transit catchment potential
Holidays (2019 – 2026)	Date-range calendar of public holiday and academic break periods	Demand modifier; lead/lag features capture anticipation dips and post-holiday return surges

3.2 Feature Engineering

3.2.1 Data Cleaning

Eight independent preprocessing scripts transform heterogeneous raw formats into a standardised daily matrix (Table 3.2). Percent-change fuel features alongside level series capture short-run economic responses (Pour et al., 2026); cyclic sine/cosine encoding avoids ordinal discontinuities at calendar boundaries (Casolaro et al., 2023).

$$\text{dow_sin} = \sin\left(\frac{2\pi \cdot \text{dow}}{7}\right), \quad \text{dow_cos} = \cos\left(\frac{2\pi \cdot \text{dow}}{7}\right)$$

$$\text{month_sin} = \sin\left(\frac{2\pi \cdot \text{month}}{12}\right), \quad \text{month_cos} = \cos\left(\frac{2\pi \cdot \text{month}}{12}\right)$$

Table 3.2

Primary Cleaning Operations Applied to Each Sources

Source	Cleaning Operations
Ridership	Date parsing, MCO binary flag, pre-/post-launch null handling, total_ridership derivation
Fuel price	Daily forward-fill reindex, percent-change derivation, back-fill of leading nulls
Holidays	Expansion to daily rows, lead/lag proximity features, cyclic DOW/month encoding
Rainfall	Version filter (final only), wide pivot (date * state), 7-day linear interpolation, bfill/ffill
GTFS	Referential integrity verification, coordinate validation, directed edge extraction, static scalars
OSM POI	Element deduplication, 7-category taxonomy, 500m catchment counts, per-stop log transforms

Population	Bounding-box filter, log1p transform, state aggregation, national
Density	median scalars
GADM	Property cleaning, centroid extraction, shared-border adjacency matrix
Boundaries	

3.2.2 Feature Alignment

All variables were aligned to consecutive daily indexes for both research periods using the merge and null-handling rules in Table 3.3. Autoregressive lags (7, 14, 28 days) were computed from the full historical ridership series before merging (Wu et al., 2023; Yusuf et al., 2025), yielding a 79-feature matrix grouped as in Table 3.4.

Table 3.3

Merge Strategy and Null Handling

Source	Join Method	Null Handling
Ridership (Targets)	reindex	Pre-launch nulls retained; filled to 0.0 in sequence assembly
Fuel Price	reindex + ffill	No gaps after forward-fill
Holiday / Cyclical	reindex + fillna(0)	Non-holiday days default to 0
Rainfall	reindex + interpolate(limit=7) + bfill/ffill	Contiguous after interpolation
Static Features	Scalar broadcast	No nulls across population density, GTFS, POI, or GADM streams

Table 3.4*79 Features Across 5 Semantic Groups*

Group	Count	Description
Targets	13	12 service-line ridership counts + total_ridership
Temporal	16	Holiday flags, lead/lag proximity days, cyclic DOW/month, year, day_of_year, is_weekend
External	30	Fuel price levels and percent-changes (15) + per-state rainfall (15)
Lag	3	ridership_lag_7, ridership_lag_14, and ridership_lag_28
Static	17	Population density, GTFS network counts, OSM POI means, GADM boundary stats
TOTAL	79	Finalized aligned multivariate input matrix

3.2.3 Sequence Building

The aligned matrix was converted to sliding-window tensors (T_{in} look-back, $T_{out} = 7$ -day horizon) with a 70%/15%/15% chronological train/validation/test split. MinMax scaling was fit on training data only to prevent leakage (Casolaro et al., 2023).

3.3 Explanatory Data Analysis

3.3.1 MCO Collapse and Unequal Recovery

The COVID-19 MCO caused an abrupt 85–90% ridership drop (affecting ~25% of the 2019–2025 series), with change-point detection identifying four distinct phases (Figures 3.1–3.2). Rail-heavy services recovered more slowly than bus services, reflecting rigid network topology versus route-level flexibility.




Figure 3.1 - Total Daily Transit Volume from 2019 to mid-2026, Featuring 6 Vertical Red Dashed Lines Pinpointing Specific Structural Shifts/Transition Points over Time




Figure 3.2 - Average Daily Usage Numbers Across Various Rail and Bus Lines Segmented into 3 Distinct Phases: Pre-MCO (blue), MCO (orange), and Post-MCO (green)

3.3.2 Northeast Monsoon Rainfall Pattern

Extreme rainfall (>50 mm/day) and wet-day ratios peak November–January, with east-coast states exceedingly west-coast frequencies (Figures 3.3–3.5). National rainfall aggregation masks regional variation that drives mode-specific choices (Ngo & Bashar, 2024).




Figure 3.3 - Comparison of Total Counts of Wet Days (≥ 10 mm), Very Wet Days (≥ 30 mm), and Extreme Days (≥ 50 mm) Across Various States with Terengganu Consistently Showing the Highest Counts




Figure 3.4 - Dashboard Visualizing the Trend and Breakdown of Extreme Rainfall Events over Time, Including Month/Annual Frequency Percentages, Annual Wet Day Counts by Category, and Extreme Event Frequency Aggregated by Month




Figure 3.5 - Dashboard Outlining General Rainfall Trends, Including Average Daily Rainfall by Month, Monthly Rainfall Anomalies, a 7-day Rolling Average Timeline, and Total Annual Rainfall from 2019 to 2026

3.3.3 Weather-Induced Ridership Surge under Heavy Rainfall

Intensity-bin analysis (Figures 3.6–3.8) shows light rain slightly suppresses travel, while heavy rain above the 75th percentile associates with increased transit ridership — consistent with modal substitution during hazardous driving conditions (Huang et al., 2022; Jiang & Cai, 2023; Rahmani et al., 2025).



Figure 3.6 - Advanced Behaviourial Analysis Focusing on Weather-driven Modal Shifts, Constrasting Heavy Rain Days against Normal Conditions through a Correlation Matrix, Monthly Trend Comparisons, and a Daily Percentage Change Surge Analysis




Figure 3.7 - Monthly Averages for Daily Rainfall against Total Ridership with Monthly Breakdown of Correlation Coefficients, r , with Corresponding Statistical Significance (p-values)




Figure 3.8 - Dashboard Analysis on Direct Impact of Wet Weather with Rainfall-vs-Ridership Scatterplot ($r = 0.1444$), Average Daily Ridership Comparison Bars, Total Rainy Day Sample Count ($n = 197$), and Historical Rainfall Time Series from 2019 to 2026

3.3.4 Fuel Price Elasticity and Modal Substitution

Post-MCO Pearson correlation between weekly RON95 and total ridership is $\sim +0.35$, with non-linear increases above RM 2.20/litre and peak lagged responses at 1–3 days (Figures 3.9–3.11). Two studies show that separating level series from price adjustments prevents models from confusing multi-year trends with sudden policy shocks (Chevance et al., 2024; Pour et al., 2026).




Figure 3.9 - Fuel Price Levels (RON95, RON97, Diesel) in MYR/Litre (top) and Weekly Price Changes for RON95 and Diesel (bottom), both from late 2018 to mid-2026




Figure 3.10 - Dashboard Analysis on Direct Relationship between Fuel Prices and Public Transit Ridership with Scatterplot with Trend Lines and Weekly Percentage Changes, and Bar Chart of Average Daily Ridership by Price Level




Figure 3.11 - Lagged correlation (from 0 to 7 days) between Changes in Fuel Prices (RON95 and Diesel) and Subsequent Changes in Transit Ridership

3.3.5 Holiday Anticipation and Return-Surge Effect

Cross-correlation reveals an ~18% ridership drops 1–2 days before public holidays and a sharp spike on the first post-holiday working day (Figures 3.12–3.15). Proximity features expressing the distance to and from holidays to allow models to learn these demand gradients directly (Wu et al., 2023).




Figure 3.12 - Broad Seasonal and Weekly Overview Displaying Average Daily Ridership Across Day Types, Monthly Distribution of Public Holidays (peaking in May), Daily Breakdown by Day of the Week, General Ridership Fluctuations Across the Months of the Year




Figure 3.13 - Assessing How the Length of Holiday Influences Travel Patterns Showing that Short Holidays (less than 3 days) Experience the Most Severe Percentage Dip in Ridership from Normal Levels with Frequency Distribution and Day-of-Week Profile Broken Down by Holiday Duration




Figure 3.14 - Ridership Trends between Academic and Public Holidays highlighting Public Holidays See Sharp Drops in Both Overall Mean Volume and Daily Percentage Change with Breakdown of Mean Ridership Across Dozens of Individual Malaysian Calendar Events




Figure 3.15 - Dashboard Tracking Transit Demand around Holiday Periods, Showing Overall Mean Total Ridership Drops on Holidays, Day-of-Week Demand Dips (Most Pronounced on Tuesdays and Wednesdays), Distinct Weekday vs Weekend Response Gaps, and Percentage of Daily Ridership Change by Holiday Regime

3.3.6 Lag Dominance and Static Near-Zero Signal

PCA of the Pearson correlation matrix shows the first principal component accounts for ~72% of variance and is dominated by ridership lags at 7, 14, and 28 days (Figures 3.16–3.17). Static network and demographic features show near-zero linear correlation, indicating they require non-linear modelling (Wu et al., 2023).




Figure 3.16 - Detailed 6 x 6 Correlation Matrix of Key Demand Forecasting Inputs (left) with Standardized Coefficients of the Dominant Predictors of Ridership (right)




Figure 3.17 - Large-scale, Lower-triangular Heatmap visualizing Complex Feature Correlation Matrix (79 x 79) for Full Demand Model

3.4 Baseline & Comparative Models

14 baseline deep-learning models form a progressive comparison chain that isolates each architectural contribution — from sequential encoding through graph propagation to series decomposition. Architecture diagrams, hyperparameters, and training configurations are documented in Appendix C.

3.4.1 Spatiotemporal Models

LSTM — Foundational sequential baseline establishing the performance floor (Barath et al., 2026). Gated memory captures daily and weekly commuter cycles without graph or attention inductive biases.

BiLSTM — Tests bidirectional encoding over the look-back window relative to LSTM (Krishnasamy et al., 2025). Relevant for mid-window holidays and disruptions whose ridership response follows within the observed window.

TPA-LSTM — Tests pattern-level attention over LSTM hidden states for multi-scale periodicity (Wei et al., 2023). Matched to weekday/weekend asymmetry and holiday suppression in Malaysian ridership.

CNN-LSTM — Tests 1-D CNN local feature extraction before recurrent encoding (Topilin et al., 2025). Three fusion modes (sequential, parallel, augmented) are evaluated per Appendix C.

CNN-BiLSTM — Combines CNN local extraction with bidirectional context (Zhuang & Cao, 2022). Most expressive LSTM-family model before explicit spatial stream decoupling.

ST-LSTM — Bridge model decoupling temporal (LSTM) and spatial (MLP) streams (Cui et al., 2025). Canonical reference for training loop and comparison logic across the codebase.

3.4.2 Graph Models

STGCN — Foundational graph baseline with fixed Pearson inter-feature adjacency and Chebyshev graph convolution (Deng, 2025). Transitions from implicit to explicit cross-feature relational encoding.

PDR-STGCN — Novel extension combining dynamic attention adjacency with periodicity-aware 2-channel input (Hu et al., 2026). Addresses static-graph and single-channel limitations of STGCN.

STSGCN — Fuses spatial and temporal graph operations in a single synchronous $3N \times 3N$ adjacency (Chen et al., 2023). Suited to simultaneous multi-feature shifts during holidays.

STFGNN — Dual graphs for cross-feature co-variation (spatial) and intra-window temporal-profile similarity (temporal), fused via a learnable gate (Chang et al., 2025).

MTGNN — End-to-end learned asymmetric adjacency from node embeddings (Wu et al., 2025). Tests whether task-specific graphs outperform Pearson correlation.

3.4.3 Attention Models

ASTGCN — Adds learnable spatial and temporal attention over the STGCN backbone (Cui et al., 2025). Adapts node and timestep weighting across normal weekdays versus holiday periods.

Autoformer — Series decomposition with FFT-based autocorrelation attention (Ma & Zhang, 2025). Tests periodic ridership as signal decomposition rather than graph propagation.

Informer — ProbSparse efficient transformer with generative multi-step decoder (Song et al., 2024). At $T_{in} = 14$, ProbSparse degenerates to near-full attention, ensuring fair comparison with Autoformer.

3.5 Hybrid Multi-scale Temporal Spatio Feature (HMT-TSF)

HMT-TSF is developed to address three key limitations identified across 14 baseline models:

- **No model captures all three types of structure simultaneously.** LSTM family models handle temporal sequences well but have no graph structure and no regime awareness; graph-based models propagate inter-feature correlations but are rigid under distributional shift, attention-based models decompose periodic signals effectively but cannot propagate domain-meaningful feature-to-feature messages.
- **No model explicitly handles the MCO regime shift.** All graph-based models use static Pearson graphs computed on training data; the MCO pandemic caused a structural break in ridership patterns that invalidates these learned correlations. Static normalisation strategies compound this problem by applying fixed-scale transformations across data from fundamentally different regimes.
- **No model uses domain-aware feature grouping.** All 14 baselines treat the 79 features as a flat vector, giving equal initial weight to structurally disparate sources.

3.5.1 Feature Selection

All 79 inputs are organised into five semantic groups per Table 3.4 (targets, temporal, external, lag, static). Non-contiguous groups are defined as index segments. Each group is independently embedded, fused via a learned softmax gate, and projected to d_{model} before the three parallel encoders (see Figure 3.18).

How Features are Used

Step 1 – Semantic Group Embedding: Each group is independently projected by a small to a common per-group embedding dimension $d/2$:

$$\text{Group } g: x_g (B, T_{in}, F_g) \rightarrow \text{Linear}(F_g, d/2) \rightarrow \text{GELU} \rightarrow (B, T_{in}, d/2)$$

Independent embedding allows each group’s internal structure to be learned without cross-group interference at the first projection stage. This is architecturally analogous to how a domain expert analyses each data source on its own before synthesizing insights across sources.

Step 2 – Gated group fusion with learned softmax weights: All group embeddings are concatenated and passed through a learned softmax group gate, which adaptively weights each group’s contribution at each timestep:

$$h_{concat} = \text{cat}[h_1, \dots, h_5] \rightarrow (B, T_{in}, n_{groups} \times d/2)$$

$$\text{gate} = \text{softmax}\left(\text{Linear}(d_{concat} \rightarrow n_{groups})\right) \rightarrow (B, T_{in}, n_{groups})$$

$$h_{gated} = \Sigma_g(\text{gate}_g \cdot h_g) \rightarrow (B, T_{in}, n_{groups} \times d/2)$$

The softmax gate forces the model to explicitly allocate attention budget across feature groups at each timestep. On holiday dates, the temporal/cyclical group receives higher weight; on normal weekdays, the target context (recent ridership) and lag groups dominate. The gate learns this allocation from data without manual tuning.

Step 3 – Projection to d_{model} : The gated fusion output is projected to d_{model} via:

$$\text{Linear}(d_{concat} \rightarrow d_{model}) \rightarrow \text{GELU} \rightarrow \text{Dropout} \rightarrow \text{Linear}(d_{model} \rightarrow d_{model}) \rightarrow$$

$$\text{LayerNorm}$$

This two-stage projection with LayerNorm compresses the fused group embeddings into a unified representation of dimension d_{model} on which all three parallel encoders then operate.

3.5.2 Key Architecture Components

3.5.2.1 Reversible Instance Normalisation (RevIN)

RevIN is applied to the raw input before feature group embedding (Kim et al., 2023). Each sample’s mean and variance are computed per feature and used to normalise the input:

$$\hat{x} = (x - \mu_{sample}) / \sigma_{sample} \times \gamma + \beta$$

where γ and β are learnable per-feature affine parameters. The primary motivation is to reduce within-batch distribution shift caused by the MCO regime change. Without instance-level normalisation, a single minibatch containing samples from multiple regimes causes gradient conflicts that impair convergence. RevIN denormalises predictions after the forecast heads and before loss computation, ensuring the loss is measured in the original MinMax-scaled space where the target scaler was fitted.

3.5.2.2 Multi-scale Temporal Convolution Network (TCN) –

Temporal Encoder

The Multi-scale TCN applies casual dilated convolutions at up to three temporal scales:

- **Scale 1 (full T_{in}):** CausalConv blocks with exponentially increasing dilation capture short-range and medium-range temporal dependencies.
- **Scale 2 ($T_{in}/2$, activated for $T_{in} \geq 28$):** CausalConv on the first half of the window; captures medium-range structures.
- **Scale 3 ($T_{in}/4$, activated for $T_{in} \geq 56$):** CausalConv on the first quarter; capture long-range structural baselines.

WaveNet-style gated activations ($\tanh \odot \sigma$) regulate information flow within each causal block. DropPath (stochastic depth) stochastically drops entire residual paths during

training, with linearly increasing rates from 0 to –drop-path argument. A learned attention pooling mechanism blends outputs across active scales, producing the final temporal summary $h_t \in \mathbb{R}^{d_{model}}$.

3.5.2.3 Spatial Graph Encoder

Rather than using the raw temporal sequence as node features (as graph-based baselines do), the Feature Graph Encoder first compresses the time dimension via learned temporal attention:

$$\hat{x}(B, T_{in}, F) \rightarrow \text{learned time-attn} \rightarrow (B, F, 1) \text{node feature vectors}$$

A 2-layer GCN then propagates signals across the Pearson-correlation adjacency ($|\text{corr}| \geq 0.1$, same construction as STGCN/ASTGCN), with global mean pooling over all F feature nodes producing $h_s \in \mathbb{R}^{d_{model}}$. This design decouples graph encoding from temporal encoding: the graph branch receives a temporal summary rather than raw sequence, allowing GCN to focus on cross-feature relational patterns without interference from temporal dynamics. Importantly, this encoder and Regime Gating Embedding both receive raw RevIN-normalised input x , bypassing the Feature Group Fusion and Temporal Transformer Block, so the graph and regime branches see the unprocessed feature signal rather than the projected d_{model} representation.

3.5.2.4 Regime Gating Embedding

The MCO period represents a structural break in Malaysia transit ridership – not merely a large shock, but a change in which features predict ridership at all. During lockdown, fuel prices and population density features become irrelevant to transit demand (which

was prohibited regardless). The Regime Gating Embedding maintains $K=3$ learnable embedding vectors representing the three operational regimes:

- **Pre-COVID:** 2019-01-01 to 2020-03-17
- **MCO:** 2020-03-18 to 2021-12-31
- **Post-MCO:** 2022-01-01 to 2025-12-31

At each forward pass, the mean-pooled input is projected to $K=3$ soft logits via a linear layer and softmax, producing a soft mixture of regime embeddings:

$$h_r = \sum_k gate_k \cdot E_k, \quad gate = \text{softmax}\left(\text{Linear}(\hat{x}.\text{mean}(T))\right)$$

This soft gating allows the model to blend adjacent regime characteristics for transitional periods (e.g., early MCO easing in 2021) without hard chronological boundaries. Crucially, no date metadata is required at inference – the regime gate is inferred from the observed feature pattern alone.

3.5.2.5 Gated Fusion

The three encoder outputs h_t (temporal TCN), h_s (spatial TCN), and h_r (regime gating) are concatenated and passed through a Squeeze-and-Excitation (SE) bottleneck gate:

$$h = \text{cat}[h_t, h_s, h_r] \quad (B, 3 \cdot d_{\text{model}})$$

$$g = \sigma(\text{bottleneck}(h)) \quad SE: 3d \rightarrow 3d//4 \rightarrow 3d, \text{ then sigmoid}$$

$$\text{out} = \text{Linear}(g \odot h \rightarrow d_{\text{model}}) \rightarrow \text{GELU} \rightarrow \text{Dropout} \rightarrow \text{LayerNorm}$$

The SE bottleneck avoid a computationally expensive $3d \times 3d$ weight matrix while still learning to calibrate which of the tree encoder streams contributes most for each input context.

3.5.2.6 Dual Forecast Heads and Custom Loss

Two forecast heads are applied to the fused embedding:

- **Primary head:** $h \rightarrow \text{Linear}(d_{model}, d_{model}) \rightarrow \text{GELU} \rightarrow \text{Linear}(d_{model}, T_{out})$ with highway residual and LayerNorm.
- **Boosting head:** $h \rightarrow \text{Linear}(d_{model}, T_{out}) \times \text{sigmoid}(\alpha)$ where α is initialised to -2.0 so $\text{sigmoid}(-2.0) \sim 0.12$ suppresses the boosting contribution early in training; the head gradually activates as training converges

Final prediction: $y = y_{primary} + y_{boost}$

The custom loss penalises both prediction accuracy and smoothness:

$$L = \text{WeightedHuber}(\text{step-decay } \gamma = 0.9) + \lambda \cdot \text{TemporalSmoothness}$$

Step 1 (1-day-ahead) has weight 1.0

Step 7 (7-day-ahead) receives weight $0.9^6 \sim 0.53$.

$\text{TemporalSmoothness} = |y_{t+1} - y_t|^2$ across T_{out} prevents oscillatory day-to-day predictions.

3.5.2.7 Future Temporal Projection – Known-Future Calendar

Conditioning

The 16 temporal features are deterministic for any future calendar date, so it was pre-computed for the T_{out} forecast steps of each window as $X_{future}: (B, T_{out}, 16)$. A per-step MLP ($n_t \rightarrow \max(2 \cdot n_t, 32) \rightarrow 1$, zero-initialised so it starts as a no-op) learns an additive correction from this known-future context – letting the model anticipate weekend dips and holiday effects inside the forecast horizon rather than extrapolating them from the look-back window.

3.5.3 Architecture Diagram




Figure 3.18 - HMT-TSF Architectural Flow Diagram

Note. It illustrates a multi-path technical processing pipeline. Begins with sequential initial steps on the far left, splits into 3 distinct parallel processing blocks in the centre (green and blue blocks) and converges back into a single sequence of analytical and output steps on the right.

3.5.4 Design Trade-offs

HMT-TSF jointly addresses temporal dynamics (multi-scale TCN), inter-feature correlations (GCN on Pearson adjacency), and MCO regime shift (RevIN + soft regime gating), with semantic group fusion allocating source-level weight per context. Key limitations remain: **(1)** higher parameter count and tuning complexity than any single baseline; **(2)** static Pearson graph sensitivity to distributional shift, partially offset by RevIN and regime gating; **(3)** manually specified $K = 3$ regime boundaries tied to Malaysian MCO chronology; **(4)** optional post-hoc CatBoost residual correction adds a less interpretable second stage. Full training configurations are in Appendix C4.

3.6 Evaluation Metrics

3.6.1 Combined Accuracy Percentage (Combined %)

Combined% serves as a composite index that aggregates absolute, proportional, and squared error metrics to provide a single performance rank for model comparison. The composite value is computed as:

$$\text{Combined\%} = \max(0, 100 - \text{MAPE} - \text{MAE\%} - \text{RMSE\%})$$

- Higher is better, clipped, cannot be negative.
- All three constituent terms are mean-demand-normalized percentages, making them dimensionally homogeneous and directly addable on the same scale.

Equal weighting reflects the operational reality of transit management, where percentage errors relative to daily volume (MAPE), average absolute passenger discrepancies (MAE%), and large individual forecast failures (RMSE%) are equally critical.

3.6.2 Constituent Metrics

MAPE%, MAE%, RMSE%, and R^2 follow the definitions in Table 2.5. In this study, all percentage errors are mean-demand-normalised so MAPE%, MAE%, and RMSE% are dimensionally homogeneous and directly composable in Combined%. Raw MAE and RMSE (absolute passenger counts) are reported separately as operational diagnostics. R^2 measures explained variance and discriminates models with similar error magnitudes but different directional tracking. Together with Combined%, these five metrics evaluate HMT-TSF against the 14 baselines across look-back horizons and MCO conditions.

$$\text{MAPE} = \frac{1}{n} \sum_{i=1}^n \frac{|\hat{y}_i - y_i|}{|y_i|} \times 100$$

- y_i = actual ridership, $\hat{y}_i$ = predicted ridership
- Unit: %, used directly in Combined%
- Lower is better.

$$\text{MAE\%} = \frac{\sum_{i=1}^n |\hat{y}_i - y_i|}{\sum_{i=1}^n y_i} \times 100 = \frac{\text{MAE}}{\bar{y}} \times 100$$

- $\bar{y}$ = mean actual ridership across all test observations
- Unit: % - scale-free; used directly in Combined%
- Raw MAE (absolute ridership counts) is report separately as an operational diagnostic.
- Lower is better.

$$\text{RMSE\%} = \frac{\text{RMSE}}{\bar{y}} \times 100 \quad \text{where} \quad \text{RMSE} = \sqrt{\frac{1}{n} \sum_{i=1}^n (\hat{y}_i - y_i)^2}$$

- Same mean-demand denominator $\bar{y}$ as MAE%
- Unit: % - used directly in Combined%
- Raw RMSE (ridership counts) is reported separately as an operational diagnostic.
- Lower is better.

$$R^2 = 1 - \frac{\sum_{i=1}^n (y_i - \hat{y}_i)^2}{\sum_{i=1}^n (y_i - \bar{y})^2}$$

- y_i = actual ridership, $\hat{y}_i$ = predicted ridership, $\bar{y}$ = mean of actual values
- Numerator = Residual Sum of Squares (SSR) – unexplained variance
- Denominator = Total Sum of Squares (SST) – total variance in the data
- Range: $-\infty$ to 1; $R^2 < 0$, indicates performance worse than predicting the mean.
- Higher is better.

3.7 Conclusion

This chapter established the complete methodological pipeline for forecasting daily Malaysian public transit ridership across twelve service lines and aggregate network demand. Eight heterogeneous data sources were collected, cleaned, and aligned into a unified 79-feature daily matrix under both MCO-inclusive (2019–2025) and MCO-exclusive (2022–2025) configurations. Feature engineering transformed this matrix into chronologically partitioned sliding-window tensors with training-only MinMax scaling, preserving temporal integrity and preventing information leakage.

Explanatory analysis confirmed that Malaysian ridership is shaped by distinct and sometimes non-linear forces: an 85–90% MCO collapse with mode-unequal recovery,

spatially heterogeneous monsoon rainfall, heavy-rain modal substitution into transit, fuel-price-driven demand elasticity, and anticipatory holiday dips followed by return surges. Autoregressive lags at 7, 14, and 28 days dominate linear correlation structure, while static network and demographic features require non-linear modelling — motivating the deep-learning approach adopted herein.

14 baseline models were selected in a progressive comparison chain spanning spatiotemporal, graph-based, and attention-based architectures, each isolating a specific architectural contribution from sequential encoding through graph propagation to series decomposition. The proposed Hybrid Multi-scale Temporal Spatio Feature forecaster (HMT-TSF) addresses three gaps left by the baselines: simultaneous multi-scale temporal, graph-relational, and regime-aware encoding; explicit handling of the MCO distributional shift via RevIN and soft regime gating; and semantic feature-group fusion over the eight data sources. Model performance is evaluated using a composite Combined Accuracy index alongside MAPE%, MAE%, RMSE%, and R^2 , with all percentage errors mean-demand-normalised for direct comparability.

With the dataset, feature pipeline, model suite, and evaluation framework fully specified, Chapter 4 presents the experimental results — comparing all 15 models across look-back horizons and MCO conditions and assessing whether HMT-TSF achieves the forecasting accuracy required for proactive transit operations.

CHAPTER 4

FINDINGS & RESULTS

4.1 Experimental Evaluation

The central question is whether a purpose-built hybrid architecture can outperform established DL paradigms for 7-day Malaysia transit ridership forecasting, and under what conditions each paradigm succeeds or fails. First, default-configuration performance under normal operating conditions (MCO-excluded, 14-day look-back) establishes the baseline ranking. Second, hyperparameter tuning tests whether capacity increases translate into genuine generalisation gains. Third, look-back window sensitivity across 14, 28, and 56 days examines how much historical context a 7-day horizon requires. Fourth, structural-break robustness under the MCO pandemic period (2020-03-18 to 2021-12-31) stress-tests each model against an 85 – 90% ridership collapse. A dedicated fit-diagnostics analysis assesses generalisation quality independently of test-set accuracy.

All models use AdamW optimisation with decoupled weight decay, HuberLoss objective, a five-epoch linear learning-rate warm-up followed by ReduceLROnPlateau scheduling, and a 70/15/15 chronological train/validation/test split. Performance is ranked by $\text{Combined\%} = \max(0, 100 - \text{MAPE\%} - \text{MAE\%} - \text{RMSE\%})$, where percentage terms are normalised by mean ridership demand. Supplementary metrics (R^2 , absolute MAE, RMSE) complete the profile. Headline configuration is `base_nomco_lb14` (base architecture, MCO-excluded dataset, 14-day look-back). Fit diagnostics derive from validation drift above the best checkpoint (threshold 25%), gap ratio between best validation loss and minimum training loss (threshold 3x), and train/validation divergence in the final training epochs.

4.2 Baseline Model Performance – Default Configuration (base_nomco_lb14)

Under the project default, baseline accuracy is tightly clustered: the top eight models occupy a 1.5 Combined% band, indicating a saturated regime in which architectural differences yield incremental rather than step-change gains. Table 4.1 presents the complete ranking with subsections below interpreting according to architectural series.

Table 4.1

Default-configuration (base_nomco_lb14) Performance of All 16 Baseline Variants, Ranked by Combined%

Rank	Model	Combined%	MAPE%	MAE%	RMSE%	R ²	MAE	RMSE
1	Informer	79.13	6.59	5.53	8.76	0.772	69,476	110,050
2	BiLSTM	79.04	6.52	5.77	8.67	0.776	72,460	109,007
3	TPA-LSTM	78.67	6.62	6.04	8.67	0.776	75,871	109,009
4	CNN-BiLSTM	78.18	6.81	6.12	8.89	0.764	76,884	111,782
5	LSTM	78.13	6.71	6.18	8.98	0.760	77,719	112,801
6	ST-LSTM	78.01	6.93	6.27	8.79	0.770	78,779	110,453
7	MTGNN	77.93	6.91	6.47	8.69	0.775	81,292	109,185

8	CNN-LSTM	77.64	6.92	6.32	9.12	0.752	79,375	114,632
9	STSGCN	76.97	7.18	6.42	9.42	0.736	80,703	118,391
10	STGCN	76.81	7.24	6.77	9.17	0.750	85,077	115,297
11	ASTGCN	75.69	7.42	6.89	9.99	0.703	86,631	125,606
12	CNN-LSTM-Augmented	75.36	7.77	7.19	9.68	0.721	90,356	121,639
13	Autoformer	74.73	7.86	7.51	9.90	0.708	94,414	124,408
14	CNN-LSTM-Parallel	74.18	8.18	7.68	9.97	0.704	96,477	125,240
15	STFGNN	73.94	8.21	7.60	10.25	0.688	95,547	128,777
16	PDR-STGCN	73.91	8.15	7.70	10.24	0.688	96,801	128,694

4.2.1 LSTM Models

Recurrent architectures are the strongest single-paradigm family for Malaysian ridership under normal conditions. The main idea is that gated sequential memory aligns with the daily and weekly periodicity that Chapter 3.3’s EDA identified as dominant demand drivers. The evidence is structural: LSTM-family models occupy five of top eight positions, with BiLSTM (79.04%, $R^2 = 0.776$), and TPA-LSTM (78.67%, $R^2 = 0.776$) leading the series and the base LSTM (78.13%, $R^2 = 0.760$) ranking fifth. LSTM achieves consistently competitive accuracy across diverse time series benchmarks as a general-purpose sequential baseline; the present ranking corroborates that claim and establishes a strong performance floor for the comparison chain (Barath et al., 2026).

Bidirectional encoding provides a measurable advantage over unidirectional recurrence. BiLSTM’s 0.91 Combined% gain over LSTM is consistent with a study who show that bidirectional windows improve traffic congestion prediction by contextualising mid-sequence events against subsequent observations (Krishnasamy et al., 2025). TPA-LSTM’s near-equal R^2 to BiLSTM (0.776) validates temporal pattern attention: A demonstration of one-dimensional CNN pattern attention over LSTM hidden states extracts multi-scale periodic signals more effectively than positional bidirectionality alone for subway passenger flow (Wei et al., 2023). CNN-BiLSTM (78.18%) and CNN-LSTM sequential model (77.64%) confirm that hierarchical local-then-global encoding can approach bidirectional performance; a finding that CNN-BiLSTM coupling reduces traffic prediction error beyond either component in isolation (Chen et al., 2022). ST-LSTM (78.01%, $R^2 = 0.770$) adds a parallel spatial MLP stream and ranks sixth, supporting another finding that decoupled spatial encoding improves urban rail passenger-flow prediction when multi-source inputs are present (Cui et al., 2025).

4.2.2 Graph Models

Graph-based models exhibit wider performance dispersion than LSTM models, reflecting heterogeneous strategies for encoding inter-feature correlations. MTGNN (77.93%, $R^2 = 0.775$) ranks seventh overall and leads the graph series, narrowly ahead of STSGCN (76.97%) and STGCN (76.81%). End-to-end learned asymmetric adjacency with multi-scale delayed inception outperforms static correlation graphs for traffic flow prediction (Wu et al., 2025); MTGNN’s placement is consistent with that finding, because asymmetric learned edges can represent directed relationships – for example, fuel-price signals influencing ridership without the reverse – that symmetric Pearson graphs cannot. STGCN benefits from Pearson-correlation feature-graph construction over the 79-feature input and performs better than earlier literature comparisons suggested. Chebyshev graph convolution interleaved with temporal gated convolution captures relational dependencies missed by purely recurrent models (Deng, 2025). Nevertheless, STGCN trails the LSTM baseline by 1.32 Combined% (76.81 versus 78.13), indicating that explicit message passing over feature correlations does not overcome recurrent inductive bias at base capacity. STSGCN (76.97%), with its synchronous $3N \times 3N$ spatial-temporal adjacency, slightly exceeds STGCN, supporting an argument that simultaneous spatiotemporal graph operations better capture coordinated multi-feature regime shifts during public holidays (Chen et al., 2023). At the lower end, PDR-STGCN (73.91%, $R^2 = 0.688$) and STFGNN (73.94%, $R^2 = 0.688$) underperform despite theoretically richer designs: PDR-STGCN’s dynamic relational graph and periodicity-aware encoding, yet limited base capacity relative to dual-graph complexity constrains its default-configuration score. STFGNN’s primary liabilities emerge in the look-back window sensitivity analyses of Chapter 4.4 and 4.5 rather than lb14 alone.

4.2.3 Attention Models

Informer (79.13%, $R^2 = 0.772$) is the single strongest baseline, narrowly ahead of BiLSTM (79.04%) by 0.09 Combined%. The main idea is that sparse attention with generative decoder can match recurrent accuracy while regularising against noise. A research applies a graph-augmented Informer to long-term traffic flow prediction and show that ProbSparse attention achieves competitive accuracy with reduced computational overhead; at $T_{in} = 14$, ProbSparse degenerates to near-full attention (approximately 13 of 14 queries active), so that approximation introduces no meaningful accuracy loss while the decoder architecture avoids autoregressive error accumulation. Informer’s head-of-field placement, combined with superior MCO robustness (Chapter 4.5) and perfect base-configuration fit record (Chapter 4.6), makes it the most well-rounded baseline.

Autoformer (74.73%, $R^2 = 0.708$) rank 13th, trailing leaders by a substantial margin. A report where stable Autoformer performance on strongly periodic signals under appropriate sequence lengths (Ma & Zhang, 2025); here, spectral decomposition across 79 heterogeneous feature channels under a moderate look-back appears to limit gains relative to simpler recurrent baselines, and MCO fragility (Chapter 4.5) further reduces practical utility. ASTGCN (75.69%, $R^2 = 0.703$) performs moderately. Dual spatial-temporal attention improves non-stationary sensitivity over static graph message passing, yet ASTGCN’s largest gains arrive only after tuning (+3.13 Combined%, Chapter 4.3) (Cui et al., 2025).

4.3 Effect of Hyperparameter Tuning

Hyperparameter tuning does not uniformly improve baseline performance. Instead, it produces model-specific accuracy shifts at a consistent generalisation cost documented in Chapter 4.6. Table 4.2 summarises tuned versus base results at `nomco_lb14`.

Table 4.2

Tuning Effect at `tuned_nomco_lb14` Versus `base_nomco_lb14`

Model	Base Combined%	Tuned Combined%	Δ Combined
Informer	79.13	79.99	+0.86
TPA-LSTM	78.67	79.95	+1.28
BiLSTM	79.04	79.44	+0.40
ST-LSTM	78.01	79.13	+1.12
ASTGCN	75.69	78.82	+3.13
LSTM	78.13	78.43	+0.30
STGCN	76.81	78.39	+1.58
CNN-LSTM-Augmented	75.36	77.10	+1.74
PDR-STGCN	73.91	75.56	+1.65
Autoformer	74.73	75.21	+0.48
MTGNN	77.93	76.40	-1.54
CNN-BiLSTM	78.18	76.12	-2.06
STSGCN	76.97	73.65	-3.33
CNN-LSTM	77.64	73.36	-4.28
CNN-LSTM-Parallel	74.18	72.53	-1.65
STFGNN	73.94	65.47	-8.47

The median tuning improvement is approximately +0.5 Combined%, indicating that test-set accuracy is broadly flat while generalisation deteriorates. The largest beneficiaries are ASTGCN (+3.13, to 78.82%), CNN-LSTM-Augmented (+1.74), PDR-STGCN (+1.65), and STGCN (+1.58). For ASTGCN, widening from $d_{\text{model}} = 64$ to 128, expanding attention heads from 4 to 8, and deepening blocks from 2 to 3 increases expressiveness of the dual attention mechanism – like the study which reports deeper attention configurations improve sensitivity to non-stationary patterns (Cui et al., 2025). STGCN’s gains from doubling hidden dimensions to 256 while strengthening regularisation aligns with another study that shows wider spatiotemporal graph networks extract richer relational representations when dropout and weight decay are co-tuned (Deng, 2025).

The most severe regressions are STFGNN (-8.47, to 65.47%), CNN-LSTM sequential (-4.28), and STSGCN (-3.33). STFGNN’s collapse is the study’s largest tuning failure: raising hidden dimensions, adding a fusion block, and increasing dropout to 0.35 causes near-total test-split breakdown, suggesting that dual-graph fusion at this training budget memorises training patterns that do not transfer. CNN-LSTM sequential degrades because widened CNN filters (32 to 64) amplify an existing single-stream bottleneck. MTGNN (-1.54) and CNN-BiLSTM (-2.06) also regress, confirming that additional capacity harms some architecture. The best tuned baseline remains Informer (79.99%), still 5.79% Combined% below HMT-TSF – a gap Chapter 4.7 examines in detail.

4.4 Lookback Window Sensitivity

A systematic sweep across lb14, lb28, and lb56 reveals that longer historical context does not improve seven-day-ahead accuracy for most architectures. The principal finding is operational: lb14 is optimal for 10 of 16 models, lb28 for 6, and lb56 for none. Table 4.3 reports Combined% across the three windows under base_nomco.

Table 4.3

Look-back Sensitivity (Combined%) Across lb14, lb28, and lb56 for All Baseline Variants (base_nomco)

Model	lb14	lb28	lb56	Best
Informer	79.13	78.63	77.17	lb14
BiLSTM	79.04	76.97	77.09	lb14
TPA-LSTM	78.67	79.08	76.36	lb28
CNN-BiLSTM	78.18	72.65	74.72	lb14
LSTM	78.13	77.48	75.98	lb14
ST-LSTM	78.01	78.86	75.60	lb28
MTGNN	77.93	78.11	77.76	lb28
CNN-LSTM	77.64	73.90	74.33	lb14
STSGCN	76.97	75.02	75.15	lb14
STGCN	76.81	77.68	74.93	lb28
ASTGCN	75.69	76.89	75.15	lb28
CNN-LSTM-Augmented	75.36	74.73	74.04	lb14
Autoformer	74.73	73.61	73.40	lb14
CNN-LSTM-Parallel	74.18	76.55	74.33	lb28
STFGNN	73.94	61.30	43.25	lb14
PDR-STGCN	73.91	72.35	72.20	lb14

Note. Best window per model is shown in bold.

14 days span exactly two weekly commuting cycles – the periodicity Chapter 3.3’s EDA and Chapter 4.8’s SHAP analysis identify as the dominant short-horizon structure – while slower seasonal variation is supplied explicitly through calendar features rather than recovered from extended history. A similar study shows that decomposition-based

forecasters require sequence lengths matched to dominant periodicity; here, additional days contribute redundancy and, for fragile architectures, noise.

MTGNN is the most window-stable model (77.93 / 78.11 / 77.76), consistent with existing research where multi-scale dilated inception preventing any single temporal scale from dominating (Wu et al., 2025). STFGNN exhibits the most severe collapse: Combined% falls from 73.94% at lb14 to 43.25% at lb56, with R^2 of -0.112 – worse than naïve mean prediction – because the temporal adjacency matrix constructed from 56-timestep profiles supplies misleading structural priors (Chang et al., 2025). CNN-LSTM sequential degrades sharply at lb28 (73.90% versus 77.64% at lb14) as the two-block CNN at base filter width compresses long-range patterns too aggressively; parallel and augmented modes, which preserve direct raw-feature access or skip connections, avoid this failure mode. HMT-TSF’s own profile (Chapter 4.7) peaks at lb14 under both MCO conditions once future-calendar conditioning is corrected, reinforcing the 14-day recommendation for seven-day horizons.

4.5 MCO Structural Break Robustness

The MCO period represents a severe distributional discontinuity in which daily boardings feel from 800,000 – 1,200,000 to 50,000 – 200,000 under mobility restrictions. Including this window (mco configuration) tests whether models trained on pre-break, break, and post-break data can forecast through the transition. The degradation metric $\Delta\text{Combined\%}$ (nomco $\rightarrow$ mco) serves as the primary robustness indicator; Table 4.4 ranks baselines at lb14.

Table 4.4

MCO Robustness at lb14 for All 16 Baseline Variants, Ranked by Combined% (Least to Most Degradation)

Model	nomco	mco	Δ Combined%	mco R^2
Informer	79.13	73.25	-5.88	0.705
BiLSTM	79.04	72.74	-6.29	0.699
CNN-LSTM-Parallel	74.18	66.89	-7.29	0.577
TPA-LSTM	78.67	71.05	-7.61	0.669
STGCN	76.81	68.55	-8.27	0.615
MTGNN	77.93	67.33	-10.60	0.581
PDR-STGCN	73.91	63.10	-10.81	0.494
CNN-LSTM-Augmented	75.36	64.50	-10.86	0.531
ST-LSTM	78.01	66.75	-11.26	0.584
STSGCN	76.97	64.20	-12.77	0.531
ASTGCN	75.69	61.69	-14.00	0.471
CNN-BiLSTM	78.18	60.59	-17.59	0.427
LSTM	78.13	58.92	-19.21	0.390
Autoformer	74.73	51.26	-23.47	0.121
CNN-LSTM	77.64	45.58	-32.06	-0.050
STFGNN	73.94	41.00	-32.94	-0.306
HMT-TSF	85.78	81.99	-3.79	0.859

Note. HMT-TSF included for reference.

The degradation spread among baselines runs from -5.88 (Informer) to -32.94 (STFGNN). Informer and BiLSTM are the most robust recurrent baselines; Informer’s sparse attention to reduced sensitivity to distributional anomalies because only the most predictive query-key pairs are engaged across regime boundaries (Song et al., 2024). Two models fail in a technically meaningful sense: CNN-LSTM sequential ($R^2 = -0.050$) and STFGNN ($R^2 = -0.306$) produce forecasts less accurate than predicting the training-set mean – despite CNN-LSTM ranking eighth under normal conditions. Sequential CNN-LSTM can

memorise local temporal patterns at the expense of adaptability, consistent with the -32.06 Combined% degradation observed here (Topilin et al., 2025).

STGCN demonstrates unexpectedly strong MCO robustness (Δ -8.27, mco $R^2 = 0.615$), outperforming more expressive models including MTGNN (Δ -10.66). STGCN’s fixed Chebyshev graph constrains prediction drift when input distributions shift – a rigidity that limits peak accuracy but caps catastrophic failure. The analysis reveals a recurring expressiveness-stability trade-off: flexible learn representations (STFGNN’s dual graphs, CNN-LSTM’s CNN-stage encoding) memories pre-break regularities that become liabilities after the break, while constrained or regime-aware designs transfer more reliably – a theme HMT-TSF addresses through RevIN and regime gating in Chapter 4.7.

4.6 Generalisation and Overfitting Analysis

Test-set Combined% alone is an unreliable deployment criterion because several high-ranking baselines achieve accuracy partly through memorisation. Fit diagnostics across all 12 configurations per model (base and tuned $\times$ nomco and mco $\times$ three lookbacks) show that all 6 LSTM models and both simple-convolution graph models (STGCN, PDR-STGCN) record zero good-fit verdicts – 0/12 each – despite strong headline scores for BiLSTM, TPA-LSTM, and CNN-BiLSTM.

The gap-ratio – best validation loss divided by minimum training loss – is the clearest signal. LSTM gap ratios span 3.3x to 13.6x, with CNN-BiLSTM-base under MCO at lb56 reaching 13.51x. PDR-STGCN is the most extreme memoriser, posting 38.61x at tuned_nomco_lb56, indicating training loss near zero while validation loss remains elevated. By contrast, Informer achieves a perfect 6/6 good-fit rate at base configuration – the only baseline with a clean record – with gap ratios of 2.16x – 2.98x consistently below the 3x threshold. This partly attributed to ProbSparse attention’s implicit

regularisation: restricting active queries to a logarithmic subset suppresses fitting of high-frequency training noise.

Among graph models, MTGNN (3/6 good-fit at base, 4/6 at tuned) and STSGCN (4/6 base) are cleanest after Informer, with MTGNN posting study-tightest gaps of 1.40x – 1.50x in tuned configurations – supporting an observation that end-to-end learned adjacency with mix-hop convolution provides intrinsic structural regularisation (Wu et al., 2025). HMT-TSF leads the full study at 19/20 good-fit verdicts across both full and feature-reduced variants (Chapter 4.7). Tuning uniformly harms diagnostics: the good-fit rate falls from 26% (base) to 14% (tuned) across all 14 baselines, confirming that expanded capacity raises gap ratios without equivalent accuracy gains. Deployment decisions must therefore pair accuracy with fit quality – a practice Chapter 5 develops into practical recommendations.

4.7 HMT-TSF Model Performance

HMT-TSF was evaluated across ten configurations (two MCO conditions $\times$ five lookbacks: 7, 14, 28, 56, 84 days). Table 4.5 presents the full results.

Table 4.5

HMT-TSF (full, feature = 79) Results Across All Ten Configurations.

Configuration	Combined%	MAPE%	MAE%	RMSE%	R ²	MAE	RMSE
nomco_lb7	84.88	4.74	4.25	6.13	0.888	53,325	76,951
nomco_lb14	85.78	4.39	3.97	5.87	0.897	49,897	73,757
nomco_lb28	84.23	4.94	4.55	6.28	0.883	57,268	78,910
nomco_lb56	82.53	5.52	5.11	6.84	0.859	64,198	85,874
nomco_lb84	77.68	6.99	6.59	8.73	0.773	82,174	108,800
mco_lb7	78.61	6.89	6.12	8.38	0.807	75,401	103,170
mco_lb14	81.99	5.68	5.18	7.15	0.859	63,853	88,228
mco_lb28	79.89	6.26	5.83	8.02	0.822	72,032	99,059
mco_lb56	79.47	6.68	5.91	7.95	0.825	73,334	98,598

mco_lb84	78.45	6.73	6.17	8.64	0.791	76,593	107,293
----------	-------	------	------	------	-------	--------	---------

Note. Bold rows denote best nomco and mco configurations.

The feature-reduced variant exceeds these values at every nomco lookback ≥ 14 (Chapter 4.9).

Performance peaks at lb14 under both MCO conditions (nomco 85.78%, mco 81.99%), declining at longer windows once X_{future} supplies explicit future calendar structure. At nomco_lb14, HMT-TSF leads every baseline on every headline metric - + 6.65 Combined% over Informer (79.13%) and 28.2% lower MAE (49,897 versus 69,476); the best tuned baseline (Informer, 79.99%) remains 5.79 points below HMT-TSF and 6.60 below HMT-TSF-FR (86.59%, Chapter 4.9). One qualification applies: HMT-TSF alone receives the known-future calendar tensor (X_{future}), so the comparison reflects architecture-plus-conditioning versus architecture-only-baselines. The gain stems from parallel multi-scale TCN, Pearson GCN message passing, RevIN, K=3 regime gating, and feature-group fusion – a combination no single-paradigm baseline implements.

HMT-TSF is also the most MCO-robust model at lb14 (Δ -3.79 versus Informer -5.88), retaining the highest absolute MCO accuracy (81.99%) despite weaker FR robustness under structural break (Chapter 4.9). It posts 19/20 good_fit verdicts (gap ratios 1.57x – 2.64x); only nomco_lb84 is overfit (+36.9% validation drift).

Three sequential non-overlapping out-of-sample blocks test whether headline performance depends on a single favourable temporal partition. The main idea is that a model fit to one chronological split may exploit idiosyncratic seasonal segments; walk-forward evaluation exposes such dependence before deployment. The evidence shows that no block falls below 71.99 Combined% or 0.707 R^2 across all ten configurations; at nomco_lb14, block Combined%

is 90.62, 82.14, and 85.12, with Block 2 weakest under nomco and Block 1 (lockdown-adjacent) weakest under mco. The analysis further shows that mco_lb84 is the most temporarily stable configuration (block spread 3.7 Combined%) while nomco_lb14 spreads 8.5 points, linking peak-accuracy deployment to nomco_lb14 or HMT-TSF-FR and cross-period consistency to longer MCO-trained windows at the accuracy cost in Table 4.5.

4.8 SHAP Feature Importance Analysis

SHAP values were computed for the trained `nomco_lb14` model using `shap.GradientExplainer` with 100 test samples as background. Absolute SHAP values were averaged over samples, time steps, and forecast horizons to produce a 79-element importance vector resolved from `feature_metadata.json`.

The highest-importance features align with established transit demand theory. Annual-cycle encodings dominate attribution magnitude: `month_cos`, `month_sin`, and `month` carry the three largest mean $|\text{SHAP}|$ values, anchoring seven-day forecasts on seasonal position – school terms, festive seasons, and the northeast monsoon. `total_ridership` is the strongest non-seasonal driver and the only feature in the top 15 of all ten configurations (100% consistency), confirming target autocorrelation as the dominant data-driven signal. Holiday structure forms the second calendar tier: `days_to_next_public_hol` ranks in the headline top 10 and appears in 80% of configurations, quantifying the pre-holiday dips and post-holiday surges identified in Chapter 3.3’s EDA. Among external covariates, unfrozen fuel grades (`fp_lv_diesel`, `fp_lv_ron97`) and monsoon-corridor rainfall (Perlis, Terengganu, Penang) complete the headline top 10 – consistent with a prove where multi-source fuel and weather signals as secondary urban rail demand drivers (Cui et al., 2025).

Cross-configuration aggregation reveals 23 features with zero importance in all 10 runs (the entire 17-feature static group plus six administered or East Malaysia fuel-price columns) and three near-zero features (RON95 level and change variants, frozen at RM2.05 post-MCO). These 26 features define the removal set for HMT-TSF-FR (Chapter 4.9). Their persistent inactivity independently validates the EDA conclusion in Chapter 3.3 that administered RON95 series and time-invariant spatial descriptors carry no day-to-day discriminative variance in the post-MCO training window. A lookback-dependent shift is observed: at `lb7 – lb28`, calendar features dominate because short context provides limited autocorrelation depth; at `lb56 – lb84`, `total_ridership` and major Klang Valley rail

lines (rail_lrt_kj, rail_mrt_kajang) take top ranks as extended windows let the model anchor on recent ridership trajectory. This shift has a direct modelling implication: feature-importance profiles are not fixed properties of the dataset but co-vary with architectural context length – a point that cautions against interpreting a single SHAP run as the definitive driver hierarchy without cross-configuration corroboration.

4.9 Feature-Reduced Variant: HMT-TSF-FR

Removing 26 zero- or near-zero-SHAP features – the entire static group plus 9 near-constant administered fuel columns – produces HMT-TSF-FR on a 53-feature input. Static descriptors are redundant because time-invariant structural capacity is implicitly encoded in historical ridership given sufficient look-back; administered fuel columns carry near-zero day-to-day variance across the post-MCO training window.

HMT-TSF-FR achieves Combined% of 86.59 at nomco_lb14 ($R^2 = 0.906$, MAE = 46,323), exceeding the full model (85.78) by +0.81 and setting the study-wide headline. The graph adjacency shrinks from 79 x 79 to 53 x 53 and explainability memory decreases by approximately 33%. The FR advantage grows with look-back (+0.81 at lb14, +1.84 at lb28, +1.52 at lb56, +4.26 at lb84), repairing nomco_lb84’s overfit verdict under feature reduction.

The trade-off emerges under structural break: HMT-TSF-FR loses to the full model in every mco configuration (Δ -0.85 at lb7 to -5.22 at lb84). Near-constant fuel-price columns evidently stabilise predictions under lockdown-spanning distributional shift; the full model should be retained for shock-prone conditions while FR is recommended for normal operations. All HMT-TSF-FR configurations remain good_fit with gap ratios within 1.66x – 2.72x, confirming that feature reduction does not introduce overfitting and that the 53-feature variant is the preferred default for production deployment under the

nomco-regime – a deployment rule that Chapter 5 formalises alongside the complementary shock-regime recommendation for the full 79-feature model.

4.10 Summary

First, HMT-TSF outperforms all 16 baselines. At nomco_lb14, Combined% reaches 85.78% (86.59 for FR), leading Informer (79.13%) by 6.65 points and reducing MAE by 28.2% (33.3% for FR). The gain reflects multi-scale TCN encoding, GCN message passing, RevIN, regime gating, and known-future calendar conditioning (X_{future}) – an input advantage unique to HMT-TSF.

Second, HMT-TSF is the most MCO-robust and most generalisable model. MCO degradation at lb14 is $\Delta -3.79$; retained MCO accuracy (81.99%) leads the field by 6.2 Combined%; and the 19/20 good-fit record is unmatched.

Third, LSTM models dominate the top eight yet overfit systematically. BiLSTM and TPA-LSTM achieve the highest baseline R^2 (0.776) but zero good-fit verdicts across all 12 configurations. Informer is the sole baseline with a clean base fit record and the most deployable alternative.

Fourth, lb14 is the decisively optimal for a 7-day horizon. Longer windows trigger severe collapses (STFGNN at lb56, CNN-LSTM at lb28) and HMT-TSF’s only overfit verdict (nomco_lb84).

Fifth, SHAP analysis confirms interpretable, domain-consistent feature hierarchies and enables principled reduction to 53 features for normal-regime deployment, with the full 79-feature model retained for shock-prone regimes.

CHAPTER 5

DISCUSSION & CONCLUSION

5.1 Discussion of Key Findings

5.1.1 Hybrid Multi-Modal Architectures Outperform Single-Paradigm Models

5.1.2 Test-set Accuracy Conceals Systematic Overfitting in Recurrent Baselines

5.1.3 14-Day Look-Back Window Is Decisively Optimal Under Normal Conditions

5.1.4 Structural Inductive Biases Determine Robustness Under Distributional Shift

5.1.5 Learned Feature Hierarchy Is Domain-Consistent and Enables Principled Feature Reduction

5.2 Implications of the Study

5.2.1 Theoretical Implications

5.2.2 Practical Implications for Malaysian Transit

5.3 Limitations of the Study

5.4 Future Works

5.5 Final Verdict

REFERENCES

Ahmad, M., Anwer, I., Yousuf, M. I., Javid, M. A., Ali, N., Tesoriere, G., & Campisi, T. (2024, May 23). Investigating the Key Factors Affecting Public Transport Ridership in Developing Countries through Structural Equation Modeling. *Sustainability*, 16(11), 4426. <https://doi.org/10.3390/su16114426>

- Amir, N. N., Anuar, N. S., Ismail, B., Azreen, N. A., & Ramli, N. A. (2025, December 28). Ridership Prediction System for Rapid Bus Kuantan and Penang using Multi-Feature Analysis. *Journal of the Malaysian Institute of Planners*, 23(6), 332 - 347. <https://doi.org/10.21837/pm.v23i39.1913>
- Barath, Z., Veres, P., & Banyai, A. (2026, March 1). Beyond Traditional Forecasting Methods: Evaluating LSTM Performance on Diverse Time Series. *Mathematics*, 14(5), 838. <https://doi.org/10.3390/math14050838>
- Casolaro, A., Capone, V., Iannuzzo, G., & Camastra, F. (2023, November 4). Deep Learning for Time Series Forecasting: Advances and Open Problems. *Information*, 14(11), 598. <https://doi.org/10.3390/info14110598>
- CCS Global Tech. (2026, March 9). *From Reactive to Proactive Decisions: How AI Enablement is Solving Everyday Transit Challenges*. CSS Global Tech. <https://ccsglobaltech.com/from-reactive-to-proactive-decisions-how-ai-enablement-is-solving-everyday-transit-challenges/>
- Chang, J., Yin, J., Hao, Y., & Gao, C. (2025, May 30). STFDSGCN: Spatio-Temporal Fusion Graph Neural Network Based on Dynamic Sparse Graph Convolution GRU for Traffic Flow Forecast. *Sensors*, 25(11), 3446. <https://doi.org/10.3390/s25113446>
- Chen, L., Ren, Q., Zheng, J., Zou, F., Luo, S., Tian, J., & Xing, Y. (2023, April 5). CSFPre: Expressway key sections based on CEEMDAN-STSGCN-FCM during the holidays for traffic flow prediction. (T. A. Rashid, Ed.) *PLoS One*, 18(4), 1 - 22. <https://doi.org/10.1371/journal.pone.0283898>
- Chen, P., Fu, X., & Wang, X. (2022, July 7). A Graph Convolutional Stacked Bidirectional Unidirectional-LSTM Neural Network for Metro Ridership Prediction. *IEEE Transactions on Intelligent Transportation Systems*, 23(7), 6950 - 6962. <https://doi.org/10.1109/TITS.2021.3065404>
- Chevance, G., Andrieu, B., Koch, N., Tonne, C., Nieuwenhuyjsen, M., & Bernard, P. (2024, December 30). How gasoline prices influence the effectiveness of interventions targeting sustainable transport modes? *Sustainable Mobility and Transport*, 1, 1 - 8. <https://doi.org/10.1038/s44333-024-00017-1>
- Cui, H., Si, B., Chi, D., Li, Y., Li, G., & Chen, Y. (2025, October 6). Short-term passenger flow prediction for urban rail systems: A deep learning approach utilizing multi-source big data. (S. Panigrahi, Ed.) *PLoS One*, 20(10), 1 - 23. <https://doi.org/10.1371/journal.pone.0333094>
- Deng, H. (2025, March 31). Traffic-Forecasting Model with Spatio-Temporal Kernel. *Electronics*, 14(7), 1410. <https://doi.org/10.3390/electronics14071410>

- Farahmand, Z. H., Gkiotsalitis, K., & Geurs, K. T. (2023, May). Predicting bus ridership based on the weather conditions using deep learning algorithms. *Transportation Research Interdisciplinary Perspectives*, 19, 100833. <https://doi.org/10.1016/j.trip.2023.100833>
- Ge, L., Sarhani, M., Voss, S., & Xie, L. (2021, October 16). Review of Transit Data Sources: Potentials, Challenges and Complementarity. *Sustainability*, 13(20), 11450. <https://doi.org/10.3390/su132011450>
- Hashimzai, I. A., & Mohammadi, M. Q. (2024, December). The Integration of Artificial Intelligence in Project Management: A Systematic Literature Review of Emerging Trends and Challenges. *TIERS Information Technology Journal*, 5(2), 152 - 164. <https://doi.org/10.38043/tiers.v5i2.5963>
- Hassan, M., Mahin, H. D., Ahmed, F., Hassan, M. M., Rahaman, A., & Abdullah, M. (2025, July 4). Assessing Public Transit Network Efficiency and Accessibility in Johor Bahru and Penang, Malaysia: A Data-driven Approach. *Results in Engineering*, 27, 106126. <https://doi.org/10.1016/j.rineng.2025.106126>
- Hu, J., Tang, B., Zhu, L., Li, Y., Hu, J., & Yang, G. (2026, January 18). PDR-STGCN: An Enhanced STGCN with Multi-Scale Periodic Fusion and a Dynamic Relational Graph for Traffic Forecasting. *Systems*, 14(1), 102. <https://doi.org/10.3390/systems14010102>
- Huang, S., Li, W., Wen, J., Zhu, M., Lu, Y., & Wu, N. (2022). Spatiotemporal Variations in Shanghai Metro Commuting Flows during Rainfall Events. *Weather, Climate and Society*, 14(3), 979 - 991. <https://doi.org/10.1175/WCAS-D-21-0167.1>
- Ibrahim, A. N., Borhan, M. N., Osman, M. H., Yazid, M. R., & Rohani, M. M. (2022, June 24). The Influence of Service Quality on User's Perceived Satisfaction with Light Rail Transit Service in Klang Valley, Malaysia. *Mathematics*, 10, 2213. <https://doi.org/10.3390/math10132213>
- Jevinger, A., Zhao, C., Persson, J. A., & Davidsson, P. (2024, March). Artificial Intelligence for improving public transport: A mapping study. *Public Transport*, 16, 99 - 158. <https://doi.org/10.1007/s12469-023-00334-7>
- Jiang, R., Yin, D., Wang, Z., Wang, Y., Deng, J., Liu, H., Cai, Z., Deng, J., Song, X., & Shibasaki, R. (2021, October 30). DL-Traff: Survey and Benchmark of Deep Learning Models for Urban Traffic Prediction. *Proceedings of the 30th ACM International Conference on Information & Knowledge Management*, 4515 - 4525. <https://doi.org/10.1145/3459637.3482000>
- Jiang, S., & Cai, C. (2023, April). The impacts of weather conditions on metro ridership: An empirical study from three mega cities in China. *Travel Behaviour and Society*, 31, 166 - 177. <https://doi.org/10.1016/j.tbs.2022.12.003>

- Jin, S., Jing, C., Wang, Y., & Lv, X. (2022, June). Spatiotemporal Graph Convolutional Neural Networks for Metro Flow Prediction. *The International Archives of the Photogrammetry Remote Sensing and Spatial Information Sciences, XLIII*, 403 - 409. <https://doi.org/10.5194/isprs-archives-XLIII-B4-2022-403-2022>
- Keller, C., Gluck, F., Gerlach, C. F., & Schlegel, T. (2022, April 1). Investigating the Potential of Data Science Methods for Sustainable Public Transport. *Sustainability, 14*, 4211. <https://doi.org/10.3390/su14074211>
- Khalil, S., Amrit, C., Koch, T., & Dugundji, E. R. (2021, May). Forecasting Public Transport Ridership: Management of Information Systems using CNN and LSTM Architectures. *Procedia Computer Science, 184*, 283 - 290. <https://doi.org/10.1016/j.procs.2021.03.037>
- Kim, T., Kim, J., Tae, Y., Park, C., Choi, J.-H., & Choo, J. (2023, February 14). Reversible Instance Normalization for Accurate Time-Series Forecasting against Distribution Shift. *ICLR 2022 Conference*, 1 - 25. <https://openreview.net/forum?id=cGDAkQo1C0p>
- Krishnasamy, L., C, S., Dhanaraj, R. K., Al-Khasawneh, M. A., Al-Shehari, T., Alsadhan, N. A., & Selvarajan, S. (2025, May 26). Intelligent traffic congestion forecasting using BiLSTM and adaptive secretary bird optimizer for sustainable urban transportation. *Scientific Reports, 15*, 18423. <https://doi.org/10.1038/s41598-025-02933-9>
- Levner, A. (2025, March 31). *AI-Powered Public Transportation Gains Momentum as Optibus Platform hits One Million Optimizations*. Optibus. <https://blog.optibus.com/ai-powered-public-transportation-gains-momentum-as-optibus-platform-hits-one-million-optimizations>
- Liu, C., Xiao, Z., Long, W., Li, T., Jiang, H., & Li, K. (2025, May). Vehicle Trajectory Data Processing, Analytics and Applications: A Survey. *ACM Comput. Surv.*, 57(9), 1 - 36. <https://doi.org/10.1145/3715902>
- Lu, K., Liu, J., Zhou, X., & Han, B. (2020, February 19). A Review of Big Data Applications in Urban Transit Systems. *IEEE Transactions on Intelligent Transportation Systems*, 22(5), 2535-2552. <https://doi.org/10.1109/TITS.2020.2973365>
- Lv, Z., Li, J., Dong, C., Li, H., & Xu, Z. (2021, June 29). Deep Learning in the COVID-19 epidemic: A deep model for urban traffic revitalization index. *Data & Knowledge Engineering*, 135, 101912. <https://doi.org/10.1016/j.datak.2021.101912>

- Ma, X., & Zhang, H. (2025, March 29). Time Series Forecasting Method Based on Multi-Scale Feature Fusion and Autoformer. *Applied Science*, 15(7), 3768. <https://doi.org/10.3390/app15073768>
- Maria-Arribas, D., Pantrigo, J. J., & Cuesta-Infante, A. (2026, February 25). A massive, graph augmented, traffic dataset for machine learning and deep learning spatio-temporal traffic analysis. *Research Square*, 1 - 17. <https://doi.org/10.21203/rs.3.rs-8670080/v1>
- Mee, C. K., Subramaniam, G., Ating, R., & Separa, L. A. (2022, September 30). Willingness to use Public Transport in Kuala Lumpur & Manila. *Environment-Behaviour Proceedings Journal*, 7(21), 1 - 9. <https://doi.org/10.21834/ebpj.v7i21.3751>
- Mohamed, A. H., Adwan, I. A., Ahmeda, A. G., Hrtemih, H., & Al-MSari, H. (2021, April 25). Identification of Affecting Factors on the Travel Time Reliability for Bus Transportation. *Knowledge-based Engineering and Science*, 2(1), 19 - 30. <https://doi.org/10.51526/kbes.2021.2.1.19-30>
- Mystakidis, A., Koukaras, P., & Tjortjis, C. (2025, February 7). Advances in Traffic Congestion Prediction: An Overview of Emerging Techniques and Methods. *Smart Cities*, 8(1), 25. <https://doi.org/10.3390/smartcities8010025>
- Ngo, N. S., & Bashar, S. (2024, December). The impacts of extreme weather events on U.S. Public transit ridership. *Transportation Research Part D: Transport and Environment*, 137, 104504. <https://doi.org/10.1016/j.trd.2024.104504>
- Pour, M. A., Zargari, F., Samimi, A., & Sahebi, S. (2026, March). Analyzing the influence of fuel price shock on urban public transit and interurban automobile travel demand: Evidence from a country with fixed fuel price regulation. *Transportation Research Interdisciplinary Perspectives* 36, 36, 101829. <https://doi.org/10.1016/j.trip.2025.101829>
- Rahmani, B., Moghaddam, A. M., & Maghrebi, M. (2025, July). Forecasting demand fluctuations of public bus transit during special events and adverse weather conditions through smart card data analysis. *Travel Behaviour and Society*, 40, 101033. <https://doi.org/10.1016/j.tbs.2025.101033>
- Rezapour, M., & Ferraro, F. R. (2021, June 16). Rail Transport Delay and Its Effects on the Perceived Importance of a Real-time Information. *Frontiers in Psychology*, 12, 1 - 11. <https://doi.org/10.3389/fpsyg.2021.619308>
- S.K.B, S., Mathivanan, S. K., Rajadurai, H., Cho, J., & Easwaramoorthy, S. V. (2024, December 30). A multi-modal geospatial-temporal LSTM based deep learning framework for predictive modeling of urban mobility patterns. *Scientific Reports*, 14, 1 - 19. <https://doi.org/10.1038/s41598-024-74237-3>

- Shi, B., Wang, Z., Yan, J., Yang, Q., & Yang, N. (2024, February 27). A Novel Spatial-Temporal Deep Learning Method for Metro Flow Prediction Considering External Factors and Periodicity. *Applied Science*, 14(5), 1949. <https://doi.org/10.3390/app14051949>
- Sobrie, L., Verschelde, M., Hennebel, V., & Roets, B. (2023, April 1). Capturing complexity over space and time via deep learning: An application to real-time delay prediction in railways. *European Journal of Operational Research*, 310(3), 1201 - 1217. <https://doi.org/10.1016/j.ejor.2023.03.040>
- Sogbe, E., Susilawati, S., & Tan, C. P. (2024, September 26). Scaling up public transport usage: a systematic literature review of service quality, satisfaction and attitude towards bus transport systems in developing countries. *Public Transport*, 17, 1 - 44. <https://doi.org/10.1007/s12469-024-00367-6>
- Son, H., Jang, J., Park, J., Balog, A., Ballantyne, P., Kwon, H. R., Singleton, A., & Hwang, J. (2025, March 5). Leveraging Advanced Technologies for (Smart) Transportation Planning: A Systematic Review. *Sustainability*, 17(5), 2245. <https://doi.org/10.3390/su17052245>
- Song, Y., Luo, R., Zhou, T., Zhou, C., & Su, R. (2024, July 24). Graph Attention Informer for Long-Term Traffic Flow Prediction under the Impact of Sports Events. *Sensors*, 24(15), 4796. <https://doi.org/10.3390/s24154796>
- Suwaidi, J. A., Aydin, R., & Rashid, H. (2022, July). Investigating Barriers and Challenges to Artificial Intelligence (AI) Implementation in Logistics Operations: A Systematic Review of Literature. *Proceedings of the 5th European International Conference on Industrial Engineering and Operations Management*, 1600 - 1616. <https://doi.org/10.46254/EU05.20220308>
- Topilin, I., Jiang, J., Feofilova, A., & Beskopylny, N. (2025, September 15). Traffic Flow Prediction via a Hybrid CPO-CNN-LSTM-Attention Architecture. *Smart Cities*, 8(5), 148. <https://doi.org/10.3390/smartcities8050148>
- Ubaidillah, N. Z., Sa'ad, N. H., Ismail, F., Nordin, N. A., Baharuddin, N., & Hassam, M. K. (2022, June). The Impact of Public Bus Service Quality on the Users' Satisfaction: Evidence from a Developing Asian City. *Review of Applied Socio-Economic Research*, 23(1), 83 - 96. <https://doi.org/10.54609/reaser.v23i1.185>
- Vujadinovic, V. L., Damjanovic, A., Cakic, A., Petkovic, D. R., Prelevic, M., Pantovic, V., Stojanovic, M., Vidojevic, D., Vranjes, D., & Bodolo, I. (2024, September 6). AI-Driven Approach for Enhancing Sustainability in Urban Public Transportation. *Sustainability*, 16(17), 7763. <https://doi.org/10.3390/su16177763>
- Wang, J., Liu, C., Wu, Z., Liao, R., Li, G., & Lu, H. (2025, March). The Roadmap and Strategy for Prioritizing the Development of Public Transport in China.

- Wei, L., Guo, D., Chen, Z., Yang, J., & Feng, T. (2023, January 16). Forecasting Short-Term Passenger Flow of Subway Stations Based on the Temporal Pattern Attention Mechanism and the Long Short-Term Memory Network. *Geo-Information*, 12(1), 25. <https://doi.org/10.3390/ijgi12010025>
- Wu, J.-L., Lu, M., & Wang, C.-Y. (2023, February 2). Forecasting metro rail transit passenger flow with multiple-attention deep neural networks and surrounding vehicle detection devices. *Applied Intelligence*, 53, 18531 - 18546. <https://doi.org/10.1007/s10489-023-04483-x>
- Wu, Z., Liu, X., & Zhang, X. (2025, May 14). Multi dynamic temporal representation graph convolutional network for traffic flow prediction. *Scientific Reports*, 15, 16734. <https://doi.org/10.1038/s41598-025-01157-1>
- Yin, X., Wu, G., Wei, J., Shen, Y., Qi, H., & Yin, B. (2022, June). Deep Learning on Traffic Prediction: Methods, Analysis, and Future Directions. *IEEE Transactions on Intelligent Transportation Systems*, 23(6), 4927 - 4943. <https://doi.org/10.1109/TITS.2021.3054840>
- Yusuf, O., Rasheed, A., & Lindseth, F. (2025, November 3). Data-driven predictive modelling of stop-level public transit patterns. *Transportation*, 1 - 53. <https://doi.org/10.1007/s11116-025-10689-4>
- Zhao, M., & Lan, C.-L. (2025, Novemeber). Modeling Travel Time Reliability for Non-Interstate National Highway System Routes. *Virginia Transportation Research Council*, 1 - 68. <https://vtrc.virginia.gov/media/vtrc/vtrc-pdf/vtrc-pdf/26-R23.pdf>
- Zhuang, W., & Cao, Y. (2022, August 30). Short-Term Traffic Flow Prediction Based on CNN-BILSTM with Multicomponent Information. *Applied Science*, 12(17), 8714. <https://doi.org/10.3390/app12178714>

APPENDICES

APPENDIX A1 – Hardware Specification

- CPU: 64 cores
- GPU: 1x A100 (UMHPC) – 32GB vRAM

- No hyperthreading

APPENDIX A2 – Data Configuration

- Look-back window (T_{in}): 14 / 28 / 56 days for the 14 base models; 7 / 14 / 28 / 56 / 84 days for HMT-TSF.
- Forecast horizon (T_{out}): 7 days
- Data split: 70% train / 15% test / 15% validation (chronological)
- Precision: Sequences stored as float16, cast to float32 before model input
- Scaling: MinMaxScaler fitted on training data only

APPENDIX B1 – Baseline Models Hyperparameters

- Epochs: 150
- Batch size: 32
- LR: 1e-3
- Patience: 15
- Dropout: 0.1
- Weight decay: 1e-4

Some per-model deviations differ from standardized hyperparameters for better comparison according to its architecture:

- STGCN (Dropout: 0.20, Weight decay = 2e-4)
- STSGCN (Epochs: 200, LR: 5e-4, Patience = 25)
- STFGNN (Dropout: 0.20, Weight decay = 3e-4)
- PDR-STGCN (Dropout: 0.15, Weight decay = 2e-4)
- ASTGCN (Dropout: 0.15, Weight decay = 2e-4)

- Autoformer (Dropout: 0.15, Weight decay = $2e-4$)


APPENDIX B2 – Baseline Models Training Optimization

- Optimiser: AdamW (decoupled weight decay)
- Loss: HuberLoss (delta = 1.0, default) – robust to ridership outliers
- LR schedule: Linear warmup → ReduceLROnPlateau

APPENDIX C1 – Spatiotemporal Models

LSTM – Long Short-Term Memory

A stacked LSTM reads the T_{in} -step look-back window left-to-right, compressing the entire input sequence into a single final hidden state h_T . This hidden state is passed directly to a two-layer MLP head to produce T_{out} simultaneous predictions. When layers > 1 , dropout is applied between stacked LSTM layers.




Hyperparameter changes for tuned variant:

- hidden $64 \rightarrow 128$
- layers $1 \rightarrow 2$
- dropout $0.10 \rightarrow 0.20$
- weight_decay $1e-4 \rightarrow 2e-4$
- Structure unchanged

BiLSTM – Bidirectional LSTM

Extends LSTM with a reversed recurrent pass over the same look-back window. The forward final hidden state h_{fwd} and backward final hidden state h_{bwd} (both from the last layer) are concatenated before the MLP head, doubling representational capacity.




Hyperparameter changes for tuned variant:

- hidden $64 \rightarrow 256$
- layers $1 \rightarrow 3$
- dropout unchanged
- MLP head input dimension grows to 512 (bidirectional concatenation).
- Structure unchanged

TPA-LSTM – Temporal Pattern Attention LSTM

A standard LSTM produces both full hidden-state sequence H and the final hidden state h_T . The TPA module takes $H_{ctx} = H[:, :-1, :]$ (all but the last step), transposes it to treat hidden dimensions as channels over time, applies a 1-D CNN to extract temporal pattern filters, adaptive-average-pools across time, scores each filter against h_T via a learned scoring matrix W_{score} , and softmax-weights the scores to produce a pattern context vector. The concatenation of h_T and context is passed to the MLP head.




Hyperparameter changes for tuned variant:


- hidden 64 $\rightarrow$ 256
- filters 32 $\rightarrow$ 128
- dropout 0.10 $\rightarrow$ 0.15
- Structure unchanged

CNN-LSTM


Sequential Mode: CNN extracts local temporal features, which the LSTM then processes for global sequential context. LSTM input is CNN output, not raw features.



Parallel Mode: CNN and LSTM process raw input independently; outputs concatenated.




Augmented Mode: Sequential CNN-LSTM with raw-input skip connection to prevent information loss from CNN compression.



Hyperparameter changes for all three tuned variants:

- `cnn_filters` 32 $\rightarrow$ 64
- `dropout` 0.10 $\rightarrow$ 0.20
- Each mode is trained and evaluated independently
- Structure unchanged

CNN-BiLSTM




Hyperparameter changes for tuned variant:

- hidden 64 $\rightarrow$ 128
- cnn_filters 32 $\rightarrow$ 64
- cnn_layers 2 $\rightarrow$ 1
- dropout 0.10 $\rightarrow$ 0.25
- Structure unchanged

ST-LSTM – Spatio-Temporal LSTM

Two parallel streams are computed independently and concatenated before the MLP head.

The spatial MLP is weight-shared across all T_{in} timesteps (time-invariant): it captures which features consistently co-activate in the window rather than when. Mean pooling over the time axis collapses temporal order to product a persistent cross-feature summary.




Hyperparameter changes for tuned variant:

- hidden 64 → 128
- spatial_hidden 32 → 128
- dropout 0.10 → 0.30
- Structure unchanged

APPENDIX C2 – Graph Models

STGCN – Spatio-Temporal Graph Convolutional Network

Input features are treated as $N = 79$ graph nodes each carrying a scalar temporal signal over T_{in} timesteps. The architecture alternates temporal gated convolutions (GLU) and Chebyshev graph convolutions in stacked ST-Conv blocks, with BatchNorm after each block.




Hyperparameter changes for tuned variant:

- hidden $128 \rightarrow 256$
- dropout $0.20 \rightarrow 0.25$
- weight_decay $2e - 4 \rightarrow 3e - 4$
- Block depth and temporal kernel unchanged
- Structure unchanged

PDR-STGCN – Periodicity-Aware Dynamic Relational STGCN

A two-channel input (original signal + weekly lag-difference) feeds a modified STGCN backbone where each graph convolution replaces the fixed Chebyshev adjacency with a mixed static/dynamic adjacency controlled by a learned scalar λ .




Hyperparameter changes for tuned variant:

- hidden 160 $\rightarrow$ 256
- n_blocks 2 $\rightarrow$ 3
- kt 3 $\rightarrow$ 2
- dk 48 $\rightarrow$ 64
- dropout 0.15 $\rightarrow$ 0.25
- Structure unchanged

STSGCN – Spatial-Temporal Synchronous Graph Convolutional Network


The $3N \times 3N$ synchronous graph (STSG) encodes both spatial adjacency (A_{spa} within each timestep) and temporal adjacency (identity block I linking adjacent timesteps). Each STSGCL layer applies Chebyshev convolution on the full STSG over a sliding 3-timestep window and then extracts the centre N nodes.



Hyperparameter changes for tuned variant:

- hidden $96 \rightarrow 128$
- dropout $0.10 \rightarrow 0.25$
- weight_decay $1e-4 \rightarrow 2e-4$
- lr $5e-4 \rightarrow 1e-3$
- Layer depth unchanged
- Structure unchanged


STFGNN – Spatio-Temporal Fusion Graph Neural Network



Hyperparameter changes for tuned variant:

- hidden $64 \rightarrow 128$
- dropout $0.20 \rightarrow 0.35$
- adj_threshold $0.10 \rightarrow 0.15$
- Layer depth is unchanged
- Structure unchanged

MTGNN – Multi-scale Temporal Graph Neural Network




Hyperparameter changes for tuned variant:

- hidden $32 \rightarrow 64$
- $d_{\text{emb}} 10 \rightarrow 7$
- dropout $0.10 \rightarrow 0.30$
- weight_decay $1e - 4 \rightarrow 3e - 4$
- Skip channels and layer depth unchanged
- Structure unchanged

APPENDIX C3 – Attention Models

ASTGCN – Attention-based STGCN

Use AMP (fp16 + GradScaler) for memory efficiency.




Hyperparameter changes for tuned variant:

- $d_model\ 64 \rightarrow 128$
- $n_heads\ 4 \rightarrow 8$
- $n_blocks\ 2 \rightarrow 3$
- $dropout\ 0.15 \rightarrow 0.20$
- $weight_decay\ 2e - 4 \rightarrow 1e - 4$
- Structure unchanged

Autoformer

FFT operations are explicitly cast to float32 inside autocast for numerical stability under AMP.




Hyperparameter changes for tuned variant:

- d_model 64 → 128
- n_heads 4 → 8
- e_layers 2 → 3
- d_ff 128 → 256
- dropout 0.15 → 0.25
- Structure unchanged

Informer

Uses AMP (fp16 + GradScaler). At $T_{in} = 14$, the single distilling step halves the encoder sequence to length 7, and ProbSparse selects approximately 13 of 14 queries (near-full attention).



Hyperparameter changes for tuned variant:

- d_model 64 → 256
- n_heads 4 → 16
- e_layers 2 → 3
- d_ff 128 → 512
- Dropout unchanged
- Structure unchanged

APPENDIX C4 – HMT-TSF Training Configurations

- Epochs: 150
- Batch size: 32
- Optimiser: AdamW (lr = 1e-3, weight_decay = 1e-3)
- LR schedule: Linear warmup (8 ep) → ReduceLROnPlateau (factor = 0.5, patience = 8)
- Gradient clip: max_norm = 1.0
- Early stopping: patience = 20 (raw val loss)
- Mixed precision: AMP fp16 on CUDA (GradScaler)
- Loss: WeightedHuber (loss_decay = 0.9) + TemporalSmoothness (smooth_weight = 0.01)
- Input noise: Gaussian noise std = 0.02 added to training inputs (data augmentation)
- d_model: 64
- n_tcn_blocks: 3
- tcn_kernel: 3
- graph_hidden: 64
- n_regimes: 3

- n_attn_heads: 4
- adj_threshold: 0.1
- drop_path: 0.2
- dropout: 0.1
- Optional residual boosting: CatBoost or sklearn MLP on train-set residuals; applied at 0.5x weight only if it improves Combined%
- Walk-forward evaluation: test set split into 3 equal blocks; per-block Combined% and R^2 reported.