UNIVERZITET U BIHAĆU
TEHNIČKI FAKULTET
BIHAĆ

RAČUNARSKE MREŽE

Laboratorijske vježbe

CISCO Packet Tracer
(Vježba 1)

mr. Amel Toroman, dipl. ing.el.
Viši asistent

Ak. 2021/2022

PRIMJER 1: Povezivanje dva računara direktnom vezom

Dva računara je najjednostavnije povezati direktnom vezom korištenjem *ethernet* priključka i odgovarajućeg *cross-over ethernet* kabla.



Ispravnost ostvarene veze se provjerava korištenjem komande **ping** u okviru *Command Prompt*-a. Potrebno je otvoriti Command Prompt računara PC0 i otkucati sljedeću komandu:

```
ping 147.91.10.3
```



Slika 1. *Testiranje ispravnosti povezivanja korištenjem ping komande*

PRIMJER 2: Hub (Tri računara i hub)

Hub je uređaj koji šalje pakete svim uređajima u mreži, nakon toga odgovara onaj paket kojem je namijenjem.



Računar	IP adresa	Subnet mask
PC1	192.168.1.101	255.255.255.0
PC2	192.168.1.102	255.255.255.0
PC3	192.168.1.103	255.255.255.0





PRIMJER 3: Switch (Tri računara i switch)

Switch je uređaj koji šalje pakete samo onim uređajima u mreži kojim je namijenjen paket.





Kao što vidimo SWITCH prosljeđuje samo računaru koji treba da primi podatke i kad on primi šalje povratnu informaciju da je paket stigao.



PRIMJER 4: Server



Računar/Server	IP adresa	Subnet mask
PC1	192.168.1.101	255.255.255.0
Server	192.168.1.254	255.255.255.0



DNS





PRIMJER 5: Wireless router






Wireless Router1
Physical
Config
GUI
Wireless-N
Broadband Router
Firmware Version: v0.93.3
Wireless-N Broadband Router
Wireless
Setup
Wireless
Security
Access Restrictions
Applications & Gaming
Administration
Basic Wireless Settings
Wireless Security
Wireless MAC Filter
Advanced Wireless Settings
Basic Wireless Settings
Help...
Network Mode:
Mixed
Network Name (SSID):
Tehnicki fakultet
Radio Band:
Auto
Wide Channel:
Auto
Standard Channel:
1 - 2.412GHz
SSID Broadcast:
Enabled
Disabled
Save Settings
Cancel Changes


PC1
Physical
Config
Desktop
Software/Services
MODULES
WMP300N
PT-HOST-NM-1AM
PT-HOST-NM-1CE
PT-HOST-NM-1CFE
PT-HOST-NM-1CGE
PT-HOST-NM-1FFE
PT-HOST-NM-1FGE
PT-HOST-NM-1W
PT-HOST-NM-1W-A
PT-HOST-NM-3G/4G
PT-HEADPHONE
PT-MICROPHONE
PT-CAMERA
PT-USB-HARD-DRIVE
Physical Device View
Zoom In
Original Size
Zoom Out
Customize Icon in Physical View
Customize Icon in Logical View
The Linksys-WMP300N module provides one 2.4GHz wireless interface suitable for connection to wireless networks. The module supports protocols that use Ethernet for LAN access.


Link Information
Connect
Profiles
Below is a list of available wireless networks. To search for more wireless networks, click the Refresh button. To view more information about a network, select the wireless network name. To connect to that network, click the Connect button below.
Wireless Network Name
CH
Signal
Tehnicki fakultet
1
91%
Site Information
Wireless Mode Infrastructure
Network Type Mixed B/G/N
Radio Band Auto
Security WEP
MAC Address 000D.BDE1.1506
Refresh
Connect
2.4GHz
Adapter is Active
Wireless-N Notebook Adapter
Wireless Network Monitor v1.0
Model No. WPC300N


WEP Key Needed for Connection
This wireless network has WEP encryption enabled. To connect to this network, select the level of WEP encryption. Enter the required passphrase or WEP key in the appropriate field below. Then click the Connect.
Security
WEP
Please select the wireless security method used by your existing wireless network.
WEP
64-bit
To use WEP encryption, select 64-bit or 128-bit
Passphrase
The Passphrase is case-sensitive and should be no more than 16 characters in length.
WEP Key 1
abcde12345
When entering this manually, it should be 10 characters for 64-bit encryption or 26 characters for 128-bit encryption. Valid hexadecimal characters are "A" through "F" and numbers "0" through "9".
Cancel
Connect


Command Prompt
Packet Tracer PC Command Line 1.0
PC>
Packet Tracer PC Command Line 1.0
PC>ping 192.168.0.101
Pinging 192.168.0.101 with 32 bytes of data:
Reply from 192.168.0.101: bytes=32 time=31ms TTL=128
Reply from 192.168.0.101: bytes=32 time=22ms TTL=128
Reply from 192.168.0.101: bytes=32 time=23ms TTL=128
Reply from 192.168.0.101: bytes=32 time=18ms TTL=128
Ping statistics for 192.168.0.101:
Packets: Sent = 4, Received = 4, Lost = 0 (0% loss),
Approximate round trip times in milli-seconds:
Minimum = 18ms, Maximum = 31ms, Average = 23ms