

it interface Serial 2/0 # retwesk 30.0.0.0 # encapsulation ppp #exit papergrid # exit # Houter rip # hetwest 200.0.0 Date: / / these commands configures nouter 0, I using starting information protocol. Similarly, use these commands. The side of and ensulter 2 for configuring. & with networks as 20.0.0.0 and 20.0.0.0 pe router 1 with networks as 30.000 and 40.000 F. Once the configuration is done, the packet is i.e., ping PC1 from pc o pocket from PCO to PCI. We use Po (config-houser) # Version 2

the type routing information protect of

be used while configuring. RIP version 2 is classless protocol which supports variablelength subnet masking

NAME	Papergrid  Date: / /							
7	7 Demonstration of WEB server and DNS wring pocket braces.							
89.	1 excet a topology?							
	Pro Switch 1 3 Servero.							
and a second of the second of	192.168.1.100							
	2. Bet the IP addens for PC and scribs. as mentioned.							
	3 set the DNS server configuration in							
	PCO config setting							
	1. Enable PNS 80 m°Ce in 80 equez → sermicos.							
	5. Web browse from Pco wing the							
error-continuent	SPRING TP PINNORGE NARIANON							
	IP address.							
	PC -> Desktop -> Web Downses -> "Enter ugl.".							
	6. We can add and edit the web server							
	Server -> Services -> DNS							
	Add the domain mame and click							
	7. Then we can meb brown from pco using the newly added domain							

## papergrid

Date: / /

8° m	c can	change addrew	the	files	g the	ping	red
and the second s	and it was an action and a second	and with the second larger December 2					
	Serve there we domain	$g \rightarrow 8ex W$ $e$ can $g$	change (1)		dit/de	lete.	the
9. 4	ferxc, to	ne nece	esary	neb	server	demou	stration.
			0				
							AS