Enterprise Support Knowledge Base

Page 1: Account Access and Lockout

Sample internal knowledge document for testing PDF ingestion, page-aware chunking, semantic retrieval, and citation grounding.

Login failure triage

When a customer reports that they cannot sign in, first confirm that they are using the correct email address and that the account is active. Ask the customer for the exact error message, the approximate time of the failed attempt, and whether the issue occurs in more than one browser or device. Support agents must never ask the customer to share a password, one-time code, access token, or session cookie.

If the customer recently reset their password but still cannot sign in, ask them to refresh the login page, clear browser cache and cookies, try an incognito or private browsing window, disable browser extensions that may interfere with authentication, and try another supported browser. If login works in a private window but fails in the normal session, stale browser data is the likely cause.

Temporary lockout

An account is temporarily locked after five consecutive failed password attempts. The lockout lasts 15 minutes and is removed automatically. Agents should not attempt to bypass the lockout or manually reset the password during the lockout period. After 15 minutes, the customer may retry once using the latest password.

Escalation criteria

Escalate the ticket to the Authentication Engineering team when the account remains inaccessible after a successful password reset, when the account is shown as active but authentication still fails, when the login service returns repeated server-side errors, or when multiple customers report similar failures at the same time. Include the customer account identifier, exact error text, failed-login timestamp, browser or device information, and troubleshooting already performed.

Enterprise Support Knowledge Base

Page 2: Multi-Factor Authentication and Device Changes

Sample internal knowledge document for testing PDF ingestion, page-aware chunking, semantic retrieval, and citation grounding.

Lost or replaced authenticator device

If a customer no longer has access to the phone or authenticator device used for multi-factor authentication, do not disable MFA based only on an email request. The customer must complete the approved identity-verification process before MFA recovery can proceed. Agents may explain the recovery process but must not request screenshots of one-time codes or authentication secrets.

Time-based one-time code issues

If an authenticator code is repeatedly rejected, ask the customer to confirm that the device date and time are set automatically. Time drift can cause valid time-based one-time passwords to fail. The customer should generate a fresh code after correcting the device clock and should avoid reusing an older code.

Backup codes

A backup recovery code may be used only once. If a backup code has already been consumed, it will not work again. Customers who still have access to their account should generate a new set of backup codes and store them securely. Support agents cannot view or retrieve a customer's existing backup codes.

MFA escalation

Escalate MFA recovery when identity verification succeeds but the enrollment cannot be reset, when repeated MFA failures occur across multiple devices, or when the account shows an inconsistent enrollment state. Include the account identifier, verification status, device type, authenticator type, and the approximate time of the failure. Never place authentication secrets in ticket messages or internal notes.

Enterprise Support Knowledge Base

Page 3: Billing, Subscription, and Refund Handling

Sample internal knowledge document for testing PDF ingestion, page-aware chunking, semantic retrieval, and citation grounding.

Duplicate charges

When a customer reports a duplicate charge, first determine whether both entries are settled transactions or whether one is only a temporary authorization hold. A temporary authorization hold may disappear automatically depending on the customer's bank. Do not promise a refund until the transaction status has been verified.

Subscription cancellation

Cancellation stops future renewals but does not automatically reverse a completed charge. After cancellation, the customer retains access until the end of the current paid period unless a separate refund is approved. Agents should confirm the subscription plan, renewal date, and cancellation timestamp before communicating the expected access end date.

Refund eligibility

Refund requests must be evaluated under the current refund policy. Agents may collect the transaction identifier, charge date, amount, subscription plan, and reason for the request. They must not ask for full card numbers, CVV values, online-banking passwords, or other payment credentials. If the case requires a manual exception, escalate it to Billing Operations.

Billing escalation

Escalate immediately when the customer reports an unknown charge that may indicate account compromise, when payment status is inconsistent across systems, when a refund has been approved but not reflected after the expected processing window, or when repeated billing failures affect several customers. Include transaction references and system observations, but exclude sensitive payment credentials.

Enterprise Support Knowledge Base

Page 4: Service Outages and Incident Communication

Sample internal knowledge document for testing PDF ingestion, page-aware chunking, semantic retrieval, and citation grounding.

Identifying a broader outage

When several unrelated customers report the same failure within a short period, agents should check the internal service-status dashboard before troubleshooting each account independently. A cluster of similar errors may indicate a platform incident rather than an individual account problem.

Customer communication during an incident

During a confirmed incident, acknowledge the impact, state that the issue is under investigation, and avoid giving an estimated recovery time unless Incident Management has published one. Do not instruct customers to repeatedly reset passwords, reinstall applications, or retry destructive actions when the fault is known to be service-wide.

Ticket handling

Link affected tickets to the active incident when the support tooling allows it. Record the customer-visible symptom, the approximate start time, region or environment if relevant, and any error code. When service is restored, update affected tickets and ask customers to retry the failed action. Close the ticket only after resolution is confirmed or the normal closure policy is satisfied.

Priority and escalation

A widespread outage affecting authentication, data access, payments, or a critical production workflow should be treated as a high-priority incident. Support should escalate through the incident-management path rather than creating separate engineering escalations for every customer. Internal notes may contain diagnostic context, but customer-visible messages should remain concise and should not expose internal infrastructure details.

End of sample knowledge document.