MAKE: ANALOGICS
Common Optical Port (COP-3 USB)

Features

- Compatible to IEC 1107, PACT and ANSI standards.
- Narrow band IR for better noise immunity.
- Galvonically isolated communication.
- No external power (self-powered from RS-232C signals).
- High impact, Compact, ABS plastic casing.

Product Description

Analogic has developed an innovative Common Optical Port for the convenience of meter readers in the field. With Analogic's CMRI and Common Optical Port, meter reader may virtually read any meter in the field.

The Common Optical Port (COP-3) has been tested for proper operation with various branded Tri-vector meters manufactured by M/s. Secure Meters, L & T, Elster, Duke Arnics, Schlumberger, Genus etc., The single optical head, multi adaptor arrangement will facilitate a low cost, Universal Solution for meter reading through CMRI, GSM/GPRS, CDMA, PSTN Modems.

Some of the important features of Common Optical Port are Highly sensitive and fast response, narrow band infrared sensors with built in optical filter to minimize daylight bias and spurious/noise and can work up to 19,200 baud rate.

Technical Specifications

Optical Band width	: 900 to 1000 nano meters
Power	: No external power, very low operating power derived from RS-232C signals.
Communication	: USB-Type "A" Connector USB - Type "C" Connector (Optional)
Cable Length	: 0.5 mts. Standard (optional 1,2,3... meters).
Weight	: 120 gms.

ANALOGICS
Redefining Technologies...
CORPORATE OFFICE
PRODUCTION UNIT-1
#9/10, Road No.6, Nacharam Industrial Estate,
Hyderabad-500076 Telangana, INDIA
Tel: (+91)-04-67355000

CMMI DEV | ML 3 APPRAISED
Appraisal # 68709 | Exp. Dec 22, 2026

For any queries, please contact:
atm@analogicgroup.com
www.analogicgroup.com

MAKE IN INDIA

Product features and specifications are subject to change without notice to improve reliability, performance, design or otherwise. Please refer to the website for latest updates