DCU

DATA CONCENTRATOR UNIT

Features

- ✓ Compact and Easy to install
- ✓ Supports: GSM/GPRS wireless communication with 2G/3G technology
- ✓ Supports MIOS compliant/ Modbus/ IEC 62056-21/ DLMS protocols for data collection from energy meters of any make and model
- ✓ Common Optical Probe to interface with any Meters/
  Interface can be made wireless using Meter Interface Unit (MIU)
- ✓ Power Outage Management
- ✓ Buffering of data in the event of loss of communication/ power interruption
- ✓ Inbuilt universal power supply (1-Phas/3-Phase) with optional battery backup
- ✓ Independent of field power supply (like 110V, 220V, 440V)
- ✓ Two way communication, facilitating monitoring, controlling and administration
- ✓ Configurable Digital I/O ports for Tripping and monitoring substation parameters
- ✓ Protection against harsh environment, EMI-EMC, Surge etc.
- ✓ Simultaneous data access from hundreds of Automatic Meter Readers (AMR)/ DCUs. Secure and reliable data transfer to server through VPN
- ✓ Server features:
  - Meter Data Acquisition & Management Software,
  - Remotely configurable and feasible firmware upgradation,
  - GPS time synchronization from server for effective energy audit
- ✓ Online monitoring of Instantaneous parameters like V's, I's, P's, PF and Power Quality etc.
- ✓ Real-time Tamper Alerts/ Event notifications via SMS

Product Description

It is an intelligent device with built-in LPR modules to acquire data from Electronic Energy Meters (EEM) or Meter Interface Units (MIU) using AMR software. Its' in-built 2G/ 3G modules then transmits data to the Data Acquisition Server Interfaced with Data Logger PC. A MIU is connected to EEM to enable wireless transmission of data from meters to DCUs. It eliminates conventional cabling requirements between meters and DCUs, thereby ensuring a quantum jump and data integrity of the system.

Specifications

Processor	**CPU** **Speed**	ARM 9 1Ghz
Operating System	**OS**	Linux OS
Memory	**RAM** **External Memory**	Upto 512 MB RAM Upto 128 GB (SD-card)
Communication Ports	**USB** **Other**	USB 2.0 Ethernet, RS232, RS485
Wireless Connectivity	**WLAN** **Connectivity** **Other**	WLAN (IEEE802.11 b/g) GSM/GPRS Low Power Radio Module
I/O Ports	**Digital Output ports** **Digital Input ports** **Analog Input ports**	24 (Relay Outputs) 24 (Opto isolated) 16 (16-bit)
Dimensions	**H x W X D in mm**	185 x 95 x 43
Operating Conditions	**Operating Temperature** **Relative Humidity**	0°C - 50°C 5 - 95% (Non-condensing)

1 - Indication LEDs
2 - Mini USB
3 - Digital I/O & Analog Inputs
4 - RS 485
5 - LAN Port
6 - SIM Slot
7 - RS 232

ANALOGICS
Redefining Technologies...

CMMIDEV/3

CORPORATE OFFICE
#54, Nagarjuna Hills
Road No. 3, Banjara Hills
Hyderabad - 500082
Telangana, INDIA
Tel: (+91)-40-67185000

For any queries, please contact
info@analogicgroup.com

www.analogicgroup.com

PRODUCTION UNIT- I
9/10, Road No. 6
Nacharam Industrial Estate
Hyderabad - 500076
Telangana, INDIA
Tel: (+91)-40-67355000

Product features and specifications are subject to change without notice to improve reliability, performance, design or otherwise. Please refer to the website for latest updates