

Git Cheat Sheet: Quick Guide for Reference

Installing on Linux	If you want to install the basic Git tools on Linux via a binary installer, you can generally do so through the package management tool that comes with your distribution. If you are	\$ sudo dnf install git-all
---------------------	---	-----------------------------

on
operatin
g
system
s such
as
Fedora
you can
use dnf.

If you \$ sudo apt install git-all
are on
a
Debian-
based
distribut
ion,
such as
Ubuntu
use the
followin
g
comma
nd

Installing on macOS	There are several ways to install Git on a Mac. The easiest way is to install it from the Github website	https://mac.github.com
---------------------	--	---

Installing on Windows	There are also a few ways to install Git on Windows. The most official build is available for	https://git-scm.com/download/win
-----------------------	---	---

download on
the Git
website
.

Configuring Git

Configure user information for all local repositories on your computer

```
$ git config --global user.name "[name]"
```

Sets the name you want to be attached to your commit transactions.

```
$ git config --global user.email "[email address]"
```

Sets the email you want to be attached to your commit transactions.

<code>\$ git config --global color.ui auto</code>	Enables helpful colorization of the command line output
---	---

<code>\$ git config --global alias</code>	Creates a Git command shortcut
---	--------------------------------

<code>\$ git config --system core.editor</code>	Sets the preferred text editor
---	--------------------------------

<code>\$ git config --global --edit</code>	Open and edit the global configuration file in the text editor
--	--

Setting Up Git Repositories

<code>\$ git init [project-name]</code>	Creates an empty repository in the project folder with the specified name
---	---

`$ git clone (repo URL)`

Download
s a project
from a
remote
service
such as
Github
and its
entire
version
history

`$ git clone (repo URL) (folder)`

Clones a
repository
to a
specific
folder

`$ git remote -v`

Displays a
list of
remote
repositori

es with
URLs

\$ git remote rm (remote repo name)

Removes
a remote
repository

\$ git fetch

Fetching
from a
repository
grabs all
the new
remote-tra
cking
branches
and tags
without
merging
those
changes
into your
own
branches.

\$ git pull

Retrieve
the most
recent
changes
from

origin and
merge

Managing File Changes

\$ git add (file name)

Adds file changes to staging. Snapshots the file in preparation for versioning.

\$ git add

Adds all directory changes to staging

\$ git add -A

Adds new and modified files to staging

\$ git rm (file_name)

Removes a file and stops tracking it.
Deletes the file from the working directory and stages the deletion

\$ git rm --cached (file_name)

Removes the file from version control but preserves the file locally

`$ git checkout <deleted file name>`

Recovers a deleted file and prepares it for commit

`$ git status`

Displays the status of modified files. Lists all new or modified files to be committed

`$ git diff`

Displays all unstaged changes in the index and the current directory. Shows file differences that are not yet staged

`$ git diff --staged`

Shows file differences between staging and the last file version.

`$ git reset [file]`

Unstages the file, but preserve its contents

`$ git commit -m "[descriptive message]"`

Records file snapshots permanently in version history

```
$ git mv [file-original] [file-renamed]
```

Changes the file name and prepares it for commit

REDO COMMITS

Erase mistakes: You would typically want to UNDO/REDO when you commit some changes to Git and realize that the changes need to be removed/reverted.

```
$ git reset [commit]
```

Undo all commits after [commit], preserving changes locally

```
$ git reset --hard  
[commit]
```

Discards all history and changes back to the specified commit

GROUP CHANGES: Commands for Git branching

You can decide how to group the changes to create meaningful commits.

```
$ git branch
```

Lists all local branches in the current repository

```
$ git branch [branch-name]
```

Creates a new branch

```
$ git checkout  
[branch-name]
```

Switches to the specified branch and updates the working directory

```
$ git merge [branch]
```

Combines the specified branch's history into your current branch

\$ git branch -d [branch-name]	Deletes the specified branch
\$ git fetch remote <branchname>	Fetches a branch from the repository
\$ git push --all	Pushes all local branches to a designated remote repository

SAVE FRAGMENTS

The Git stash command removes changes from your index and “stashes” them away for later. It is useful if you wish to pause what you are doing and work on something else for a while. You cannot stash more than one set of changes at a time.

\$ git stash	Temporarily stores all modified tracked files
\$ git stash pop	Restores the most recently stashed files
\$ git stash list	Lists all stashed changesets
\$ git stash drop	Discards the most recently stashed changeset

Review History

Browse and view the version history of your project files.

<code>\$ git log</code>	Lists version history for the current branch
<code>\$ git log --follow [file]</code>	Lists version history for a file, including renames
<code>\$ git diff [first-branch]...[second-branch]</code>	Shows content differences and conflicts between two branches
<code>\$ git show [commit]</code>	Outputs metadata and content changes of the specified commit

Git Glossary

Branch	Branches represent specific versions of a repository that “branch out” from your main project. Branches allow you to keep track of experimental changes you make to repositories and revert to older versions
Commit	Each time you save/commit the state of your project in Git, it basically takes a picture of what all your files look like at that moment and stores a reference to that snapshot. To be efficient, if the files have not changed, Git does not store the file again but has a link to the previous identical file it has already stored.
Checkout	The git checkout command switches between branches or restores working tree files. It is used to undo the effects of changes to your repository.

Fetch	The Git fetch command copies and downloads all of a branch's files to your device. Use it to save the latest changes to your repositories. It is possible to fetch multiple branches simultaneously
Index	Whenever you add, delete or alter a file, it remains in the index until you are ready to commit the changes. It is like a staging area for Git. Use the Git status command to see the contents of your index.
Repositories	Git repositories hold all of your project's files including branches, tags, and commits
Pull	Pull requests represent suggestions for changes to the master branch. The Git pull command is used to add changes to the master branch
Push	The git push command is used to update remote branches with the latest changes you have committed
Stash	Stashing takes the state of your working directory — that is, your modified tracked files and staged changes — and saves it on a stack of unfinished changes that you can reapply at any time.
Staging	The staging area is a simple file, generally contained in your Git directory that stores information about what will go into your next commit. It's sometimes referred to as the index.