IPSec

Principles of Information Security and Privacy (CSE607)

M.Tech. I, Semester I



Department of Computer Science and Technology S.V.National Institute of Technology-Surat


October 7, 2022

Overview

Encapsulating Security Payload

- The Encapsulating Security Payload provides confidentiality services, including confidentiality of message contents and limited traffic flow confidentiality.
- As an optional feature, ESP can also provide an authentication service.

Encapsulating Security Payload



Encryption and Authentication Algorithms

- Three-key triple DES
- RC5
- IDEA
- Three-key triple IDEA
- CAST
- Blowfish
- If the algorithm used to encrypt the payload requires cryptographic synchronization data, such as an initialization vector (IV), then these data may be carried explicitly at the beginning of the Payload Data field.
- If included, an IV is usually not encrypted, although it is often referred to as being part of the ciphertext.

Padding

- If an encryption algorithm requires the plaintext to be a multiple of some number of bytes (e.g., the multiple of a single block for a block cipher), the Padding field is used to expand the plaintext (consisting of the Payload Data, Padding, Pad Length, and Next Header fields) to the required length.
- The ESP format requires that the Pad Length and Next Header fields be right aligned within a 32- bit word. Equivalently, the ciphertext must be an integer multiple of 32 bits. The Padding field is used to assure this alignment.
- Additional padding may be added to provide partial traffic flow confidentiality by concealing the actual length of the payload.

Transport mode operation

- At the source, the block of data consisting of the ESP trailer plus the entire transport-layer segment is encrypted and the plaintext of this block is replaced with its ciphertext to form the IP packet for transmission. Authentication is added if this option is selected.
- The packet is then routed to the destination. Each intermediate router needs to examine and process the IP header plus any plaintext IP extension headers but does not need to examine the ciphertext.
- The destination node examines and processes the IP header plus any
 plaintext IP extension headers. Then, on the basis of the SPI in the
 ESP header, the destination node decrypts the remainder of the
 packet to recover the plaintext transport-layer segment.

Tunnel mode operation


- The source prepares an inner IP packet with a destination address of the target internal host. This packet is prefixed by an ESP header; then the packet and ESP trailer are encrypted and Authentication Data may be added. The resulting block is encapsulated with a new IP header (base header plus optional extensions such as routing and hop-by-hop options for IPv6) whose destination address is the firewall; this forms the outer IP packet.
- The outer packet is routed to the destination firewall. Each intermediate router needs to examine and process the outer IP header plus any outer IP extension headers but does not need to examine the ciphertext.

Tunnel mode operation

- The destination firewall examines and processes the outer IP header plus any outer IP extension headers. Then, on the basis of the SPI in the ESP header, the destination node decrypts the remainder of the packet to recover the plaintext inner IP packet. This packet is then transmitted in the internal network.
- The inner packet is routed through zero or more routers in the internal network to the destination host.

Transport and Tunnel mode


IPv6



Combining Security Associations

- Transport adjacency: Refers to applying more than one security protocol to the same IP packet, without invoking tunneling. This approach to combining AH and ESP allows for only one level of combination; further nesting yields no added benefit since the processing is performed at one IPsec instance: the (ultimate) destination.
- Iterated tunneling: Refers to the application of multiple layers of security protocols effected through IP tunneling. This approach allows for multiple levels of nesting, since each tunnel can originate or terminate at a different IPsec site along the path.

Combining Security Associations



[◆]ロト ◆御 ト ◆ 恵 ト ◆ 恵 ・ り へ ②