

Artificial Neural Networks

- The Brain
- Brain vs. Computers
- The Perceptron
- Multilayer networks
- Some Applications



KR - SCET

Artificial Neural Networks

- Other terms/names
 - connectionist
 - parallel distributed processing
 - neural computation
 - adaptive networks..
- History
 - 1943-McCulloch & Pitts are generally recognised as the designers of the first neural network
 - 1949-First learning rule
 - 1969-Minsky & Papert - perceptron limitation - Death of ANN
 - 1980's - Re-emergence of ANN - multi-layer networks

KR - SCET

Brain and Machine

- The Brain
 - Pattern Recognition
 - Association
 - Complexity
 - Noise Tolerance




- The Machine
 - Calculation
 - Precision
 - Logic

3

KR - SCET

The contrast in architecture



- The Von Neumann architecture uses a single processing unit;
 - Tens of millions of operations per second
 - Absolute arithmetic precision

- The brain uses many slow unreliable processors acting in parallel




4

KR - SCET

Features of the Brain

- Ten billion (10^{10}) neurons
- On average, several thousand connections
- Hundreds of operations per second



KR - SCEI

Features of the Brain

- Die off frequently (never replaced)
- Compensates for problems by massive parallelism



KR - SCET

6

The biological inspiration



- The brain has been extensively studied by scientists.
- Vast complexity prevents all but fundamental understanding.
- Even the behaviour of an individual neuron is extremely complex

KR - SCET

7

The biological inspiration




- Single "percepts" distributed among many neurons
- Localized parts of the brain are responsible for certain well-defined functions (e.g. vision, motion).
- Which features are integral to the brain's performance?
- Which are incidentals imposed by the fact of biology?

KR - SCET


8

The Structure of Neurons



KR - SCET

9



KR - SCET

The Structure of Neurons

A neuron has a cell body, a branching input structure (the dendrite) and a branching output structure (the axon)

- Axons connect to dendrites via synapses.
- Electro-chemical signals are propagated from the dendritic input, through the cell body, and down the axon to other neurons

KR - SCET

11


The Structure of Neurons

- A neuron only fires if its input signal exceeds a certain amount (the threshold) in a short time period.
- Synapses vary in strength
 - Good connections allowing a large signal
 - Slight connections allow only a weak signal.
 - Synapses can be either excitatory or inhibitory.

KR - SCET


12

The Artificial Neuron (Perceptron)



13

A Simple Model of a Neuron (Perceptron)



- Each neuron has a threshold value
- Each neuron has weighted inputs from other neurons
- The input signals form a weighted sum
- If the activation level exceeds the threshold, the neuron "fires"

KR - SCET

14

A Theory of Memory

Hopfield [1982] introduced a neural network that he proposed as a theory of memory. A Hopfield network has the following interesting features:

- Distributed Representation
- Distributed, Asynchronous
- Content-Addressable Memory
- Fault Tolerance


KR - SCET

A Theory of Memory

- **Distributed Representation** : A memory is stored as a pattern across a set of processing elements.
- **Distributed, Asynchronous** : each processing elements makes decisions based only on its own local situation.
- **Content-Addressable Memory** : A number of patterns can be stored in a network.
- **Fault Tolerance** : if few processing elements fails, the network functions properly.

KR - SCET

A Simple Hopfield Network




KR - SCET

A Simple Hopfield Network

- Positive connection tends to activate unit each other
- How is network operated
 - A random unit is chosen
 - If any of its neighbours are active, the unit computes the sum of the weights on the connections to those active neighbours
 - If the sum is positive, the unit becomes active
 - Otherwise it becomes inactive.
 - Another Random unit is chosen and the process is repeated until no more units can change state
 - This process is called as **Parallel Relaxation**

KR - SCET

The Four Stable States of a Particular Hopfield Net



KR - SCET

A Hopfield Net as a Model of Content-Addressable Memory




KR - SCET

A Neuron and a Perceptron




KR - SCET

Perceptron with Adjustable Threshold Implemented as Additional Weight




KR - SCET

A Perceptron with Many Inputs and Many Outputs




KR - SCET

An Early Notion of an Intelligent System Built from Trainable Perceptrons



KR - SCET


An Artificial Neuron



- Each hidden or output neuron has weighted input connections from each of the units in the preceding layer.
- The unit performs a weighted sum of its inputs, and subtracts its threshold value, to give its activation level.
- Activation level is passed through a sigmoid activation function to determine output.

KR - SCET


25



KR - SCET

Supervised Learning

- Training and test data sets
- Training set; input & target



Sepal length	Sepal width	Petal length	Petal width	Class
5.1	3.5	1.4	0.2	0
4.9	3.0	1.4	0.2	2
4.7	3.2	1.3	0.2	0
4.6	3.1	1.5	0.2	1

KR - SCET

27


What is required for ANN sol

For any problem solving using ANN

- There are two aspects
 - Network Design (structure)
 - Weights

KR - SCET

Perceptron Training




$$\text{Output} = \begin{cases} 1 & \text{if } \sum w_i x_i > t \\ 0 & \text{otherwise} \end{cases}$$


- Linear threshold is used.
- W - weight value
- t - threshold value

KR - SCET

29



Perceptron Training




- Output = $\begin{cases} 1 & \text{if } \sum w_i x_i > t \\ 0 & \text{otherwise} \end{cases}$
- Linear threshold is used.
 - W - weight value
 - t - threshold value

KR - SCET

31

Simple network



KR - SCET

32

Learning algorithm

While epoch produces an error
 Present network with next inputs from epoch
 Error = T - O
 If Error \neq 0 then
 $W_j = W_j + LR * I_j * \text{Error}$
 End If
End While

KR - SCET

33

Learning algorithm

Epoch : Presentation of the entire training set to the neural network.
 In the case of the AND function an epoch consists of four sets of inputs being presented to the network (i.e. [0,0], [0,1], [1,0], [1,1])

Error: The error value is the amount by which the value output by the network differs from the target value. For example, if we required the network to output 0 and it output a 1, then Error = -1

KR - SCET

34

Learning algorithm

Target Value, T : When we are training a network we not only present it with the input but also with a value that we require the network to produce. For example, if we present the network with [1,1] for the AND function the target value will be 1

Output, O : The output value from the neuron

I_j : Inputs being presented to the neuron


W_j : Weight from input neuron (I_j) to the output neuron

LR : The learning rate. This dictates how quickly the network converges. It is set by a matter of experimentation. It is typically 0.1

KR - SCET

35

Training Perceptrons




For AND		
A	B	Output
0	0	0
0	1	0
1	0	0
1	1	1

- What are the weight values?
- Initialize with random weight values

KR - SCET


36

Training Perceptrons



KR - SCET

37



Example : AND Gate

Let's take a look at an example. The initial weight values are 0.3, 0.5, and -0.4 (taken from the above example) and we are trying to learn the AND function.

If we present the network with the first training pair $([0,0])$, from the first epoch, nothing will happen to the weights (due to multiplying by zero).

The next training pair $([0,1])$ will result in the network producing zero (by virtue of the step0 function). As zero is the required output there is no error so training continues.

KR - SCET

KR - SCET

40

The next training pair $([1,0])$ produces an output of one. The required output is 0. **Therefore the error is -1**

This means we have to adjust the weights.

This is done as follows (assuming $LR = 0.1$)

$$W_0 = 0.3 + 0.1 * -1 * -1 = 0.4$$

$$W_1 = 0.5 + 0.1 * 1 * -1 = 0.4$$

$$W_2 = -0.4 + 0.1 * 0 * -1 = -0.4$$

Therefore, the new weights are 0.4, 0.4, -0.4.

KR - SCET

41

- Finally we apply the input $[1,1]$ to the network. This also produces an error and the new weight values will be 0.3, 0.5 and -0.3.
- Training continues until an epoch is presented that does not produce an error.
- If we continue with the training until we get no errors from an entire epoch the weights would be 0.4, 0.4, 0.3.

KR - SCET

42

Learning in Neural Networks

- Learn values of weights from I/O pairs
- Start with random weights
- Load training example's input
- Observe computed input
- Modify weights to reduce difference
- Iterate over all training examples
- Terminate when weights stop changing OR when error is very small

KR - SCET

43

Neural Network

- OR Gate
- Ex-OR Gate

KR - SCET


Decision boundaries

- In simple cases, divide feature space by drawing a hyperplane across it.
- Known as a decision boundary.
- Discriminant function: returns different values on opposite sides. (straight line)
- Problems which can be thus classified are linearly separable.

KR - SCET


45

A Linearly Separable Pattern Classification Problem




KR - SCET

Decision Surface of a Perceptron



Linearly separable




Non-Linearly separable

- Perceptron is able to represent some useful functions
- AND(x_1, x_2) choose weights $w_0 = -1.5$, $w_1 = 1$, $w_2 = 1$
- But functions that are not linearly separable (e.g. XOR) are not representable

KR - SCET

47


Linear Separability



KR - SCET


48

Rugby players & Ballet dancers



KR - SCET


AND GATE



Linearly Separable ?

KR - SCET


OR GATE



Linearly Separable ?

KR - SCET

Ex-OR GATE



Linearly Separable ?

KR - SCET


Hyperplane partitions

- A single Perceptron (i.e. output unit) with connections from each input can perform, and learn, a linear separation.
- Perceptrons have a step function activation.
- Units with a sigmoid activation also act as a linear discriminant, if interpreted correctly.
 - Use activation mid-point

KR - SCET

KR - SCET


A Multilayer Perceptron That Solves the XOR Problem



KR - SCET

442


A Multilayer Perceptron That Solves the XOR Problem



KR - SCET

442


A more generic model



- A multi layer "perceptron"
- Can compose arbitrarily complicated Boolean functions


KR - SCET

Perceptron on real value




KR - SCET

Complicated decision boundaries



KR - SCET


Complicated decision boundaries



- Build a network of units with a single output that fires if the input is in the coloured area
- Can now be composed into "networks" to compute arbitrary classification "boundaries"


KR - SCET

Complicated decision boundaries




KR - SCET

Complicated decision boundaries




KR - SCET

Complicated decision boundaries




KR - SCET

Complicated decision boundaries



KR - SCET

Complicated decision boundaries




KR - SCET

Complicated decision boundaries

- If all networks are added with a weight of 1 each, we get our desire solution


KR - SCET

Complicated decision boundaries



KR - SCET


More Complicated decision boundaries



- Network to fire if the input is in the coloured area
- OR two polygons
- A Third Layer is required

KR - SCET

More Complicated decision boundaries




KR - SCET

More Complicated decision boundaries

- If we can do these boundaries, we can also solve any complex problem in the same manner.


KR - SCET

More Complicated decision boundaries



KR - SCET













More Complicated decision boundaries



- Classification problems : Finding decision boundaries in high-dimension space
- Can be performed by MLP

KR - SCET


Different Non-Linearly Separable Problems

Structure	Types of Decision Regions	Exclusive-OR Problem	Classes with Meshed regions	Most General Region Shapes
Single-Layer 	Half Plane Bounded By Hyperplane			
Two-Layer 	Convex Open Or Closed Regions			
Three-Layer 	Arbitrary (Complexity Limited by No. of Nodes)			

KR - SCET

73

Multilayer Perceptron (MLP)



KR - SCET

74

Types of Layers


- The input layer.
 - Introduces input values into the network.
 - No activation function or other processing.
- The hidden layer(s).
 - Perform classification of features
 - Two hidden layers are sufficient to solve any problem
 - Features imply more layers may be better
- The output layer.
 - Functionally just like the hidden layers
 - Outputs are passed on to the world outside the neural network.

KR - SCET

75

Activation functions

- Transforms neuron's input into output.
- Features of activation functions:
 - A squashing effect is required
 - Prevents accelerating growth of activation levels through the network.
 - Simple and easy to calculate



KR - SCET

Standard activation functions

- The hard-limiting threshold function
 - Corresponds to the biological paradigm
 - either fires or not
- Sigmoid functions ('S'-shaped curves)
 - The logistic function
 - The hyperbolic tangent (symmetrical)
 - Both functions have a simple differential
 - Only the shape is important

$$\phi(x) = \frac{1}{1 + e^{-ax}}$$

KR - SCET

77

Training Algorithms

- Adjust neural network weights to map inputs to outputs.
- Use a set of sample patterns where the desired output (given the inputs presented) is known.
- The purpose is to learn to generalize
 - Recognize features which are common to good and bad exemplars

KR - SCET

78

Back-Propagation

- A training procedure which allows multi-layer feedforward Neural Networks to be trained;
- Can theoretically perform "any" input-output mapping;
- Can learn to solve linearly inseparable problems.

KR - SCET

79

Activation functions and training

- For feed-forward networks:
 - A continuous function can be differentiated allowing gradient-descent.
 - Back-propagation is an example of a gradient-descent technique.
 - Reason for prevalence of sigmoid

KR - SCET

80

Applications


- The properties of neural networks define where they are useful.
 - Can learn complex mappings from inputs to outputs, based solely on samples
 - Difficult to analyse: firm predictions about neural network behaviour difficult;
 - Unsuitable for safety-critical applications.
 - Require limited understanding from trainer, who can be guided by heuristics.

KR - SCET

81


Neural network for OCR

- feedforward network
- trained using Back-propagation



KR - SCET

OCR for 8x10 characters




- NN are able to generalise
- learning involves generating a partitioning of the input space
- for single layer network input space must be linearly separable
- what is the dimension of this input space?
- how many points in the input space?
- this network is binary(uses binary values)
- networks may also be continuous

KR - SCET

83

Engine management



- The behaviour of a car engine is influenced by a large number of parameters
 - temperature at various points
 - fuel/air mixture
 - lubricant viscosity.
- Major companies have used neural networks to dynamically tune an engine depending on current settings.

KR - SCET



84

ALVINN

Drives 70 mph on a public highway



30 outputs
for steering
4 hidden
units
30x32 pixels
as inputs
KR - SCET



30x32 weights
into one out of
four hidden
unit

Signature recognition

- Each person's signature is different.
- There are structural similarities which are difficult to quantify.
- One company has manufactured a machine which recognizes signatures to within a high level of accuracy.
 - Considers speed in addition to gross shape.
 - Makes forgery even more difficult.

KR - SCET

86

Sonar target recognition



- Distinguish mines from rocks on sea-bed
- The neural network is provided with a large number of parameters which are extracted from the sonar signal.
- The training set consists of sets of signals from rocks and mines.

KR - SCET

87

Stock market prediction



- "Technical trading" refers to trading based solely on known statistical parameters; e.g. previous price
- Neural networks have been used to attempt to predict changes in prices.
- Difficult to assess success since companies using these techniques are reluctant to disclose information.

KR - SCET

88

Mortgage assessment



- Assess risk of lending to an individual.
- Difficult to decide on marginal cases.
- Neural networks have been trained to make decisions, based upon the opinions of expert underwriters.
- Neural network produced a 12% reduction in defaulters compared with human experts.

KR - SCET

89

Neural Network Problems

- Many Parameters to be set
- Over fitting
- long training times
- ...

KR - SCET

90

Parameter setting

- Number of layers
- Number of neurons
 - too many neurons, require more training time
- Learning rate
 - from experience, value should be small ~ 0.1
- Momentum term
- ..

KR - SCET

91

Over-fitting

- With sufficient nodes can classify any training set exactly
- May have poor generalisation ability.
- Cross-validation with some patterns
 - Typically 30% of training patterns
 - Validation set error is checked each epoch
 - Stop training if validation error goes up

KR - SCET

92

Training time

- How many epochs of training?
 - Stop if the error fails to improve (has reached a minimum)
 - Stop if the rate of improvement drops below a certain level
 - Stop if the error reaches an acceptable level
 - Stop when a certain number of epochs have passed

KR - SCET

93

Questions

1. What is linearly Separable problem? Give example.
2. Which type of problems can not be solved by Single layer perceptron ? Give example.
3. What is Activation function?
4. Why non-linear activation functions are used in ANN?
5. What is Biased input?
6. What is Learning Rate and what is the typical value(s) of it ?
7. In order to solve a complex problem, what is required to change/add in a neural network?
8. What is Feed Forward Neural Network?
9. What is Back Propagation Learning algorithm?
10. State at-least 3 applications of ANN.

KR - SCET

94