




SQL INTERVIEW PREPARATION GUIDE

100 ESSENTIAL SQL QUERIES

SQL Interview Preparation Guide



Created by Rani Thakare

100 Essential SQL Queries for Data Analysts

Section 1: Basic Queries (1–10)

Select all columns

```
SELECT * FROM employees;
```

Select specific columns

```
SELECT first_name, last_name, hire_date FROM employees;
```

Count all rows

```
SELECT COUNT(*) FROM employees;
```

Count non-null values

```
SELECT COUNT(salary) FROM employees;
```

Find unique values

```
SELECT DISTINCT department FROM employees;
```

Filter using WHERE

```
SELECT * FROM employees WHERE department = 'Sales';
```

Filter with AND

```
SELECT * FROM employees WHERE department = 'Sales' AND salary > 60000;
```

Filter with OR

```
SELECT * FROM employees WHERE department = 'Sales' OR department = 'Marketing';
```

Complex filter (AND + OR)

```
SELECT * FROM employees WHERE (department = 'Sales' OR department = 'Marketing') AND salary > 70000;
```

Exclude a value using NOT

```
SELECT * FROM employees WHERE department <> 'IT';
```

Section 2: Filtering & Pattern Matching (11–20)

Filter by list using IN

```
SELECT * FROM employees WHERE department IN ('Sales', 'Marketing', 'IT');
```

Exclude list using NOT IN

```
SELECT * FROM employees WHERE department NOT IN ('Sales', 'Marketing');
```

Filter values in a range

```
SELECT * FROM employees WHERE salary BETWEEN 50000 AND 75000;
```

String contains (case-insensitive)

```
SELECT * FROM employees WHERE first_name ILIKE '%jo%';
```

String starts with pattern

```
SELECT * FROM employees WHERE last_name LIKE 'Smit%';
```

String ends with pattern

```
SELECT * FROM employees WHERE email LIKE '%@gmail.com';
```

NULL values

```
SELECT * FROM employees WHERE manager_id IS NULL;
```

Non-NULL values

```
SELECT * FROM employees WHERE manager_id IS NOT NULL;
```

Filter by date range

```
SELECT * FROM employees WHERE hire_date BETWEEN '2023-01-01' AND '2023-12-31';
```

Pattern at specific position

```
SELECT * FROM employees WHERE first_name LIKE '_a%';
```

Section 3: Sorting & Limiting (21–30)

Sort ascending

```
SELECT * FROM employees ORDER BY last_name ASC;
```

Sort descending

```
SELECT * FROM employees ORDER BY salary DESC;
```

Sort by multiple columns

```
SELECT * FROM employees ORDER BY department ASC, salary DESC;
```

Top 10 highest paid

```
SELECT * FROM employees ORDER BY salary DESC LIMIT 10;
```

Latest 5 hired employees

```
SELECT * FROM employees ORDER BY hire_date DESC LIMIT 5;
```

DISTINCT + ORDER BY

```
SELECT DISTINCT department FROM employees ORDER BY department;
```

Pagination: rows 11–20

```
SELECT * FROM employees ORDER BY employee_id OFFSET 10 LIMIT 10;
```

Highest salary employee

```
SELECT * FROM employees ORDER BY salary DESC LIMIT 1;
```

Second-highest salary

```
SELECT DISTINCT salary FROM employees ORDER BY salary DESC LIMIT 1 OFFSET 1;
```

Order by calculated field

```
SELECT first_name, last_name, (salary * 0.1) AS bonus FROM employees ORDER BY bonus DESC;
```

Section 4: Aggregation & Grouping (31–40)

Count rows per group

```
SELECT department_id, COUNT(*) FROM employees GROUP BY department_id;
```

Average salary per department

```
SELECT department_id, AVG(salary) AS avg_salary FROM employees GROUP BY department_id;
```

Total salary per department

```
SELECT department_id, SUM(salary) AS total_salary FROM employees GROUP BY department_id;
```

Maximum salary per department

```
SELECT department_id, MAX(salary) AS max_salary FROM employees GROUP BY department_id;
```

Minimum salary per department

```
SELECT department_id, MIN(salary) AS min_salary FROM employees GROUP BY department_id;
```

Filter groups using HAVING

```
SELECT department_id, AVG(salary) AS avg_salary  
FROM employees  
GROUP BY department_id  
HAVING AVG(salary) > 65000;
```

Departments with more than 5 employees

```
SELECT department_id, COUNT(*) AS emp_count  
FROM employees  
GROUP BY department_id  
HAVING COUNT(*) > 5;
```

Filter then group

```
SELECT department_id, AVG(salary) AS avg_salary  
FROM employees  
WHERE hire_date >= '2022-01-01'  
GROUP BY department_id;
```

Group by multiple columns

```
SELECT department_id, job_id, AVG(salary) AS avg_salary  
FROM employees
```

GROUP BY department_id, job_id;

Highest earner per department

SELECT department_id, first_name, last_name, salary

FROM employees e

WHERE salary = (SELECT MAX(salary) FROM employees WHERE department_id = e.department_id);

Section 5: Joins (41–60)

INNER JOIN

```
SELECT e.first_name, d.department_name
FROM employees e
INNER JOIN departments d ON e.department_id = d.department_id;
```

LEFT JOIN

```
SELECT e.first_name, d.department_name
FROM employees e
LEFT JOIN departments d ON e.department_id = d.department_id;
```

LEFT JOIN with no match

```
SELECT e.first_name
FROM employees e
LEFT JOIN departments d ON e.department_id = d.department_id
WHERE d.department_id IS NULL;
```

RIGHT JOIN

```
SELECT e.first_name, d.department_name
FROM employees e
RIGHT JOIN departments d ON e.department_id = d.department_id;
```

FULL OUTER JOIN

```
SELECT e.first_name, d.department_name
FROM employees e
FULL OUTER JOIN departments d ON e.department_id = d.department_id;
```

Self JOIN (employees & managers)

```
SELECT e.first_name AS employee, m.first_name AS manager
FROM employees e
JOIN employees m ON e.manager_id = m.employee_id;
```

Join three tables

```
SELECT e.first_name, p.project_name, d.department_name
FROM employees e
JOIN projects p ON e.employee_id = p.employee_id
```

JOIN departments d **ON** e.department_id = d.department_id;

Cross Join

SELECT * **FROM** employees **CROSS JOIN** departments;

Left Join with filtering (unassigned products)

SELECT p.product_name, s.sale_id

FROM products p

LEFT JOIN sales s **ON** p.product_id = s.product_id

WHERE s.sale_id **IS NULL**;

Aggregation on joined table

SELECT d.department_name, **AVG**(e.salary) **AS** avg_salary

FROM employees e

JOIN departments d **ON** e.department_id = d.department_id

GROUP BY d.department_name;

Section 6: Subqueries (61–75)

Subquery in WHERE clause (single value)

```
SELECT first_name, last_name FROM employees WHERE salary > (SELECT AVG(salary) FROM employees);
```

Subquery in WHERE clause (multiple values)

```
SELECT first_name, last_name
```

```
FROM employees
```

```
WHERE department_id IN (SELECT department_id FROM departments WHERE location_city = 'San Francisco');
```

Subquery in FROM clause (derived table)

```
SELECT d.department_name, a.avg_salary
```

```
FROM departments d
```

```
JOIN (
```

```
SELECT department_id, AVG(salary) AS avg_salary
```

```
FROM employees
```

```
GROUP BY department_id ) a ON d.department_id = a.department_id; Subquery in SELECT clause (scalar subquery) SELECT first_name, salary, (SELECT AVG(salary) FROM employees)
```

```
AS company_avg_salary FROM employees; Correlated subquery: salary > dept average
```

```
SELECT e.first_name, e.salary
```

```
FROM employees e
```

```
WHERE e.salary > (
```

```
SELECT AVG(salary)
```

```
FROM employees WHERE department_id = e.department_id ); EXISTS to check existence
```

```
SELECT department_name
FROM departments d
WHERE EXISTS (
    SELECT 1
FROM employees e
WHERE e.department_id = d.department_id AND e.salary > 100000
);
```

NOT EXISTS to find non-matching rows

```
SELECT department_name
FROM departments d
WHERE NOT EXISTS (
    SELECT 1
FROM employees e
WHERE e.department_id = d.department_id
);
```

Employees who have placed orders

```
SELECT e.first_name, e.last_name
FROM employees e
WHERE EXISTS (
    SELECT 1
FROM orders o
WHERE o.employee_id = e.employee_id
);
```

Total salary per department using subquery

```
SELECT department_name,
    (SELECT SUM(salary) FROM employees WHERE department_id = d.department_id) AS
total_salary
FROM departments d;
```

Department with highest average salary

```
SELECT department_name
FROM departments
```

```
WHERE department_id = (  
SELECT department_id  
FROM employees  
GROUP BY department_id  
ORDER BY AVG(salary) DESC  
LIMIT 1  
);
```

Customers who ordered a specific product

```
SELECT customer_name  
FROM customers  
WHERE customer_id IN (  
SELECT customer_id  
FROM orders  
WHERE product_id = 123  
);
```

Employees earning more than average salary

```
SELECT COUNT(*)  
FROM employees  
WHERE salary > (SELECT AVG(salary) FROM employees);
```

Customers who have not placed an order

```
SELECT customer_name  
FROM customers  
WHERE customer_id NOT IN (SELECT DISTINCT customer_id FROM orders);
```

Employees earning less than average by job title

```
SELECT e.first_name, e.salary, e.job_title  
FROM employees e  
WHERE e.salary < (SELECT AVG(salary) FROM employees WHERE job_title = e.job_title);
```

Employees in department of any employee with name containing 'T'

```
SELECT employee_id, first_name, last_name  
FROM employees
```

```
WHERE department_id IN (  
SELECT department_id  
FROM employees  
WHERE first_name LIKE '%T%'  
);
```

Section 7: Window Functions (76–85)

ROW_NUMBER()

```
SELECT first_name, department_id, salary,
```

```
    ROW_NUMBER() OVER (PARTITION BY department_id ORDER BY salary DESC) AS rn
```

```
FROM employees;
```

RANK()

```
SELECT first_name, department_id, salary,
```

```
    RANK() OVER (PARTITION BY department_id ORDER BY salary DESC) AS rank
```

```
FROM employees;
```

DENSE_RANK()

```
SELECT first_name, department_id, salary,
```

```
    DENSE_RANK() OVER (PARTITION BY department_id ORDER BY salary DESC) AS dense_rank
```

```
FROM employees;
```

NTILE()

```
SELECT first_name, salary,
```

```
    NTILE(4) OVER (ORDER BY salary DESC) AS quartile
```

```
FROM employees;
```

LEAD()

```
SELECT order_date, total_amount,
```

```
    LEAD(total_amount, 1) OVER (ORDER BY order_date) AS next_order_amount
```

```
FROM orders;
```

LAG()

```
SELECT order_date, total_amount,
```

```
    LAG(total_amount, 1, 0) OVER (ORDER BY order_date) AS prev_order_amount
```

```
FROM orders;
```

Running total

```
SELECT order_date, total_amount,
```

```
    SUM(total_amount) OVER (ORDER BY order_date ROWS BETWEEN UNBOUNDED  
PRECEDING AND CURRENT ROW) AS running_total
```

```
FROM orders;
```

Moving average (last 3 rows)

```
SELECT order_date, total_amount,  
       AVG(total_amount) OVER (ORDER BY order_date ROWS BETWEEN 2 PRECEDING AND  
CURRENT ROW) AS moving_avg  
FROM orders;
```

Top 3 employees by department using RANK()

```
SELECT * FROM (  
  SELECT first_name, department_id, salary,  
         RANK() OVER (PARTITION BY department_id ORDER BY salary DESC) AS rn  
  FROM employees  
) AS ranked_employees  
WHERE rn <= 3;
```

Percentage of total sales per product

```
SELECT product_id,  
       SUM(sales) AS product_sales,  
       SUM(SUM(sales)) OVER () AS total_sales,  
       (SUM(sales)/SUM(SUM(sales)) OVER())*100 AS percentage_of_total  
FROM sales  
GROUP BY product_id;
```

Section 8: CTEs & Data Manipulation (86–100)

Basic CTE

```
WITH dept_avg AS (  
    SELECT department_id, AVG(salary) AS avg_salary  
    FROM employees  
    GROUP BY department_id )  
SELECT e.first_name, e.salary, da.avg_salary  
FROM employees e  
JOIN dept_avg da ON e.department_id = da.department_id;
```

INSERT INTO

```
INSERT INTO employees (first_name, last_name, salary)  
VALUES ('John', 'Doe', 60000);
```

UPDATE

```
UPDATE employees  
SET salary = salary * 1.05  
WHERE department_id = 'IT';
```

DELETE

```
DELETE FROM employees WHERE employee_id = 101;
```

TRUNCATE TABLE

```
TRUNCATE TABLE old_data;
```

UNION

```
SELECT first_name FROM employees
```

UNION

```
SELECT first_name FROM customers;
```

UNION ALL

```
SELECT first_name FROM employees
```

UNION ALL

```
SELECT first_name FROM customers;
```

CASE statement

```
SELECT first_name, salary,
```

CASE

WHEN salary > 100000 THEN 'High Earner'

WHEN salary BETWEEN 50000 AND 100000 THEN 'Mid-Range'

ELSE 'Junior'

END AS salary_level

FROM employees;

Pivot with CASE

SELECT department_id,

COUNT(CASE WHEN salary >= 70000 THEN 1 END) AS high_salary_count,

COUNT(CASE WHEN salary < 70000 THEN 1 END) AS low_salary_count

FROM employees

GROUP BY department_id;

CAST

SELECT CAST(order_date AS DATE) FROM orders;

COALESCE

SELECT COALESCE(email, 'No Email Provided') FROM employees;

NULLIF

SELECT NULLIF(salary, 0) FROM employees;

Recursive CTE

WITH RECURSIVE subordinates AS (

SELECT employee_id, manager_id

FROM employees

WHERE manager_id = 1

UNION ALL

SELECT e.employee_id, e.manager_id

FROM employees e

JOIN subordinates s ON e.manager_id = s.employee_id)

SELECT * FROM subordinates;

GROUPING SETS

SELECT department_id, job_id, SUM(salary)

FROM employees

GROUP BY GROUPING SETS ((department_id), (job_id), ());

ROLLUP

SELECT department_id, job_id, SUM(salary)

FROM employees

GROUP BY ROLLUP(department_id, job_id);

Thank you!