CareerTrack – API Documentation

Full-Stack Job Portal and Recruitment Management System | Handover draft

Overview

• MERN-based job portal. Public visitors can browse published jobs and apply without candidate registration. Admin users authenticate and manage jobs and applications.

Technology

• Frontend: React, Vite, React Router and Axios.

• Backend: Node.js and Express REST API.

• Database: MongoDB with Mongoose.

• Admin authentication: JWT bearer token; passwords hashed with bcrypt.

• Resume upload: Multer; current implementation checks PDF/DOC/DOCX type and applies a 5 MB limit.

Authentication and conventions

• Protected admin endpoints require Authorization: Bearer .

• JSON is used for ordinary API requests/responses; resume download and CSV export return files.

• Candidate resumes and personal information must not be exposed by public endpoints.

Endpoint catalogue

• POST /api/auth/login — administrator login.

• GET /api/jobs — public published-job listing and search/filter.

• GET /api/jobs/:id — public job details.

• POST /api/applications — public application submission (multipart/form-data; resume field).

• POST /api/applications/track — public tracking by application ID and email.

• GET /api/dashboard/stats — protected dashboard statistics.

• GET /api/applications — protected application list; status, job/date filters and pagination as implemented.

• PATCH /api/applications/:id/status — protected status and internal-notes update.

• GET /api/applications/export/csv — protected CSV export.

• GET /api/applications/:id/resume — protected resume download.

• DELETE /api/applications/:id — protected application deletion.

• Job administration routes are defined in Backend/src/routes/adminJobRoutes.js; verify exact HTTP methods and paths from that file before publishing as a definitive API contract.

Application statuses

• Submitted

• Under Review

• Shortlisted

• Interview Scheduled

• Selected

• Rejected

Security and deployment notes

• Keep .env out of Git and use placeholder values in .env.example only.

• Do not commit Backend/uploads or real candidate resumes.

• Resume storage currently uses local disk; use persistent/cloud storage for production deployments where the filesystem may be ephemeral.

• Verify CORS origins, secrets and exact environment variable names in the current backend source.

Verification

• This is a handover draft based on the project implementation details reviewed during development. Confirm exact route mounts, payload field names and response examples against the current source and Postman collection.