PrepLang: a data-aware compiler for data-preparation pipelines that reuses its proofs on new batches

Nikhil V

School of Computer Science and Engineering, Vellore Institute of Technology, Vellore 632014, Tamil Nadu, India

Abstract

PrepLang is a compiler, written in C++17, for a small language of table and image preprocessing pipelines. It reads the input data at compile time, proves or refutes the pipeline's data contracts before any data is processed, removes the checks and operations the data makes useless, and generates a pandas and OpenCV program. The generated program keeps every removal behind a guard with the input facts it depends on, so it runs unchanged on new batches and runs a removal again only on a batch that breaks its facts. The repository also holds Lean 4 proofs for a core of the analysis, a lifter for pandas scripts, a tool that composes compiled stages, a tool that releases differentially private facts to compile against, and the complete evaluation.

Keywords: data-aware compilation, data validation, speculative optimization, deoptimization, data pipelines, differential privacy

1. Motivation and significance

Data-preparation mistakes propagate silently into models [1]. A preparation pipeline is usually a script over pandas [2] and OpenCV [3] that cannot know, until it runs, whether a column it normalizes holds numbers or whether the images it saves as PNG hold float pixels; validators such as TFDV [4], Deequ [5], Great Expectations [6] and pandera [7] check the data separately from the code that transforms it. PrepLang uses a property of batch preparation that compilers leave unused: the inputs exist when the pipeline is compiled. As F# type providers do for types [8], but for values, it reads every CSV cell, Parquet footer and image header, follows types, missing values, value ranges and image properties through the pipeline, proves or refutes each

Email address: atnikhil06@gmail.com (Nikhil V)

Nr.	Code metadata description	Please fill in this column
C1	Current code version	[v2.0.0: tag this release]
C2	Permanent link to code/repository used for this code version	`https://github.com/Nikhi00718/preLang` [make it public]
C3	Permanent link to Reproducible Capsule	None; `eval/paper_numbers.py` regenerates every number from the raw results
C4	Legal Code License	[an OSI-approved licence, e.g. MIT, in a LICENSE file]
C5	Code versioning system used	git
C6	Software code languages, tools, and services used	C++17 (no external libraries); Python 3 with pandas, NumPy, PyArrow, OpenCV; Lean 4; CMake
C7	Compilation requirements, operating environments and dependencies	CMake 3.16+, a C++17 compiler (tested: Visual Studio 2022, Windows 11); Python 3.12 with pandas, PyArrow, OpenCV; Lean 4.34.1 (optional, for the proofs)
C8	If available, link to developer documentation/manual	`README.md`; the READMEs of `eval/`, `paper/`, `proofs/`, `docs/`
C9	Support email for questions	atnikhil06@gmail.com

Table 1: Code metadata (mandatory)

contract before any data is processed, and removes the checks and operations the data makes useless.

Such proofs hold for one file, while the pipeline runs again next month on a file with the same layout and other values. PrepLang therefore computes, for every removal, the facts about the input it depends on (its *item certificate*), and the generated program checks them on each new batch: a removal whose facts hold stays removed, one whose facts a batch breaks runs again (*selective deoptimization*, from dynamic compilers [9, 10]), and a batch is refused only for facts no run-time code can stand in for, such as a changed column type. A user writes a `.prep` program, compiles it against the current batch, reads the diagnostics and deploys the generated program for every later batch. The theory and the full evaluation are in an accompanying research article submitted to this journal; this article describes the software.

2. Software description

2.1. Software architecture

The compiler (`src/`, about 11,300 lines of C++17 without external libraries) runs lexer, LL(1) parser, semantic analysis, IR, optimizer, certifier and code generator in turn. The *schema* readers scan CSV files in parallel and read Parquet footers and PNG and JPEG headers; the *semantic analyzer* computes the abstract dataset state (types, missing values, value intervals, image properties) and decides every contract; the *optimizer* removes, speculatively, what the state shows to have no effect; the *certifier* re-runs the analysis under weakened input facts, reading no data, to find the admission certificate and one item certificate per removal (Fig. 1); the *back end* generates one




Figure 1: How PrepLang compiles once and reuses the result. The certifier re-runs the analysis with weaker input facts, reading no data; on a new batch, the generated program runs a removed instruction i only if the batch breaks its item certificate $\mathcal{C}_i$.

Python program that admits a batch and guards every removed instruction with `deopt(i)`, and writes the certificates to `preplang_contract.json`.

The repository also holds `proofs/` (1477 lines of Lean 4 [11]: selective deoptimization is exact for any monotone and sound analysis, and the analysis of a core of the language is sound and monotone), `tests/` (285 checks in 10 suites, with randomized soundness tests), a lifter of pandas scripts (`frontend/`), the composition and release tools (`tools/`), a local editor app (`studio/`) and the evaluation (`eval/`).

2.2. Software functionalities

- **Compile-time checking:** misspelled or removed columns, type errors and broken contracts (`NOT_NULL`, `BETWEEN`, `UNIQUE`, `REFERENCES`, schemas, image channels and sizes, match rates of images and labels), reported with the line, the offending row and a hint.
- **Data-driven optimization:** proven checks and no-effect operations are removed, unused columns are not loaded, image pipelines are streamed; rewrites that change the output need `-approx`.
- **Reuse:** admission by certificate, and re-enabled removals with the reason printed.
- **Composition:** `tools/contracts.py` checks one stage's published guarantees against the next stage's certificates and writes the contract a producer must meet.
- **Private compilation:** the data owner releases differentially private facts at the cells the program's numbers define (`-queries`, `tools/release_facts.py`); the analyst compiles with `-facts` without opening any input file, and every run stays exact.

- **Inspection:** every phase can be printed (`-tokens` to `-python`), with an execution plan (`-explain`) and the files a run would touch (`-dry-run`).

3. Illustrative example

```
LOAD "students.csv" AS students;
EXPECT students.age NUMBER;
EXPECT students.marks BETWEEN 0 AND 100;
EXPECT students.name NOT_NULL;
FILTER students WHERE marks >= 50;
EXPECT students.marks BETWEEN 60 AND 100;
SAVE students AS "clean.csv";
```

Compiled against an eight-row `students.csv` (from `examples/tabular/`), PrepLang proves the first three contracts and checks the fourth at run time, since after the filter it only knows that the marks lie in $[50, 95]$. It removes the range and not-null checks speculatively, and `-certificate` shows the facts the range check needs: marks at least 0 and at most 100. Run on a later batch in which a mark is 104, the generated program re-enables the check and stops where a fresh compilation would:

```
Deoptimized line 3: EXPECT students.marks BETWEEN 0 AND 100:
  marks goes up to 104, above 100
ContractError: line 3: students.marks has values outside 0 to 100
```

A batch within the facts runs with both checks removed; a batch whose `age` holds text is refused, since no generated code can stand in for the analysis of another type.

4. Impact

The evaluation in `eval/` measures PrepLang against the tools a data engineer uses today:

- **Reuse on real data.** On 238 real monthly batches of three public datasets, the compiled programs handle 221 (93%) exactly as a fresh compilation would, with 0 wrong; Great Expectations and pandera, set up on the same data, refuse 92–93% of the months a fresh compilation runs, and TFDV admits months on which the optimized program does not do what a fresh compilation does.
- **Mistakes before processing.** All 24 injected mistakes are reported at compile time, in 22–39 ms, where a script-style interpreter crashes on 20 and writes wrong output on 4; on 16 million Parquet rows a misspelled column is reported in 0.02 s instead of after 2.81 s; 18 of

44 real failures from GitHub issues are reported before any data is processed.

- **Cost and gain.** An optimized table pipeline runs in 0.47 s instead of 0.79 s, an image pipeline in 10 MiB instead of 922 MiB; admission changes the median run time by −1% and compiling takes 21–35 ms.
- **Other people's code.** Lifted pandas scripts from GitHub reproduce their results on new batches in 3198 of 3212 runs and in all 3255 monthly runs of 72 scripts written by others.
- **Without seeing the data.** 4,879 private compilations from released, noisy or random facts ran 64,179 times, all exact; at equal budget the release at the program's numbers keeps every removal of the taxi and traffic pipelines, where fixed bins keep 60% and 83%, and HDMM [12] and AIM [13], given the same cells and threshold, do no better.

One script, `eval/paper_numbers.py`, regenerates every number from the raw results, with the baselines in pinned environments (`eval/README.md`). PrepLang is a research prototype, built by the author and partly within a compiler-design course; it has no users outside the author's experiments yet. Others can extend its abstract state, certifier and code generator, and compare on the same batches.

5. Limitations and conclusions

The language has no joins or aggregations and generates Python only; a changed column type is refused rather than handled; the mechanized proofs cover a core of the analysis and the rest is tested; the compiler is tested on Windows 11 only. Planned work is joins, generated code that adapts to type changes, Linux continuous integration and packaging. PrepLang compiles a pipeline once and runs it on later batches exactly as a fresh compilation would, re-enabling only the removals a batch makes unsafe.

Declaration of competing interest

The author declares no known competing financial interests or personal relationships that could have appeared to influence the work reported in this paper.

Funding

This research did not receive any specific grant from funding agencies in the public, commercial, or not-for-profit sectors.

References

[1] D. Sculley, G. Holt, D. Golovin, E. Davydov, T. Phillips, D. Ebner, V. Chaudhary, M. Young, J.-F. Crespo, and D. Dennison, "Hidden technical debt in machine learning systems," in *Advances in Neural Information Processing Systems (NeurIPS)*, 2015, pp. 2503–2511.

[2] W. McKinney, "Data structures for statistical computing in Python," in *Proc. 9th Python in Science Conf. (SciPy)*, 2010, pp. 56–61.

[3] G. Bradski, "The OpenCV library," *Dr. Dobb's Journal of Software Tools*, 2000.

[4] E. Breck, N. Polyzotis, S. Roy, S. E. Whang, and M. Zinkevich, "Data validation for machine learning," in *Proc. Conf. on Machine Learning and Systems (MLSys)*, 2019.

[5] S. Schelter, D. Lange, P. Schmidt, M. Celikel, F. Biessmann, and A. Grafberger, "Automating large-scale data quality verification," *Proc. VLDB Endowment*, vol. 11, no. 12, pp. 1781–1794, 2018.

[6] Great Expectations, "Great Expectations: data quality testing," `https://greatexpectations.io`.

[7] N. Bantilan, "pandera: Statistical data validation of pandas dataframes," in *Proc. 19th Python in Science Conf. (SciPy)*, 2020, pp. 116–124.

[8] T. Petricek, G. Guerra, and D. Syme, "Types from data: Making structured data first-class citizens in F#," in *Proc. 37th ACM SIGPLAN Conf. on Programming Language Design and Implementation (PLDI)*, 2016, pp. 477–490.

[9] U. Hölzle, C. Chambers, and D. Ungar, "Debugging optimized code with dynamic deoptimization," in *Proc. ACM SIGPLAN Conf. on Programming Language Design and Implementation (PLDI)*, 1992, pp. 32–43.

[10] A. Barrière, S. Blazy, O. Flückiger, D. Pichardie, and J. Vitek, "Formally verified speculation and deoptimization in a JIT compiler," *Proc. ACM Program. Lang.*, vol. 5, no. POPL, pp. 1–26, 2021.

[11] L. de Moura and S. Ullrich, "The Lean 4 theorem prover and programming language," in *Proc. 28th Int. Conf. on Automated Deduction (CADE)*, LNCS 12699, 2021, pp. 625–635.

[12] R. McKenna, G. Miklau, M. Hay, and A. Machanavajjhala, "Optimizing error of high-dimensional statistical queries under differential privacy," *Proc. VLDB Endowment*, vol. 11, no. 10, pp. 1206–1219, 2018.

[13] R. McKenna, B. Mullins, D. Sheldon, and G. Miklau, "AIM: An adaptive and iterative mechanism for differentially private synthetic data," *Proc. VLDB Endowment*, vol. 15, no. 11, pp. 2599–2612, 2022.