

# **VISVESVARAYA TECHNOLOGICAL UNIVERSITY**

“JnanaSangama”, Belgaum -590014, Karnataka.



## **LAB REPORT**

**on**

## **COURSE TITLE**

*Submitted by*

**NIKHIL ABRAHAM (1BM19CS101)**

*in partial fulfillment for the award of the degree of*

**BACHELOR OF ENGINEERING**

*in*

**COMPUTER SCIENCE AND ENGINEERING**



**B.M.S. COLLEGE OF ENGINEERING**

(Autonomous Institution under VTU)

**BENGALURU-560019**

**May-2022 to July-2022**

**B. M. S. College of Engineering,**  
**Bull Temple Road, Bangalore 560019**  
(Affiliated To Visvesvaraya Technological University, Belgaum)  
**Department of Computer Science and Engineering**



**CERTIFICATE**

This is to certify that the Lab work entitled “MACHINE LEARNING” carried out by **NIKHIL ABRAHAM (1BM19CS101)**, who is bonafide student of **B. M. S. College of Engineering**. It is in partial fulfillment for the award of **Bachelor of Engineering in Computer Science and Engineering** of the Visvesvaraya Technological University, Belgaum during the year 2022. The Lab report has been approved as it satisfies the academic requirements in respect of a **Course Title - (Course code)** work prescribed for the said degree.

Name of the Lab-Incharge  
Designation  
Department of CSE  
BMSCE, Bengaluru

**Dr. Asha G R**  
Assistant Professor  
Department of CSE  
BMSCE, Bengaluru

## Index Sheet

SL NO	EXPERIMENT	PAGE NO
1	FIND S ALGORITHM	3
2	CANDIDATE ELIMINATION ALGORITHM	4
3	DECISION TREE USING ID3 ALGORITHM	6
4	LINEAR REGRESSION	10
5	NAÏVE BAYES NETWORK	12

### WEEK 1

#### FIND S ALGORITHM

```
import pandas as pd
import numpy as np

#to read the data in the csv file
print("USN:1BM19CS101")
data = pd.read_csv(r"C:\Users\admin\Downloads\data.csv")
print(data,"\n")

#making an array of all the attributes
d = np.array(data)[:,:-1]
print("The attributes are: ",d)

#segragating the target that has positive and negative examples
target = np.array(data)[:,-1]
print("The target is: ",target)

#training function to implement find-s algorithm
def train(c,t):
    for i, val in enumerate(t):
```

```

    if val == "Yes":
        specific_hypothesis = c[i].copy()
        break

for i, val in enumerate(c):
    if t[i] == "Yes":
        for x in range(len(specific_hypothesis)):
            if val[x] != specific_hypothesis[x]:
                specific_hypothesis[x] = '?'
            else:
                pass

return specific_hypothesis

#obtaining the final hypothesis
print("\n The final hypothesis is:",train(d,target))

```

## OUTPUT

```

USN:1BM19CS095
    Time Weather Temperature Company Humidity    Wind Goes
0  Morning   Sunny         Warm      Yes    Mild  Strong  Yes
1  Evening   Rainy         Cold      No     Mild  Normal  No
2  Morning   Sunny      Moderate    Yes   Normal  Normal  Yes
3  Evening   Sunny         Cold      Yes    High  Strong  Yes

The attributes are: [['Morning' 'Sunny' 'Warm' 'Yes' 'Mild' 'Strong']
['Evening' 'Rainy' 'Cold' 'No' 'Mild' 'Normal']
['Morning' 'Sunny' 'Moderate' 'Yes' 'Normal' 'Normal']
['Evening' 'Sunny' 'Cold' 'Yes' 'High' 'Strong']]
The target is: ['Yes' 'No' 'Yes' 'Yes']
n The final hypothesis is: ['?' 'Sunny' '?' 'Yes' '?' '?']

```

## WEEK 2

### CANDIDATE ELIMINATION ALGORITHM

```

Import
numpy
as np

import pandas as pd

data = pd.read_csv(r'C:\Users\admin\Downloads\enjoysport.csv')

```

```

concepts = np.array(data.iloc[:,0:-1])
print("\nInstances are:\n",concepts)
target = np.array(data.iloc[:, -1])
print("\nTarget Values are: ",target)

def learn(concepts, target):
    specific_h = concepts[0].copy()
    print("\nInitialization of specific_h and general_h")
    print("\nSpecific Boundary: ", specific_h)
    general_h = [["?" for i in range(len(specific_h))] for i in
range(len(specific_h))]
    print("\nGeneric Boundary: ",general_h)

    for i, h in enumerate(concepts):
        print("\nInstance", i+1 , "is ", h)
        if target[i] == "yes":
            print("Instance is Positive ")
            for x in range(len(specific_h)):
                if h[x]!= specific_h[x]:
                    specific_h[x] ='?'
                    general_h[x][x] ='?'

        if target[i] == "no":
            print("Instance is Negative ")
            for x in range(len(specific_h)):
                if h[x]!= specific_h[x]:
                    general_h[x][x] = specific_h[x]
                else:
                    general_h[x][x] = '?'

        print("Specific Boundary after ", i+1, "Instance is ", specific_h)
        print("Generic Boundary after ", i+1, "Instance is ", general_h)
        print("\n")

    indices = [i for i, val in enumerate(general_h) if val == ['?', '?', '?', '?',
'?', '?']]
    for i in indices:
        general_h.remove(['?', '?', '?', '?', '?', '?'])
    return specific_h, general_h

s_final, g_final = learn(concepts, target)

print("Final Specific_h: ", s_final, sep="\n")
print("Final General_h: ", g_final, sep="\n")

```

## OUTPUT

```

Instances are:
[['sunny' 'warm' 'normal' 'strong' 'warm' 'same']
 ['sunny' 'warm' 'high' 'strong' 'warm' 'same']
 ['rainy' 'cold' 'high' 'strong' 'warm' 'change']
 ['sunny' 'warm' 'high' 'strong' 'cool' 'change']]

Target Values are: ['yes' 'yes' 'no' 'yes']

Initialization of specific_h and general_h

Specific Boundary: ['sunny' 'warm' 'normal' 'strong' 'warm' 'same']

Generic Boundary: [['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?',
'?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?']]

Instance 1 is ['sunny' 'warm' 'normal' 'strong' 'warm' 'same']
Instance is Positive
Specific Boundary after 1 Instance is ['sunny' 'warm' 'normal' 'strong' 'warm' 'same']
Generic Boundary after 1 Instance is [['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?',
'?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?']]

Instance 2 is ['sunny' 'warm' 'high' 'strong' 'warm' 'same']
Instance is Positive
Specific Boundary after 2 Instance is ['sunny' 'warm' '?' 'strong' 'warm' 'same']
Generic Boundary after 2 Instance is [['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?',
'?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?']]

Instance 3 is ['rainy' 'cold' 'high' 'strong' 'warm' 'change']
Instance is Negative
Specific Boundary after 3 Instance is ['sunny' 'warm' '?' 'strong' 'warm' 'same']
Generic Boundary after 3 Instance is [['sunny', '?', '?', '?', '?', '?'], ['?', 'warm', '?', '?', '?', '?'], ['?', '?', '?',
'?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', 'same']]

Instance 4 is ['sunny' 'warm' 'high' 'strong' 'cool' 'change']
Instance is Positive
Specific Boundary after 4 Instance is ['sunny' 'warm' '?' 'strong' '?' '?']
Generic Boundary after 4 Instance is [['sunny', '?', '?', '?', '?', '?'], ['?', 'warm', '?', '?', '?', '?'], ['?', '?', '?',
'?', '?', '?'], ['?', '?', '?', '?', '?', '?'], ['?', '?', '?', '?', '?', '?']]

Final Specific_h:
['sunny' 'warm' '?' 'strong' '?' '?']
Final General_h:
[['sunny', '?', '?', '?', '?', '?'], ['?', 'warm', '?', '?', '?', '?']]

```

## WEEK 3

### DECISION TREE USING ID3 ALGORITHM

```

import
math

import csv
def load_csv(filename):
    lines=csv.reader(open(filename,"r"))
    dataset = list(lines)
    headers = dataset.pop(0)
    return dataset,headers

class Node:
    def __init__(self,attribute):
        self.attribute=attribute

```

```

        self.children=[]
        self.answer=""

def subtables(data,col,delete):
    dic={}
    coldata=[row[col] for row in data]
    attr=list(set(coldata))

    counts=[0]*len(attr)
    r=len(data)
    c=len(data[0])
    for x in range(len(attr)):
        for y in range(r):
            if data[y][col]==attr[x]:
                counts[x]+=1

    for x in range(len(attr)):
        dic[attr[x]]=[[0 for i in range(c)] for j in range(counts[x])]
        pos=0
        for y in range(r):
            if data[y][col]==attr[x]:
                if delete:
                    del data[y][col]
                dic[attr[x]][pos]=data[y]
                pos+=1
    return attr,dic

def entropy(S):
    attr=list(set(S))
    if len(attr)==1:
        return 0

    counts=[0,0]
    for i in range(2):
        counts[i]=sum([1 for x in S if attr[i]==x])/(len(S)*1.0)

    sums=0
    for cnt in counts:
        sums+=-1*cnt*math.log(cnt,2)
    return sums

def compute_gain(data,col):
    attr,dic = subtables(data,col,delete=False)

    total_size=len(data)
    entropies=[0]*len(attr)
    ratio=[0]*len(attr)

    total_entropy=entropy([row[-1] for row in data])
    for x in range(len(attr)):
        ratio[x]=len(dic[attr[x]])/(total_size*1.0)
        entropies[x]=entropy([row[-1] for row in dic[attr[x]]])
        total_entropy-=ratio[x]*entropies[x]
    return total_entropy

```

```

def build_tree(data, features):
    lastcol=[row[-1] for row in data]
    if(len(set(lastcol))==1):
        node=Node("")
        node.answer=lastcol[0]
        return node

    n=len(data[0])-1
    gains=[0]*n
    for col in range(n):
        gains[col]=compute_gain(data,col)
    split=gains.index(max(gains))
    node=Node(features[split])
    fea = features[:split]+features[split+1:]

    attr,dic=subtables(data,split,delete=True)

    for x in range(len(attr)):
        child=build_tree(dic[attr[x]],fea)
        node.children.append((attr[x],child))
    return node

def print_tree(node,level):
    if node.answer!="":
        print("  "*level,node.answer)
        return

    print("  "*level,node.attribute)
    for value,n in node.children:
        print("  "*(level+1),value)
        print_tree(n,level+2)

def classify(node,x_test,features):
    if node.answer!="":
        print(node.answer)
        return
    pos=features.index(node.attribute)
    for value, n in node.children:
        if x_test[pos]==value:
            classify(n,x_test,features)

'''Main program'''
dataset,features=load_csv(r"C:\Users\admin\Downloads\id3.csv")
node1=build_tree(dataset,features)

print("The decision tree for the dataset using ID3 algorithm is")
print_tree(node1,0)
testdata,features=load_csv(r"C:\Users\admin\Downloads\id3_test.csv")

```



```
for xtest in testdata:
    print("The test instance:",xtest)
    print("The label for test instance:")
    classify(node1,xtest,features)
```

## OUTPUT

```
The decision tree for the dataset using ID3 algorithm is
Outlook
  overcast
    yes
  rain
    Wind
      strong
        no
      weak
        yes
  sunny
    Humidity
      high
        no
      normal
        yes
The test instance: ['rain', 'cool', 'normal', 'strong']
The label for test instance:
no
The test instance: ['sunny', 'mild', 'normal', 'strong']
The label for test instance:
yes
```

## WEEK 4

### LINEAR REGRESSION

```
import numpy as np
import matplotlib.pyplot as plt
import pandas as pd

dataset = pd.read_csv('salary_data.csv')
X = dataset.iloc[:, :-1].values
y = dataset.iloc[:, 1].values

from sklearn.model_selection import train_test_split
X_train, X_test, y_train, y_test = train_test_split(X, y, test_size=1/3,
random_state=0)
```

```

# Fitting Simple Linear Regression to the Training set
from sklearn.linear_model import LinearRegression
regressor = LinearRegression()
regressor.fit(X_train, y_train)

# Predicting the Test set results
y_pred = regressor.predict(X_test)

# Visualizing the Training set results
viz_train = plt
viz_train.scatter(X_train, y_train, color='red')
viz_train.plot(X_train, regressor.predict(X_train), color='blue')
viz_train.title('Salary VS Experience (Training set)')
viz_train.xlabel('Year of Experience')
viz_train.ylabel('Salary')
viz_train.show()

# Visualizing the Test set results
viz_test = plt
viz_test.scatter(X_test, y_test, color='red')
viz_test.plot(X_train, regressor.predict(X_train), color='blue')
viz_test.title('Salary VS Experience (Test set)')
viz_test.xlabel('Year of Experience')
viz_test.ylabel('Salary')
viz_test.show()

```

## OUTPUT





## LAB 5

### NAÏVE BAYES NETWORK

```
import pandas as pd
from sklearn.model_selection import train_test_split
from sklearn.naive_bayes import GaussianNB
from sklearn import metrics

df = pd.read_csv(r"C:\Users\admin\Downloads\data5.csv")
col_names = ['num_preg', 'glucose_conc', 'diastolic_bp', 'thickness',
             'insulin', 'bmi', 'diab_pred', 'age']
predicted_class = ['diabetes']

X = df[col_names].values
y = df[predicted_class].values

print(df.head)
xtrain,xtest,ytrain,ytest=train_test_split(X,y,test_size=0.4)

print ('\n the total number of Training Data :',ytrain.shape)
print ('\n the total number of Test Data :',ytest.shape)

clf = GaussianNB().fit(xtrain,ytrain.ravel())
predicted = clf.predict(xtest)
predictTestData= clf.predict([[6,148,72,35,0,33.6,0.627,50]])
```

```

print('\n Confusion matrix')
print(metrics.confusion_matrix(ytest,predicted))

print('\n Accuracy of the classifier
is',metrics.accuracy_score(ytest,predicted))

print('\n The value of Precision', metrics.precision_score(ytest,predicted))

print('\n The value of Recall', metrics.recall_score(ytest,predicted))

print("Predicted Value for individual Test Data:", predictTestData)

```

<bound	method	NDFrame.head of	num_preg	glucose_conc	diastolic_bp	thickness	insulin	bmi \
0	6	148	72	35	0	33.6		
1	1	85	66	29	0	26.6		
2	8	183	64	0	0	23.3		
3	1	89	66	23	94	28.1		
4	0	137	40	35	168	43.1		
..	...	...	...	...	...	...		
763	10	101	76	48	180	32.9		
764	2	122	70	27	0	36.8		
765	5	121	72	23	112	26.2		
766	1	126	60	0	0	30.1		
767	1	93	70	31	0	30.4		

	diab_pred	age	diabetes
0	0.627	50	1
1	0.351	31	0
2	0.672	32	1
3	0.167	21	0
4	2.288	33	1
..	...	...	...
763	0.171	63	0
764	0.340	27	0
765	0.245	30	0
766	0.349	47	1
767	0.315	23	0

[768 rows x 9 columns]>

the total number of Training Data : (460, 1)

the total number of Test Data : (308, 1)

```

Confusion matrix
[[176  29]
 [ 40  63]]

```

Accuracy of the classifier is 0.775974025974026

The value of Precision 0.6847826086956522

The value of Recall 0.6116504854368932

Predicted Value for individual Test Data: [1]

