


# PL/SQL



# PL/SQL

**Introduction to PL/SQL**

**Data types in PL/SQL**

**Control Structures in PL/SQL**

**Functions in PL/SQL**

# PL/SQL

Procedure

Cursor

Trigger

Exception In PL/SQL

# PL/SQL

## Introduction to PL/SQL

- ❖ **PL/SQL is a combination of SQL along with the procedural features of programming languages.**
- ❖ **Properties of programming as well as the great interaction with database.**

**Points to Ponder:-**

**PLSQL IS NOT A CASE SENSITIVE LANGUAGE.**

# PL/SQL

## Comments in PL/SQL

The PL/SQL compiler ignores comments but you should not.

Single-line comments begin with a double hyphen (--)

Multiline comments begin with a slashasterisk (/\*), end with an asterisk-

# PL/SQL

## Important PL/SQL Concepts

- ❖ **DECLARE :-** if you want to declare a variable in plsql program then it takes place in declare section.
- ❖ **BEGIN:-** is used to start the working of program.
- ❖ **END:-** is used to terminate the begin.

**Points to Ponder:-**

**DELIMITER IS USED TO RUN (/)**

# PL/SQL

## What to do Previously

- ❖ **SET SERVEROUTPUT ON :-** is run after every time when you login in a session.

# PL/SQL

## To show OUTPUT on Your Screen

**DBMS\_OUTPUT.PUT\_LINE** command  
for e.g. if `sal=10` and you want to print it.

Then it looks like

```
dbms_output.put_line('the salary is ' || sal);
```



# PL/SQL

## Value assign in Variable

**Declare**

**Num number(11);**

**Begin**

**Num:=5;**

**End;**

**/**

# PL/SQL

## User's Input for a Variable

```
DECLARE  
N NUMBER(11);  
  
BEGIN  
DBMS_OUTPUT.PUT_LINE('ENTER A NUMBER:-');  
N:=&N;  
DBMS_OUTPUT.PUT_LINE('THE VALUE IS'||N);  
  
END;  
/
```

# PL/SQL

Sample program to print your 'Hello World'

**BEGIN**

**DBMS\_OUTPUT.PUT\_LINE('Hello World');**

**END;**

**/**

# PL/SQL

## Control Structures in PL/SQL

### IF STATEMENT

#### Syntax:-

```
IF condition THEN  
statement 1;  
ELSE  
statement 2;  
END IF;
```

#### Points to Ponder:-

**IF STATEMENT WORKS AS SIMILAR AS C OR C++**

# PL/SQL

## Control Structures in PL/SQL

### IF STATEMENT EXAMPLE

```
DECLARE  
Age number(11);  
Begin  
Age:=&age;  
If age>18 then  
Dbms_output.put_line('You can vote');  
Else  
Dbms_output.put_line('You cannot vote');  
End if;  
End;  
/
```

# PL/SQL

## Control Structures in PL/SQL

### IF WITH SQL TABLE

**Declare**

**A number(11);**

**Begin**

**Select sal into a from empcp where  
    ename='MARTIN';**

**If a>1000 then**

**Update empcp set comm=comm+1000 where  
    ename='MARTIN';**

**Else**

**Update empcp set comm=comm+500 where  
    ename='MARTIN';End if;End;/**

# PL/SQL

## Control Structures in PL/SQL

### LOOPS IN PL/SQL

**1)SIMPLE LOOP**

**2)WHILE LOOP**

**3)FOR LOOP**

# PL/SQL

## Control Structures in PL/SQL

### FOR LOOP

**Print number from 1 to 10 using FOR loop**

**BEGIN**

**FOR i in [REVERSE] 1 ..10 Loop**

**Dbms\_output.put\_line(i);**

**END Loop;**

**End;**

**/**

**Points to Ponder:-**

**(For FOR LOOP has NO need to initialize variable i explicitly but it need in while )**



# PL/SQL

## Control Structures in PL/SQL

### WHILE LOOP

**Print number from 1 to 10 using WHILE loop**

**Declare**

**i number(3):=0;**

**Begin**

**While i<10 loop**

**i:=i+1;**

**Dbms\_output.put\_line(i);**

**End loop;**

**End;**

**/**

# PL/SQL

## Control Structures in PL/SQL

### SYNTAX OF SIMPLE LOOP

#### **LOOP**

**Statement 1;**

**Statement 2;**

**Exit condition**

**End loop;**

# PL/SQL

## Control Structures in PL/SQL

### SIMPLE LOOP EXAMPLE

**Declare**

**I number(2):=0;**

**Begin**

**Loop**

**dbms\_output.put\_line('Before Increment value of  
variable I: ' || I);**

**I:=I+1;**

**dbms\_output.put\_line('After Increment value of  
variable I: ' || I);**

**EXIT when (I>0);END loop;END;/**

# PL/SQL

## Control Structures in PL/SQL

### SYNTAX OF "CASE"

**CASE (expression)**

```
WHEN <value1> THEN action_block1;  
WHEN <value2> THEN action_block2;  
WHEN <value3> THEN action_block3;  
ELSE action_block_default;  
END CASE;
```

# PL/SQL

## Control Structures in PL/SQL

### EXAMPLE OF "CASE"

```
Declare
a NUMBER :=55;
b NUMBER :=5;
arth_operation VARCHAR2(20) :='MULTIPLY';
BEGIN
dbms_output.put_line('Program started.' );
CASE (arth_operation)
WHEN 'ADD' THEN dbms_output.put_line('Addition of the numbers are:' || a+b );
WHEN 'SUBTRACT' THEN dbms_output.put_line('Subtraction of the numbers are: ' || a-b );
WHEN 'MULTIPLY' THEN dbms_output.put_line('Multiplication of the numbers are: ' || a*b
);
WHEN 'DIVIDE' THEN dbms_output.put_line('Division of the numbers are:' || a/b);
ELSE dbms_output.put_line('No operation action defined. Invalid operation');
END CASE;
dbms_output.put_line('Program completed.' );
END;
/
```

# PL/SQL

## Functions in PL/SQL

### "IN" PARAMETER

- ❖ This is similar to passing parameters in programming languages.
- ❖ We can pass values to the stored procedure and function through these parameters or variables.
- ❖ This type of parameter is a read only parameter.

### Points to Ponder:-

**We can assign the value of IN type parameter to a variable or use it in a query, but we cannot change its value inside the procedure.**

# PL/SQL

## Functions in PL/SQL

### "IN" PARAMETER SYNTAX

```
CREATE [OR REPLACE] FUNCTION function_name  
(param_name1 IN data_type, param_name2 IN  
  data_type.. )
```

**Here:-**

- (i) param\_name1, param\_name2... are unique parameter names.**
- (ii) data\_type - defines the DataType of the variable.**
- (iii) IN - is optional, by default it is a IN type parameter.**

# PL/SQL

## Functions in PL/SQL

### “OUT” PARAMETER

- ❖ The OUT parameters are used to send the OUTPUT from a procedure or a function.
- ❖ This is a write-only parameter i.e. we cannot pass values to OUT parameter while executing the stored procedure, but we can assign values to OUT parameter inside the stored procedure and the calling program can receive this output value.



# PL/SQL

## Functions in PL/SQL

### "OUT" PARAMETER SYNTAX

**CREATE [OR REPLACE] PROCEDURE  
procedure\_name**

**(param\_name1 IN data\_type, param\_name2 IN  
data\_type , param\_name3 OUT data\_type)**

**Here:-**

- (i) param\_name1, param\_name2 are unique parameter Names and can not be modified with in procedure.**
- (ii) param\_name3 can be modified with in procedure.**
- (iii) data\_type - defines the DataType of the variable.**

# PL/SQL

## Functions in PL/SQL

### EXAMPLE ON "IN" AND "OUT"

```
CREATE OR REPLACE PROCEDURE procname_outparam (inparam1 in VARCHAR2,outParam2  
OUT VARCHAR2)
```

```
IS
```

```
BEGIN
```

```
outParam2 := 'Hello World OUT parameter I am changeable parameter' || inparam1;
```

```
END;
```

```
/
```

**Run it:-**

```
DECLARE
```

```
outParam2 VARCHAR2(100);
```

```
inparam1 VARCHAR2(100);
```

```
BEGIN
```

```
Procname_outparam ('i am IN parameter',outParam2);
```

```
DBMS_OUTPUT.PUT_LINE(outParam2);
```

```
END;
```

```
/
```

# PL/SQL

## Functions in PL/SQL

### “INOUT” PARAMETER

- ❖ The IN OUT parameter allows us to pass values into a procedure and get output values from the procedure.
- ❖ This parameter is used if the value of the IN parameter can be changed in the calling program.
- ❖ By using IN OUT parameter we can pass values into a parameter and return a value to the calling program using the same parameter. But this is possible only if the value passed to the procedure and output value have a same data type.

# PL/SQL

## Functions in PL/SQL

### "IN OUT" PARAMETER SYNTAX

```
CREATE [OR REPLACE] PROCEDURE  
  procedure_name  
  (param_name IN OUT data_type)
```

**Here:-**

- (i) param\_name are unique parameter Names and can not be modified with in procedure.**
- (ii) param\_name3 can be modified with in procedure.**
- (iii) data\_type - defines the DataType of the variable.**

# PL/SQL

## Functions in PL/SQL

### DEFINITION OF FUNCTION

**Functions is a standalone PL/SQL subprogram. Like PL/SQL procedure, functions have a unique name by which it can be referred. These are stored as PL/SQL database objects. Below are some of the characteristics of functions.**

- ❖ **Functions are a standalone block that is mainly used for calculation purpose.**
- ❖ **Function use RETURN keyword to return the value, and the data type of this is defined at the time of creation.**

# PL/SQL

## Functions in PL/SQL

### What is Function

- ❖ **A Function should either return a value or raise the exception, i.e. return is mandatory in functions.**

### **Points to Ponder:-**

- \* Function with no DML statements can be directly called in SELECT query whereas the function with DML operation can only be called from other PL/SQL blocks.**
- \* Function can also return the value through OUT parameters other than using RETURN.**

# PL/SQL

## Functions in PL/SQL

### SYNTAX OF FUNCTION

#### CREATE OR REPLACE FUNCTION

```
<function_name>  
(  
  < variable_name parameter IN/OUT <datatype>  
)  
RETURN <datatype>  
[ IS | AS ]  
<declaration_part>  
BEGIN  
  <execution part>  
RETURN (value/var);  
END<function_name>;
```

# PL/SQL

## Functions in PL/SQL

### EXAMPLE ON FUNCTION

```
create or replace function f_mul( x in int,y in int)
return int
as
z int;
begin
z:= x*y;
return(z);
End f_mul;
/
```

#### Points to Ponder:-

- \* calling function from select query

```
select f_mul(12,10) from dual;
```
- \* calling a function from a program

```
Declare
a int;b int;c int;
Begin
a:= &a;b:=&b;
c:=f_mul(a,b);
dbms_output.put_line('Result:' || c);End;/
```



# PL/SQL

## Functions in PL/SQL

### EXAMPLE ON FUNCTION

#### Points to Ponder:-

##### \* calling a function from procedure

```
(I) create or replace procedure proc_mul(x int,y int,z out int)
as
begin
z:=f_mul(x,y);
End;
/

(II) Declare
    a int;
    b int;
    c int;
Begin
    a:=&a;
    b:=&b;
    proc_mul(a,b,c);
    dbms_output.put_line('value of a:' ||a || 'value of b:' ||b);
    dbms_output.put_line('Multiplication of aXb is :-' || c);
End;
/
```

# PL/SQL

## Procedure in PL/SQL

### DEFINITION OF PROCEDURE

**A Procedure is a subprogram unit that consists of a group of PL/SQL statements. Each procedure in Oracle has its own unique name by which it can be referred. This subprogram unit is stored as a database object. Below are the characteristics of this subprogram unit.**

- ❖ **Procedures are standalone blocks of a program that can be stored in the database.**
- ❖ **Call to these procedures can be made by referring to their name, to execute the PL/SQL statements.**

# PL/SQL

## Procedure in PL/SQL

### DEFINITION OF PROCEDURE

- ❖ It is mainly used to execute a process in PL/SQL.
- ❖ It can have nested blocks, or it can be defined and nested inside the other blocks or packages.
- ❖ The values can be passed into the procedure or fetched from the procedure through parameters.
- ❖ Procedure can have a RETURN statement to return the control to the calling block, but it cannot return any values through the RETURN statement.
- ❖ Procedures cannot be called directly from SELECT statements. They can be called from another block or through EXEC keyword.

# PL/SQL

## Procedure in PL/SQL

### SYNTAX OF PROCEDURE

```
CREATE [OR REPLACE ] PROCEDURE <name>[(argvarDatatype,  
    argvarDatatype)]
```

```
IS/AS
```

```
<declaration>
```

```
BEGIN
```

```
Statement1
```

```
Statement2
```

```
-----
```

```
-----
```

```
EXCEPTION
```

```
Statement1
```

```
Statement2
```

```
-----
```

```
-----
```

```
END;/Note:-[] i.e OPTIONAL
```

# PL/SQL

## Procedure in PL/SQL

### EXAMPLE ON PROCEDURE

```
CREATE OR REPLACE PROCEDURE proc_empcntno(vdesg emp.job%type)
AS
    empcntno int;
BEGIN
    select count(*) into empcntno from emp
    where job=vdesg;
    dbms_output.put_line('Entered Designation is:' || vdesg);
    dbms_output.put_line('NO. of Employees:' || empcntno);
END ;
/
```

# PL/SQL

## Procedure in PL/SQL

### IMPORTANT POINT ABOUT PROCEDURE

- \* **Executing Multiple Queries .**
- \* **Reduces no. of hits to DB.**
- \* **Improve DB performance and N/W performance.**
- \* **Enhanceability.**
- \* **Reusability.**
- \* **Modularity.**

# PL/SQL

## Exception in PL/SQL

- 1) Exception**
- 2)Exception Handling**
- 3) Structure of Exception Handling.**
- 4) Types of Exception Handling.**

# PL/SQL

## Exception in PL/SQL

### WHAT IS EXCEPTION

**An error occurs during the program execution is called Exception in PL/SQL. PL/SQL facilitates programmers to catch such conditions using exception block in the program and an appropriate action is taken against the error condition.**



# PL/SQL

## Exception in PL/SQL

### EXCEPTION HANDLING

**PL/SQL provides a feature to handle the Exceptions which occur in a PL/SQL Block known as exception Handling. Using Exception Handling we can test the code and avoid it from exiting abruptly.**

**When an exception occurs a messages which explains its cause is received.**

**PL/SQL Exception message consists of three parts.**

- 1) Type of Exception(Exception Handler)**
- 2) An Error Code**
- 3) A message**

# PL/SQL

## Exception in PL/SQL

### STRUCTURE OF HANDLING EXCEPTION

**DECLARE**

Declaration section

**BEGIN**

Exception section

**EXCEPTION**

**WHEN ex\_name1 THEN**

-Error handling statements

**WHEN ex\_name2 THEN**

-Error handling statements

**WHEN Others THEN**

-Error handling statements

**END**

# PL/SQL

## Exception in PL/SQL

### TYPES OF EXCEPTION

**There are 3 types of Exceptions.**

- a) Named System Exceptions**
- b) Unnamed System Exceptions**
- c) User-defined Exceptions**

# PL/SQL

## Exception in PL/SQL

### NAMED SYSTEM EXCEPTIONS

**System exceptions are automatically raised by Oracle, *when a program violates a RDBMS rule*. There are some system exceptions which are raised frequently, so they are pre-defined and given a name in Oracle which are known as Named System Exceptions.**

# PL/SQL

## Exception in PL/SQL

### NAMED SYSTEM EXCEPTIONS

**For example: NO\_DATA\_FOUND and ZERO\_DIVIDE are called Named System exceptions.**

**Named system exceptions are:**

- 1) Not Declared explicitly,**
- 2) Raised implicitly when a predefined Oracle error occurs,**
- 3) caught by referencing the standard name within an exception-handling routine.**

# PL/SQL

## Exception in PL/SQL

### NAMED SYSTEM EXCEPTIONS

Exception Name	Reason(Message)	Error Number
<b>CURSOR_ALREADY_OPEN</b>	When you open a cursor that is already open.	<b>ORA-06511</b>

# PL/SQL

## Exception in PL/SQL

### NAMED SYSTEM EXCEPTIONS

Exception Name	Reason(Message)	Error Number
INVALID_CURSOR	When you perform an invalid operation on a cursor like closing a cursor, fetch data from a cursor that is not opened.	ORA-01001
NO_DATA_FOUND	When a SELECT...INTO clause does not return any row from a table.	ORA-01403

# PL/SQL

## Exception in PL/SQL

### NAMED SYSTEM EXCEPTIONS

Exception Name	Reason(Message)	Error Number
TOO_MANY_ROWS	When you SELECT or fetch more than one row into a record or variable.	ORA-01422
ZERO_DIVIDE	When you attempt to divide a number by zero.	ORA-01476.



# PL/SQL

## Exception in PL/SQL

### PROGRAM ON NAMED SYSTEM EXCEPTION

**Create or Replace Procedure proc\_excep(vdesg emp.job%type)**

**is**

**vename varchar2(20);**

**Begin**

**select ename into vename from emp**

**where job =vdesg;**

**dbms\_output.put\_line('Name:-' || vename);**

**Exception**

**when NO\_DATA\_FOUND then**

**dbms\_output.put\_line('No Employee existed with given job');**

**when TOO\_MANY\_ROWS then**

**dbms\_output.put\_line('Multiple employees existed ,use explicit cursor');**

**End proc\_excep;**

**/**

# PL/SQL

## Exception in PL/SQL

### USER DEFINED EXCEPTIONS

Apart from system exceptions we can explicitly define exceptions based on **business rules**. These are known as user-defined exceptions.

Steps to be followed to use user-defined exceptions:

- They should be explicitly declared in the declaration section.
- They should be explicitly raised in the Execution Section.
- They should be handled by referencing the user-defined exception name in the exception section.

# PL/SQL

## Exception in PL/SQL

### SYNTAX OF USER DEFINED EXCEPTION

```
Declare  
var_name Exception  
Begin  
Statement1  
Statement2  
Raise <var_name>;  
Exception  
  When <var_name> then  
    Statement1  
    Statement2  
End;  
/
```

# PL/SQL

## Exception in PL/SQL

### EXAMPLE ON USER DEFINED EXCEPTION

Create or Replace Procedure proc\_comm (veid int)

```
is
vcomm int;
c_miss Exception;
Begin
    select comm into vcomm from emp where empno=veid;
    if vcomm IS NOT NULL then
        dbms_output.put_line('Comm of' || veid || 'is' || vcomm);
    else
        RAISE c_miss;
    end if;
Exception
when NO_DATA_FOUND then
    dbms_output.put_line('EmpId Not Existed');
when TOO_MANY_ROWS then
    dbms_output.put_line('Duplicate EmpId');
when c_miss then
    dbms_output.put_line('Comm is Not Existed');
End proc_comm;
```

/

# PL/SQL

## Exception in PL/SQL

### UNNAMED EXCEPTIONS

- ❖ It is also known as **PRAGMA EXCEPTION\_INIT.**
- ❖ It is the way to associate user defined exception with oracle predefined error.
- ❖ If the oracle predefined error is not having name then we can assign name to that error using **PRAGMA EXCEPTION\_INIT.**

# PL/SQL

## Exception in PL/SQL

### SYNTAX OF UNNAMED EXCEPTION

#### DECLARE

```
    user_define_exception_name EXCEPTION;  
    PRAGMA EXCEPTION_INIT(user_define_exception_name,-  
error_number);  
BEGIN  
    statement(s);  
    IF condition THEN  
        RAISE user_define_exception_name;  
    END IF;  
EXCEPTION  
    WHEN user_define_exception_name THEN  
        User defined statement (action) will be taken;  
END;  
/
```

#### Points to Ponder:-

- \* **exception\_name** and **error\_number** define on yourself, where **exception\_name** is character string up to **2048 bytes** support and **error\_number** is a negative integer range from **-20000** to **-20999**.

# PL/SQL

## Exception in PL/SQL

### PROGRAM ON UNNAMED EXCEPTION

**DECLARE**

```
myex EXCEPTION;  
PRAGMA EXCEPTION_INIT(myex,-20015);  
n NUMBER := &n;
```

**BEGIN**

```
FOR i IN 1..n LOOP  
  dbms_output.put_line(i);  
  IF i=n THEN  
    RAISE myex;  
  END IF;  
END LOOP;
```

**EXCEPTION**

```
  WHEN myex THEN  
    dbms_output.put_line('loop finish');
```

**END;**

**/**

# PL/SQL

## Cursor in PL/SQL

### DEFINITION OF CURSOR

- ❖ **A cursor is a temporary work area created in the system memory when a SQL statement is executed. A cursor contains information on a select statement and the rows of data accessed by it.**
- ❖ **This temporary work area is used to store the data retrieved from the database, and manipulate this data. A cursor can hold more than one row, but can process only one row at a time. The set of rows the cursor holds is called the active set.**



# PL/SQL

## Cursor in PL/SQL

### TYPES OF CURSOR

**There are two types of cursors in PL/SQL:**

- ❖ **Implicit cursors**
- ❖ **Explicit cursors**

# PL/SQL

## Cursor in PL/SQL

### IMPLICIT CURSOR

- ❖ **Managed by Oracle Engine**
- ❖ **Allocation and deallocation is done by Oracle Engine.**
- ❖ **Used by DML,DQL.**

# PL/SQL

## Cursor in PL/SQL

### PROPERTIES OF IMPLICIT CURSOR

- ❖ **SQL%ISOPEN**
- ❖ **SQL%FOUND**
- ❖ **SQL%NOTFOUND**
- ❖ **SQL%ROWCOUNT**

# PL/SQL

## Cursor in PL/SQL

### PROGRAM ON IMPLICIT CURSOR

```
Create or Replace procedure proc_sal_update(vjob in emp.job%type,incr in int)
is
Begin
    update empcp
    set sal=sal+((sal*incr)/100)
    where job=vjob;
    if (sql%found) then
        dbms_output.put_line('Updation is Successful');
        dbms_output.put_line('Number of '||vjob||'s updated:'
        ||SQL%ROWCOUNT);
    else
        dbms_output.put_line('Updation Failed');
        dbms_output.put_line('Number of '||vjob||'s updated:'
        ||SQL%ROWCOUNT);
    end if;
End proc_sal_update;
/
```

# PL/SQL

## Cursor in PL/SQL

### EXPLICIT CURSOR

- ❖ **Managed by User**
- ❖ **Allocation and deallocation is done by User.**
- ❖ **To display multiple records using subprogram/procedure.**

**Its has four steps to define it;-**

**I)Declare Cursor**

**II)Open Cursor**

**III)Fetch data from cursor**

**IV)Close Cursor**

# PL/SQL

## Cursor in PL/SQL

### SYNTAX OF EXPLICIT CURSOR

#### I) Declare Cursor

```
CURSOR <cursor_name> IS select  
column_name..... from <table_name>  
where condition;
```

#### II) Open Cursor

```
OPEN <cursor_name>;
```

#### III) fetch data from Cursor

```
FETCH <cursor_name> INTO <var>
```

#### IV) Close Cursor

```
CLOSE <cursor_name>;
```

# PL/SQL

## Cursor in PL/SQL

### PROPERTIES OF EXPLICIT CURSOR

- ❖ **<cursor\_name>%ISOPEN**
- ❖ **<cursor\_name>%FOUND**
- ❖ **<cursor\_name>%NOTFOUND**
- ❖ **<cursor\_name>%ROWCOUNT**

# PL/SQL

## Cursor in PL/SQL

### PROGRAM ON EXPLICIT CURSOR

**DECLARE**

**CURSOR my\_cursor IS SELECT sal + NVL(comm, 0) wages, ename**

**FROM emp;**

**my\_rec my\_cursor%ROWTYPE;**

**BEGIN**

**OPEN my\_cursor;**

**LOOP**

**FETCH my\_cursor INTO my\_rec;**

**EXIT WHEN my\_cursor%NOTFOUND;**

**IF my\_rec.wages > 2000 THEN**

**dbms\_output.put\_line(my\_rec.wages||' '||my\_rec.ename);**

**END IF;**

**END LOOP;**

**CLOSE my\_cursor;**

**END;**

**/**



# PL/SQL

## Trigger in PL/SQL

### DEFINITION

**Triggers are stored programs, which are automatically executed or fired when some events occur. Triggers are, in fact, written to be executed in response to any of the following events –**

- \*A database manipulation (DML) statement (DELETE, INSERT, or UPDATE)**
- \*A database definition (DDL) statement (CREATE, ALTER, or DROP).**
- \*A database operation (SERVERERROR, LOGON, LOGOFF, STARTUP, or SHUTDOWN).**

# PL/SQL

## Trigger in PL/SQL

### SYNTAX OF TRIGGER

```
CREATE [OR REPLACE ] TRIGGER trigger_name
{BEFORE | AFTER | }
{INSERT [OR] | UPDATE [OR] | DELETE}
[OF col_name]
ON table_name
[REFERENCING OLD AS o NEW AS n]
[FOR EACH ROW]
WHEN (condition)
DECLARE
    Declaration-statements
BEGIN
    Executable-statements
EXCEPTION
    Exception-handling-statements
END
```

# PL/SQL

## Trigger in PL/SQL

### PROGRAM ON DML CURSOR

```
CREATE OR REPLACE TRIGGER display_salary_changes1
BEFORE DELETE OR INSERT OR UPDATE ON empcp1
FOR EACH ROW
WHEN (old.deptno > 0)
DECLARE
    sal_diff number;
BEGIN
    sal_diff := :NEW.sal - :OLD.sal;
    dbms_output.put_line('Old salary: ' || :OLD.sal);
    dbms_output.put_line('New salary: ' || :NEW.sal);
    dbms_output.put_line('Salary difference: ' || sal_diff);
END;
/
```

# Thank you!

