CHAPTER 6

IMPLEMENTATION

Statistical Properties of Colour Channels

```
from PIL import Image

importnumpy as np

importscipy

fromscipy import stats

import cv2

importskimage

fromskimage.measure import shannon_entropy

importmatplotlib.pyplot as plt

import pandas as pd

classsmp_values():

defmean_properties(image):

    #image=cv2.imread(r"C:\Users\Pavan\Desktop\Project\image_1.jpg")

b,g,r=cv2.split(image)

rgb_img=cv2.merge([r,g,b])

    #plt.imshow(rgb_img)

    #plt.imshow(image)

red=image[:,:,2]

    Mean=list()

    Range=list()
```

```
    Deviation=list()
    Entropy=list()
Skewness=list()
    Kurtosis=list()
    r1=r.mean()
Mean.append(r1)
    r2=skimage.measure.shannon_entropy(r,base=10)
Entropy.append(r2)
    r3=r.std()
Deviation.append(r3)
    r4=np.ptp(r)
Range.append(r4)
    t=scipy.stats.skew(r)
    #print(b)
    r5=t.mean()
Skewness.append(r5)
    c=scipy.stats.kurtosis(r,axis=0,fisher=False)
    #print(c)
    r6=c.mean()
Kurtosis.append(r6)
    g1=g.mean()
Mean.append(g1)
    g2=skimage.measure.shannon_entropy(g,base=10)
```

```
Entropy.append(g2)
        g3=g.std()
Deviation.append(g3)
        g4=np.ptp(g)
Range.append(g4)
        e=scipy.stats.skew(g)
        #print(b)
        g5=e.mean()
Skewness.append(g5)
        f=scipy.stats.kurtosis(g,axis=0,fisher=False)
        #print(c)
        g6=f.mean()
Kurtosis.append(g6)
        b1=b.mean()
Mean.append(b1)
        b2=skimage.measure.shannon_entropy(b,base=10)
Entropy.append(b2)
        b3=b.std()
Deviation.append(b3)
        b4=np.ptp(b)
Range.append(b4)
        h=scipy.stats.skew(b)
        #print(b)
```

```
        b5=h.mean()
Skewness.append(b5)
        i=scipy.stats.kurtosis(b,axis=0,fisher=False)
        #print(c)
        b6=i.mean()
Kurtosis.append(b6)
        #print(Mean)
        #print(Entropy)
        #print(Deviation)
        #print(Range)
        #print(Skewness)
        #print(Kurtosis)
        #df1= pd.DataFrame(Mean, columns = ['Mean_R', 'Mean_G','Mean_B'])
        df1= pd.DataFrame([Mean])
        df1.columns =['Mean_R', 'Mean_G','Mean_B']
        df2= pd.DataFrame([Deviation])
        df2.columns =['Standard_deviation_R', 'Standard_deviation_G','Standard_deviation_B']
        df3= pd.DataFrame([Skewness])
        df3.columns =['Skewness_R', 'Skewness_G','Skewness_B']
        df4= pd.DataFrame([Kurtosis])
        df4.columns =['Kurtosis_R', 'Kurtosis_G','Kurtosis_B']
        df5= pd.DataFrame([Entropy])
        df5.columns =['Entropy_R', 'Entropy_G','Entropy_B']
```

```
    df6= pd.DataFrame([Range])
    df6.columns =['Range_R', 'Range_G','Range_B']
frames = [df1, df2, df3, df4, df5, df6]
result = pd.concat(frames, axis=1, sort=False)
return(result)
```

Gray Level Co-Occurrence Matrix (GLCM)

```
importnumpy as np
import cv2
importskimage
fromskimage.feature import greycomatrix, greycoprops
import pandas as pd
classglcm_prop():
defglclm_properties(image):
    #image=cv2.imread(r"C:\Users\Pavan\Desktop\Project\image_1.jpg")
result=cv2.cvtColor(image, cv2.COLOR_BGR2GRAY)
    #print(image)
    #print(result)
    #print(result.max())
angles = [0, np.pi/4, np.pi/2, 3*np.pi/4]
entropy=[]
ASM_val=[]
    Contrast=[]
```

```
Corrleation=[]
new_angle=0
for i in range(4):
new_angle=angles[i]
g_e= greycomatrix(result, [1],[new_angle], 256, symmetric=False, normed=True)
entr = skimage.measure.shannon_entropy(g_e)
correlation = greycoprops(g_e, 'correlation')
        ASM = greycoprops(g_e, 'ASM')
contrast = greycoprops(g_e, 'contrast')
entropy.append(entr)
ASM_val.append(ASM[0][0])
Contrast.append(contrast[0][0])
Corrleation.append(correlation[0][0])
    #asm,contrast,corrleation,entropy
    dummy0=[]
dummy0.append(ASM_val[0])
dummy0.append(Contrast[0])
dummy0.append(Corrleation[0])
dummy0.append(entropy[0])
    dummy45=[]
dummy45.append(ASM_val[1])
dummy45.append(Contrast[1])
dummy45.append(Corrleation[1])
```

```
dummy45.append(entropy[1])
        dummy90=[]
dummy90.append(ASM_val[2])
dummy90.append(Contrast[2])
dummy90.append(Corrleation[2])
dummy90.append(entropy[2])
        dummy135=[]
dummy135.append(ASM_val[3])
dummy135.append(Contrast[3])
dummy135.append(Corrleation[3])
dummy135.append(entropy[3])
        df1= pd.DataFrame([dummy0])
        df1.columns =['ASM_0', 'Contrast_0','Corrleation_0','entropy_0']
        df2= pd.DataFrame([dummy45])
        df2.columns =['ASM_45', 'Contrast_45','Corrleation_45','entropy_45']
        df3= pd.DataFrame([dummy90])
        df3.columns =['ASM_90', 'Contrast_90','Corrleation_90','entropy_90']
        df4= pd.DataFrame([dummy135])
        df4.columns =['ASM_135', 'Contrast_135','Corrleation_135','entropy_135']
frames = [df1, df2, df3, df4]
result_glcm = pd.concat(frames, axis=1, sort=False)
return(result_glcm)
```

Gray Level Run Lengths (GLRL)

```
importSimpleITK as sitk
importnumpy as np
import cv2
fromskimage.color import rgb2gray
fromskimage.feature import greycomatrix, greycoprops
import pandas as pd

classglrlm_prop():
defglrlm_properties(image):
    #image=cv2.imread(r"C:\Users\Pavan\Desktop\Project\image_1.jpg")

grayscale = rgb2gray(image)

grayscale = np.array(grayscale)
im = sitk.GetImageFromArray(grayscale)
test_arr = np.ones((grayscale.shape), dtype='uint8')
ma = sitk.GetImageFromArray(test_arr)

    # Store to nrrd:
sitk.WriteImage(im, 'image.nrrd')
sitk.WriteImage(ma, 'mask.nrrd', True)  # enable compression to save disk space

    # or extract features:
fromradiomics import featureextractor
extractor = featureextractor.RadiomicsFeatureExtractor(r'path/to/params.yml')
features = extractor.execute(im, im, label=1)

glrlm=[]

glrlm.append(float(features['original_glrlm_ShortRunEmphasis']))
glrlm.append(float(features['original_glrlm_LongRunEmphasis']))
```

```
glrlm.append(float(features['original_glrlm_GrayLevelNonUniformity']))
glrlm.append(float(features['original_glrlm_RunLengthNonUniformity']))
glrlm.append(float(features['original_glrlm_RunPercentage']))
glrlm.append(float(features['original_glrlm_LowGrayLevelRunEmphasis']))
glrlm.append(float(features['original_glrlm_HighGrayLevelRunEmphasis']))
glrlm.append(float(features['original_glrlm_ShortRunLowGrayLevelEmphasis']))
glrlm.append(float(features['original_glrlm_ShortRunHighGrayLevelEmphasis']))
glrlm.append(float(features['original_glrlm_LongRunLowGrayLevelEmphasis']))
glrlm.append(float(features['original_glrlm_LongRunHighGrayLevelEmphasis']))

    df1= pd.DataFrame([glrlm])
    df1.columns =['Short_run_emphasis_0',
'Long_run_emphasis_0','Gray_level_nonuniformity_0'
,'Run_length_nonuniformity_0','Run_percentage_0','Low_gray_level_run_emphasis_0','High
_gray_level_run_emphasis_0','Short_run_Low_gray_level_emphasis_0','Short_run_High_gra
y_level_emphasis_0','Long_run_Low_gray_level_emphasis_0','Long_run_High_gray_level_
emphasis_0']

    df2= pd.DataFrame([glrlm])
    df2.columns =['Short_run_emphasis_45',
'Long_run_emphasis_45','Gray_level_nonuniformity_45'
,'Run_length_nonuniformity_45','Run_percentage_45','Low_gray_level_run_emphasis_45','H
igh_gray_level_run_emphasis_45','Short_run_Low_gray_level_emphasis_45','Short_run_Hig
h_gray_level_emphasis_45','Long_run_Low_gray_level_emphasis_45','Long_run_High_gray
_level_emphasis_45']

    df3= pd.DataFrame([glrlm])
    df3.columns =['Short_run_emphasis_90',
'Long_run_emphasis_90','Gray_level_nonuniformity_90'
,'Run_length_nonuniformity_90','Run_percentage_90','Low_gray_level_run_emphasis_90','H
igh_gray_level_run_emphasis_90','Short_run_Low_gray_level_emphasis_90','Short_run_Hig
h_gray_level_emphasis_90','Long_run_Low_gray_level_emphasis_90','Long_run_High_gray
_level_emphasis_90']
```

```
    df4= pd.DataFrame([glrlm])
    df4.columns =['Short_run_emphasis_135',
'Long_run_emphasis_135','Gray_level_nonuniformity_135'
,'Run_length_nonuniformity_135','Run_percentage_135','Low_gray_level_run_emphasis_13
5','High_gray_level_run_emphasis_135','Short_run_Low_gray_level_emphasis_135','Short_r
un_High_gray_level_emphasis_135','Long_run_Low_gray_level_emphasis_135','Long_run_
High_gray_level_emphasis_135']

frames = [df1, df2, df3, df4]
result_glrlm = pd.concat(frames, axis=1, sort=False)

return(result_glrlm)
```

Support Vector Machine (SVM)

```
import pickle

header_list =['Mean_R', 'Mean_G','Mean_B','Standard_deviation_R',
'Standard_deviation_G','Standard_deviation_B','Skewness_R',
'Skewness_G','Skewness_B','Kurtosis_R', 'Kurtosis_G','Kurtosis_B','Entropy_R',
'Entropy_G','Entropy_B','Range_R', 'Range_G','Range_B','ASM_0',
'Contrast_0','Corrleation_0','entropy_0','ASM_45',
'Contrast_45','Corrleation_45','entropy_45','ASM_90',
'Contrast_90','Corrleation_90','entropy_90','ASM_135',
'Contrast_135','Corrleation_135','entropy_135','Short_run_emphasis_0',
'Long_run_emphasis_0','Gray_level_nonuniformity_0'
,'Run_length_nonuniformity_0','Run_percentage_0','Low_gray_level_run_emphasis_0','High
_gray_level_run_emphasis_0','Short_run_Low_gray_level_emphasis_0','Short_run_High_gra
y_level_emphasis_0','Long_run_Low_gray_level_emphasis_0','Long_run_High_gray_level_
emphasis_0','Short_run_emphasis_45',
'Long_run_emphasis_45','Gray_level_nonuniformity_45'
,'Run_length_nonuniformity_45','Run_percentage_45','Low_gray_level_run_emphasis_45','H
igh_gray_level_run_emphasis_45','Short_run_Low_gray_level_emphasis_45','Short_run_Hig
h_gray_level_emphasis_45','Long_run_Low_gray_level_emphasis_45','Long_run_High_gray
```

```
_level_emphasis_45','Short_run_emphasis_90',
'Long_run_emphasis_90','Gray_level_nonuniformity_90'
,'Run_length_nonuniformity_90','Run_percentage_90','Low_gray_level_run_emphasis_90','H
igh_gray_level_run_emphasis_90','Short_run_Low_gray_level_emphasis_90','Short_run_Hig
h_gray_level_emphasis_90','Long_run_Low_gray_level_emphasis_90','Long_run_High_gray
_level_emphasis_90','Short_run_emphasis_135',
'Long_run_emphasis_135','Gray_level_nonuniformity_135'
,'Run_length_nonuniformity_135','Run_percentage_135','Low_gray_level_run_emphasis_13
5','High_gray_level_run_emphasis_135','Short_run_Low_gray_level_emphasis_135','Short_r
un_High_gray_level_emphasis_135','Long_run_Low_gray_level_emphasis_135','Long_run_
High_gray_level_emphasis_135','Result']

import pandas as pd
fromsklearn.model_selection import train_test_split
df = pd.read_csv("dataset.csv", names=header_list)

X_train_1=df.iloc[:,:-1]
Y_train_1=df.iloc[:,-1]
X_train, X_test, y_train, y_test = train_test_split(X_train_1,Y_train_1, test_size=0.2)
fromsklearn import svm
classifier = svm.SVC(kernel='linear')
classifier.fit(X_train, y_train)

#predicting Y values for test data
Y_pred = classifier.predict(X_test)

#confusion matrix for tested datatsets
fromsklearn.metrics import confusion_matrix
cm = confusion_matrix(y_test, Y_pred)

#Store the trainined SVM Model for future use
pickle.dump(classifier,open(r'C:\Users\Pavan\Desktop\Project\corrosion_detection\predictor\
model\model.pkl', 'wb'))
```