

exp - 5 - Proteus 8 Professional - Source Code

File Project Build Edit Debug System Help



Schematic Capture Source Code X Save Project

Projects
80C310
Source Files
main.asm

```
main.asm
1 int x0, x1, x2, x3, x4, x5, x6, x7, x8, x9;
2 int delay_time = 200;
3
4 void setup() {
5     // configure pin 12 as an input and enable the internal pull-up resistor
6     pinMode(12, INPUT_PULLUP);
7     pinMode(1, OUTPUT);
8     pinMode(2, OUTPUT);
9     pinMode(3, OUTPUT);
10    pinMode(4, OUTPUT);
11    pinMode(5, OUTPUT);
12    pinMode(6, OUTPUT);
13    pinMode(7, OUTPUT);
14 }
15
16 void loop() {
17     // read the pushbutton value into a variable
18     int sensorVal = digitalRead(12);
19
20     if (sensorVal == LOW) {
21         x0 = true;
22         while (digitalRead(12) == LOW); // Wait for button release
23     }
24
25     while (x0) {
26         zero();
27         sensorVal = digitalRead(12);
28         if (sensorVal == LOW) {
29             x1 = true;
30             x0 = false;
31             while (digitalRead(12) == LOW); // Wait for button release
32         }
33     }
34
35     while (x1) {
36         one();
37         sensorVal = digitalRead(12);
38         if (sensorVal == LOW) {
39             x2 = true;
40             x1 = false;
41             while (digitalRead(12) == LOW); // Wait for button release
42         }
43     }
44 }
```

