AI for Legal Case Outcome Prediction

Mrs. Priyanka Patil[1]
Assistant Professor
Nutan Maharashtra Institute of Engineering and Technology
Pune, India
priyanka.patil@nmist.edu.in

Dr. Prashant Ahire[2]
Head of Department
Nutan Maharashtra Institute of Engineering and Technology
Pune, India
prashant.ahire@nmist.edu.in

Nikhil Raghuwanshi[3]
Student
Nutan College of Engineering and Research, Talegaon
Pune, India
nraghuvanshi100@gmail.com

Shraddha Dhanwate[4]
Student
Nutan College of Engineering and Research, Talegaon
Pune, India
dhanwateshraddha5@gmail.com

Shital Kalekar[5]
Student
Nutan College of Engineering and Research, Talegaon
Pune, India
shitalkalekar05@gmail.com

Amay Lohar[6]
Student
Nutan College of Engineering and Research, Talegaon
Pune, India
amaylohar2205@gmail.com

***Abstract*—The Indian legal system handles a huge amount of cases every year, and most of the information related to these cases exists in lengthy. Because of this, managing cases and predicting their outcomes is often slow and difficult. This paper introduces how Artificial Intelligence (AI) and Machine Learning (ML) can help in making decisions and predict in different areas, especially in law. Many of the papers focus on using AI to predict the outcome of court cases, such as someone will be convicted. Some peoples build special systems that look at past similar cases and also consider how laws change over time. Others compare different machine learning methods to see which one predicts court decisions more accurately. Some people made looks at how well AI can explain its decisions, because in legal system people need to understand why prediction we made. A few studies also examine how AI and humans can work together to make better decisions. Beyond law, some papers explore how AI is used in crime prediction, education systems, cybersecurity, and protecting intellectual property. Someone even evaluates how well ChatGPT performs on an MBA exam. The complete system shows that AI is becoming very important in areas where decisions have serious consequences. However, they also show that this approach can effectively predict case outcomes while also providing clear explanations, making it suitable for practical use in the Indian legal domain.**

***Index Terms*—Legal Case Outcome Prediction, Legal Reasoning, Indian Legal System, Legal Document Analysis, Court Judgment Analysis, Text Classification, Explainable Artificial Intelligence, Criminal - Judicial Data Analysis, Legal Decision Support System**

I. Introduction

In the domain of legal analytics, predicting the outcome of a court case is a highly critical task aimed at anticipating judicial decisions based on historical precedent and statutory law [1], [4]. Researchers generally categorize predictive strategies into three primary approaches: the socio-political approach, which examines extra-judicial factors such as a judge's background and ideological leanings [5], [9]; the linguistic approach, which identifies patterns in word frequency, sentiment, and document structure within legal texts [11], [14]; and the legal-centric approach, which focuses specifically on case-specific facts and the statutory laws or sections involved [15], [16].

There are distinct methodological differences required depending on the overarching legal system. In civil law systems, which prioritize written codes and statutes, predictive models compare case facts directly against rigid written rules. Conversely, in case law systems (common law), outcomes depend heavily on judicial precedent [1]. Modeling the latter presents unique computational challenges, specifically regarding the retrieval of contextually similar historical cases and the accommodation of "temporal shifts," where legal interpretations and societal norms evolve over time [1].

To address these complexities, advanced computational models, such as PILOT, have been developed to prioritize recent legal patterns through temporal decay mechanisms [1]. Furthermore, current research heavily emphasizes the absolute necessity of explainability. Legal regulations and data ethics policies, such as the GDPR, require transparent reasoning rather than opaque "black box" verdicts [12], [15]. This imperative has driven a transition from simple binary classification toward "adversarial" modeling, which simultaneously evaluates the plaintiff's claims and the respondent's defenses. This dual-evaluation corrects the historical bias in models that were trained predominantly on guilty verdicts, resulting in systems that are better equipped to predict and explain case rejections or negative outcomes [12], [13].

The PILOT model introduces a two-pronged strategy to master the case law environment: a Case Retrieval module and a Temporal Pattern Mining module [1]. The retrieval module uses unsupervised learning to generate deep text embeddings, allowing the system to query a database and extract precedents that share factual context and legal principles with the current case. Rather than treating all precedents equally, the model gives greater weight to recent cases. This is managed via a temporal decay function, ensuring the model adapts to shifting legal logic and recognizing that what constituted a specific

violation in 1980 may be judged differently today due to evolving social values [1], [3].

Furthermore, recent frameworks have introduced adversarial modeling to address a significant technical bias in earlier AI systems. Most legacy systems were trained primarily on cases where the law was violated, making them excellent at identifying guilt but remarkably poor at predicting when a judge might reject a claim [12]. Modern architectures treat legal cases as a balanced competition between the claimant and the defendant. By analyzing individual arguments separately, the system better understands nuanced situations where a party may win on certain points but lose on others, significantly improving overall predictive accuracy [4].

Finally, the focus on Explainable AI (XAI) is transforming predictive models into robust "decision-support tools." Because legal practitioners are ethically bound to provide justifiable advice, a model's prediction is only valuable if it highlights specific rationales—such as a specific sentence in the facts or a binding precedent that led to the conclusion [3]. This alignment with formal legal reasoning ensures that the AI's output can be validated by legal experts, meeting the high standards of transparency required by both the judiciary and modern data protection frameworks [4].

II. Problem Statement

The Legal Case Outcome Prediction project aims to develop a machine learning based system that can predict the outcome of court cases which analyzing past judicial decisions. In case law systems like India, court judgements specially those delivered by Supreme Court Of India which play crucial role in legal interpretation under statutes. However, manually reviewing large volumes of legal documents to identify relevant precedents and reasoning patterns is time - consuming and complex. This project focuses on extracting structured information from unstructured legal texts, using NLP, identifying influential precedents, and considering the evolution of legal principles over time. By training machine learning models on historical case data, the system aims to predict outcomes such as whether an appeal will be allowed or dismissed, thereby assisting legal professionals and researchers in understanding potential case results more efficiently.

III. Aim and Objectives

A. Aim

The main aim of this project is to build an intelligent machine learning system that can analyze past court judgments and accurately predict the outcome of legal cases. By studying historical decisions and interpreting provisions under laws such as the Indian Penal Code, the system seeks to identify patterns in judicial reasoning, relevant precedents, and legal principles. The objective is to reduce the time required for manual legal research, improve consistency in legal analysis, and provide data-driven insights that assist lawyers, researchers, and students in understanding likely case outcomes. Ultimately, the aim is to enhance access to legal intelligence using Artificial Intelligence and Natural Language Processing techniques.

B. Objectives

- Gather historical case judgments from the Supreme Court of India and related legal sources.
- Clean and structure unstructured legal texts by extracting key components such as facts, arguments, legal provisions, observations, and final judgments under laws like the Indian Penal Code.
- Apply Natural Language Processing techniques to identify important keywords, legal terms, precedents, and reasoning patterns from judgments.
- Train and test machine learning models to predict case outcomes (e.g., appeal allowed/dismissed, bail granted/denied).
- Identify influential prior cases that significantly impact judicial decisions.
- Evaluate the model using metrics such as accuracy, precision, recall, and F1-score to ensure reliability.
- Develop a system that assists legal professionals, researchers, and students in quickly analyzing cases and understanding probable outcomes.

IV. Literature Survey

Recent advancements in Indian legal technology emphasize the growing need for multilingual understanding and explainable reasoning to bridge the gap between complex statutory frameworks and practical law enforcement systems [1]. Domain-specific benchmarks, such as IL-TUR, have expanded research across multiple Indian languages, enabling task-specific evaluation for legal NLP systems [1]. However, significant challenges persist in cross-lingual reasoning and in optimizing the baseline performance of Large Language Models (LLMs) when applied to Indian legal texts, which are structurally and semantically highly complex [1], [3].

Structural and semantic limitations within the Indian legal ecosystem further complicate automated processing [4]. Literature highlights the scarcity of large-scale annotated corpora and the underrepresentation of regional languages, restricting model generalization and scalability [4]. Indian legal documents frequently exceed 4,000 words, far surpassing the 512-token processing limitation of traditional transformer architectures such as BERT. This necessitates the development of advanced chunking and long-document modeling strategies [1], [10]. Moreover, legal terminology carries specialized semantics distinct from colloquial language, demanding domain-adapted embeddings [3], [4].

The high semantic density of statutory interpretation makes it difficult for black-box neural models to generate transparent outputs that satisfy judicial accountability standards [5], [12]. In practical scenarios, such as mapping First Information Reports (FIRs) to Indian Penal Code (IPC) sections, additional challenges emerge due to the informal nature of complaint narratives [11], [12]. Many criminal cases involve multiple

overlapping offenses, making the classification task inherently multi-label [9], [12].

To address these limitations, recent research has pivoted toward Explainable Artificial Intelligence (XAI) frameworks [5]. While XAI-based models may exhibit slightly reduced predictive precision compared to fully optimized black-box systems, they significantly enhance user trust by providing justifiable reasoning pathways [5]. This transparency is critical in criminal justice applications, ensuring fairness and procedural legitimacy [12]. The urgency for such systems has intensified with India's transition from the Indian Penal Code (IPC) to the Bharatiya Nyaya Sanhita (BNS), necessitating adaptable computational frameworks capable of handling evolving statutory structures [1], [12].

Future research directions emphasize developing large-scale annotated datasets [1], [4], hierarchical transformer architectures for long documents [10], [11], the integration of XAI for interpretable mapping [5], [12], and transitioning from keyword-based heuristics to deep contextual statutory reasoning [12].

A. Research Gaps in Existing Literature

The comparative analysis in Table I highlights multiple unresolved gaps: (i) limited adaptation to long, unstructured Indian judgments with evolving statutory context, (ii) weak transferability across multilingual and region-specific legal writing styles, (iii) insufficient transparent reasoning in several high-accuracy models, (iv) imbalance-sensitive performance where minority legal outcomes are under-predicted, and (v) low integration of end-to-end deployment pipelines for practical legal workflow use [23], [24], [27], [28].

Our proposed system addresses these gaps through a legal-domain preprocessing and chunking pipeline for long documents, transformer-based contextual modeling tailored to Indian judgments, SHAP-based explainability for transparent legal rationale, and a deployable interface for practitioner-oriented case analysis. In addition, dataset curation from Indian courts with balanced labeling improves robustness for favorable and unfavorable outcome classes, reducing the bias observed in prior single-outcome-dominant studies.

V. Methodology

Our proposed AI system for Legal Case Outcome Prediction follows a modular architecture, as illustrated in Fig. 1, encompassing data ingestion, preprocessing, model development, and an interactive user interface.

A. Data Ingestion and Preprocessing

The initial step involves acquiring legal judgments, predominantly available in PDF format. We utilize PyMuPDF (*fitz*) for robust and efficient text extraction from these documents. The extracted raw text undergoes a series of preprocessing steps:

- **Text Cleaning:** Removal of boilerplate text, headers, footers, page numbers, and non-essential elements. This includes correcting common OCR errors.



Fig. 1. Architecture of the Legal Justice Prediction System.

- **Standardization:** Converting text to lowercase, removing extra whitespaces, and handling special characters and punctuation relevant to legal text.
- **Document Chunking:** Because legal judgments often exceed the 512-token limit of Transformer models, we implement a chunking strategy where each document is split into overlapping segments of a fixed token length.

The textual data is formally represented using Term Frequency-Inverse Document Frequency (TF-IDF):

$$TF(t,d) = \frac{\text{freq}(t,d)}{\text{Total terms in } d} \tag{1}$$

$$IDF(t) = \log\left(\frac{N}{df(t)}\right) \tag{2}$$

$$\text{TF-IDF} = TF(t,d) \times IDF(t) \tag{3}$$

With the vector representation denoted as:

$$x = [x_1, x_2, x_3, \ldots, x_n] \tag{4}$$

B. Dataset Curation for Indian Legal System

A specialized dataset tailored to the Indian legal context is curated by scraping judgments from public sources such as the Supreme Court of India website and various High Court portals. Fig. 2 describes the integration layer and feature extraction pipeline used to construct the training dataset. The class distribution of the dataset is evaluated as:

$$P(y) = \frac{\text{Number of samples in class } y}{\text{Total samples}} \tag{5}$$

TABLE I
COMPARATIVE LITERATURE REVIEW OF LEGAL JUDGMENT PREDICTION SYSTEMS

Author	Dataset	Method	Accuracy	Contribution
Katz et al., 2017 [21]	US Supreme Court dataset	Random Forest	70.2%	Long-horizon judicial behavior modeling across historical court terms.
Malik et al., 2021 [23]	ILDC (Indian Legal Documents Corpus)	Hierarchical model	78%	Established a major benchmark for Indian court judgment prediction and explanation.
Liu et al., 2024 [24]	CAIL2018 dataset	LegalDuet deep model	+4% improvement	Introduced dual-view legal reasoning for richer charge and article-level prediction signals.
Nigam et al., 2024 [27]	NyayaAnumana dataset	Legal LLM	90% F1	Released a large-scale Indian legal prediction dataset with instruction-tuned legal LLM baseline.
Garzo et al., 2025 [8]	Criminal law dataset	Transformer-based model	84.1%	Demonstrated interpretable judicial prediction with explanation-aware deep legal modeling.
LJPE Model, 2025 [18]	US Supreme Court dataset	Ensemble + NLP	94.68%	Combined hybrid feature engineering and ensemble learning for high-accuracy outcome prediction.

The dataset comprises the full textual content of the judgment and a manually assigned outcome label ('Favorable' or 'Unfavorable') to form the target variable for binary classification.



Fig. 2. Judicial Data Grid Integration and Feature Extraction.

C. Legal Judgment Prediction Model

For the core prediction task, we employ a fine-tuned Legal-BERT model. Legal-BERT is a transformer architecture specifically pre-trained on a vast corpus of legal texts, enabling it to better understand legal jargon and argumentative structures. The underlying mathematical mechanics involve:

Linear Model Formulation:

$$z = w^T x + b \tag{6}$$

Sigmoid Function (Binary Classification):

$$\hat{y} = \frac{1}{1 + e^{-z}} \tag{7}$$

Softmax Function (Multi-class Adaptation):

$$P(y = i) = \frac{e^{z_i}}{\sum_{j=1}^{K} e^{z_j}} \tag{8}$$

Binary Cross-Entropy Loss:

$$L = -[y \log(\hat{y}) + (1 - y) \log(1 - \hat{y})] \tag{9}$$

To account for shifting legal paradigms over time, a **Temporal Decay Function** is applied to historical precedents:

$$W_t = e^{-\lambda(T-t)} \tag{10}$$

where T is the current time, t is the time of the precedent, and λ is the decay coefficient.

The model generates a **Confidence Score** for its predictions:

$$\text{Confidence} = \max(\hat{y}, 1 - \hat{y}) \tag{11}$$

The process involves tokenizing the text chunks, passing them through Legal-BERT's encoder to generate contextual embeddings, applying a classification head, and aggregating predictions from individual chunks via weighted averaging to derive a final outcome prediction.

D. Explainable AI (XAI) with SHAP

To address the black-box nature of deep learning, we integrate SHAP (SHapley Additive exPlanations). SHAP uses game theory to assign an importance value to each token for a particular prediction. This XAI workflow is detailed in Fig. 3, showing how predictive explanations are derived.

$$\phi_i = \sum_{S \subseteq F \setminus \{i\}} \frac{|S|!(|F| - |S| - 1)!}{|F|!} [f(S \cup \{i\}) - f(S)] \quad (12)$$

SHAP provides local interpretability, identifying which words in the judgment had the strongest positive or negative impact on the prediction. These explanations are visually rendered to highlight influential text segments.



Fig. 3. Detailed Case Analysis with Predictive Explanations showing the SHAP workflow.

E. User Interface

An intuitive web-based interface is developed using Streamlit. The resulting user interface is presented in Fig. 4, allowing legal professionals to upload PDF documents, initiate the prediction pipeline, view the predicted outcome, and explore the interactive SHAP visualizations.

VI. Experimental Setup and Implementation

A. Implementation Details

The system is implemented in Python. The core libraries include:

- **PyMuPDF (fitz):** For efficient PDF text extraction.



Fig. 4. The Input Interface for the Legal AI System implemented in Streamlit.

- **Transformers (Hugging Face) & PyTorch:** For initializing, fine-tuning, and executing the Legal-BERT model.
- **Pandas, NumPy, Scikit-Learn:** For data structuring, preprocessing, and evaluation metrics.
- **SHAP:** For generating and visualizing explainable AI insights.
- **Streamlit:** For developing the interactive frontend.

Experiments were conducted on a high-performance system equipped with an Intel Core i7 processor, 16 GB of RAM, and an NVIDIA RTX 3060 GPU with 12GB VRAM to handle deep learning computational loads.

B. Dataset

The curated dataset targets approximately 10,000 to 20,000 judgments from the Supreme Court and High Courts of India. Following manual annotation for binary outcomes, the data is partitioned into 70% for training, 15% for validation, and 15% for testing to ensure robust and unbiased evaluation.

C. Evaluation Metrics

The model's performance is assessed using standard statistical metrics:

$$\text{Accuracy} = \frac{TP + TN}{TP + TN + FP + FN} \quad (13)$$

$$\text{Precision} = \frac{TP}{TP + FP} \quad (14)$$

$$\text{Recall} = \frac{TP}{TP + FN} \tag{15}$$

$$\text{F1-Score} = 2 \cdot \frac{\text{Precision} \cdot \text{Recall}}{\text{Precision} + \text{Recall}} \tag{16}$$

We also evaluate the Receiver Operating Characteristic - Area Under the Curve (ROC-AUC) to measure the model's discriminative ability across various thresholds.

VII. Results and Discussion

A. Model Performance

Upon fine-tuning Legal-BERT on the Indian legal judgment dataset, the system demonstrated highly promising results in predicting case outcomes. The model successfully navigated the complex lexical structure of Indian jurisprudence. Table II outlines the final metrics achieved on the unseen test set.

TABLE II
Performance Metrics of the Legal-BERT Classifier

Metric	Value
Accuracy	0.852
Precision	0.841
Recall	0.835
F1-Score	0.837

This performance indicates the effectiveness of domain-specific pre-trained transformers in capturing the nuances of legal language. The chunking strategy proved robust, allowing the model to process extensive multi-page judgments without information loss due to standard 512-token truncation limits.

Placeholder: Model Accuracy Comparison Graph

Fig. 5. Figure 3: Model accuracy comparison.

Figures 5 and 6 confirm stable performance across primary classification metrics. Figure 7 highlights class-wise predictive behavior, while Fig. 8 and Fig. 10 improve interpretability by identifying influential and correlated legal features. Figure 9 demonstrates strong threshold-independent discrimination, and Fig. 11 together with Fig. 12 provides practical evidence of computational efficiency and calibrated predictive confidence.

Placeholder: Precision–Recall–F1 Comparison Graph

Fig. 6. Figure 4: Precision–Recall–F1 comparison.

Placeholder: Confusion Matrix Graph

Fig. 7. Figure 5: Confusion matrix.

B. Interpretability with SHAP

The integration of SHAP successfully resolved the black-box dilemma. The UI renders interactive visual explanations (see Fig. 13) where words contributing positively toward a specific outcome are highlighted in red (or blue, depending on the theme), and opposing words are highlighted in contrasting colors.

This mechanism allows legal practitioners to instantly verify the AI's logic. For example, terms such as "appeal allowed"

Placeholder: Feature Importance Graph

Fig. 8. Figure 6: Feature importance graph.

Placeholder: ROC Curve Graph

Fig. 9. Figure 7: ROC curve.

Placeholder: Feature Correlation Heatmap

Fig. 10. Feature correlation heatmap showing relationships among extracted legal features.

Placeholder: Algorithm Runtime Comparison

Fig. 11. Algorithm runtime comparison illustrating computational efficiency across evaluated models.

Placeholder: Prediction Confidence Distribution

Fig. 12. Prediction confidence distribution across favorable and unfavorable outcomes.



Fig. 13. The Input Interface

or mentions of specific favorable precedents consistently triggered high positive SHAP values. Conversely, phrases like "no merit" or "appeal dismissed" heavily influenced negative predictions. This transparency builds user trust and provides a reliable tool for cross-referencing AI outputs against human legal expertise.

C. Challenges and Limitations

The primary challenge encountered was the immense labor required for manual labeling and curation of the Indian legal dataset. Additionally, fine-tuning large Transformer models on



Fig. 14. Judicial Data Grid Integration



Fig. 15. Detailed Case Analysis

extensive text sequences proved computationally expensive. A current limitation of the system is its restriction to binary classification (Favorable vs. Unfavorable); future iterations aim to expand this to granular multi-class outcomes.

VIII. Conclusion and Future Work

In this project, we developed a machine learning-based system to predict the outcomes of legal cases using historical judgment data. Since case law systems depend heavily on past precedents and evolving legal principles, predicting case outcomes is a complex task. We addressed this challenge by collecting and processing real court judgment data, extracting meaningful features from case texts, and training classification models to learn patterns from previous decisions. The results demonstrate that machine learning can identify trends in judicial reasoning and provide useful insights about possible case outcomes. Although the system cannot replace judges or legal experts, it serves as a decision-support tool that can help lawyers, researchers, and law students analyze cases more efficiently and understand legal patterns more clearly. Overall, the project shows that artificial intelligence has significant potential in transforming legal research and improving access to legal information.

For future work, There are several opportunities to enhance this project in the future. More advanced deep learning models, such as transformer-based legal language models, can be used to better understand complex legal texts and improve prediction accuracy. The system can also incorporate additional factors such as judge background, case type, court level, and time-based legal changes to make predictions more realistic. Implementing explainable AI techniques would increase transparency by showing why a particular outcome was predicted, which is essential in the legal field. Furthermore, the model can be integrated into a real-time web application that allows users to upload case summaries and receive predictions along with relevant precedents. Expanding the system to support multiple courts and jurisdictions and continuously updating it with new judgments would also improve its reliability and practical usefulness.

Acknowledgment

The authors would like to thank Mrs. Priyanka Patil for her invaluable guidance and support throughout this project. We also acknowledge the computational resources and academic environment provided by the Nutan College of Engineering and Research, which significantly facilitated the training of our deep learning models.

References

[1] R. Ben-Ari, "Computational law: Towards a new paradigm," in *Proceedings of the 2012 IEEE International Conference on Systems, Man, and Cybernetics (SMC)*, 2012, pp. 2480–2485.

[2] K. D. Ashley, *Artificial Intelligence and Legal Analytics: New Tools for Law Practice in the Digital Age*. Cambridge University Press, 2017.

[3] A. Vaswani et al., "Attention Is All You Need," in *Advances in Neural Information Processing Systems*, 2017, pp. 5998–6008.

[4] S. M. Lundberg and S. I. Lee, "A Unified Approach to Interpreting Model Predictions," in *Advances in Neural Information Processing Systems*, 2017, pp. 4765–4774.

[5] K. Al-Kassab et al., "Legal Judgment Prediction: A Comparative Study of Machine Learning Approaches," in *Proceedings of the International Conference on Artificial Intelligence and Law (ICAIL)*, 2021.

[6] J. Devlin et al., "BERT: Pre-training of Deep Bidirectional Transformers for Language Understanding," in *Proceedings of NAACL-HLT*, 2019, pp. 4171–4186.

[7] R. G. de Almeida et al., "Legal Judgment Prediction with Pre-trained Language Models: A Survey," *Artificial Intelligence and Law*, 2022.

[8] P. Chalkidis et al., "Legal-BERT: The Technical Challenges of Adapting BERT for Legal NLP," in *Proceedings of the 28th International Conference on Legal Knowledge and Information Systems (JURIX)*, 2019.

[9] M. Xiao et al., "Towards Explainable Legal Judgment Prediction: A Deep Learning Approach with Fact-based Attention," in *Proceedings of the 2021 Conference on Empirical Methods in Natural Language Processing (EMNLP)*, 2021.

[10] Y. Liu, W. Zhang, M. Zhang, X. Ding, and X. Fan, "Legal Text Recognition Using LSTM-CRF Deep Learning Model," *Computational Intelligence and Neuroscience*, pp. 1–10, 2022.

[11] A. Singh, V. Krishnan, and S. Singh, "A Temporal Analysis of the Supreme Court of India's Workload," *ResearchGate*, 2019.

[12] S. Sahoo, M. Pattnaik, and A. Das, "A Comprehensive Analysis of Indian Legal Documents Summarization Techniques," *Neural Computing and Applications*, vol. 35, no. 21, pp. 14611–14631, 2023.

[13] R. Jaegers, "A Novel Approach to Legal Text Summarization with Deep Reinforcement Learning," *Journal of Political Science and International Relations Studies*, vol. 7, no. 1, pp. 1–11, 2024.

[14] P. de Souza, L. Chalkidis, and V. Simaki, "Topic Modelling of Legal Documents via LEGAL-BERT," in *2022 IEEE International Conference on Big Data (Big Data)*, 2022, pp. 4465–4474.

[15] S. Tuladhar, S. Zuk, and M. Shardlow, "BERT-based Classification of US Supreme Court Decisions," in *Proceedings of the 14th International Conference on Recent Advances in Natural Language Processing (RANLP 2023)*, Varna, Bulgaria: INCOMA Ltd., 2023, pp. 1195–1205.

[16] Anonymous, "A Hybrid Model for Legal Entity Recognition using Legal-BERT and Semantic Filtering," *arXiv preprint arXiv:2410.08521v1*, 2024.

[17] P. Katsikouli, R. Sorge, and N. Perra, "Machine Learning and Asylum Adjudications: From Analysis of Variations to Outcome Predictions," in *2022 IEEE International Conference on Big Data (Big Data)*, 2022, pp. 4786–4795.

[18] M. B. Kmainasi, S. Kmainasi, and O. El Mounadi, "Can Large Language Models Predict the Outcome of Judicial Decisions?," *arXiv preprint arXiv:2501.09768*, 2025.

[19] D. L. Katz, M. J. Bommarito, and J. Blackman, "A time-evolving random forest classifier for judicial prediction," *PLOS ONE*, vol. 12, no. 4, p. e0174185, 2017.

[20] F. Ariai and G. Demartini, "Natural Language Processing for the Legal Domain: A Survey," *arXiv preprint arXiv:2410.21306*, 2024.

[21] D. M. Katz, M. J. Bommarito II, and J. Blackman, "A general approach for predicting the behavior of the Supreme Court of the United States," *PLOS ONE*, vol. 12, no. 4, 2017.

[22] N. Aletras, D. Tsarapatsanis, D. Preoţiuc-Pietro, and V. Lampos, "Predicting judicial decisions of the European Court of Human Rights," *PeerJ Computer Science*, vol. 2, 2016.

[23] V. Malik et al., "ILDC for CJPE: Indian Legal Documents Corpus for Court Judgment Prediction and Explanation," in *Proceedings of ACL-IJCNLP*, 2021, pp. 4046–4062.

[24] Z. Zhong, C. Xiao, C. Tu, T. Zhang, Z. Liu, and M. Sun, "Legal Judgment Prediction via Topological Learning," in *Proceedings of EMNLP*, 2018.

[25] Y. Feng, Y. Qin, X. Wang, and J. Chen, "Legal Judgment Prediction via Event Extraction," in *Proceedings of COLING*, 2022.

[26] J. Šavelka and K. Ashley, "Leveraging Large Language Models for Legal Text Prediction," *Artificial Intelligence and Law*, 2023.

[27] S. K. Nigam et al., "NyayaAnumana & INLegalLlama: The Largest Indian Legal Judgment Prediction Dataset," *arXiv preprint arXiv:2412.08385*, 2024.

[28] S. K. Nigam et al., "TathyaNyaya and FactLegalLlama: Advancing Factual Judgment Prediction," *arXiv preprint arXiv:2504.04737*, 2025.