



SQL Cheat Sheet

The SQL cheat sheet provides you with the most commonly used SQL statements for your reference. You can download the SQL cheat sheet as follows:

Download 3-page SQL cheat sheet in PDF format (<https://www.sqltutorial.org/wp-content/uploads/2016/04/SQL-cheat-sheet.pdf>)

SQL CHEAT SHEET <http://www.sqltutorial.org>

QUERYING DATA FROM A TABLE

SELECT c1, c2 FROM t;
Query data in columns c1, c2 from a table

SELECT * FROM t;
Query all rows and columns from a table

**SELECT c1, c2 FROM t
WHERE condition;**
Query data and filter rows with a condition

**SELECT DISTINCT c1 FROM t
WHERE condition;**
Query distinct rows from a table

**SELECT c1, c2 FROM t
ORDER BY c1 ASC [DESC];**
Sort the result set in ascending or descending order

**SELECT c1, c2 FROM t
ORDER BY c1
LIMIT n OFFSET offset;**
Skip offset of rows and return the next n rows

**SELECT c1, aggregate(c2)
FROM t
GROUP BY c1;**
Group rows using an aggregate function

**SELECT c1, aggregate(c2)
FROM t
GROUP BY c1
HAVING condition;**
Filter groups using HAVING clause

QUERYING FROM MULTIPLE TABLES

**SELECT c1, c2
FROM t1
INNER JOIN t2 ON condition;**
Inner join t1 and t2

**SELECT c1, c2
FROM t1
LEFT JOIN t2 ON condition;**
Left join t1 and t2

**SELECT c1, c2
FROM t1
RIGHT JOIN t2 ON condition;**
Right join t1 and t2

**SELECT c1, c2
FROM t1
FULL OUTER JOIN t2 ON condition;**
Perform full outer join

**SELECT c1, c2
FROM t1
CROSS JOIN t2;**
Produce a Cartesian product of rows in tables

**SELECT c1, c2
FROM t1, t2;**
Another way to perform cross join

**SELECT c1, c2
FROM t1 A
INNER JOIN t2 B ON condition;**
Join t1 to itself using INNER JOIN clause

USING SQL OPERATORS

**SELECT c1, c2 FROM t1
UNION [ALL]
SELECT c1, c2 FROM t2;**
Combine rows from two queries

**SELECT c1, c2 FROM t1
INTERSECT
SELECT c1, c2 FROM t2;**
Return the intersection of two queries

**SELECT c1, c2 FROM t1
MINUS
SELECT c1, c2 FROM t2;**
Subtract a result set from another result set

**SELECT c1, c2 FROM t1
WHERE c1 [NOT] LIKE pattern;**
Query rows using pattern matching %, _

**SELECT c1, c2 FROM t
WHERE c1 [NOT] IN value_list;**
Query rows in a list

**SELECT c1, c2 FROM t
WHERE c1 BETWEEN low AND high;**
Query rows between two values

**SELECT c1, c2 FROM t
WHERE c1 IS [NOT] NULL;**
Check if values in a table is NULL or not

SQL CHEAT SHEET <http://www.sqltutorial.org>



MANAGING TABLES

```
CREATE TABLE t (
  id INT PRIMARY KEY,
  name VARCHAR NOT NULL,
  price INT DEFAULT 0
);
```

Create a new table with three columns

```
DROP TABLE t;
```

Delete the table from the database

```
ALTER TABLE t ADD column;
```

Add a new column to the table

```
ALTER TABLE t DROP COLUMN c;
```

Drop column c from the table

```
ALTER TABLE t ADD constraint;
```

Add a constraint

```
ALTER TABLE t DROP constraint;
```

Drop a constraint

```
ALTER TABLE t1 RENAME TO t2;
```

Rename a table from t1 to t2

```
ALTER TABLE t1 RENAME c1 TO c2;
```

Rename column c1 to c2

```
TRUNCATE TABLE t;
```

Remove all data in a table

USING SQL CONSTRAINTS

```
CREATE TABLE t(
  c1 INT, c2 INT, c3 VARCHAR,
  PRIMARY KEY (c1,c2)
);
```

Set c1 and c2 as a primary key

```
CREATE TABLE t1(
  c1 INT PRIMARY KEY,
  c2 INT,
  FOREIGN KEY (c2) REFERENCES t2(c2)
);
```

Set c2 column as a foreign key

```
CREATE TABLE t(
  c1 INT, c1 INT,
  UNIQUE(c2,c3)
);
```

Make the values in c1 and c2 unique

```
CREATE TABLE t(
  c1 INT, c2 INT,
  CHECK(c1 > 0 AND c1 >= c2)
);
```

Ensure c1 > 0 and values in c1 >= c2

```
CREATE TABLE t(
  c1 INT PRIMARY KEY,
  c2 VARCHAR NOT NULL
);
```

Set values in c2 column not NULL

MODIFYING DATA

```
INSERT INTO t(column_list)
VALUES(value_list);
```

Insert one row into a table

```
INSERT INTO t(column_list)
VALUES (value_list),
       (value_list), ....;
```

Insert multiple rows into a table

```
INSERT INTO t1(column_list)
SELECT column_list
FROM t2;
```

Insert rows from t2 into t1

```
UPDATE t
SET c1 = new_value;
```

Update new value in the column c1 for all rows

```
UPDATE t
SET c1 = new_value,
    c2 = new_value
WHERE condition;
```

Update values in the column c1, c2 that match the condition

```
DELETE FROM t;
```

Delete all data in a table

```
DELETE FROM t
WHERE condition;
```

Delete subset of rows in a table

SQL CHEAT SHEET <http://www.sqltutorial.org>



MANAGING VIEWS

```
CREATE VIEW v(c1,c2)
AS
SELECT c1, c2
FROM t;
```

Create a new view that consists of c1 and c2

```
CREATE VIEW v(c1,c2)
AS
SELECT c1, c2
FROM t;
WITH [CASCADED | LOCAL] CHECK OPTION;
```

Create a new view with check option

```
CREATE RECURSIVE VIEW v
AS
select-statement -- anchor part
UNION [ALL]
select-statement; -- recursive part
```

Create a recursive view

```
CREATE TEMPORARY VIEW v
AS
SELECT c1, c2
FROM t;
```

Create a temporary view

```
DROP VIEW view_name;
```

Delete a view

MANAGING INDEXES

```
CREATE INDEX idx_name
ON t(c1,c2);
```

Create an index on c1 and c2 of the table t

```
CREATE UNIQUE INDEX idx_name
ON t(c3,c4);
```

Create a unique index on c3, c4 of the table t

```
DROP INDEX idx_name;
```

Drop an index

SQL AGGREGATE FUNCTIONS

```
AVG
```

returns the average of a list

```
COUNT
```

returns the number of elements of a list

```
SUM
```

returns the total of a list

```
MAX
```

returns the maximum value in a list

```
MIN
```

returns the minimum value in a list

MANAGING TRIGGERS

```
CREATE OR MODIFY TRIGGER trigger_name
WHEN EVENT
ON table_name TRIGGER_TYPE
EXECUTE stored_procedure;
```

Create or modify a trigger

WHEN

- **BEFORE** – invoke before the event occurs
- **AFTER** – invoke after the event occurs

EVENT

- **INSERT** – invoke for INSERT
- **UPDATE** – invoke for UPDATE
- **DELETE** – invoke for DELETE

TRIGGER_TYPE

- **FOR EACH ROW**
- **FOR EACH STATEMENT**

```
CREATE TRIGGER before_insert_person
BEFORE INSERT
ON person FOR EACH ROW
EXECUTE stored_procedure;
```

Create a trigger invoked before a new row is inserted into the person table

```
DROP TRIGGER trigger_name;
```

Delete a specific trigger

Querying data from a table

Query data in columns c1, c2 from a table

```
SELECT c1, c2 FROM t;
```

Query all rows and columns from a table

```
SELECT * FROM t;
```

Query data and filter rows with a condition

```
SELECT c1, c2 FROM t  
WHERE condition;
```

Query distinct rows from a table

```
SELECT DISTINCT c1 FROM t  
WHERE condition;
```

Sort the result set in ascending or descending order

```
SELECT c1, c2 FROM t  
ORDER BY c1 ASC [DESC];
```

Skip *offset* of rows and return the next n rows

```
SELECT c1, c2 FROM t  
ORDER BY c1  
LIMIT n OFFSET offset;
```

Group rows using an aggregate function

```
SELECT c1, aggregate(c2)
FROM t
GROUP BY c1;
```

Filter groups using HAVING clause

```
SELECT c1, aggregate(c2)
FROM t
GROUP BY c1
HAVING condition;
```

Querying from multiple tables

Inner join t1 and t2

```
SELECT c1, c2
FROM t1
INNER JOIN t2 ON condition;
```

Left join t1 and t1

```
SELECT c1, c2
FROM t1
LEFT JOIN t2 ON condition;
```

Right join t1 and t2

```
SELECT c1, c2
FROM t1
RIGHT JOIN t2 ON condition;
```

Perform full outer join

```
SELECT c1, c2
FROM t1
FULL OUTER JOIN t2 ON condition;
```

Produce a Cartesian product of rows in tables

```
SELECT c1, c2
FROM t1
CROSS JOIN t2;
```

Another way to perform cross join

```
SELECT c1, c2
FROM t1, t2;
```

Join t1 to itself using INNER JOIN clause

```
SELECT c1, c2
FROM t1 A
INNER JOIN t1 B ON condition;
```

Using SQL Operators

Combine rows from two queries

```
SELECT c1, c2 FROM t1
UNION [ALL]
SELECT c1, c2 FROM t2;
```

Return the intersection of two queries

```
SELECT c1, c2 FROM t1
INTERSECT
```

```
SELECT c1, c2 FROM t2;
```

Subtract a result set from another result set

```
SELECT c1, c2 FROM t1  
MINUS  
SELECT c1, c2 FROM t2;
```

Query rows using pattern matching %, _

```
SELECT c1, c2 FROM t1  
WHERE c1 [NOT] LIKE pattern;
```

Query rows in a list

```
SELECT c1, c2 FROM t  
WHERE c1 [NOT] IN value_list;
```

Query rows between two values

```
SELECT c1, c2 FROM t  
WHERE c1 BETWEEN low AND high;
```

Check if values in a table is NULL or not

```
SELECT c1, c2 FROM t  
WHERE c1 IS [NOT] NULL;
```

Managing tables

Create a new table with three columns

```
CREATE TABLE t (  
    id INT PRIMARY KEY,
```

```
    name VARCHAR NOT NULL,  
    price INT DEFAULT 0  
);
```

Delete the table from the database

```
DROP TABLE t ;
```

Add a new column to the table

```
ALTER TABLE t ADD column;
```

Drop column c from the table

```
ALTER TABLE t DROP COLUMN c ;
```

Add a constraint

```
ALTER TABLE t ADD constraint;
```

Drop a constraint

```
ALTER TABLE t DROP constraint;
```

Rename a table from t1 to t2

```
ALTER TABLE t1 RENAME TO t2;
```

Rename column c1 to c2

```
ALTER TABLE t1 RENAME c1 TO c2 ;
```

Remove all data in a table

```
TRUNCATE TABLE t;
```

Using SQL constraints

Set c1 and c2 as a primary key

```
CREATE TABLE t(  
    c1 INT, c2 INT, c3 VARCHAR,  
    PRIMARY KEY (c1,c2)  
);
```

Set c2 column as a foreign key

```
CREATE TABLE t1(  
    c1 INT PRIMARY KEY,  
    c2 INT,  
    FOREIGN KEY (c2) REFERENCES t2(c2)  
);
```

Make the values in c1 and c2 unique

```
CREATE TABLE t(  
    c1 INT, c1 INT,  
    UNIQUE(c2,c3)  
);
```

Ensure c1 > 0 and values in c1 >= c2

```
CREATE TABLE t(  
    c1 INT, c2 INT,  
    CHECK(c1> 0 AND c1 >= c2)  
);
```

Set values in c2 column not NULL


```
CREATE TABLE t(  
    c1 INT PRIMARY KEY,  
    c2 VARCHAR NOT NULL  
);
```

Modifying **Data**

Insert one row into a table

```
INSERT INTO t(column_list)  
VALUES(value_list);
```

Insert multiple rows into a table

```
INSERT INTO t(column_list)  
VALUES (value_list),  
      (value_list), ...;
```

Insert rows from t2 into t1

```
INSERT INTO t1(column_list)  
SELECT column_list  
FROM t2;
```

Update new value in the column c1 for all rows

```
UPDATE t  
SET c1 = new_value;
```

Update values in the column c1, c2 that match the condition

```
UPDATE t  
SET c1 = new_value,
```

```
        c2 = new_value  
WHERE condition;
```

Delete all data in a table

```
DELETE FROM t;
```

Delete subset of rows in a table

```
DELETE FROM t  
WHERE condition;
```

Managing Views

Create a new view that consists of c1 and c2

```
CREATE VIEW v(c1,c2)  
AS  
SELECT c1, c2  
FROM t;
```

Create a new view with check option

```
CREATE VIEW v(c1,c2)  
AS  
SELECT c1, c2  
FROM t;  
WITH [CASCADED | LOCAL] CHECK OPTION;
```

Create a recursive view

```
CREATE RECURSIVE VIEW v  
AS  
select-statement -- anchor part
```

```
UNION [ALL]  
select-statement; -- recursive part
```

Create a temporary view

```
CREATE TEMPORARY VIEW v  
AS  
SELECT c1, c2  
FROM t;
```

Delete a view

```
DROP VIEW view_name;
```

Managing indexes

Create an index on c1 and c2 of the t table

```
CREATE INDEX idx_name  
ON t(c1,c2);
```

Create a unique index on c3, c4 of the t table

```
CREATE UNIQUE INDEX idx_name  
ON t(c3,c4)
```

Drop an index

```
DROP INDEX idx_name;
```

Managing triggers

Create or modify a trigger

```
CREATE OR MODIFY TRIGGER trigger_name  
WHEN EVENT  
ON table_name TRIGGER_TYPE  
EXECUTE stored_procedure;
```

WHEN

- **BEFORE** – invoke before the event occurs
- **AFTER** – invoke after the event occurs

EVENT

- **INSERT** – invoke for INSERT
- **UPDATE** – invoke for UPDATE
- **DELETE** – invoke for DELETE

TRIGGER_TYPE

- **FOR EACH ROW**
- **FOR EACH STATEMENT**

Delete a specific trigger

```
DROP TRIGGER trigger_name;
```