



```
EXISTS sales;
sales (
INTEGER,
e TEXT,
name TEXT,
EXT,
INTEGER,
_unit REAL,
unt REAL

sales VALUES
01', 'Alice', 'Laptop', 1, 800.0, 800.0),
02', 'Bob', 'Mouse', 2, 20.0, 40.0),
03', 'Charlie', 'Keyboard', 1, 50.0, 50.0);

DISTINCT customer_name) AS total_customers FROM sales;

antity) AS total_quantity FROM sales;

tal_amount) AS total_revenue FROM sales;

*) AS total_orders FROM sales;
```

☒ Case Sensitive ☒ Whole Words ☐ Regular Expression

without errors.
rned in 4ms

total_orders FROM sales;

Edit Database Cell

Mode: Text

NULL

No cell active.
Type: NULL; Size: 0 bytes

Remote

Identity

Name



```
EXISTS sales;
sales (
INTEGER,
e TEXT,
name TEXT,
EXT,
INTEGER,
_unit REAL,
unt REAL

sales VALUES
01', 'Alice', 'Laptop', 1, 800.0, 800.0),
02', 'Bob', 'Mouse', 2, 20.0, 40.0),
03', 'Charlie', 'Keyboard', 1, 50.0, 50.0);

DISTINCT customer_name) AS total_customers FROM sales;

antity) AS total_quantity FROM sales;

tal_amount) AS total_revenue FROM sales;

*) AS total_orders FROM sales;
```

☐ Case Sensitive ☐ Whole Words ☐ Regular Expression

without errors.
rned in 6ms

```
ount) AS total_revenue FROM sales;
```

Edit Database Cell

Mode: Text

NULL

No cell active.
Type: NULL; Size: 0 bytes

Remote

Identity

DBHub.io Local Current Database

Name

SQL Log Plot DB Schema Remote



```
EXISTS sales;
sales (
INTEGER,
e TEXT,
name TEXT,
EXT,
INTEGER,
_unit REAL,
unt REAL

sales VALUES
01', 'Alice', 'Laptop', 1, 800.0, 800.0),
02', 'Bob', 'Mouse', 2, 20.0, 40.0),
03', 'Charlie', 'Keyboard', 1, 50.0, 50.0);

DISTINCT customer_name) AS total_customers FROM sales;
```

```
quantity) AS total_quantity FROM sales;
```

```
total_amount) AS total_revenue FROM sales;
```

```
*) AS total_orders FROM sales;
```

☐ Case Sensitive ☐ Whole Words ☐ Regular Expression

without errors.

urned in 6ms

```
CT customer_name) AS total_customers FROM sales;
```

Edit Database Cell

Mode: Text

NULL

No cell active.
Type: NULL; Size: 0 bytes

Remote

Identity

DBHub.io Local Current Database

Name

SQL Log Plot DB Schema Remote



```
EXISTS sales;
sales (
INTEGER,
e TEXT,
name TEXT,
EXT,
INTEGER,
_unit REAL,
unt REAL

sales VALUES
01', 'Alice', 'Laptop', 1, 800.0, 800.0),
02', 'Bob', 'Mouse', 2, 20.0, 40.0),
03', 'Charlie', 'Keyboard', 1, 50.0, 50.0);

DISTINCT customer_name) AS total_customers FROM sales;

ntity) AS total_quantity FROM sales;

tal_amount) AS total_revenue FROM sales;

*) AS total_orders FROM sales;
```

☐ Case Sensitive ☐ Whole Words ☐ Regular Expression

without errors.
rned in 8ms

```
) AS total_quantity FROM sales;
```

Edit Database Cell

Mode: Text

NULL

No cell active.
Type: NULL; Size: 0 bytes

Remote

Identity

Name



```
EXISTS sales;
sales (
INTEGER,
e TEXT,
name TEXT,
EXT,
INTEGER,
_unit REAL,
unt REAL

sales VALUES
01', 'Alice', 'Laptop', 1, 800.0, 800.0),
02', 'Bob', 'Mouse', 2, 20.0, 40.0),
03', 'Charlie', 'Keyboard', 1, 50.0, 50.0);

DISTINCT customer_name) AS total_customers FROM sales;

antity) AS total_quantity FROM sales;

tal_amount) AS total_revenue FROM sales;

*) AS total_orders FROM sales;
```

☐ Case Sensitive ☐ Whole Words ☐ Regular Expression

without errors.
rned in 6ms

total_orders FROM sales;

Edit Database Cell

Mode: Text

NULL

No cell active.
Type: NULL; Size: 0 bytes

Remote

Identity

Name