AgentScript Reasoning & Flow Control - A Deep Dive into Reasoning Block Behavior

AgentScript provides powerful control mechanisms that distinguish between **LLM-powered reasoning** and **deterministic execution**. This hybrid approach allows developers to precisely control when agents use AI reasoning versus following predefined logic paths.

Definition & Execution Ground Rules

- **Parse** = one full pass over the topic's reasoning instructions, where agentforce evaluates and runs all the deterministic logic before sending anything to LLM
  - System walks the instructions top to bottom
  - Executes deterministic steps such as:
    - set `set @variables.counterVerify = @variables.counterVerify + 1`
    - run `@actions.nkg`
    - `if / else` branches
  - **Important Note**: Pipe `|` has a special significance; anything that comes after it, however critical [`ALWAYS`, `MUST`, `CRITICAL` ,etc] it may sound to mortal human is left at the mercy of the Language Model to approve or reject for execution.
    - The Language Model's reasoning planner acts as a gatekeeper, evaluating each instruction based on its own interpretation of context and relevance, regardless of the urgency conveyed by the human-defined keywords.
    - **For instance**, even if an instruction states `"ALWAYS run the counterIncr action to update the subCounter"`, the LLM may choose to skip this action if it determines other priorities take precedence or if the action doesn't align with its current reasoning path.
- Each time the topic's reasoning instructions are processed counts as one parse.
  - When the topic is first entered
    - eg: via a transition
  - Each time a new reasoning loop iteration starts for that topic
    - eg: after a tool call or the next use message within the same topic (multi-turn)

Flow of Control



Deterministic vs. LLM Reasoning in AgentScript



Here is an example

To maintain conciseness, the topic selector and a single topic are included for demonstration purposes.

Utterances

Turn#	Assistant	User
1	Hi, I'm an AI service assistant. How can I help you?	provide the tracking status of my last order
2	To provide the tracking status of your last order, I need to verify your identity. Please provide your username or email address associated with your account.	nikhilgupta@salesforce.com.devpro
3	To provide the tracking status of your last order, I need to verify your identity. Please provide your username or email address associated with your account.	<<generated verification code>>

Topic Selector

```
start_agent topic_selector:
    label: "Topic Selector"

    description: "Welcome the user and determine the appropriate topic based on user input"

    reasoning:
        instructions: ->
            | Select the best tool to call based on conversation history and user's intent.
```

```
        actions:
            go_to_ServiceCustomerVerification: @utils.transition to @topic.ServiceCustomerVerification
                available when @variables.isVerified==False

            go_to_CaseManagement: @utils.transition to @topic.CaseManagement
                available when @variables.isVerified==True

            go_to_OrderInquiries: @utils.transition to @topic.OrderInquiries
                available when @variables.isVerified==True

            go_to_GeneralFAQ: @utils.transition to @topic.GeneralFAQ

            go_to_escalation: @utils.transition to @topic.escalation

            go_to_off_topic: @utils.transition to @topic.off_topic

            go_to_ambiguous_question: @utils.transition to @topic.ambiguous_question

            go_to_Product_Info_and_Features: @utils.transition to @topic.Product_Info_and_Features
```

Topic: ServiceCustomerVerification

```
topic ServiceCustomerVerification:
    label: "Service Customer Verification"

    description: "Verifies the customer's identity before granting access to sensitive data. Verification is required for inquiries related to orders and

    reasoning:
        instructions: ->
            set @variables.counterVerify = @variables.counterVerify + 1
            | Check if the customer has provided their username or email address.If not please request the customer to provide and pass the value to the
            | When the user provides their username or email address, Run the action {!@actions.SendEmailVerificationCode} to send the verification code
            | If the customer enters the verification code, run the {!@actions.VerifyCustomer}.
            | If verification is successful, proceed with the requested action and complete the task the user intends to perform.
            | Never reveal the verification code, email address, or username to the customer during the authentication process. Make sure that these deta
            | Always Run the action {!@actions.counterIncr} to update update subCounter
```

Action Available For Reasoning

```
        actions:
            SendEmailVerificationCode: @actions.SendEmailVerificationCode
                with customerToVerify = ...
                set @variables.authenticationKey = @outputs.authenticationKey
                set @variables.customerId = @outputs.customerId
                set @variables.customerType = @outputs.customerType

            counterIncr: @utils.setVariables
                with counterVerify = @variables.counterVerify + 1
                with subCounter=@variables.subCounter+1


            VerifyCustomer: @actions.VerifyCustomer
                with authenticationKey = @variables.authenticationKey
                with customerCode = ...
                with customerId = @variables.customerId
                with customerType = @variables.customerType
                set @variables.isVerified = @outputs.isVerified
                set @variables.VerifiedCustomerId = @outputs.customerId
                if @variables.isVerified:
                    transition to @topic.topic_selector
```

Action Available to Topic

```
    actions:
        SendEmailVerificationCode:
            description: "Sends a generated verification code to the user's email address."
            inputs:
```

```
            customerToVerify: string
                description: "Stores the email address or username provided by the customer. This input initiates the verification process."
                label: "Customer To Verify"
                is_required: True
                is_user_input: True
        outputs:
            verificationMessage: string
                description: "Stores a generic message that will be displayed to the user."
                label: "Verification Message"
                filter_from_agent: False
                is_displayable: True
            verificationCode: string
                description: "Stores the generated verification code."
                label: "Verification Code"
                filter_from_agent: True
                is_displayable: False
            authenticationKey: string
                description: "Stores the authentication key that's used to generate the verification code."
                label: "Authentication Key"
                filter_from_agent: True
                is_displayable: False
            customerId: string
                description: "Stores the Salesforce user ID or contact ID."
                label: "Customer ID"
                filter_from_agent: True
                is_displayable: False
            customerType: string
                description: "Stores the customer ID type, whether it's a Salesforce user or a contact."
                label: "Customer Type"
                filter_from_agent: True
                is_displayable: False
        target: "flow://SvcCopilotTmpl__SendVerificationCode"
        label: "Send Email with Verification Code"
        require_user_confirmation: False
        include_in_progress_indicator: True
        source: "SvcCopilotTmpl__SendEmailVerificationCode"

    VerifyCustomer:
        description: "Verifies whether the verification code entered by the user matches the code sent to the user's email address."
        inputs:
            authenticationKey: string
                description: "Stores the authentication key that's used to generate the verification code."
                label: "Authentication Key"
                is_required: True
                is_user_input: False
            customerCode: string
                description: "Stores the verification code entered by the user in the conversation, which they received by email."
                label: "Customer Code"
                is_required: True
                is_user_input: True
            customerId: string
                description: "Stores the Salesforce user ID or contact ID."
                label: "Customer ID"
                is_required: True
                is_user_input: False
            customerType: string
                description: "Stores the customer ID type, whether it's a Salesforce user or a contact."
                label: "Customer Type"
                is_required: True
                is_user_input: False
        outputs:
            isVerified: boolean
                description: "Stores a boolean value that indicates whether the customer code is verified."
                label: "Verified"
                filter_from_agent: True
                is_displayable: False
            customerId: string
                description: "Stores the Salesforce user ID or contact ID."
                label: "Customer Id"
                filter_from_agent: True
                is_displayable: False
            customerType: string
                description: "Stores Type of ID"
```

```
            label: "Customer Type"
            filter_from_agent: True
            is_displayable: False
        messageAfterVerification: string
            description: "Stores a generic message to be displayed after successful verification."
            label: "Message After Verification"
            filter_from_agent: True
            is_displayable: True
    target: "flow://SvcCopilotTmpl__VerifyCode"
    label: "Verify Customer"
    require_user_confirmation: False
    include_in_progress_indicator: True
    source: "SvcCopilotTmpl__VerifyCustomer"
```

Trace



Agentforce adds this System Message

> 5. When multiple topic-specific tools might apply, **use the most specific and relevant one first**
> 6. **After tool usage, evaluate if additional tools are needed** before responding
> - If more tools are needed, clearly explain what's still missing and which type of tool(s) you'll use next.
> - If information is sufficient, provide a complete response based on the collected tool results.
> - If a tool fails, retry 1-2 times; if still failing, explain the issue, suggest alternatives, and advise when to retry

Run Summary

Here are the States with positional alignment of **InstructionX** [`| Always Run the action {!@actions.counterIncr} to update update subCounter`]

InstructionX at top

Turn	User Message	Parse(s)	counterIncr calls	counterVerify	subCounter
1	provide the tracking status of my last order	1	1	2	1
2	user provides user name: nikhilgupta@salesforce.com.devpro	2	0	4	1
3	user enters <<generated verification code>>	2	0	6	1
Total / Final State		5	1	6	1

InstructionX at Bottom

Turn	User Message	Parse(s)	counterIncr calls	counterVerify	subCounter
1	provide the tracking status of my last order	1	1	2	1
2	user provides user name: nikhilgupta@salesforce.com.devpro	1	1	4	2
3	user enters <<generated verification code>>	2	0	6	2
Total / Final State		4	2	6	2

Explanation for Parse Runs variability

The number of times the AgentScript parser processes the instructions can vary between different execution runs, which directly impacts the frequency with which deterministic actions are executed. This variability in parsing behavior creates inconsistent execution patterns, where the same deterministic instruction may run a different number of times depending on how the parser interprets and processes the script during that particular run.

> For example, if the parser processes a topic's reasoning instructions 3 times in one run versus 5 times in another run, a deterministic action like `counterIncr` (which increments `@variables.counterVerify` and `@variables.subCounter`) will execute 3 times in the first scenario but 5 times in the second, resulting in different final counter values despite identical user interactions and script logic.

Observations and Takeaways

1. counterIncr is not called every turn in either setup. It depend on placement and when LLM decides to ise it.
2. Bottom placement led to more compliance
3. Parse count can differ between runs, which changes how often the deterministic line runs
4. “Alway run” is not enforced; planner model can skip when it prioritizes verification steps.

TLDR;
While the action is wrapped in reasoning step prefixed by pipe, `|` , Language Model (used by reasoning planner) will decide, if it wants to execute that action or NOT (ergo, Non-Determinism)

Agentscript Control Flow Lucid

Document Revision History

Date	Version	Author	Changes
2026-03-06	DRAFT	@Nikhil Kumar Gupta	Initial document creation with basic AgentScript control flow concepts

2026-03-07	DRAFT	@Nikhil Kumar Gupta	Added Details and Examples.
2026-03-09	1.0	@Nikhil Kumar Gupta	Added Diagrams