Use of Model Predictive Control (MPC) for Rocket Altitude Correction

Nikhil Peri, Anthony Lin, Manit Ginoya, Paul Buzuloiu uOttawa Rocketry Team {nperi104, alin102 mgino015, pbuzu025}@uottawa.ca

Abstract—

KeywordsModel Predictive Control, Aerospace.

I. Introduction

Rockets unlike other aircraft have high speed and dynamic flights, as a result rocket control systems have to be extremely responsive and precise. Classical control systems based on observed sensor feedback would not be able to meet the demands of rocket flight since the latency between plant actuation affecting the the physical world and detecting that change through sensor observations is too slow for such dynamic flight environments. Model Predictive Control (MPC) solves these problems by introducing state estimation. This process involves maintianing a kenetic

II. AIRBRAKE MODEL

III. MODEL PREDICTIVE CONTROL

The complexity of rocket flight partially arises from the numerous states required to fully define an entire set of dynamics. These states include acceleration, velocity, position, orientation, angular speed and angular acceleration of the rocket in all three spatial dimensions. Additionally, the states related to the actuators (in this case, the servo motor controlling the airbrakes) must also be considered. Desiging a classical controller or even a digitally implmented classicial controller would bring along several inconveniences; for this reason, a model predictive controller was considered and implemented.

The major concept of model predictive control is to maintain a real time simulation; This simulation's role is to produce a prediction of future system states using feedback from sensors and the system's current states. For the case of achiving a particular target altitude by deploying airbrakes, the MPC will produce a predicted final altitude every control loop. Using this predicted final altitude, the error between the predicted final altitude and the desired final altitude will be calculated. The final part of the MPC process is to map the calculated error to a specific (whether heuristic or deterministic) control signal that will be sent to the airbrake actuator.




Fig. 1: Overall Control Diagram of airbrake system

IV. IMEPLEMENTATION
V. CONCLUSION
VI. ACKNOWLEDGEMENT
REFERENCES