

# Rajalakshmi Engineering College

Name: Nikhil Vinayak P  
Email: 240701359@rajalakshmi.edu.in  
Roll no: 240701359  
Phone: 9884558531  
Branch: REC  
Department: CSE - Section 5  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## 2024\_28\_III\_OOPS Using Java Lab

### 2028\_REC\_OOPS using Java\_Week 6\_Q5

Attempt : 1  
Total Mark : 10  
Marks Obtained : 10

#### Section 1 : Coding

##### 1. Problem statement:

Tim was tasked with developing a grocery shopping app. You have a class hierarchy that includes Item, Produce, and OrganicProduce. Your goal is to calculate the total cost of a shopping list, which may contain a mix of regular produce and organic produce items. Additionally, you need to apply discounts to organic items. Apply a 10% discount on organic produce items

Class Hierarchy:

Item: Base class for all items.

Produce: Subclass of Item for regular produce items.

OrganicProduce: Subclass of Produce for organic produce items.

### ***Input Format***

The first line of input consists of an integer, 'n'.

For each 'n' item, the user will provide:

- A string 'type' representing the item type ('Regular' or 'Organic').
- A string 'name' represents the item name.
- A double 'price' represents the item price.

### ***Output Format***

The output will display the total cost of the shopping list, including discounts on organic items.

Refer to the sample output for format specifications.

### ***Sample Test Case***

Input: 1

Regular Banana 1.99

Output: 1.99

### ***Answer***

```
import java.util.Scanner;

// You are using Java
class Item {
    protected String name;
    protected double price;
    public Item(String name, double price) {
        this.name=name;
        this.price=price;
    }
    public double calculateCost() {
        return price;
    }
}

class Produce extends Item {
    public Produce(String name, double price) {
        super(name, price);
    }
}
```

```

    }
}
class OrganicProduce extends Produce {
    public OrganicProduce(String name, double price) {
        super(name, price);
    }
    public double calculateCost() {
        return price*0.90;
    }
}

```

```

public class Main {
    public static void main(String[] args) {
        Scanner sc = new Scanner(System.in);

        int n = sc.nextInt();
        sc.nextLine(); // Consume newline

        double totalCost = 0.0;

        for (int i = 0; i < n; i++) {
            String type = sc.next();
            String name = sc.next();
            double price = sc.nextDouble();

            if (type.equals("Regular")) {
                Item item = new Produce(name, price);
                totalCost += item.calculateCost();
            } else if (type.equals("Organic")) {
                Item item = new OrganicProduce(name, price);
                totalCost += item.calculateCost();
            }
        }

        System.out.printf("%.2f%n", totalCost);
    }
}

```

**Status :** Correct

**Marks :** 10/10