

# Rajalakshmi Engineering College

Name: Nikhilesh D  
Email: 240701360@rajalakshmi.edu.in  
Roll no: 240701360  
Phone: 9940617256  
Branch: REC  
Department: I CSE FD  
Batch: 2028  
Degree: B.E - CSE

Scan to verify results



## NeoColab\_REC\_CS23231\_DATA STRUCTURES

### REC\_DS using C\_Week 7\_COD\_Question 3

Attempt : 1  
Total Mark : 10  
Marks Obtained : 7.5

#### Section 1 : Coding

##### 1. Problem Statement

In a messaging application, users maintain a contact list with names and corresponding phone numbers. Develop a program to manage this contact list using a dictionary implemented with hashing.

The program allows users to add contacts, delete contacts, and check if a specific contact exists. Additionally, it provides an option to print the contact list in the order of insertion.

##### ***Input Format***

The first line consists of an integer  $n$ , representing the number of contact pairs to be inserted.

Each of the next  $n$  lines consists of two strings separated by a space: the name of the contact (key) and the corresponding phone number (value).

The last line contains a string k, representing the contact to be checked or removed.

### **Output Format**

If the given contact exists in the dictionary:

1. The first line prints "The given key is removed!" after removing it.
2. The next n - 1 lines print the updated contact list in the format: "Key: X; Value: Y" where X represents the contact's name and Y represents the phone number.

If the given contact does not exist in the dictionary:

1. The first line prints "The given key is not found!".
2. The next n lines print the original contact list in the format: "Key: X; Value: Y" where X represents the contact's name and Y represents the phone number.

Refer to the sample outputs for the formatting specifications.

### **Sample Test Case**

Input: 3

Alice 1234567890

Bob 9876543210

Charlie 4567890123

Bob

Output: The given key is removed!

Key: Alice; Value: 1234567890

Key: Charlie; Value: 4567890123

### **Answer**

// You are using GCC

```
void insertKeyValuePair(Dictionary *dict, const char *key, const char *value) {  
    strcpy(dict->pairs[dict->size].key, key);  
    strcpy(dict->pairs[dict->size].value, value);  
    dict->size++;  
}
```

```

void removeKeyValuePair(Dictionary *dict, const char *key) {
    for (int i=0; i<dict->size; i++) {
        if (strcmp(dict->pairs[i].key,key)==0) {
            for (int j=i; j<dict->size-1; j++) {
                dict->pairs[j]=dict->pairs[j+1];
            }
            dict->size--;
            break;
        }
    }
}

int doesKeyExist(Dictionary *dict, const char *key) {
    for (int i=0; i<dict->size; i++) {
        if (strcmp(dict->pairs[i].key,key)==0)
            return 1;
    }
    return 0;
}

void printDictionary(Dictionary *dict) {
    for (int i=0; i<dict->size; i++) {
        printf("Key: %s; Value: %s\n", dict->pairs[i].key, dict->pairs[i].value);
    }
}

```

**Status :** Partially correct

**Marks :** 7.5/10