Rajalakshmi Engineering College

Name: Nikhilesh D

Email: 240701360@rajalakshmi.edu.in

Roll no: 240701360 Phone: 9940617256

Branch: REC

Department: I CSE FD

Batch: 2028

Degree: B.E - CSE



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 2_COD_Question 5

Attempt : 2 Total Mark : 10 Marks Obtained : 10

Section 1: Coding

1. Problem Statement

Ashwin is tasked with developing a simple application to manage a list of items in a shop inventory using a doubly linked list. Each item in the inventory has a unique identification number. The application should allow users to perform the following operations:

Create a List of Items: Initialize the inventory with a given number of items. Each item will be assigned a unique number provided by the user and insert the elements at end of the list.

Delete an Item: Remove an item from the inventory at a specific position.

Display the Inventory: Show the list of items before and after deletion.

If the position provided for deletion is invalid (e.g., out of range), it should

display an error message.

Input Format

The first line contains an integer n, representing the number of items to be initially entered into the inventory.

The second line contains n integers, each representing the unique identification number of an item separated by spaces.

240701360

The third line contains an integer p, representing the position of the item to be deleted from the inventory.

Output Format

The first line of output prints "Data entered in the list:" followed by the data values of each node in the doubly linked list before deletion.

If p is an invalid position, the output prints "Invalid position. Try again."

If p is a valid position, the output prints "After deletion the new list:" followed by the data values of each node in the doubly linked list after deletion.

Refer to the sample output for the formatting specifications.

Sample Test Case

```
Input: 4
1 2 3 4
5
Output: Data entered in the list:
node 1 : 1
node 2 : 2
node 3 : 3
node 4 : 4
Invalid position. Try again.

Answer

// You are using GCC
void DIListcreation(int n) {
int i,data;
```

```
stnode=(struct node*)malloc(sizeof(struct node));
scanf("%d",&data);
stnode->num=dati
 struct node*fnnode, *tmp;
if(n>=1){
   stnode->num=data;
   stnode->preptr=NULL;
    stnode->nextptr=NULL;
    ennode=stnode;
    for(i=2;i<=n;i++){
      fnnode=(struct node*)malloc(sizeof(struct node));
      scanf("%d",&data);
      fnnode->num=data;
      fnnode->preptr=ennode;
      fnnode->nextptr=NULL;
      ennode->nextptr=fnnode;
      ennode=fnnode;
}
void DIListDeleteAnyNode(int pos) {
 struct node*curnode;
 int i;
 curnode=stnode;
 for(i=1;i<pos &&curnode!=NULL;i++){
   curnode=curnode->nextptr;
 if(curnode!=NULL){
   if(curnode->preptr!=NULL)
      curnode->preptr->nextptr=curnode->nextptr;
    else
      stnode=curnode->nextptr;
    if(curnode->nextptr!=NULL)
      curnode->nextptr->preptr=curnode->preptr;
    free(curnode);
void DIListDeleteFirstNode() {
```

```
240701360
  if(stnode!=NULL){
    struct node*tmp=stnode;
    stnode=stnode->nextptr;
    if(stnode!=NULL){
      stnode->preptr=NULL;
    free(tmp);
  }
}
void DIListDeleteLastNode() {
  if(ennode!=NULL){
   struct node*tmp=ennode;
    ennode=ennode->preptr;
    if(ennode!=NULL)
      ennode->nextptr=NULL;
    else
      stnode=NULL;
    free(tmp);
}
void displayDlList(int m) {
 struct node*tmp;
 int i=1;
\if(stnode==NULL){
   printf("Invalid position. Try again.");
  else{
    tmp=stnode;
    if(m==1)
     printf("Data entered in the list: \n");
    else
     printf("After deletion the new list: \n");
    while(tmp!=NULL){
      printf("node %d : %d\n",i,tmp->num);
      j++;
      tmp=tmp->nextptr;
```

240701360

}
Status: Correct Marks : 10/10

2,0701360