Rajalakshmi Engineering College

Name: Nikhilesh D

Email: 240701360@rajalakshmi.edu.in

Roll no: 240701360 Phone: 9940617256

Branch: REC

Department: I CSE FD

Batch: 2028

Degree: B.E - CSE



NeoColab_REC_CS23231_DATA STRUCTURES

REC_DS using C_Week 4_COD_Question 3

Attempt : 1 Total Mark : 10 Marks Obtained : 10

Section 1: Coding

1. Problem Statement

Write a program to implement a queue using an array and pointers. The program should provide the following functionalities:

Insert an element into the queue. Delete an element from the queue. Display the elements in the queue.

The queue has a maximum capacity of 5 elements. If the queue is full and an insertion is attempted, a "Queue is full" message should be displayed. If the queue is empty and a deletion is attempted, a "Queue is empty" message should be displayed.

Input Format

Each line contains an integer representing the chosen option from 1 to 3.

Option 1: Insert an element into the queue followed by an integer representing the element to be inserted, separated by a space.

Option 2: Delete an element from the queue.

Option 3: Display the elements in the queue.

Output Format

For option 1 (insertion):-

- 1. The program outputs: "<data> is inserted in the queue." if the data is successfully inserted.
- 2. "Queue is full." if the queue is already full and cannot accept more elements.

For option 2 (deletion):-

- 1. The program outputs: "Deleted number is: <data>" if an element is successfully deleted and returns the value of the deleted element.
- 2. "Queue is empty." if the queue is empty no elements can be deleted.

For option 3 (display):-

- 1. The program outputs: "Elements in the queue are: <element1> <element2> ... <elementN>" where <element1>, <element2>, ..., <elementN> represent the elements present in the queue.
- 2. "Queue is empty." if the queue is empty no elements can be displayed.

For invalid options, the program outputs: "Invalid option."

Refer to the sample output for the formatting specifications.

Sample Test Case

Input: 1 10

240701300

```
240701360
Output: 10 is inserted in the queue.
    Elements in the queue are: 10
    Invalid option.
    Answer
    #include <stdio.h>
    #include <stdlib.h>
    #define max 5
    int queue[max];
    int front = -1, rear = -1;
// You are using GCC int insertq(int *data)
      if (rear==max-1)
      {
         return 0;
      if (front==-1 && rear==-1)
         front=rear=0;
      else
         rear++;
      queue[rear]=*data;
      return 1;
    }
    int delq()
      if (front==-1 || front>rear)
         printf("Queue is empty.\n");
        return -1;
int deleted=queue[front];
```

240701360

240101360

```
240701360
  front++;
\\ if (front>rear)
    front=rear=-1;
  printf("Deleted number is: %d\n", deleted);
  return deleted:
void display()
  if (front==-1 || front>rear)
    printf("Queue is empty.\n");
    return;
  printf("Elements in the queue are: ");
  for (int i=front; i<=rear; i++)
    printf("%d ", queue[i]);
  printf("\n");
int main()
  int data, reply, option;
  while (1)
    if (scanf("%d", &option) != 1)
       break;
     switch (option)
       case 1:
         if (scanf("%d", &data) != 1)
            break;
         reply = insertq(&data);
         if (reply == 0)
            printf("Queue is full.\n");
            printf("%d is inserted in the queue.\n", data);
eak;
e 2:
          break;
       case 2:
```

```
240101360
                                              240101360
                   Called without arguments
        delq(); //
                     240701
        break;
      case 3:
        display();
        break;
      default:
        printf("Invalid option.\n");
        break;
    }
  }
  return 0;
                                                                 Marks: 10/10
Status: Correct
```

240701360

10101360

240701360

A0101360

240701360

240701360

240701360

240701360